

# Rakesh Gupta

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/11035886/publications.pdf>

Version: 2024-02-01

81  
papers

477  
citations

759055

12  
h-index

887953

17  
g-index

81  
all docs

81  
docs citations

81  
times ranked

86  
citing authors

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 1  | Analysis of Stochastic Models in Manufacturing Systems Pertaining to Repair Machine Failure. , 2019, , 7-1-7-50.  |     | 1         |
| 2  | A two dissimilar unit parallel system with two phase repair by skilled and ordinary repairmen. International Journal of Systems Assurance Engineering and Management, 2014, 5, 554-561.   | 1.5 | 3         |
| 3  | Cost benefit analysis of a two dissimilar unit cold standby system with Weibull failure and repair laws. International Journal of Systems Assurance Engineering and Management, 2013, 4, 327-334.   | 1.5 | 13        |
| 4  | An operating orbit system with two dissimilar units and corresponding standbys. Journal of Statistics and Management Systems, 2008, 11, 65-76.  | 0.3 | 0         |
| 5  | Profit analysis of a system with mutual changeover of units and correlated failures and repairs. Journal of Quality in Maintenance Engineering, 1999, 5, 128-140.   | 1.0 | 1         |
| 6  | A two-non-identical-unit parallel system with correlated lifetimes. International Journal of Systems Science, 1999, 30, 1123-1129.  | 3.7 | 7         |
| 7  | On the profit comparison of two stochastic models each pertaining to a two-unit standby system with fixed preparation time and hyperexponential repair time distributions. International Journal of Systems Science, 1999, 30, 1309-1317. | 3.7 | 5         |
| 8  | Cost-benefit analysis of a two-unit standby system with post-repair, activation time and correlated failures and repairs. Journal of Quality in Maintenance Engineering, 1997, 3, 55-63.  | 1.0 | 1         |
| 9  | A two dissimilar unit multi-component system with correlated failures and repairs. Microelectronics Reliability, 1997, 37, 845-849.   | 0.9 | 7         |
| 10 | Analysis of a system having super-priority, priority and ordinary units with arbitrary distributions. Microelectronics Reliability, 1997, 37, 851-856.  | 0.9 | 1         |
| 11 | Cost-benefit analysis of a complex system with correlated failures and repairs. Journal of Quality in Maintenance Engineering, 1996, 2, 50-59.  | 1.0 | 1         |
| 12 | Stochastic analysis of a two-unit cold standby system with maximum repair time and correlated failures and repairs. Journal of Quality in Maintenance Engineering, 1996, 2, 66-76.  | 1.0 | 3         |
| 13 | A two-unit duplicating standby system with correlated failure-repair/vbreplacement times. Microelectronics Reliability, 1996, 36, 517-523.  | 0.9 | 2         |
| 14 | Cost-benefit analysis of a multi-unit parallel trichotomous system with random shocks. Microelectronics Reliability, 1996, 36, 701-706.   | 0.9 | 3         |
| 15 | A two-unit system with correlated failures and repairs, and random appearance and disappearance of repairman. International Journal of Systems Science, 1996, 27, 561-566.  | 3.7 | 5         |
| 16 | A cold standby system with arrival time of server and correlated failures and repairs. Microelectronics Reliability, 1995, 35, 739-742.   | 0.9 | 2         |
| 17 | Analysis of a two unit standby system with preparation time and correlated failures and repairs. Microelectronics Reliability, 1995, 35, 1163-1165.   | 0.9 | 4         |
| 18 | Stochastic analysis of a priority unit standby system with repair machine failure. International Journal of Systems Science, 1995, 26, 2435-2440.   | 3.7 | 3         |

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 19 | Analysis of a two-unit standby system with fixed allowed down time and truncated exponential lifetime distributions. Reliability Engineering and System Safety, 1994, 44, 119-124. | 5.1 | 4         |
| 20 | Profit analysis of a two-unit man-machine system with random appearance and disappearance of the operator. Microelectronics Reliability, 1994, 34, 1133-1136.                      | 0.9 | 0         |
| 21 | Analysis of a standby system with dependent repair time and slow switching device. Microelectronics Reliability, 1994, 34, 383-386.  | 0.9 | 5         |
| 22 | A two-unit system with allowed down time and random check of standby. Microelectronics Reliability, 1994, 34, 1381-1385.   | 0.9 | 0         |
| 23 | Profit analysis of a system with two-units having guarantee periods and delayed operation of standby. Microelectronics Reliability, 1994, 34, 1387-1390.                           | 0.9 | 1         |
| 24 | Cost-benefit analysis of a two-unit standby system with a proviso of repair-machine failure. Microelectronics Reliability, 1994, 34, 1391-1394.                                    | 0.9 | 1         |
| 25 | Stochastic analysis of a fault tolerant network system. Microelectronics Reliability, 1993, 33, 303-306.   | 0.9 | 0         |
| 26 | A two-unit system subject to a partial-failure mode and gamma repair-time distribution. Microelectronics Reliability, 1993, 33, 2277-2280.   | 0.9 | 1         |
| 27 | Cost benefit analysis of a complex system with correlated failures and repairs. Microelectronics Reliability, 1993, 33, 2281-2284.   | 0.9 | 3         |
| 28 | Analysis of a multiunit solar energy system model. Microelectronics Reliability, 1993, 33, 1461-1465.  | 0.9 | 2         |
| 29 | Comparison of two stochastic alternative phase models. Microelectronics Reliability, 1993, 33, 501-507.  | 0.9 | 0         |
| 30 | Profit analysis of a two-unit priority standby system subject to degradation and random shocks. Microelectronics Reliability, 1993, 33, 1073-1079.                                 | 0.9 | 4         |
| 31 | Reliability analysis of a satellite-based computer communication network system. Microelectronics Reliability, 1993, 33, 119-126.  | 0.9 | 6         |
| 32 | A multi-component standby system subject to inspection and truncated normal failure time distribution. Microelectronics Reliability, 1993, 33, 127-131.                            | 0.9 | 1         |
| 33 | Profit evaluation of a two unit cold standby system with random change in units. International Journal of Systems Science, 1992, 23, 367-377.                                      | 3.7 | 7         |
| 34 | Two unit cold standby system with correlated failures and repairs. International Journal of Systems Science, 1992, 23, 379-391.  | 3.7 | 25        |
| 35 | Profit analysis of a trichotomous system. Reliability Engineering and System Safety, 1992, 37, 39-44.  | 5.1 | 3         |
| 36 | Cost analysis of a two-unit chargeable standby system with interchangeable units and two types of failure. Microelectronics Reliability, 1992, 32, 775-779.                        | 0.9 | 1         |

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 37 | A stochastic model of a system with two phases of operation. <i>Microelectronics Reliability</i> , 1992, 32, 799-803.  | 0.9 | 0         |
| 38 | A two-unit priority standby system subject to random shocks and Releigh failure-time distribution. <i>Microelectronics Reliability</i> , 1992, 32, 1713-1723.                      | 0.9 | 16        |
| 39 | Cost-benefit analysis of a one-unit system with n degraded states due to random shocks. <i>International Journal of Systems Science</i> , 1991, 22, 2339-2346.                     | 3.7 | 0         |
| 40 | Analysis of a two-unit cold standby system with degradation and linearly increasing failure rates. <i>International Journal of Systems Science</i> , 1991, 22, 2329-2338.          | 3.7 | 4         |
| 41 | Cost analysis of a three-unit standby system subject to random shocks and linearly increasing failure rates. <i>Reliability Engineering and System Safety</i> , 1991, 33, 249-263. | 5.1 | 11        |
| 42 | A single-server two-unit warm standby system with n failure modes, fault detection and inspection. <i>Microelectronics Reliability</i> , 1991, 31, 841-845.                        | 0.9 | 1         |
| 43 | CHE failure in a two-unit standby system with slow switch, repair and post repair. <i>Microelectronics Reliability</i> , 1991, 31, 219-222.  | 0.9 | 2         |
| 44 | Analysis of a complex system composed of two sub-systems with their standbys. <i>Microelectronics Reliability</i> , 1991, 31, 453-463.   | 0.9 | 1         |
| 45 | Comparison of two stochastic models for two-unit series system with cold standbys. <i>Microelectronics Reliability</i> , 1991, 31, 1105-1111.                                      | 0.9 | 2         |
| 46 | Profit analysis of a two-unit cold standby system with abnormal weather condition. <i>Microelectronics Reliability</i> , 1991, 31, 1-5.  | 0.9 | 11        |
| 47 | Profit analysis of a two multi-component unit standby system with MRT. <i>Microelectronics Reliability</i> , 1991, 31, 7-10.   | 0.9 | 3         |
| 48 | Two-unit redundant system with inspection and adjustable rates. <i>Microelectronics Reliability</i> , 1991, 31, 11-14.   | 0.9 | 9         |
| 49 | Profit analysis of a two-unit priority standby system subject to degradation. <i>International Journal of Systems Science</i> , 1991, 22, 61-72.                                   | 3.7 | 11        |
| 50 | Profit analysis of two-unit priority standby system with rest period of the operator. <i>Microelectronics Reliability</i> , 1990, 30, 649-654.                                     | 0.9 | 4         |
| 51 | Profit analysis of a two-unit cold standby system with varying physical conditions of the repairman. <i>Microelectronics Reliability</i> , 1990, 30, 655-660.                      | 0.9 | 5         |
| 52 | Stochastic analysis of a multi-unit cold standby system working in orbit form. <i>Microelectronics Reliability</i> , 1990, 30, 845-850.  | 0.9 | 0         |
| 53 | Cost-benefit analysis of two-unit cold standby system with the provision of rest to a unit. <i>International Journal of Systems Science</i> , 1990, 21, 1451-1462.                 | 3.7 | 3         |
| 54 | Cost-benefit analysis of two-unit parallel system with administrative delay in repair. <i>International Journal of Systems Science</i> , 1990, 21, 1369-1379.                      | 3.7 | 5         |

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 55 | Operating orbit system with two dissimilar units and corresponding standby. International Journal of Systems Science, 1990, 21, 495-501.  | 3.7 | 1         |
| 56 | Profit function analysis of system with mixture of warm and cold standby. International Journal of Systems Science, 1990, 21, 1577-1587.  | 3.7 | 2         |
| 57 | Profit analysis of two-unit priority standby system with administrative delay in repair. International Journal of Systems Science, 1989, 20, 1703-1712.                                   | 3.7 | 33        |
| 58 | Analysis of a three-unit redundant system with two types of repair and inspection. Microelectronics Reliability, 1989, 29, 769-773.   | 0.9 | 12        |
| 59 | A single server multi-component two-unit cold standby system with inspection and imperfect switching device. Microelectronics Reliability, 1986, 26, 873-877.                             | 0.9 | 10        |
| 60 | Cost-benefit analysis of a multi-component standby system with inspection and slow switch. Microelectronics Reliability, 1986, 26, 879-882.   | 0.9 | 8         |
| 61 | Profit analysis of a two-unit standby system with two types of repair and preventive maintenance. Microelectronics Reliability, 1986, 26, 435-441.  | 0.9 | 4         |
| 62 | Cost-benefit analysis of a single server three-unit redundant system with inspection, delayed replacement and two types of repair. Microelectronics Reliability, 1986, 26, 247-253.       | 0.9 | 7         |
| 63 | Cost-benefit analysis of a one-server two-unit standby system subject to imperfect switching device, random inspection and k-failure modes. Microelectronics Reliability, 1986, 26, 7-11. | 0.9 | 2         |
| 64 | Probabilistic analysis of a two-unit cold standby system with two-phase repair and preventive maintenance. Microelectronics Reliability, 1986, 26, 13-18.                                 | 0.9 | 5         |
| 65 | Cost-Benefit Analysis of a 2-Unit Warm-Standby System with Inspection, Repair, and Post Repair. IEEE Transactions on Reliability, 1986, 35, 70-70.  | 3.5 | 3         |
| 66 | Analysis of a 1-Server, 3-Unit, Redundant System with Inspection and Delayed Replacement. IEEE Transactions on Reliability, 1986, 35, 606-610.  | 3.5 | 3         |
| 67 | Cost analysis of a system with partial failure mode and abnormal weather conditions. Microelectronics Reliability, 1985, 25, 461-466.   | 0.9 | 11        |
| 68 | Profit analysis of a cold standby system with two repair distributions. Microelectronics Reliability, 1985, 25, 467-472.  | 0.9 | 14        |
| 69 | Cost analysis of a two unit cold standby system under different weather conditions. Microelectronics Reliability, 1985, 25, 655-659.  | 0.9 | 19        |
| 70 | Cost analysis of a two unit priority standby system with imperfect switch and arbitrary distributions. Microelectronics Reliability, 1985, 25, 65-69.                                     | 0.9 | 22        |
| 71 | Cost analysis of a two-unit cold standby system with two types of operation and repair. Microelectronics Reliability, 1985, 25, 71-75.  | 0.9 | 16        |
| 72 | Cost analysis of a two-unit standby system with delayed replacement and better utilization of units. Microelectronics Reliability, 1985, 25, 81-86.                                       | 0.9 | 9         |

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 73 | Availability analysis of a four-state Markov system. International Journal of Systems Science, 1984, 15, 977-982.                          | 3.7 | 0         |
| 74 | Availability analysis of a two-unit cold standby system with two switching failure modes. Microelectronics Reliability, 1984, 24, 419-423. | 0.9 | 11        |
| 75 | Analysis of a two-unit standby system with three modes and imperfect switching device. Microelectronics Reliability, 1984, 24, 425-429.    | 0.9 | 15        |
| 76 | A multistate system with two repair distributions. Microelectronics Reliability, 1983, 23, 337-340.  | 0.9 | 16        |
| 77 | Analysis of a two-unit cold standby system with three modes. Microelectronics Reliability, 1983, 23, 1041-1044.                            | 0.9 | 11        |
| 78 | Reliability analysis of multi-unit cold standby system with two operating modes. Microelectronics Reliability, 1983, 23, 1045-1050.        | 0.9 | 6         |
| 79 | A multicomponent two-unit cold standby system with three modes. Microelectronics Reliability, 1983, 23, 799-803.                           | 0.9 | 4         |
| 80 | A multi-standby multi-failure mode system with repair and replacement policy. Microelectronics Reliability, 1983, 23, 809-812.             | 0.9 | 6         |
| 81 | A single unit multicomponent system subject to various types of failures. Microelectronics Reliability, 1983, 23, 813-816.                 | 0.9 | 13        |