

# Ungyu Paik

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/11043749/publications.pdf>

Version: 2024-02-01

277  
papers

17,207  
citations

25423

59  
h-index

18944

123  
g-index

278  
all docs

278  
docs citations

278  
times ranked

24381  
citing authors

#	ARTICLE	IF	CITATIONS
1	Strategy to utilize amorphous phase of semiconductor toward excellent and reliable photochemical water splitting performance: Roles of interface dipole moment and reaction parallelization. International Journal of Energy Research, 2022, 46, 3674-3685.	2.2	5
2	Effect of Ta <sup>5+</sup> doping on the thermal physical properties of defective fluorite Y <sub>3</sub> NbO <sub>7</sub> ceramics. Journal of the American Ceramic Society, 2022, 105, 1358-1366.	1.9	6
3	Preparation and characterization of slurry for CMP. , 2022, , 323-354.		2
4	Highly reversible cycling with Dendrite-Free lithium deposition enabled by robust SEI layer with low charge transfer activation energy. Applied Surface Science, 2022, 572, 151439.	3.1	8
5	An integrated strategy based on Schiff base reactions to construct unique two-dimensional nanostructures for intrinsic pseudocapacitive sodium/lithium storage. Chemical Engineering Journal, 2022, 429, 132339.	6.6	12
6	Heterostructure design of Fe <sub>2</sub> (MoO <sub>4</sub> ) <sub>3</sub> decorated MoO <sub>3</sub> nanorods for boosting catalytic activity in high-performance lithium sulfur batteries. Electrochimica Acta, 2022, 401, 139535.	2.6	4
7	High-Performance Asymmetric Flow-Electrode Capacitive Mixing with MnO <sub>2</sub> -Coated Activated Carbon Flow-Electrode for Energy Harvesting from Salinity Gradient Power. , 2022, 4, 618-625.		7
8	Toward High Rate Performance Solid-State Batteries. Advanced Energy Materials, 2022, 12, .	10.2	24
9	Design of inorganic/organic bi-layered Li protection layer enabled dendrite-free practical Li metal battery. Chemical Engineering Journal, 2022, 450, 137993.	6.6	7
10	Subcontinuous 2D La <sub>0.6</sub> Sr <sub>0.4</sub> CoO <sub>3-<math>\delta</math></sub> nanosheet as an efficient charge conductor for boosting the cathodic activity of solid oxide fuel cells. Electrochimica Acta, 2021, 366, 137371.	2.6	8
11	A robust solid electrolyte interphase layer coated on polyethylene separator surface induced by Ge interlayer for stable Li-metal batteries. Electrochimica Acta, 2021, 370, 137703.	2.6	10
12	Epitaxial Growth of Nanostructured Li <sub>2</sub> Se on Lithium Metal for All Solid-State Batteries. Advanced Science, 2021, 8, e2004204.	5.6	36
13	Amorphous Nickel-Iron Borophosphate for a Robust and Efficient Oxygen Evolution Reaction. Advanced Energy Materials, 2021, 11, 2100624.	10.2	120
14	Blocking of radiative thermal conduction in Zn <sup>2+</sup> -incorporated high-entropy A <sub>2</sub> B <sub>2</sub> O <sub>7</sub> fluorite oxides. Ceramics International, 2021, 47, 33544-33553.	2.3	10
15	Ion-Conducting Channel Implanted Anode Matrix for All-Solid-State Batteries with High Rate Capability and Stable Anode/Solid Electrolyte Interface. Advanced Energy Materials, 2021, 11, 2102045.	10.2	19
16	Stable artificial solid electrolyte interphase with lithium selenide and lithium chloride for dendrite-free lithium metal anodes. Journal of Power Sources, 2021, 506, 230158.	4.0	21
17	Cross Effect of Surface Area and Electrical Conductivity for Carbonaceous Materials in Flow-electrode Capacitive Mixing (F-CapMix) and Flow-electrode Capacitive Deionization (FCDI): Solid-like Behavior of Flow-electrode. ACS Sustainable Chemistry and Engineering, 2021, 9, 13514-13525.	3.2	12
18	Si nanoparticles embedded in carbon nanofiber sheathed with Li <sub>6</sub> PS <sub>5</sub> Cl as an anode material for all-solid-state batteries. Journal of Power Sources, 2021, 510, 230425.	4.0	21

#	ARTICLE	IF	CITATIONS
19	Effect of cation substitution on thermophysical properties of fluorite A3BO7 ceramics. Journal of Alloys and Compounds, 2021, 883, 160848.	2.8	7
20	Glass-like thermal conductivity in mass-disordered high-entropy (Y,Yb)2(Ti, Zr, Hf)2O7 for thermal barrier material. Materials and Design, 2021, 210, 110059.	3.3	27
21	Dendrite-free lithium plating enabled by yolk shell structured ZnO/C sphere coated polyethylene separator for stable lithium metal anodes. Journal of Alloys and Compounds, 2021, 885, 161157.	2.8	8
22	Enhanced Electrochemical Performance and Durability of the BaCo <sub>0.4</sub> Fe <sub>0.4</sub> Zr <sub>0.1</sub> Y <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> Composite Cathode of Protonic Ceramic Fuel Cells via Forming Nickel Oxide Nanoparticles. ACS Applied Energy Materials, 2021, 4, 11564-11573.	2.5	11
23	Hot corrosion behavior in thermal barrier coatings with heterogeneous splat boundary. Corrosion Science, 2020, 163, 108225.	3.0	10
24	Copper Nitride Nanowires Printed Li with Stable Cycling for Li Metal Batteries in Carbonate Electrolytes. Advanced Materials, 2020, 32, e1905573.	11.1	105
25	Lithiophilic surface treatment of metal- and metallic compound-based frameworks by gas nitriding for lithium metal batteries. Journal of Power Sources, 2020, 477, 228776.	4.0	20
26	Hot-corrosion resistance and phase stability of Yb2O3-Gd2O3-Y2O3 costabilized zirconia-based thermal barrier coatings against Na2SO4-V2O5 molten salts. Surface and Coatings Technology, 2020, 400, 126197.	2.2	34
27	Facile <i>ex situ</i> formation of a LiF-polymer composite layer as an artificial SEI layer on Li metal by simple roll-press processing for carbonate electrolyte-based Li metal batteries. Journal of Materials Chemistry A, 2020, 8, 17229-17237.	5.2	63
28	Understanding the thermal decomposition mechanism of La2Zr2O7 during isothermal exposure. Surface and Coatings Technology, 2020, 389, 125546.	2.2	8
29	Unprecedentedly Low CO <sub>2</sub> Transport through Vertically Aligned, Conical Silicon Nanotube Membranes. Nano Letters, 2020, 20, 4754-4760.	4.5	9
30	High Rate Capability of a LiNi <sub>0.84</sub> Co <sub>0.12</sub> Mn <sub>0.04</sub> O <sub>2</sub> Cathode with a Uniform Conducting Network of Functionalized Graphene Nanoribbons for Li-Ion Batteries. Industrial & Engineering Chemistry Research, 2020, 59, 12889-12895.	1.8	3
31	Improvement in hot corrosion resistance and chemical stability of YSZ by introducing a Lewis neutral layer on thermal barrier coatings. Corrosion Science, 2020, 173, 108776.	3.0	10
32	Controlled swelling behavior and stable cycling of silicon/graphite granular composite for high energy density in lithium ion batteries. Journal of Power Sources, 2020, 457, 228021.	4.0	43
33	Crack-Growth Behavior in Thermal Barrier Coatings with Cyclic Thermal Exposure. Coatings, 2019, 9, 365.	1.2	11
34	Interface engineering of yttrium stabilized zirconia/gadolinium doped ceria bi-layer electrolyte solid oxide fuel cell for boosting electrochemical performance. Journal of Power Sources, 2019, 435, 226776.	4.0	30
35	Current Status of Self-Supported Catalysts for Robust and Efficient Water Splitting for Commercial Electrolyzer. ChemCatChem, 2019, 11, 5898-5912.	1.8	47
36	Crack-Resistance Behavior of an Encapsulated, Healing Agent Embedded Buffer Layer on Self-Healing Thermal Barrier Coatings. Coatings, 2019, 9, 358.	1.2	7

#	ARTICLE	IF	CITATIONS
37	Facile fabrication strategy of highly dense gadolinium-doped ceria/yttria-stabilized zirconia bilayer electrolyte via cold isostatic pressing for low temperature solid oxide fuel cells. <i>Journal of Power Sources</i> , 2019, 415, 112-118.	4.0	30
38	Advantageous crystalline-amorphous phase boundary for enhanced electrochemical water oxidation. <i>Energy and Environmental Science</i> , 2019, 12, 2443-2454.	15.6	315
39	In Situ Cross-linked Carboxymethyl Cellulose-Polyethylene Glycol Binder for Improving the Long-Term Cycle Life of Silicon Anodes in Li Ion Batteries. <i>Industrial &amp; Engineering Chemistry Research</i> , 2019, 58, 8123-8130.	1.8	35
40	Sb-based electrode materials for rechargeable batteries. <i>Journal of Materials Chemistry A</i> , 2018, 6, 8159-8193.	5.2	95
41	LiCl-LiI molten salt electrolyte with bismuth-lead positive electrode for liquid metal battery. <i>Journal of Power Sources</i> , 2018, 377, 87-92.	4.0	50
42	Boosting Electrochemical Water Oxidation with Metal Hydroxide Carbonate Templated Prussian Blue Analogues. <i>Angewandte Chemie</i> , 2018, 130, 1255-1259.	1.6	25
43	WO <sub>3</sub> nanofibrous backbone scaffolds for enhanced optical absorbance and charge transport in metal oxide (Fe <sub>2</sub> O <sub>3</sub> , BiVO <sub>4</sub> ) semiconductor photoanodes towards solar fuel generation. <i>Applied Surface Science</i> , 2018, 447, 331-337.	3.1	18
44	Boosting Electrochemical Water Oxidation with Metal Hydroxide Carbonate Templated Prussian Blue Analogues. <i>Angewandte Chemie - International Edition</i> , 2018, 57, 1241-1245.	7.2	180
45	Metal Organic Framework Derived Materials: Progress and Prospects for the Energy Conversion and Storage. <i>Advanced Materials</i> , 2018, 30, e1705146.	11.1	376
46	WO <sub>3</sub> /W:BiVO <sub>4</sub> /BiVO <sub>4</sub> graded photoabsorber electrode for enhanced photoelectrocatalytic solar light driven water oxidation. <i>Physical Chemistry Chemical Physics</i> , 2017, 19, 4648-4655.	1.3	38
47	Communication-Synergistic Effect of Mixed Particle Size on W CMP Process: Optimization Using Experimental Design. <i>ECS Journal of Solid State Science and Technology</i> , 2017, 6, P42-P44.	0.9	12
48	Cross-linked poly(acrylic acid)-carboxymethyl cellulose and styrene-butadiene rubber as an efficient binder system and its physicochemical effects on a high energy density graphite anode for Li-ion batteries. <i>Electrochemistry Communications</i> , 2017, 77, 103-106.	2.3	45
49	Synthesis of hierarchical porous TiNb <sub>2</sub> O <sub>7</sub> nanotubes with controllable porosity and their application in high power Li-ion batteries. <i>Journal of Materials Chemistry A</i> , 2017, 5, 6958-6965.	5.2	62
50	Synergistic protective effect of a BN-carbon separator for highly stable lithium sulfur batteries. <i>NPG Asia Materials</i> , 2017, 9, e375-e375.	3.8	85
51	Highly Dispersed Fe <sup>3+</sup> -Substituted Colloidal Silica Nanoparticles for Defect-Free Tungsten Chemical Mechanical Planarization. <i>ECS Journal of Solid State Science and Technology</i> , 2017, 6, P405-P409.	0.9	5
52	Structure-designed synthesis of FeS <sub>2</sub> @C yolk-shell nanoboxes as a high-performance anode for sodium-ion batteries. <i>Energy and Environmental Science</i> , 2017, 10, 1576-1580.	15.6	475
53	Communication-Corrosion Behavior of Tungsten Metal Gate in the Presence of Hydrogen Peroxide at Acidic Medium. <i>ECS Journal of Solid State Science and Technology</i> , 2017, 6, P169-P171.	0.9	7
54	Synergetic control of band gap and structural transformation for optimizing TiO <sub>2</sub> photocatalysts. <i>Applied Catalysis B: Environmental</i> , 2017, 210, 513-521.	10.8	37

#	ARTICLE	IF	CITATIONS
55	In-plane Deformation Mechanics for Highly Stretchable Electronics. <i>Advanced Materials</i> , 2017, 29, 1604989.	11.1	141
56	Multi-objective optimization of tungsten CMP slurry for advanced semiconductor manufacturing using a response surface methodology. <i>Materials and Design</i> , 2017, 117, 131-138.	3.3	30
57	Increase in Ce <sup>3+</sup> Concentration of Ceria Nanoparticles for High Removal Rate of SiO <sub>2</sub> in Chemical Mechanical Planarization. <i>ECS Journal of Solid State Science and Technology</i> , 2017, 6, P681-P685.	0.9	36
58	Self-Supported Nickel Iron Layered Double Hydroxide-Nickel Selenide Electrocatalyst for Superior Water Splitting Activity. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 33766-33774.	4.0	257
59	Dielectric Polarization of a High-Energy Density Graphite Anode and Its Physicochemical Effect on Li-Ion Batteries. <i>Industrial &amp; Engineering Chemistry Research</i> , 2017, 56, 13776-13782.	1.8	5
60	Ce <sup>3+</sup> -enriched core-shell ceria nanoparticles for silicate adsorption. <i>Journal of Materials Research</i> , 2017, 32, 2829-2836.	1.2	20
61	Thermal durability and fracture behavior of layered Yb-Gd-Y-based thermal barrier coatings in thermal cyclic exposure. <i>Surface and Coatings Technology</i> , 2017, 323, 39-48.	2.2	17
62	Miniaturized Battery-Free Wireless Systems for Wearable Pulse Oximetry. <i>Advanced Functional Materials</i> , 2017, 27, 1604373.	7.8	248
63	Microstructural control of new intercalation layered titanoniobates with large and reversible d-spacing for easy Na <sup>+</sup> ion uptake. <i>Science Advances</i> , 2017, 3, e1700509.	4.7	42
64	Concentrator photovoltaic module architectures with capabilities for capture and conversion of full global solar radiation. <i>Proceedings of the National Academy of Sciences of the United States of America</i> , 2016, 113, E8210-E8218.	3.3	48
65	Soft, thin skin-mounted power management systems and their use in wireless thermography. <i>Proceedings of the National Academy of Sciences of the United States of America</i> , 2016, 113, 6131-6136.	3.3	139
66	Formation of Co <sub>3</sub> O <sub>4</sub> microframes from MOFs with enhanced electrochemical performance for lithium storage and water oxidation. <i>Chemical Communications</i> , 2016, 52, 6269-6272.	2.2	137
67	Partially reduced SnO <sub>2</sub> nanoparticles anchored on carbon nanofibers for high performance sodium-ion batteries. <i>Electrochemistry Communications</i> , 2016, 72, 91-95.	2.3	42
68	Role of the oxidation state of cerium on the ceria surfaces for silicate adsorption. <i>Applied Surface Science</i> , 2016, 389, 311-315.	3.1	37
69	Formation of Ni-Co-MoS <sub>2</sub> Nanoboxes with Enhanced Electrocatalytic Activity for Hydrogen Evolution. <i>Advanced Materials</i> , 2016, 28, 9006-9011.	11.1	511
70	General synthesis of vanadium-based mixed metal oxides hollow nanofibers for high performance lithium-ion batteries. <i>Journal of Power Sources</i> , 2016, 329, 190-196.	4.0	40
71	A soft, wearable microfluidic device for the capture, storage, and colorimetric sensing of sweat. <i>Science Translational Medicine</i> , 2016, 8, 366ra165.	5.8	933
72	Microstructure design for blended feedstock and its thermal durability in lanthanum zirconate based thermal barrier coatings. <i>Surface and Coatings Technology</i> , 2016, 308, 40-49.	2.2	25

#	ARTICLE	IF	CITATIONS
73	Size-dependent interactions of silica nanoparticles with a flat silica surface. <i>Journal of Colloid and Interface Science</i> , 2016, 483, 177-184.	5.0	25
74	Synergistic Ultrathin Functional Polymer-Coated Carbon Nanotube Interlayer for High Performance Lithium-Sulfur Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2016, 8, 20092-20099.	4.0	102
75	Battery-free, stretchable optoelectronic systems for wireless optical characterization of the skin. <i>Science Advances</i> , 2016, 2, e1600418.	4.7	336
76	N-doped graphene layers encapsulated NiFe alloy nanoparticles derived from MOFs with superior electrochemical performance for oxygen evolution reaction. <i>Scientific Reports</i> , 2016, 6, 34004.	1.6	104
77	Etching-Induced Fe <sub>3</sub> O <sub>4</sub> @Carbon with an Ultralong Cycling Life for Lithium Storage. <i>Advanced Energy Materials</i> , 2016, 6, 1502318.	10.2	158
78	Sb@C coaxial nanotubes as a superior long-life and high-rate anode for sodium ion batteries. <i>Energy and Environmental Science</i> , 2016, 9, 2314-2318.	15.6	414
79	Two-dimensional Nafion nanoweb anion-shield for improved electrochemical performances of lithium-sulfur batteries. <i>Journal of Materials Chemistry A</i> , 2016, 4, 11203-11206.	5.2	35
80	Exploring Graphene Quantum Dots/TiO <sub>2</sub> interface in photoelectrochemical reactions: Solar to fuel conversion. <i>Electrochimica Acta</i> , 2016, 187, 249-255.	2.6	79
81	Carbon coated porous nickel phosphides nanoplates for highly efficient oxygen evolution reaction. <i>Energy and Environmental Science</i> , 2016, 9, 1246-1250.	15.6	839
82	Nickel cobalt phosphides quasi-hollow nanocubes as an efficient electrocatalyst for hydrogen evolution in alkaline solution. <i>Chemical Communications</i> , 2016, 52, 1633-1636.	2.2	271
83	TiO <sub>2</sub> as an active or supplemental material for lithium batteries. <i>Journal of Materials Chemistry A</i> , 2016, 4, 14-31.	5.2	166
84	Miniaturized Flexible Electronic Systems with Wireless Power and Near-Field Communication Capabilities. <i>Advanced Functional Materials</i> , 2015, 25, 4761-4767.	7.8	148
85	Freestanding rGO-SWNT-STN Composite Film as an Anode for Li Ion Batteries with High Energy and Power Densities. <i>Nanomaterials</i> , 2015, 5, 2380-2390.	1.9	4
86	Porosity-Controlled TiNb <sub>2</sub> O <sub>7</sub> Microspheres with Partial Nitridation as A Practical Negative Electrode for High-Power Lithium-Ion Batteries. <i>Advanced Energy Materials</i> , 2015, 5, 1401945.	10.2	153
87	Interpolymer complexes of poly(acrylic acid) and poly(ethylene glycol) for low dishing in STI CMP. <i>Applied Surface Science</i> , 2015, 353, 499-503.	3.1	15
88	Hydroxylated carbon nanotube enhanced sulfur cathodes for improved electrochemical performance of lithium-sulfur batteries. <i>Chemical Communications</i> , 2015, 51, 13682-13685.	2.2	55
89	Electrospun porous lithium manganese phosphate-carbon nanofibers as a cathode material for lithium ion batteries. <i>Journal of Materials Chemistry A</i> , 2015, 3, 17713-17720.	5.2	20
90	Modulating the interaction between gold and TiO <sub>2</sub> nanowires for enhanced solar driven photoelectrocatalytic hydrogen generation. <i>Physical Chemistry Chemical Physics</i> , 2015, 17, 19371-19378.	1.3	16

#	ARTICLE	IF	CITATIONS
91	Soft network composite materials with deterministic and bio-inspired designs. <i>Nature Communications</i> , 2015, 6, 6566.	5.8	392
92	Encapsulation of S/SWNT with PANI Web for Enhanced Rate and Cycle Performance in Lithium Sulfur Batteries. <i>Scientific Reports</i> , 2015, 5, 8946.	1.6	42
93	Porous $\text{TiNb}_2\text{O}_7$ nanofibers decorated with conductive $\text{Ti}^{1-x}\text{Nb}_x\text{N}$ bumps as a high power anode material for Li-ion batteries. <i>Journal of Materials Chemistry A</i> , 2015, 3, 8590-8596.	5.2	90
94	Microstructure control of the graphite anode with a high density for Li ion batteries with high energy density. <i>Electrochimica Acta</i> , 2015, 166, 367-371.	2.6	28
95	Electrospun Sn-doped $\text{LiTi}_2(\text{PO}_4)_3/\text{C}$ nanofibers for ultra-fast charging and discharging. <i>Journal of Materials Chemistry A</i> , 2015, 3, 10395-10402.	5.2	43
96	Thermal durability of thermal barrier coatings with bond coat composition in cyclic thermal exposure. <i>Surface and Coatings Technology</i> , 2015, 284, 69-74.	2.2	12
97	Graphene as an Interfacial Layer for Improving Cycling Performance of Si Nanowires in Lithium-Ion Batteries. <i>Nano Letters</i> , 2015, 15, 6658-6664.	4.5	69
98	Stackable, three dimensional carbon-metal oxide composite for high performance supercapacitors. <i>Journal of Materials Chemistry A</i> , 2015, 3, 20459-20464.	5.2	15
99	Lithium salt of carboxymethyl cellulose as an aqueous binder for thick graphite electrode in lithium ion batteries. <i>Macromolecular Research</i> , 2015, 23, 719-725.	1.0	23
100	Epidermal Electronics with Advanced Capabilities in Near-Field Communication. <i>Small</i> , 2015, 11, 906-912.	5.2	224
101	Exfoliation of titanium oxide powder into nanosheets using hydrothermal reaction and its reassembly into flexible papers for thin-film capacitors. <i>Journal of Solid State Chemistry</i> , 2015, 224, 76-81.	1.4	8
102	Control of Adhesion Force Between Ceria Particles and Polishing Pad in Shallow Trench Isolation Chemical Mechanical Planarization. <i>Journal of Nanoscience and Nanotechnology</i> , 2014, 14, 4351-4356.	0.9	15
103	Nitridated $\text{Si-Ti-Ni}$ alloy as an anode for Li rechargeable batteries. <i>Journal of Power Sources</i> , 2014, 253, 282-286.	4.0	22
104	3D-interconnected Nanoporous RGO-CNT Structure for Supercapacitors Application. <i>Electrochimica Acta</i> , 2014, 125, 536-542.	2.6	46
105	Surface Coverage Dependent Cycle Stability of Core-Shell Nanostructured Electrodes for Use in Lithium Ion Batteries. <i>Advanced Energy Materials</i> , 2014, 4, 1300472.	10.2	18
106	Si nanotubes array sheathed with $\text{SiN/SiO}_x\text{Ny}$ layer as an anode material for lithium ion batteries. <i>Journal of Electroceramics</i> , 2014, 32, 66-71.	0.8	13
107	One-Dimensional Silicon Nanostructures for Li Ion Batteries. <i>Journal of Physical Chemistry Letters</i> , 2014, 5, 720-731.	2.1	61
108	$\text{Li}_2\text{MnSiO}_4$ /carbon nanofiber cathodes for Li-ion batteries. <i>Ionics</i> , 2014, 20, 1351-1359.	1.2	18

#	ARTICLE	IF	CITATIONS
109	Electrochemical Properties of Si-Ge Heterostructures as an Anode Material for Lithium Ion Batteries. <i>Advanced Functional Materials</i> , 2014, 24, 1458-1464.	7.8	78
110	Effects of physico-chemical properties between poly(ethyleneimine) and silica abrasive on copper chemical mechanical planarization. <i>Microelectronic Engineering</i> , 2014, 113, 50-54.	1.1	10
111	Synthesis and anti-bacterial activity of AuNRs-PS-MNPs. <i>Materials Letters</i> , 2014, 137, 479-482.	1.3	9
112	Control of bond coat microstructure in HVOF process for thermal barrier coatings. <i>Surface and Coatings Technology</i> , 2014, 260, 63-67.	2.2	4
113	Germanium coating boosts lithium uptake in Si nanotube battery anodes. <i>Physical Chemistry Chemical Physics</i> , 2014, 16, 17930.	1.3	31
114	Enhanced photocatalytic performance at a Au/N-TiO <sub>2</sub> hollow nanowire array by a combination of light scattering and reduced recombination. <i>Physical Chemistry Chemical Physics</i> , 2014, 16, 17748-17755.	1.3	26
115	Core-Shell Tubular Nanostructured Electrode of Hollow Carbon Nanofiber/Manganese Oxide for Electrochemical Capacitors. <i>Electrochimica Acta</i> , 2014, 141, 39-44.	2.6	29
116	Three-dimensional Gd-doped TiO <sub>2</sub> fibrous photoelectrodes for efficient visible light-driven photocatalytic performance. <i>RSC Advances</i> , 2014, 4, 11750-11757.	1.7	31
117	Synergistic Metal-Metal Oxide Nanoparticles Supported Electrocatalytic Graphene for Improved Photoelectrochemical Glucose Oxidation. <i>ACS Applied Materials &amp; Interfaces</i> , 2014, 6, 4864-4871.	4.0	100
118	TiO <sub>2</sub> nanotube branched tree on a carbon nanofiber nanostructure as an anode for high energy and power lithium ion batteries. <i>Nano Research</i> , 2014, 7, 491-501.	5.8	42
119	Role of the Surface Chemistry of Ceria Surfaces on Silicate Adsorption. <i>ACS Applied Materials &amp; Interfaces</i> , 2014, 6, 7388-7394.	4.0	44
120	Gold nanoparticle-composite nanofibers for enzymatic electrochemical sensing of hydrogen peroxide. <i>Analyst</i> , 2013, 138, 5025.	1.7	28
121	Facile Synthesis of Ultrathin ZnO Nanotubes with Well-Organized Hexagonal Nanowalls and Sealed Layouts: Applications for Lithium Ion Battery Anodes. <i>Journal of Physical Chemistry C</i> , 2013, 117, 1037-1043.	1.5	95
122	Microstructure Evolution and Interface Stability of Thermal Barrier Coatings with Vertical Type Cracks in Cyclic Thermal Exposure. <i>Journal of Thermal Spray Technology</i> , 2013, 22, 671-679.	1.6	15
123	Acid-base interaction between carbon black and polyurethane molecules with different amine values: Dispersion stability of carbon black suspension for use in lithium ion battery cathodes. <i>Electrochimica Acta</i> , 2013, 111, 946-951.	2.6	19
124	3D Cross-Linked Nanoweb Architecture of Binder-Free TiO <sub>2</sub> Electrodes for Lithium Ion Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2013, 5, 11525-11529.	4.0	64
125	Hydrogen treated, cap-opened Si nanotubes array anode for high power lithium ion battery. <i>Journal of Power Sources</i> , 2013, 244, 463-468.	4.0	37
126	Electrospun Li <sub>4</sub> Ti <sub>5</sub> O <sub>12</sub> nanofibers sheathed with conductive TiN/TiO <sub>N</sub> layer as an anode material for high power Li-ion batteries. <i>Journal of Power Sources</i> , 2013, 244, 726-730.	4.0	60



#	ARTICLE	IF	CITATIONS
127	Effect of post heat treatment on thermal durability of thermal barrier coatings in thermal fatigue tests. <i>Surface and Coatings Technology</i> , 2013, 215, 46-51.	2.2	26
128	Control of H <sub>2</sub> O generated during the CO <sub>2</sub> hardening process in a casting mold. <i>Ceramics International</i> , 2013, 39, 3993-3998.	2.3	7
129	Stretchable batteries with self-similar serpentine interconnects and integrated wireless recharging systems. <i>Nature Communications</i> , 2013, 4, 1543.	5.8	1,169
130	Facile Synthesis of Free-Standing Silicon Membranes with Three-Dimensional Nanoarchitecture for Anodes of Lithium Ion Batteries. <i>Nano Letters</i> , 2013, 13, 3340-3346.	4.5	69
131	Sol-gel nanoglues for an organic binder-free TiO <sub>2</sub> nanofiber anode for lithium ion batteries. <i>Nanoscale</i> , 2013, 5, 3230.	2.8	30
132	Three dimensional-TiO <sub>2</sub> nanotube array photoanode architectures assembled on a thin hollow nanofibrous backbone and their performance in quantum dot-sensitized solar cells. <i>Chemical Communications</i> , 2013, 49, 2810.	2.2	48
133	Effect of ambient pressure on the selective growth of square In <sub>2</sub> O <sub>3</sub> nanowires. <i>Metals and Materials International</i> , 2013, 19, 623-627.	1.8	0
134	Quantum Dot Based Heterostructures for Unassisted Photoelectrochemical Hydrogen Generation. <i>Advanced Energy Materials</i> , 2013, 3, 176-182.	10.2	101
135	Thermal Fatigue Behavior of Air-Plasma Sprayed Thermal Barrier Coating with Bond Coat Species in Cyclic Thermal Exposure. <i>Materials</i> , 2013, 6, 3387-3403.	1.3	27
136	LEGO-like assembly of peelable, deformable components for integrated devices. <i>NPG Asia Materials</i> , 2013, 5, e66-e66.	3.8	12
137	Patterned oxide semiconductor by electrohydrodynamic jet printing for transparent thin film transistors. <i>Applied Physics Letters</i> , 2012, 100, .	1.5	60
138	Si/Ge Double-Layered Nanotube Array as a Lithium Ion Battery Anode. <i>ACS Nano</i> , 2012, 6, 303-309.	7.3	225
139	SnO <sub>2</sub> encapsulated TiO <sub>2</sub> hollow nanofibers as anode material for lithium ion batteries. <i>Electrochemistry Communications</i> , 2012, 22, 81-84.	2.3	58
140	A Ge inverse opal with porous walls as an anode for lithium ion batteries. <i>Energy and Environmental Science</i> , 2012, 5, 9028.	15.6	104
141	Dominant Factors Governing the Rate Capability of a TiO <sub>2</sub> Nanotube Anode for High Power Lithium Ion Batteries. <i>ACS Nano</i> , 2012, 6, 8308-8315.	7.3	184
142	Powder preparation for a shell mold using a new coating process. <i>Ceramics International</i> , 2012, 38, 2749-2755.	2.3	4
143	Nanostructured Materials for Energy Storage Devices. <i>The Electrical Engineering Handbook</i> , 2012, , 713-738.	0.2	0
144	Silicon nanowires with a carbon nanofiber branch as lithium-ion anode material. <i>Journal of Materials Chemistry</i> , 2011, 21, 12619.	6.7	35

#	ARTICLE	IF	CITATIONS
145	High Open Circuit Voltage Quantum Dot Sensitized Solar Cells Manufactured with ZnO Nanowire Arrays and Si/ZnO Branched Hierarchical Structures. <i>Journal of Physical Chemistry Letters</i> , 2011, 2, 1984-1990.	2.1	71
146	Nitridated TiO <sub>2</sub> hollow nanofibers as an anode material for high power lithium ion batteries. <i>Energy and Environmental Science</i> , 2011, 4, 4532.	15.6	242
147	Enhanced Electrochemical Properties of LiFePO <sub>4</sub> Electrodes with Carboxylated Poly(vinyl) Tj ETQq1 1 0.784314 rgBT /Ov Chemistry C, 2011, 115, 16242-16246.	1.5	14
148	Analysis of thermoelastic characteristics for vertical-cracked thermal barrier coatings through mathematical approaches. <i>Surface and Coatings Technology</i> , 2011, 206, 1615-1620.	2.2	3
149	Optical properties of laterally aligned Si nanowires for transparent electronics applications. <i>Nano Research</i> , 2011, 4, 817-823.	5.8	4
150	Strategic dispersion of carbon black and its application to ink-jet-printed lithium cobalt oxide electrodes for lithium ion batteries. <i>Journal of Power Sources</i> , 2011, 196, 6449-6455.	4.0	33
151	A new in situ process in precision casting for mold fabrication. <i>Journal of the European Ceramic Society</i> , 2011, 31, 1581-1588.	2.8	12
152	Microstructure design and mechanical properties of thermal barrier coatings with layered top and bond coats. <i>Surface and Coatings Technology</i> , 2010, 205, 1229-1235.	2.2	31
153	Interfacial stability and contact damage resistance by incorporating buffer layer in thermal barrier coatings. <i>Progress in Organic Coatings</i> , 2010, 68, 135-141.	1.9	2
154	Interfacial stability and contact damage resistance by incorporating buffer layer in thermal barrier coatings. <i>Progress in Organic Coatings</i> , 2010, 67, 95-101.	1.9	4
155	Thermal cycling behavior and interfacial stability in thick thermal barrier coatings. <i>Surface and Coatings Technology</i> , 2010, 205, 1250-1255.	2.2	41
156	Enhancement of electro-optical properties in holographic polymer-dispersed liquid crystal films by incorporation of multiwalled carbon nanotubes into a polyurethane acrylate matrix. <i>Polymer International</i> , 2010, 59, 1289-1295.	1.6	10
157	GaAs photovoltaics and optoelectronics using releasable multilayer epitaxial assemblies. <i>Nature</i> , 2010, 465, 329-333.	13.7	524
158	Nanoscale printing simplified. <i>Nature Nanotechnology</i> , 2010, 5, 385-386.	15.6	15
159	Increase in the Adsorption Density of Anionic Molecules on Ceria for Defect-Free STI CMP. <i>Journal of the Electrochemical Society</i> , 2010, 157, H72.	1.3	17
160	Multiselectivity Chemical Mechanical Polishing for NAND Flash Memories beyond 32 nm. <i>Journal of the Electrochemical Society</i> , 2010, 157, H607.	1.3	8
161	Ceria CMP Slurry for the Construction of Floating Gates in MLC NAND Flash Memory below 51 nm. <i>Electrochemical and Solid-State Letters</i> , 2010, 13, H339.	2.2	3
162	Epitaxial growth of one-dimensional GaN nanostructures with enhanced near-band edge emission by chemical vapor deposition. <i>Applied Physics Letters</i> , 2010, 96, 011105.	1.5	13

#	ARTICLE	IF	CITATIONS
163	MICROSTRUCTURAL EVOLUTION AND RESIDUAL STRESSES OF AIR-PLASMA SPRAYED THERMAL BARRIER COATINGS UNDER THERMAL EXPOSURE. <i>Surface Review and Letters</i> , 2010, 17, 337-343.	0.5	5
164	Effect of Organic Additive on Surface Roughness of Polycrystalline Silicon Film after Chemical Mechanical Polishing. <i>Japanese Journal of Applied Physics</i> , 2010, 49, 010216.	0.8	4
165	Synthesis of ZnO nanotubes and nanotube-nanorod hybrid hexagonal networks using a hexagonally close-packed colloidal monolayer template. <i>Journal of Materials Chemistry</i> , 2010, 20, 5136.	6.7	18
166	Evaluation of Surface Acid and Base Properties of $\text{LiFePO}_4$ in Aqueous Medium with pH and Its Electrochemical Properties. <i>Journal of Physical Chemistry C</i> , 2010, 114, 4466-4472.	1.5	25
167	Thermal and mechanical properties of sintered bodies and EB-PVD layers of $\text{Y}_2\text{O}_3$ added $\text{Gd}_2\text{Zr}_2\text{O}_7$ ceramics for thermal barrier coatings. <i>Journal of Alloys and Compounds</i> , 2010, 507, 448-455.	2.8	50
168	Arrays of Sealed Silicon Nanotubes As Anodes for Lithium Ion Batteries. <i>Nano Letters</i> , 2010, 10, 1710-1716.	4.5	804
169	Nanoscale, Electrified Liquid Jets for High-Resolution Printing of Charge. <i>Nano Letters</i> , 2010, 10, 584-591.	4.5	120
170	Vertical Pillar-Superlattice Array and Graphene Hybrid Light Emitting Diodes. <i>Nano Letters</i> , 2010, 10, 2783-2788.	4.5	129
171	Effect of Additives on the Dispersion Properties of Aqueous Based $\text{C/LiFePO}_4$ paste and its Impact on Lithium Ion Battery High Power Properties. <i>KONA Powder and Particle Journal</i> , 2009, 27, 239-245.	0.9	6
172	Fluidic Properties of Carbon Nanotube Inks and Field Emission Properties of Ink Jet-Printed Emitters. <i>Japanese Journal of Applied Physics</i> , 2009, 48, 111601.	0.8	9
173	(111) Faceted Ceria and Its Influence on STI CMP for Memory Devices Below 50 nm. <i>Electrochemical and Solid-State Letters</i> , 2009, 12, H449.	2.2	1
174	Constraints of the Corning on Plugs of W Film in W Chemical Mechanical Planarization. <i>Electrochemical and Solid-State Letters</i> , 2009, 12, H218.	2.2	1
175	Damage resistance of $\text{SiC}$ and $\text{Si}_3\text{N}_4$ coatings with control of microstructure and thickness. <i>Progress in Organic Coatings</i> , 2009, 64, 274-280.	1.9	3
176	A tailored design for dispersion stabilization of a dispersant-free $\text{BaMgAl}_{10}\text{O}_{17}:\text{Eu}^{2+}$ (BAM) paste based on the acid/base properties of the particle surface. <i>Materials Chemistry and Physics</i> , 2009, 113, 909-912.	2.0	2
177	Microstructure and mechanical properties of zirconia-based thermal barrier coatings with starting powder morphology. <i>Surface and Coatings Technology</i> , 2009, 204, 802-806.	2.2	18
178	Two-dimensional nanohybridization of gold nanorods and polystyrene colloids. <i>Applied Physics Letters</i> , 2009, 94, 084104.	1.5	23
179	High-Removal Selectivity Through Interaction Between Polyacrylamide and $\text{SiO}_2$ Film in Poly Isolation Chemical Mechanical Planarization. <i>Journal of Nanoscience and Nanotechnology</i> , 2009, 9, 3780-3784.	0.9	12
180	Comparison of multiwalled carbon nanotubes and carbon black as percolative paths in aqueous-based natural graphite negative electrodes with high-rate capability for lithium-ion batteries. <i>Journal of Power Sources</i> , 2008, 184, 308-311.	4.0	36

#	ARTICLE	IF	CITATIONS
181	Dispersion properties of aqueous-based LiFePO <sub>4</sub> pastes and their electrochemical performance for lithium batteries. <i>Ultramicroscopy</i> , 2008, 108, 1256-1259.	0.8	68
182	Surface Polarity and Shape-Controlled Synthesis of ZnO Nanostructures on GaN Thin Films Based on Catalyst-Free Metalorganic Vapor Phase Epitaxy. <i>Advanced Materials</i> , 2008, 20, 4464-4469.	11.1	44
183	Crack suppression and residual stress in BaTiO <sub>3</sub> based Ni-MLCCs of Y5V specification through post-process. <i>Journal of Materials Processing Technology</i> , 2008, 205, 160-167.	3.1	7
184	Shrinkage behavior and interfacial diffusion in Ni-based internal electrodes with BaTiO <sub>3</sub> additive. <i>Ceramics International</i> , 2008, 34, 1487-1494.	2.3	8
185	Crystalline structure of ceria particles controlled by the oxygen partial pressure and STI CMP performances. <i>Ultramicroscopy</i> , 2008, 108, 1292-1296.	0.8	20
186	Effect of hydroxyl groups in PVB on the microstructure of electrophoretically deposited green bodies for thermal barrier coatings. <i>Colloids and Surfaces A: Physicochemical and Engineering Aspects</i> , 2008, 313-314, 23-26.	2.3	7
187	Anisotropic mechanical properties and contact damage in air-plasma-sprayed thermal barrier coatings with bond coating nature and thermal exposure condition. <i>Progress in Organic Coatings</i> , 2008, 61, 300-307.	1.9	8
188	Phase transformation and oxidation behavior of Pt-modified MCrAlY coatings. <i>Progress in Organic Coatings</i> , 2008, 61, 316-320.	1.9	14
189	Exfoliation of Single-Walled Carbon Nanotubes Induced by the Structural Effect of Perylene Derivatives and Their Optoelectronic Properties. <i>Journal of Physical Chemistry C</i> , 2008, 112, 15267-15273.	1.5	35
190	Nanoscale Patterns of Oligonucleotides Formed by Electrohydrodynamic Jet Printing with Applications in Biosensing and Nanomaterials Assembly. <i>Nano Letters</i> , 2008, 8, 4210-4216.	4.5	205
191	Refractive index engineering of transparent ZrO <sub>2</sub> -polydimethylsiloxane nanocomposites. <i>Journal of Materials Chemistry</i> , 2008, 18, 1751.	6.7	123
192	Effect of Carboxymethyl Cellulose on Aqueous Processing of LiFePO <sub>4</sub> Cathodes and Their Electrochemical Performance. <i>Electrochemical and Solid-State Letters</i> , 2008, 11, A175.	2.2	35
193	Catalyst-free synthesis and cathodoluminescent properties of ZnO nanobranches on Si nanowire backbones. <i>Journal of Materials Research</i> , 2008, 23, 3403-3408.	1.2	7
194	Effect of Alkaline Agent on Polishing Rate of Nitrogen-Doped Ge <sub>2</sub> Sb <sub>2</sub> Te <sub>5</sub> Film in Chemical Mechanical Polishing. <i>Electrochemical and Solid-State Letters</i> , 2008, 11, H288.	2.2	18
195	Effect of abrasive material properties on polishing rate selectivity of nitrogen-doped Ge <sub>2</sub> Sb <sub>2</sub> Te <sub>5</sub> to SiO <sub>2</sub> film in chemical mechanical polishing. <i>Journal of Materials Research</i> , 2008, 23, 3323-3329.	1.2	12
196	Constraints on removal of Si <sub>3</sub> N <sub>4</sub> film with conformation-controlled poly(acrylic acid) in shallow-trench isolation chemical-mechanical planarization (STI CMP). <i>Journal of Materials Research</i> , 2008, 23, 49-54.	1.2	15
197	Design of fine phosphor system for the improvement in the luminescent properties of the phosphor layer in the plasma display panel: Theoretical and experimental analysis. <i>Applied Physics Letters</i> , 2008, 93, .	1.5	12
198	Growth of nitrogen doped ZnO films through a nitrogen diffusion process from WN films formed by a cosputtering technique. <i>Journal of Vacuum Science &amp; Technology B</i> , 2008, 26, 1696.	1.3	4

#	ARTICLE	IF	CITATIONS
199	Effect of Alkaline Agent in Colloidal Silica Slurry for Polycrystalline Silicon Chemical Mechanical Polishing. Japanese Journal of Applied Physics, 2007, 46, 5089-5094.	0.8	24
200	Nanotopography Impact of Surfactant Concentration and Molecular Weight of Nano-ceria Slurry on Remaining Oxide Thickness Variation after Shallow Trench Isolation Chemical Mechanical Polishing. Japanese Journal of Applied Physics, 2007, 46, 5076.	0.8	3
201	Effects of Calcination and Milling Process Conditions for Ceria Slurry on Shallow-Trench-Isolation Chemical Mechanical Polishing Performance. Japanese Journal of Applied Physics, 2007, 46, 7671.	0.8	9
202	Luminescent properties of BaMgAl10O17:Eu <sup>2+</sup> phosphor layer prepared with phosphate ester. Journal of Materials Research, 2007, 22, 3309-3315.	1.2	5
203	Influence of Crystalline Structure of Ceria on the Remaining Particles in the STI CMP. Journal of the Electrochemical Society, 2007, 154, H642.	1.3	11
204	Effects of abrasive particle size and molecular weight of poly(acrylic acid) in ceria slurry on removal selectivity of SiO <sub>2</sub> /Si <sub>3</sub> N <sub>4</sub> films in shallow trench isolation chemical mechanical planarization. Journal of Materials Research, 2007, 22, 777-787.	1.2	16
205	Dispersion Stability of Single-Walled Carbon Nanotubes Using Nafion in Bisolvent. Journal of Physical Chemistry C, 2007, 111, 2477-2483.	1.5	66
206	A new design strategy for dispersion stabilization of Ni particles based on the surface acid and base properties of Ni particles. Journal of Colloid and Interface Science, 2007, 312, 265-271.	5.0	4
207	Effects of the Size and the Concentration of the Abrasive in a Colloidal Silica (SiO <sub>2</sub> ) Slurry with Added TMAH on Removal Selectivity of Polysilicon and Oxide Films in Polysilicon Chemical Mechanical Polishing. Journal of the Korean Physical Society, 2007, 51, 214.	0.3	10
208	Dispersant-Ethyl Cellulose Binder Interactions at the Ni Particle-Dihydroterpineol Interface. Journal of the American Ceramic Society, 2006, 89, 3050-3055.	1.9	26
209	Effect of thermal fatigue on mechanical characteristics and contact damage of zirconia-based thermal barrier coatings with HVOF-sprayed bond coat. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2006, 429, 173-180.	2.6	24
210	Effect of poly(acrylic acid) on adhesion strength and electrochemical performance of natural graphite negative electrode for lithium-ion batteries. Journal of Power Sources, 2006, 161, 612-616.	4.0	110
211	Mechanical characterization and thermal behavior of HVOF-sprayed bond coat in thermal barrier coatings (TBCs). Surface and Coatings Technology, 2006, 200, 4355-4362.	2.2	59
212	Effect of bond coat nature and thickness on mechanical characteristic and contact damage of zirconia-based thermal barrier coatings. Surface and Coatings Technology, 2006, 201, 3483-3490.	2.2	28
213	Improvement in the volume efficiency of multilayered ceramic capacitors (MLCCs). Journal of Electroceramics, 2006, 17, 351-354.	0.8	2
214	Surface modification of BaTiO <sub>3</sub> with yttrium, and dissolution and adsorption/precipitation behaviors of BaTiO <sub>3</sub> . Journal of Electroceramics, 2006, 17, 355-358.	0.8	2
215	Microstructural evolution of BaTiO <sub>3</sub> /ultrahigh-molecular-weight poly(ethylene) (UHMWPE) cast body: influence of free organic additive in a nonaqueous medium. Journal of Electroceramics, 2006, 17, 345-349.	0.8	1
216	The effect of carboxymethyl cellulose swelling on the stability of natural graphite particulates in an aqueous medium for lithium ion battery anodes. Journal of Electroceramics, 2006, 17, 657-660.	0.8	39

#	ARTICLE	IF	CITATIONS
217	The Effect of the physico-chemical properties of cellulosic polymers on the Si wafer polishing process. <i>Journal of Electroceramics</i> , 2006, 17, 835-839.	0.8	10
218	Crack formation in MLCCs depending on position with and without post-heat treatment. <i>Journal of Electroceramics</i> , 2006, 17, 381-385.	0.8	3
219	The effect of heat-treatment on the suspension stability and gelation behavior of $\text{Li}_2\text{O}\text{--}\text{BaO}\text{--}\text{Al}_2\text{O}_3\text{--}\text{SiO}_2\text{--}\text{CaO}$ (LBASC). <i>Materials Chemistry and Physics</i> , 2006, 99, 418-423.	2.0	8
220	Reduction of Large Particles in Ceria Slurry by Aging and Selective Sedimentation and its Effect on Shallow Trench Isolation Chemical Mechanical Planarization. <i>Japanese Journal of Applied Physics</i> , 2006, 45, 6790-6794.	0.8	12
221	Dependence of Non-Prestonian Behavior of Ceria Slurry with Anionic Surfactant on Abrasive Concentration and Size in Shallow Trench Isolation Chemical Mechanical Polishing. <i>Japanese Journal of Applied Physics</i> , 2006, 45, 3896-3904.	0.8	5
222	Effect of Calcination Process on Synthesis of Ceria Particles, and Its Influence on Shallow Trench Isolation Chemical Mechanical Planarization Performance. <i>Japanese Journal of Applied Physics</i> , 2006, 45, 4893-4897.	0.8	7
223	Atomic force microscopy study of the role of molecular weight of poly(acrylic acid) in chemical mechanical planarization for shallow trench isolation. <i>Journal of Materials Research</i> , 2006, 21, 473-479.	1.2	20
224	Aqueous processing of natural graphite particulates for lithium-ion battery anodes and their electrochemical performance. <i>Journal of Power Sources</i> , 2005, 147, 249-255.	4.0	181
225	Crack suppression behavior with post-process parameters in $\text{BaTiO}_3$ -based Ni-MLCCs. <i>Ceramics International</i> , 2005, 31, 655-661.	2.3	8
226	Rheological and electrokinetic behavior associated with concentrated nanosize silica hydrosols. <i>Materials Chemistry and Physics</i> , 2005, 91, 205-211.	2.0	9
227	Effects of Abrasive Size and Surfactant Concentration on the Non-Prestonian Behavior of Ceria Slurry in Shallow Trench Isolation Chemical Mechanical Polishing. <i>Japanese Journal of Applied Physics</i> , 2005, 44, L136-L139.	0.8	9
228	Agglomerated Large Particles under Various Slurry Preparation Conditions and Their Influence on Shallow Trench Isolation Chemical Mechanical Polishing. <i>Japanese Journal of Applied Physics</i> , 2005, 44, 7770-7776.	0.8	7
229	The Effect of Cerium Precursor Agglomeration on the Synthesis of Ceria Particles and Its Influence on Shallow Trench Isolation Chemical Mechanical Polishing Performance. <i>Japanese Journal of Applied Physics</i> , 2005, 44, 8422-8426.	0.8	9
230	Effect of Dispersant Addition during Ceria Abrasive Milling Process on Light Point Defect (LPD) Formation after Shallow Trench Isolation Chemical Mechanical Polishing (STI-CMP). <i>Japanese Journal of Applied Physics</i> , 2005, 44, L238-L241.	0.8	5
231	Dependence of pH, Molecular Weight, and Concentration of Surfactant in Ceria Slurry on Saturated Nitride Removal Rate in Shallow Trench Isolation Chemical Mechanical Polishing. <i>Japanese Journal of Applied Physics</i> , 2005, 44, 4752-4758.	0.8	11
232	Effect of Carboxymethyl Cellulose on Aqueous Processing of Natural Graphite Negative Electrodes and their Electrochemical Performance for Lithium Batteries. <i>Journal of the Electrochemical Society</i> , 2005, 152, A1763.	1.3	191
233	Synthesis of SiC microtube with villus-like morphology and SiC fiber. <i>Journal of Materials Research</i> , 2005, 20, 409-416.	1.2	10
234	Influence of Physical Characteristics of Ceria Particles on Polishing Rate of Chemical Mechanical Planarization for Shallow Trench Isolation. <i>Japanese Journal of Applied Physics</i> , 2004, 43, 7427-7433.	0.8	23

#	ARTICLE	IF	CITATIONS
235	Dependence of Nanotopography Impact on Abrasive Size and Surfactant Concentration in Ceria Slurry for Shallow Trench Isolation Chemical Mechanical Polishing. Japanese Journal of Applied Physics, 2004, 43, L1-L4.	0.8	13
236	Nanotopography Impact and Non-Prestonian Behavior of Ceria Slurry in Shallow Trench Isolation Chemical Mechanical Polishing (STI-CMP). Japanese Journal of Applied Physics, 2004, 43, L217-L220.	0.8	9
237	A Reverse Selectivity Ceria Slurry for the Damascene Gate Chemical Mechanical Planarization Process. Japanese Journal of Applied Physics, 2004, 43, 7434-7438.	0.8	11
238	Effect of Molecular Weight of Surfactant in Nano Ceria Slurry on Shallow Trench Isolation Chemical Mechanical Polishing (CMP). Japanese Journal of Applied Physics, 2004, 43, L1060-L1063.	0.8	23
239	Analysis of Residual Stress and Damage Durability with Thermal Fatigue Behavior in Thermal Barrier Coatings. Materials Research Society Symposia Proceedings, 2004, 821, 264.	0.1	1
240	Nanotopography impact in shallow-trench isolation chemical mechanical polishing analysis method and consumable dependence. Journal of Materials Research, 2004, 19, 1783-1790.	1.2	3
241	Mullite Precursor Synthesis in Aqueous Conditions: Dependence of Mullite Crystallization and Grain Size and Morphology on Solution pH and Precursor Salt. Journal of Materials Research, 2004, 19, 1133-1138.	1.2	2
242	Effects of Grain Size and Abrasive Size of Polycrystalline Nano-particle Ceria Slurry on Shallow Trench Isolation Chemical Mechanical Polishing. Japanese Journal of Applied Physics, 2004, 43, L365-L368.	0.8	16
243	Microstructure and permittivity of sintered BaTiO <sub>3</sub> : influence of particle surface chemistry in an aqueous medium. Materials Research Bulletin, 2004, 39, 93-102.	2.7	14
244	Evaluation of residual stress in BaTiO <sub>3</sub> -based Ni-MLCCs with X7R characteristics. Journal of Materials Science: Materials in Electronics, 2004, 15, 253-259.	1.1	10
245	Effects of chemical structure and molecular weight of plasticizer on physical properties of green tape in BaTiO <sub>3</sub> /PVB system. Journal of the European Ceramic Society, 2004, 24, 733-738.	2.8	21
246	Green microstructure and mechanical properties of BaTiO <sub>3</sub> -poly(vinyl butyral) tape-cast bodies. Journal of Materials Science Letters, 2003, 22, 1639-1641.	0.5	2
247	Suspension stability and consolidation behavior of ultrafine BaTiO <sub>3</sub> particles in nonazeotropic solvent system. Materials Chemistry and Physics, 2003, 82, 181-187.	2.0	17
248	Pore evolution and microstructure with heating profile in BaTiO <sub>3</sub> -based Ni-MLCCs with Y5V specification. Materials Research Bulletin, 2003, 38, 555-565.	2.7	5
249	Effect of the molecular weight of poly(ethylene glycol) on the plasticization of green sheets composed of ultrafine BaTiO <sub>3</sub> particles and poly(vinyl butyral). Materials Research Bulletin, 2003, 38, 1021-1032.	2.7	22
250	Control of residual stresses with post process in BaTiO <sub>3</sub> -based Ni-MLCCs. Materials & Design, 2003, 24, 169-176.	5.1	12
251	Binder removal and microstructure with burnout conditions in BaTiO <sub>3</sub> based Ni-MLCCs. Ceramics International, 2003, 29, 939-946.	2.3	12
252	Consolidation of aqueous concentrated silicon nitride suspension by direct coagulation casting. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2003, 342, 93-100.	2.6	22

#	ARTICLE	IF	CITATIONS
253	Effect of molecular mass of poly(vinyl butyral) and lamination pressure on the pore evolution and microstructure of BaTiO <sub>3</sub> laminates. <i>Materials Science &amp; Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2003, 362, 174-180.	2.6	11
254	The role of 2-methyl-2,4-pentanediol modifier and its interaction with poly(vinyl butyral) binder in BaTiO <sub>3</sub> and Li <sub>2</sub> O-B <sub>2</sub> O <sub>3</sub> -BaO-SiO <sub>2</sub> glass suspensions. <i>Colloids and Surfaces A: Physicochemical and Engineering Aspects</i> , 2003, 224, 83-91.	2.3	10
255	Internal stresses in BaTiO <sub>3</sub> /Ni MLCCs. <i>Journal of the European Ceramic Society</i> , 2003, 23, 1427-1434.	2.8	43
256	Effects of PVB on the gelation behavior of BaTiO <sub>3</sub> -based dielectric particles and glass suspension. <i>Journal of the European Ceramic Society</i> , 2003, 23, 2315-2322.	2.8	18
257	Influence of [Ba + Ca]/[Ti + Zr] Ratio on the Interfacial Property of (Ba,Ca)(Ti,Zr)O <sub>3</sub> (BCTZ) Powders in an Aqueous Medium. <i>Journal of the American Ceramic Society</i> , 2003, 86, 1034-1036.	1.9	7
258	Influence of Barium Dissolution on the Electrokinetic Properties of Colloidal BaTiO <sub>3</sub> in an Aqueous Medium. <i>Journal of the American Ceramic Society</i> , 2003, 86, 1662-1668.	1.9	24
259	Effects of precursor pH and composition on the grain morphology and size of mullite ceramics in aqueous system. <i>Materials Letters</i> , 2003, 57, 3239-3244.	1.3	7
260	Effect of poly(acrylic acid) and poly(vinyl alcohol) on the solubility of colloidal BaTiO <sub>3</sub> in an aqueous medium. <i>Journal of Materials Research</i> , 2003, 18, 1266-1274.	1.2	17
261	Synthesis behavior and grain morphology in mullite ceramics with precursor pH and sintering temperature. <i>Journal of Materials Research</i> , 2003, 18, 81-87.	1.2	12
262	Influence of the electrokinetic behaviors of abrasive ceria particles and the deposited plasma-enhanced tetraethylorthosilicate and chemically vapor deposited Si <sub>3</sub> N <sub>4</sub> films in an aqueous medium on chemical mechanical planarization for shallow trench isolation. <i>Journal of Materials Research</i> , 2003, 18, 2163-2169.	1.2	37
263	Surfactant Effect on Oxide-to-Nitride Removal Selectivity of Nano-abrasive Ceria Slurry for Chemical Mechanical Polishing. <i>Japanese Journal of Applied Physics</i> , 2003, 42, 5420-5425.	0.8	32
264	Effects of Abrasive Morphology and Surfactant Concentration on Polishing Rate of Ceria Slurry. <i>Japanese Journal of Applied Physics</i> , 2003, 42, 1150-1153.	0.8	42
265	Effects of the Physical Characteristics of Cerium Oxide on Plasma-Enhanced Tetraethylorthosilicate Removal Rate of Chemical Mechanical Polishing for Shallow Trench Isolation. <i>Japanese Journal of Applied Physics</i> , 2003, 42, 1227-1230.	0.8	20
266	The Stability of Nano Fumed Silica Particles and Its Influence on Chemical Mechanical Planarization for Interlayer Dielectrics. <i>Japanese Journal of Applied Physics</i> , 2002, 41, 4509-4512.	0.8	10
267	Dissolution and reprecipitation of barium at the particulate BaTiO <sub>3</sub> -aqueous solution interface. <i>Materials Research Bulletin</i> , 2002, 37, 1623-1631.	2.7	19
268	Effect of particle dispersion on microstructure and strength of reaction-bonded silicon carbide. <i>Materials Science &amp; Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2002, 334, 267-274.	2.6	53
269	Effect of particle size on gelcasting process and green properties in alumina. <i>Materials Science &amp; Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2002, 337, 212-221.	2.6	45
270	Effects of precursor pH and sintering temperature on synthesizing and morphology of sol-gel processed mullite. <i>Ceramics International</i> , 2002, 28, 935-940.	2.3	42



#	ARTICLE	IF	CITATIONS
271	Title is missing!. Journal of Materials Science Letters, 2000, 19, 2113-2116.	0.5	1
272	Influence of Solids Concentration on the Isoelectric Point of Aqueous Barium Titanate. Journal of the American Ceramic Society, 2000, 83, 2381-2384.	1.9	51
273	Dispersant-Binder Interactions in Aqueous Silicon Nitride Suspensions. Journal of the American Ceramic Society, 1999, 82, 833-840.	1.9	73
274	The effect of electrostatic repulsive forces on the stability of BaTiO <sub>3</sub> particles suspended in non-aqueous media. Colloids and Surfaces A: Physicochemical and Engineering Aspects, 1998, 135, 77-88.	2.3	74
275	Aqueous Processing of Sintered Reaction-Bonded Silicon Nitride: I, Dispersion Properties of Silicon Powder. Journal of the American Ceramic Society, 1997, 80, 1781-1788.	1.9	50
276	Dispersion of alumina and silica powders in non-aqueous media: Mixed-solvent effects. Ceramics International, 1993, 19, 241-250.	2.3	17
277	Effect of aminosilane adsorption on rheology of silica powders in nonaqueous media. Journal of Materials Science, 1992, 27, 5692-5700.	1.7	12