List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/1111286/publications.pdf Version: 2024-02-01



| # | Article | IF | CITATIONS |
|----|--|--------------------|-------------------------------|
| 1 | Piezoelectric sensor based on electrospun poly(vinylidene fluoride)/sulfonated poly(1,4â€phenylene) Tj ETQq1 1 | 0.78431 | 4 rg <mark></mark> BT /Overlo |
| 2 | Polysomnographic Observation Using Triboelectric Pressure Sensor Composed of Polymer-Pairs Having Coarse Surface. Fibers and Polymers, 2022, 23, 1490-1499. | 2.1 | 9 |
| 3 | New Evaluation Methods of Average Molecular Weight and the Degree of Branching of Poly(1,4-phenylene sulfide) Samples through Their Partial Sulfonation. Fibers and Polymers, 2022, 23, 900-913. | 2.1 | 1 |
| 4 | Piezoelectric-piezocapacitive hybrid sensor based on electrospun Poly(vinylidene) Tj ETQq0 0 0 rgBT /Overlock 1 Sensors and Actuators A: Physical, 2021, 331, 112993. | .0 Tf 50 62 4.1 | 27 Td (fluoride 11 |
| 5 | Multilayered Fabric Pressure Sensor for Real-Time Piezo-Impedance Imaging of Pressure Distribution. IEEE Transactions on Instrumentation and Measurement, 2020, 69, 565-572. | 4.7 | 15 |
| 6 | Lifetime Prediction of High Tenacity Polyester Yarns for Hydrolytic Degradation Used for Soil Reinforcement. Fibers and Polymers, 2020, 21, 1663-1668. | 2.1 | 3 |
| 7 | Novel Hybrid Pressure Sensor Based on Electrospun Spandex-Polyvinylidene Fluoride Composite Nanofiber Webs. Fibers and Polymers, 2020, 21, 2962-2975. | 2.1 | 5 |
| 8 | Electrospun Polyvinylidene Fluoride-Polyoctafluoropentyl Acrylate-Hydroxyapatite Blend Based Piezoelectric Pressure Sensors. Macromolecular Research, 2019, 27, 743-749. | 2.4 | 24 |
| 9 | Electrospun Spandex Nanofiber Webs with Ionic Liquid for Highly Sensitive, Low Hysteresis Piezocapacitive Sensor. Fibers and Polymers, 2019, 20, 337-347. | 2.1 | 11 |
| 10 | Infrared spectroscopic studies on crystalline phase transition of PVDF and PVDF/hyperbranched polyester blend ultrathin films. Vibrational Spectroscopy, 2018, 94, 74-82. | 2.2 | 10 |
| 11 | Integration of piezo-capacitive and piezo-electric nanoweb based pressure sensors for imaging of static and dynamic pressure distribution. , 2017, 2017, 21-24. | | 2 |
| 12 | Piezoelectric characteristics of electrospun PVDF as a function of phase-separation temperature and metal salt content. Macromolecular Research, 2017, 25, 981-988. | 2.4 | 32 |
| 13 | Uniaxially drawn polylactic acid film based physiological sensor for monitoring sleeping parameters. Fibers and Polymers, 2017, 18, 1898-1905. | 2.1 | 7 |
| 14 | Highly precise nanofiber web-based dry electrodes for vital signal monitoring. RSC Advances, 2016, 6, 40045-40057. | 3.6 | 15 |
| 15 | Electrospun polyvinylidene fluoride-polyoctafluoropentyl acrylate blend based piezocapacitive pressure sensors. Macromolecular Research, 2016, 24, 670-674. | 2.4 | 26 |
| 16 | Hyperbranched polyester as a crosslinker in polyurethane formation: real-time monitoring using in situ FTIR. Polymer Bulletin, 2016, 73, 2867-2888. | 3.3 | 13 |
| 17 | FTIR studies on polymorphic control of PVDF ultrathin films by heat-controlled spin coater. Journal of Materials Science, 2016, 51, 3619-3627. | 3.7 | 21 |
| 18 | Preparation and evaluation of poly(vinylidene fluoride)-sulfonated poly(1,4-phenylene sulfide) based membranes with improved hydrophilicity. Macromolecular Research, 2015, 23, 86-93. | 2.4 | 11 |

| # | Article | IF | CITATIONS |
|----|---|-----|-----------|
| 19 | Piezoelectric properties of electrospun poly(l-lactic acid) nanofiber web. Materials Letters, 2015, 148, 58-62. | 2.6 | 77 |
| 20 | Physical properties and fibrillation tendency of regenerated cellulose fiber dry jet-wet spun from high-molecular weight cotton linter Pulp/NMMO solution. Fibers and Polymers, 2015, 16, 1618-1628. | 2.1 | 12 |
| 21 | Dyeing behavior of chemically modified poly(1,4-phenylene sulfide) fiber towards disperse, anionic, and cationic dyes. Fibers and Polymers, 2014, 15, 1168-1174. | 2.1 | 4 |
| 22 | Nanofiber Web Textile Dry Electrodes for Long-Term Biopotential Recording. IEEE Transactions on Biomedical Circuits and Systems, 2013, 7, 204-211. | 4.0 | 89 |
| 23 | Transition from Nanorod to Nanotube of Poly(vinylidene trifluoroethylene) Ferroelectric Nanofiber. Macromolecules, 2013, 46, 3067-3073. | 4.8 | 19 |
| 24 | Cyclodextrin-Based Nanocomplexes for Sustained Delivery of Human Growth Hormone. Journal of Nanoscience and Nanotechnology, 2013, 13, 7306-7311. | 0.9 | 7 |
| 25 | Preparation and Characterization of Cotton Linter Based Regenerated Cellulose Fiber by Dry Jet-wet Spinning. Textile Science and Engineering, 2013, 50, 25-34. | 0.4 | 4 |
| 26 | Effect of Thermal Cycling on the Ferroelectric Characteristics of Vinylidene Fluoride-Trifluoroethylene Copolymer Thin Films. Advanced Materials Research, 2012, 584, 201-204. | 0.3 | 1 |
| 27 | Synthetic Studies and Structural Aspects of some Metallacyclic Derivatives of Titanium (IV) - Better Precursors for Titania. Advanced Materials Research, 2012, 584, 411-414. | 0.3 | 1 |
| 28 | Flexible electrode belt for EIT using nanofiber web dry electrodes. Physiological Measurement, 2012, 33, 1603-1616. | 2.1 | 18 |
| 29 | Molecular chaperone-like hyaluronic acid nanoparticles: Implications as the carrier for protein delivery systems. Macromolecular Research, 2012, 20, 1007-1010. | 2.4 | 4 |
| 30 | Simple Synthesis of Palladium Nanoparticles, β-Phase Formation, and the Control of Chain and Dipole Orientations in Palladium-Doped Poly(vinylidene fluoride) Thin Films. Langmuir, 2012, 28, 10310-10317. | 3.5 | 154 |
| 31 | Respiration Monitoring Using an Electromagnetic Interference Shielding PVDF Film-Embedded Elastic Belt. Textile Science and Engineering, 2012, 49, 392-401. | 0.4 | 2 |
| 32 | Fabrication of micropatterned ferroelectric gamma poly(vinylidene fluoride) film for non-volatile polymer memory. Journal of Materials Chemistry, 2011, 21, 3619. | 6.7 | 41 |
| 33 | Origin of Piezoelectricity in an Electrospun Poly(vinylidene fluorideâ€ŧrifluoroethylene) Nanofiber Webâ€Based Nanogenerator and Nanoâ€Pressure Sensor. Macromolecular Rapid Communications, 2011, 32, 831-837. | 3.9 | 316 |
| 34 | Influence of the organic electrolyte and anodization conditions on the preparation of well-aligned TiO2 nanotube arrays in dye-sensitized solar cells. Solar Energy, 2011, 85, 1551-1559. | 6.1 | 35 |
| 35 | Effect of Dissolved Cadmium Chloride and Ammonium Chloride Salts on the Enthalpy of Mixing of the Methanol + Benzene System at 303.15 K. Chinese Journal of Chemical Engineering, 2010, 18, 995-999. – | 3.5 | 2 |
| 36 | Annealing effect upon chain orientation, crystalline morphology, and polarizability of ultra-thin P(VDF-TrFE) film for nonvolatile polymer memory device. Polymer, 2010, 51, 6319-6333. | 3.8 | 80 |

| # | Article | IF | CITATIONS |
|----|--|---------------------|------------------|
| 37 | Effect of Dissolved Inorganic Salts on the Enthalpy of Mixing of the Ethanol + Pyridine System at 303.15 K. Journal of Chemical & Engineering Data, 2010, 55, 3567-3571. | 1.9 | 4 |
| 38 | A NOVEL PIEZOELECTRIC PVDF FILM-BASED PHYSIOLOGICAL SENSING BELT FOR A COMPLEMENTARY RESPIRATION AND HEARTBEAT MONITORING SYSTEM. Integrated Ferroelectrics, 2009, 107, 53-68. | 0.7 | 42 |
| 39 | Printable Ferroelectric PVDF/PMMA Blend Films with Ultralow Roughness for Low Voltage Nonâ€Volatile Polymer Memory. Advanced Functional Materials, 2009, 19, 2812-2818. | 14.9 | 239 |
| 40 | Crystalline Structure and Ferroelectric Response of Poly(vinylidene fluoride)/Organically Modified Silicate Thin Films Prepared by Heat Controlled Spin Coating. Macromolecular Chemistry and Physics, 2009, 210, 951-960. | 2.2 | 40 |
| 41 | Preparation and characterization of nylon 6/organoclay nanocomposite filament fibers. Polymer Composites, 2009, 30, 265-273. | 4.6 | 10 |
| 42 | Deterioration in mechanical properties of glass fiberâ€reinforced nylon 6,6 composites by aqueous calcium chloride mixture solutions. Polymer Composites, 2009, 30, 481-489. | 4.6 | 9 |
| 43 | Effect of thickness on the crystallinity and Curie transition behavior in P(VDF/TrFE) (72/28) copolymer thin films using FTIR-transmission spectroscopy. Vibrational Spectroscopy, 2009, 49, 101-109. | 2.2 | 43 |
| 44 | Polymeric gate dielectric interlayer of cross-linkable poly(styrene-r-methylmethacrylate) copolymer for ferroelectric PVDF-TrFE field effect transistor memory. Organic Electronics, 2009, 10, 849-856. | 2.6 | 40 |
| 45 | UCST-Type Phase Separation and Crystallization Behavior in Poly(vinylidene fluoride)/Poly(methyl) Tj ETQq1 1 0.78 | 34314 rgB 4.8 | T_Qverlock |
| 46 | Preferential formation of electroactive crystalline phases in poly(vinylidene fluoride)/organically modified silicate nanocomposites. Journal of Polymer Science, Part B: Polymer Physics, 2008, 46, 2173-2187. | 2.1 | 147 |
| 47 | Synthesis and characterization of poly(trimethylene terephthalate)/polyhedral oligomeric silsesquixanes nanocomposites. Polymer Composites, 2008, 29, 894-901. | 4.6 | 13 |
| 48 | Physical properties of poly(trimethylene terephthalate)/organoclay nanocomposites obtained via melt compounding and in situ polymerization. Polymer Composites, 2008, 29, 1328-1336. | 4.6 | 10 |
| 49 | Direct Preparation of Nanoscale Thin Films of Poly(vinylidene fluoride) Containing <i>β</i> â€Crystalline Phase by Heatâ€Controlled Spin Coating. Macromolecular Chemistry and Physics, 2008, 209, 2516-2526. | 2.2 | 96 |
| 50 | Metal Saltâ€Induced Ferroelectric Crystalline Phase in Poly(vinylidene fluoride) Films. Macromolecular Rapid Communications, 2008, 29, 1316-1321. | 3.9 | 66 |
| 51 | Studies on the recycling of glycolyzed nylon 66 using novel chain extenders. Polymer Degradation and Stability, 2008, 93, 392-400. | 5.8 | 11 |
| 52 | Ordered Ferroelectric PVDFâ^'TrFE Thin Films by High Throughput Epitaxy for Nonvolatile Polymer Memory. Macromolecules, 2008, 41, 8648-8654. | 4.8 | 105 |
| 53 | Phase Separation and Crystallization Behavior of Poly(vinylidene fluoride)/Poly(1,4-butylene adipate) Blends under an Electric Field. Macromolecules, 2008, 41, 3598-3604. | 4.8 | 16 |
| 54 | Molecular and Crystalline Microstructure of Ferroelectric Poly(vinylidene) Tj ETQq0 0 0 rgBT /Overlock 10 Tf 50 67 | ' Td (fluori 4.8 | de- <i>co</i> 50 |

| # | Article | IF | CITATIONS |
|----|--|------------------|----------------------|
| 55 | Fabrication and Electrical Studies of P(VDF/TrFE)(72/28) Copolymer based Non-Volatile Memory Devices as a Function of Varying Device Structures. Materials Research Society Symposia Proceedings, 2008, 1071, 1. | 0.1 | 0 |
| 56 | Comparative electrical bistable characteristics of ferroelectric poly(vinylidene) Tj ETQq0 0 0 rgBT /Overlock 10 Tf Physics Letters, 2008, 93, 182902. | 50 707 Td 3.3 | (fluoride-trif 30 |
| 57 | Spin cast ferroelectric beta poly(vinylidene fluoride) thin films via rapid thermal annealing. Applied Physics Letters, 2008, 92, . | 3.3 | 141 |
| 58 | Recovery of remanent polarization of poly(vinylidene fluoride-co-trifluoroethylene) thin film after high temperature annealing using topographically nanostructured aluminium bottom electrode. Applied Physics Letters, 2007, 90, 222903. | 3.3 | 23 |
| 59 | In-situ Synthesis and Characterization of Polyamide 6/POSS Nanocomposites. Macromolecular Symposia, 2007, 249-250, 295-302. | 0.7 | 27 |
| 60 | Heartbeat Monitoring Technique Based on Corona-Poled PVDF Film Sensor for Smart Apparel Application. Solid State Phenomena, 2007, 124-126, 299-302. | 0.3 | 25 |
| 61 | Ultrathin Ferroelectric P(VDF/TrFE) Copolymer Film in Low-Cost Non-Volatile Data Storage Applications. Macromolecular Symposia, 2007, 249-250, 13-20. | 0.7 | 13 |
| 62 | Degradation of Nylon 6,6 and Class Fiber Reinforced Nylon 6,6 by Aqueous Solutions of Ethylene Glycol and Calcium Chloride. ACS Symposium Series, 2007, , 103-113. | 0.5 | 0 |
| 63 | Localized Pressure-Induced Ferroelectric Pattern Arrays of Semicrystalline Poly(vinylidene fluoride) by Microimprinting. Advanced Materials, 2007, 19, 581-586. | 21.0 | 100 |
| 64 | Origin of deterioration in mechanical properties of glass fiber reinforced nylon 6,6 composites by aqueous ethylene glycol solution. Polymer Composites, 2007, 28, 778-784. | 4.6 | 8 |
| 65 | Poly(vinylidene fluoride)/poly(ethylene-co-vinyl acetate) (20/80) blend. II. Crystalline structure and morphology. Fibers and Polymers, 2007, 8, 335-346. | 2.1 | 4 |

66

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 73 | Spinodal phase separation and isothermal crystallization behavior in blends of VDF/TrFE(75/25) copolymer and poly(1,4-butylene adipate) (I). Fibers and Polymers, 2003, 4, 188-194. | 2.1 | 5 |
| 74 | Release of albumin from chitosan-coated pectin beads in vitro. International Journal of Pharmaceutics, 2003, 250, 371-383. | 5.2 | 92 |
| 75 | Determination of intrinsic physical constants of poly(trimethylene terephthalate) from drawn filament. Polymer International, 2003, 52, 35-41. | 3.1 | 9 |
| 76 | Effect of P(MMA-co-MAA) compatibilizer on the miscibility of nylon 6/PVDF blends. European Polymer Journal, 2003, 39, 1249-1265. | 5.4 | 30 |
| 77 | Infrared spectroscopic analysis of poly(trimethylene terephthalate). Polymer, 2001, 42, 1023-1033. | 3.8 | 59 |
| 78 | Miscibility, phase behavior, and Curie transition in blends of vinylidene fluoride/trifluoroethylene copolymer and Poly(1,4-butylene adipate). Polymer, 1999, 40, 6125-6134. | 3.8 | 9 |
| 79 | Toughening and phase separation behavior of nylon 6-PEG block copolymers andin situ nylon 6-PEG blend viain situ anionic polymerization. Journal of Applied Polymer Science, 1999, 73, 1285-1303. | 2.6 | 20 |
| 80 | Phase Diagram and Photopolymerization Behavior of Mixtures of UV-Curable Multifunctional Monomer and Low Molar Mass Nematic Liquid Crystal. Macromolecules, 1998, 31, 6806-6812. | 4.8 | 54 |
| 81 | Curie transition, ferroelectric crystal structure and ferroelectricity of a VDF/TrFE (7525) copolymer: 2. The effect of poling on Curie transition and ferroelectric crystal structure. Polymer, 1997, 38, 4881-4889. | 3.8 | 48 |
| 82 | Kinetics of adiabatic anionic copolymerization of ?-caprolactam in the presence of various activators. Journal of Applied Polymer Science, 1997, 66, 1195-1207. | 2.6 | 27 |
| 83 | Mechanism and kinetics of adiabatic anionic polymerization of ε-caprolactam in the presence of various activators. Journal of Applied Polymer Science, 1995, 57, 1347-1358. | 2.6 | 28 |
| 84 | Factors determining the formation of the β crystalline phase of poly(vinylidene fluoride) in poly(vinylidene fluoride)-poly(methyl methacrylate) blends. Vibrational Spectroscopy, 1995, 9, 147-159. | 2.2 | 67 |
| 85 | Curie transition, ferroelectric crystal structure, and ferroelectricity of a VDF/TrFE(75/25) copolymer 1. The effect of the consecutive annealing in the ferroelectric state on curie transition and ferroelectric crystal structure. Journal of Polymer Science, Part B: Polymer Physics, 1994, 32, 2444 | 2.1 | 56 |
| 86 | An infra-red spectroscopic study of structural reorganization of a uniaxially drawn VDF/TrFE copolymer in an electric field. Polymer, 1994, 35, 3612-3618. | 3.8 | 27 |
| 87 | Curie transition and piezoelectricity of the blends of a ferroelectric VDF/TrFE copolymer and PMMA. Journal of Applied Polymer Science, 1993, 47, 1781-1789. | 2.6 | 12 |
| 88 | Miscibility, crystallization, and melting of the blends of a ferroelectric VDF/TrFE copolymer and PMMA. Journal of Applied Polymer Science, 1993, 49, 7-13. | 2.6 | 8 |
| 89 | Spectroscopic studies on the effect of field strength upon the curie transition of a VDF/TrFE copolymer. Journal of Polymer Science, Part B: Polymer Physics, 1993, 31, 1555-1566. | 2.1 | 15 |
| 90 | Degradation mechanism and morphological change of PET by PEG–diamine. Journal of Applied Polymer Science, 1989, 37, 2855-2871. | 2.6 | 6 |

| # | Article | IF | CITATIONS |
|----|---|-----|-----------|
| 91 | The evaluation of the surface characteristic of the PET film and fabric treated with PEG–diamine. Journal of Applied Polymer Science, 1986, 32, 6017-6024. | 2.6 | 20 |
| 92 | Ferroelectric P(VDF/TrFE) Ultrathin Film for SPM-Based Data Storage Devices. Solid State Phenomena, 0, 124-126, 303-306. | 0.3 | 9 |
| 93 | PVDF Nanoweb Touch Sensors Prepared Using Electro-Spinning Process for Smart Apparels Applications. Advances in Science and Technology, 0, , . | 0.2 | 11 |
| 94 | Spin-Coating Temperature Induced Changes in Ferroelectric Crystallinity in Polyvinylidene Fluoride Ultrathin Films. Advanced Materials Research, 0, 584, 197-200. | 0.3 | 9 |
| 95 | Alkoxyalkanol Modified Ti(OCHMe ₂) ₄ : Synthesis and Characterization of Novel [(OPr ⁱ) _{4-n} Ti (OC ₂ H ₄ OR) _n]. Advanced Materials Research. 0. 584, 415-419. | 0.3 | 2 |