

Virgil Provenzano

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/11376659/publications.pdf>

Version: 2024-02-01

9
papers

1,124
citations

1684188

5
h-index

1474206

9
g-index

11
all docs

11
docs citations

11
times ranked

1220
citing authors

#	ARTICLE	IF	CITATIONS
1	Hysteresis of magnetostructural transitions: Repeatable and non-repeatable processes. Physica B: Condensed Matter, 2014, 435, 138-143.	2.7	5
2	Modeling the fractional magnetic states of magnetostructural transformations. Physica B: Condensed Matter, 2014, 435, 50-53.	2.7	2
3	Magnetization model for a Heusler alloy. Journal of Applied Physics, 2013, 113, .	2.5	3
4	Characterization of the Mixed-Phase States Using Self-Similarity Phenomenon for First-Order Magnetocaloric Metamagnets. IEEE Transactions on Magnetics, 2012, 48, 3992-3994.	2.1	0
5	Reorientation of magnetic dipoles at the antiferroelectric-paraelectric phase transition of $\langle \text{mml:math xmlns:mml="http://www.w3.org/1998/Math/MathML" display="inline"> < \text{mml:mrow} < \text{mml:msub} < \text{mml:mrow} < \text{mml:mtext} > \text{Bi} < / \text{mml:mtext} > < / \text{mml:mrow} > < \text{mml:mn} > 1 < / \text{mml:mn} > \langle / \text{mml:mrow} > \langle / \text{mml:math} >$ Physical Review B, 2010, 81, .	3.2	117
6	Effects of variations in coating materials and process conditions on the thermal cycle properties of NiCrAlY/YSZ thermal barrier coatings. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2006, 425, 94-106.	5.6	49
7	Phase formation, crystal chemistry, and properties in the system $\text{Bi}_2\text{O}_3\text{-Fe}_2\text{O}_3\text{-Nb}_2\text{O}_5$. Journal of Solid State Chemistry, 2006, 179, 3900-3910.	2.9	123
8	Reduction of hysteresis losses in the magnetic refrigerant $\text{Gd}_5\text{Ge}_2\text{Si}_2$ by the addition of iron. Nature, 2004, 429, 853-857.	27.8	747
9	Effects of surface oxidation during HVOF processing on the primary stage oxidation of a CoNiCrAlY coating. Surface and Coatings Technology, 2004, 185, 228-233.	4.8	74