

Alessandro Trifiletti

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/11648225/alessandro-trifiletti-publications-by-year.pdf>

Version: 2024-04-26

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

70
papers

701
citations

16
h-index

24
g-index

77
ext. papers

867
ext. citations

2
avg, IF

3.94
L-index

#	Paper	IF	Citations
70	A New Fully Closed-Loop, High-Precision, Class-AB CCII for Differential Capacitive Sensor Interfaces. <i>Electronics (Switzerland)</i> , 2022 , 11, 903	2.6	
69	An improved reversed miller compensation technique for three-stage CMOS OTAs with double pole-zero cancellation and almost single-pole frequency response. <i>International Journal of Circuit Theory and Applications</i> , 2020 , 48, 1990-2005	2	3
68	0.6-V CMOS cascode OTA with complementary gate-driven gain-boosting and forward body bias. <i>International Journal of Circuit Theory and Applications</i> , 2020 , 48, 15-27	2	12
67	. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , 2018 , 65, 1504-1508	3.5	11
66	Streamline calibration modelling for a comprehensive design of ATI-based digitizers. <i>Measurement: Journal of the International Measurement Confederation</i> , 2018 , 125, 386-393	4.6	15
65	A Novel 0.6V MCML D-Latch Topology exploiting Dynamic Body Bias Threshold Lowering 2018 ,		1
64	Low power DDA-based instrumentation amplifier for neural recording applications in 65 nm CMOS. <i>AEU - International Journal of Electronics and Communications</i> , 2018 , 92, 30-35	2.8	19
63	Fully Differential Class-AB OTA with Improved CMRR. <i>Journal of Circuits, Systems and Computers</i> , 2017 , 26, 1750169	0.9	1
62	Multivariate Analysis Exploiting Static Power on Nanoscale CMOS Circuits for Cryptographic Applications. <i>Lecture Notes in Computer Science</i> , 2017 , 79-94	0.9	4
61	Template attacks exploiting static power and application to CMOS lightweight crypto-hardware. <i>International Journal of Circuit Theory and Applications</i> , 2017 , 45, 229-241	2	11
60	Novel measurements setup for attacks exploiting static power using DC pico-ammeter 2017 ,		4
59	A new class-AB Flipped Voltage Follower using a common-gate auxiliary amplifier 2016 ,		6
58	A shared memory, parameterized and configurable in FPGA, for use in multiprocessor systems 2016 ,		2
57	Comparative performance analysis and complementary triode based CMFB circuits for fully differential class AB symmetrical OTAs with low power consumption. <i>International Journal of Circuit Theory and Applications</i> , 2016 , 44, 1039-1054	2	15
56	CMOS Non-tailed differential pair. <i>International Journal of Circuit Theory and Applications</i> , 2016 , 44, 1468-1477	4	
55	Design and validation through a frequency-based metric of a new countermeasure to protect nanometer ICs from side-channel attacks. <i>Journal of Cryptographic Engineering</i> , 2015 , 5, 269-288	1.9	11
54	Subsampling Models of Bandwidth Mismatch for Time-Interleaved Converter Calibration. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , 2015 , 62, 957-961	3.5	9

53	Leakage Power Analysis attacks against a bit slice implementation of the Serpent block cipher 2014		7
52	88- μ S A 1-MHz Stray-Insensitive CMOS Current-Mode Interface IC for Differential Capacitive Sensors. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2014 , 61, 1905-1916	3.9	29
51	Effectiveness of Leakage Power Analysis Attacks on DPA-Resistant Logic Styles Under Process Variations. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2014 , 61, 429-442	3.9	36
50	Adaptive frequency compensation for maximum and constant bandwidth feedback amplifiers. <i>International Journal of Circuit Theory and Applications</i> , 2013 , 41, 424-440	2	3
49	An improved common-mode feedback loop for the differential-difference amplifier. <i>Analog Integrated Circuits and Signal Processing</i> , 2013 , 74, 33-48	1.2	5
48	Improved Digital Background Calibration of Time-Interleaved Pipeline A/D Converters. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , 2013 , 60, 86-90	3.5	16
47	Process and terminations variations aware stability criteria for microwave amplifiers. <i>International Journal of RF and Microwave Computer-Aided Engineering</i> , 2013 , 23, 619-626	1.5	
46	A Flip-Flop for the DPA Resistant Three-Phase Dual-Rail Pre-Charge Logic Family. <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2012 , 20, 2128-2132	2.6	11
45	Efficient Digital Background Calibration of Time-Interleaved Pipeline Analog-to-Digital Converters. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2012 , 59, 1373-1383	3.9	28
44	Autotuning technique for CMOS current mode capacitive sensor interfaces 2012 ,		1
43	Exploiting the Body of MOS Devices for High Performance Analog Design. <i>IEEE Circuits and Systems Magazine</i> , 2011 , 11, 8-23	3.2	29
42	Avoiding the Gain-Bandwidth Trade Off in Feedback Amplifiers. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2011 , 58, 2108-2113	3.9	15
41	Delay-Based Dual-Rail Precharge Logic. <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2011 , 19, 1147-1153	2.6	24
40	Leakage Power Analysis attacks: Effectiveness on DPA resistant logic styles under process variations 2011 ,		4
39	Leakage Power Analysis Attacks: A Novel Class of Attacks to Nanometer Cryptographic Circuits. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2010 , 57, 355-367	3.9	68
38	Behavioral Modeling for Calibration of Pipeline Analog-To-Digital Converters. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2010 , 57, 1255-1264	3.9	14
37	0.9-V CMOS cascode amplifier with body-driven gain boosting. <i>International Journal of Circuit Theory and Applications</i> , 2009 , 37, 193-202	2	25
36	Extraction of CAD-compatible statistical nonlinear models of GaAs HEMT MMICs. <i>Microwave and Optical Technology Letters</i> , 2009 , 51, 2163-2166	1.2	

35	A novel low-voltage low-power fully differential voltage and current gained CCII for floating impedance simulations. <i>Microelectronics Journal</i> , 2009 , 40, 20-25	1.8	34
34	Impact of Process Variations on LPA Attacks Effectiveness 2009 ,		3
33	Design Solutions for Sample-and-Hold Circuits in CMOS Nanometer Technologies. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , 2009 , 56, 459-463	3.5	24
32	Near-optimum switched capacitor sample-and-hold circuit 2009 ,		2
31	Analysis and Implementation of a Minimum-Supply Body-Biased CMOS Differential Amplifier Cell. <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2009 , 17, 172-180	2.6	18
30	High-Level Side-Channel Attack Modeling and Simulation for Security-Critical Systems on Chips. <i>IEEE Transactions on Dependable and Secure Computing</i> , 2008 , 5, 164-176	3.9	20
29	Switched Capacitor Sample-and-Hold Circuit with Input Signal Range beyond Supply Voltage 2008 ,		3
28	A low-power sample-and-hold circuit based on a switched-opamp technique 2008 ,		1
27	The Universal Circuit Simulator: A Mixed-Signal Approach to n -Port Network and Impedance Synthesis. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , 2007 , 54, 2178-2183	3.9	9
26	Linearization Technique for Source-Degenerated CMOS Differential Transconductors. <i>IEEE Transactions on Circuits and Systems Part 2: Express Briefs</i> , 2007 , 54, 848-852		28
25	Design, realization, and test of a 900 MHz ceramic oscillator. <i>Microwave and Optical Technology Letters</i> , 2007 , 49, 1713-1717	1.2	0
24	Analysis of data dependence of leakage current in CMOS cryptographic hardware 2007 ,		16
23	A Sample-and-Hold Circuit with Very Low Gain Error for Time Interleaving Applications 2007 ,		1
22	Very Low Voltage CMOS Two-stage Amplifier 2007 ,		1
21	A Simple Technique for Fast Digital Background Calibration of A/D Converters. <i>Eurasip Journal on Advances in Signal Processing</i> , 2007 , 2008,	1.9	1
20	Sub-1V CMOS OTA with Body-driven Gain Boosting 2007 ,		6
19	Stability Criterion for Two-Port Network With Input and Output Terminations Varying in Elliptic Regions. <i>IEEE Transactions on Microwave Theory and Techniques</i> , 2006 , 54, 4049-4055	4.1	4
18	Input-Matching and Offset-Cancelling Networks for Limiting Amplifiers in Optical Communication Systems. <i>Analog Integrated Circuits and Signal Processing</i> , 2006 , 47, 23-32	1.2	1

17	Three-Phase Dual-Rail Pre-charge Logic. <i>Lecture Notes in Computer Science</i> , 2006 , 232-241	0.9	51
16	Behavioral model of a noisy VCO for efficient time-domain simulation. <i>Microwave and Optical Technology Letters</i> , 2004 , 40, 352-355	1.2	1
15	A new procedure for nonlinear statistical model extraction of GaAs FET-integrated circuits. <i>International Journal of RF and Microwave Computer-Aided Engineering</i> , 2003 , 13, 348-356	1.5	1
14	Wideband LNA design by parallel FETs. <i>Microwave and Optical Technology Letters</i> , 2002 , 32, 280-284	1.2	0
13	A new model to analyze the effects of noise in a real oscillator. <i>Microwave and Optical Technology Letters</i> , 2002 , 32, 305-307	1.2	3
12	A new instantaneous model of MESFET and HEMT devices for large-signal circuit design. <i>Microwave and Optical Technology Letters</i> , 2001 , 29, 187-190	1.2	1
11	Bias correction and yield optimization of MMICs with external digital control. <i>Microwave and Optical Technology Letters</i> , 2001 , 31, 134-137	1.2	1
10	Design of narrowband amplifiers with conditionally stable transistors. <i>Microwave and Optical Technology Letters</i> , 2001 , 31, 208-210	1.2	
9	A novel bias-dependent rational model for MESFET and HEMT devices. <i>Microwave and Optical Technology Letters</i> , 2000 , 24, 102-106	1.2	2
8	A new topology for a transimpedance amplifier with postfabrication bandwidth adjustment. <i>Microwave and Optical Technology Letters</i> , 2000 , 25, 47-51	1.2	1
7	A new procedure for the extraction of a multibias linear model for MESFETs and HEMTs. <i>Microwave and Optical Technology Letters</i> , 2000 , 25, 263-266	1.2	1
6	A low-power clock and data recovery circuit for 2.5 Gb/s SDH receivers 2000 ,		3
5	Design criteria for optical receivers in broadband optical systems. <i>Microwave and Optical Technology Letters</i> , 1999 , 20, 50-53	1.2	1
4	A new algorithm to extract the nonlinear model of MESFETS and HEMTS. <i>Microwave and Optical Technology Letters</i> , 1999 , 20, 297-302	1.2	9
3	A synthesis-oriented approach to design stable circuits. <i>Microwave and Optical Technology Letters</i> , 1999 , 23, 354-357	1.2	6
2	Monolithic 2.5-Gb/s clock and data recovery circuit based on silicon bipolar technology 1998 ,		2
1	A new design approach for monolithic transimpedance receivers based on root-locus techniques. <i>Microwave and Optical Technology Letters</i> , 1994 , 7, 692-696	1.2	2