

Haigun Lee

List of Publications by Citations

Source: <https://exaly.com/author-pdf/12054378/haigun-lee-publications-by-citations.pdf>

Version: 2024-04-28

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

59
papers

982
citations

20
h-index

29
g-index

59
ext. papers

1,128
ext. citations

2.7
avg, IF

3.73
L-index

#	Paper	IF	Citations
59	A superconducting joint for GdBa ₂ Cu ₃ O ₇ F-coated conductors. <i>NPG Asia Materials</i> , 2014 , 6, e98-e98	10.3	88
58	Field Mapping, NMR Lineshape, and Screening Currents Induced Field Analyses for Homogeneity Improvement in LTS/HTS NMR Magnets. <i>IEEE Transactions on Applied Superconductivity</i> , 2008 , 18, 856-859	1.8	64
57	A Solid Nitrogen Cooled MgB ₂ "Demonstration" Coil for MRI Applications. <i>IEEE Transactions on Applied Superconductivity</i> , 2008 , 18, 912-915	1.8	58
56	Stability and quench protection of coated YBCO "Composite" tape. <i>IEEE Transactions on Applied Superconductivity</i> , 2005 , 15, 1683-1686	1.8	55
55	MOF-derived CoP-nitrogen-doped carbon@NiFeP nanoflakes as an efficient and durable electrocatalyst with multiple catalytically active sites for OER, HER, ORR and rechargeable zinc-air batteries. <i>Chemical Engineering Journal</i> , 2022 , 428, 131115	14.7	42
54	Quench and recovery of YBCO tape experimental and simulation results. <i>IEEE Transactions on Applied Superconductivity</i> , 2003 , 13, 1772-1775	1.8	39
53	Operation and performance analyses of 350 and 700 MHz low-/high-temperature superconductor nuclear magnetic resonance magnets: A march toward operating frequencies above 1 GHz. <i>Journal of Applied Physics</i> , 2009 , 105, 024501	2.5	38
52	Electromagnetic levitation of a superconducting disc with a DC field generated by electromagnets: Part 1. Theoretical and experimental results on operating modes, lift-to-weight ratio, and suspension stiffness. <i>Cryogenics</i> , 1997 , 37, 807-816	1.8	36
51	A "persistent-mode" magnet comprised of YBCO annuli. <i>IEEE Transactions on Applied Superconductivity</i> , 2005 , 15, 2352-2355	1.8	35
50	Stability of bare and copper-laminated YBCO samples: experimental & simulation results. <i>IEEE Transactions on Applied Superconductivity</i> , 2004 , 14, 1290-1293	1.8	30
49	Design analysis of a solid nitrogen cooled permanent high-temperature superconducting magnet system. <i>Cryogenics</i> , 2002 , 42, 617-634	1.8	28
48	A permanent high-temperature superconducting magnet operated in thermal communication with a mass of solid nitrogen. <i>Cryogenics</i> , 2002 , 42, 229-244	1.8	28
47	Joint Characteristics of YBCO Coated Conductor by Removing a Metallic Stabilizer. <i>IEEE Transactions on Applied Superconductivity</i> , 2008 , 18, 1220-1223	1.8	27
46	A high-temperature superconducting double-pancake insert for an NMR magnet. <i>IEEE Transactions on Applied Superconductivity</i> , 2003 , 13, 1546-1549	1.8	27
45	Practical Design of a 10 MW Superconducting Wind Power Generator Considering Weight Issue. <i>IEEE Transactions on Applied Superconductivity</i> , 2013 , 23, 5201805-5201805	1.8	26
44	A low- and high-temperature superconducting NMR magnet: design and performance results. <i>IEEE Transactions on Applied Superconductivity</i> , 2003 , 13, 1550-1553	1.8	24
43	Three-dimensional bimetal TMO supported carbon based electrocatalyst developed via dry synthesis for hydrogen and oxygen evolution. <i>Applied Surface Science</i> , 2020 , 505, 144642	6.7	23

42	'Electromaglev' ('active-maglev') Magnetic levitation of a superconducting disk with a DC field generated by electromagnets: Part 3. Theoretical results on levitation height and stability. <i>Cryogenics</i> , 1998 , 38, 743-756	1.8	22
41	. <i>IEEE Transactions on Applied Superconductivity</i> , 2007 , 17, 1446-1449	1.8	22
40	. <i>IEEE Transactions on Applied Superconductivity</i> , 2003 , 13, 1640-1643	1.8	21
39	Effect of micro-ceramic fillers in epoxy composites on thermal and electrical stabilities of GdBCO coils. <i>Composites Part B: Engineering</i> , 2016 , 94, 190-196	10	18
38	Joint Characteristics of the YBCO Coated Conductor (CC) by Chemical Etching. <i>IEEE Transactions on Applied Superconductivity</i> , 2009 , 19, 2835-2838	1.8	18
37	Electromaglev ('Active-maglev') Magnetic levitation of a superconducting disk with a DC field generated by electromagnets. Part 4: theoretical and experimental results on supercurrent distributions in field-cooled YBCO disks. <i>Cryogenics</i> , 1999 , 39, 893-903	1.8	18
36	High- T_c Superconducting High Gradient Magnetic Separator Using Solid Nitrogen Cooling System for Purification of CMP Wastewater. <i>IEEE Transactions on Applied Superconductivity</i> , 2013 , 23, 3700505-3700505	1.8	17
35	Challenging endeavor to integrate gallium and carbon via direct bonding to evolve GaN on diamond architecture. <i>Scripta Materialia</i> , 2018 , 142, 138-142	5.6	13
34	High-temperature superconducting current lead incorporating operation in the current-sharing mode. <i>Cryogenics</i> , 2000 , 40, 209-219	1.8	13
33	Detection of 'hot spots' in HTS coils and test samples with acoustic emission signals. <i>IEEE Transactions on Applied Superconductivity</i> , 2004 , 14, 1298-1301	1.8	12
32	Repetitive Over-Current Characteristics of the Joints Between the YBCO Coated Conductor. <i>IEEE Transactions on Applied Superconductivity</i> , 2009 , 19, 2419-2422	1.8	10
31	'Electromaglev' ('Active-Maglev') Magnetic levitation of a superconducting disk with a DC field generated by electromagnets: Part 2 Theoretical and experimental results on lift-to-weight ratio and lateral stiffness. <i>Cryogenics</i> , 1998 , 38, 419-427	1.8	9
30	Experimental Analysis of a Splice Method Between YBCO Coated Conductors on Various Bending Diameters. <i>IEEE Transactions on Applied Superconductivity</i> , 2010 , 20, 1577-1580	1.8	8
29	Active Magnetic Levitation with YBCO Samples 1997 , 1379-1384		8
28	A Study on Charge/Discharge Characteristics of No-Insulation GdBCO Magnets Energized via a Flux Injector. <i>IEEE Transactions on Applied Superconductivity</i> , 2017 , 27, 1-6	1.8	7
27	Fabrication and Charging Test of HTS Field Windings Using HTS Contactless Rotary Excitation Device. <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-7	1.8	7
26	. <i>IEEE Transactions on Applied Superconductivity</i> , 2015 , 25, 1-5	1.8	7
25	Effects of Melting Diffusion and Annealing in Oxygen on Superconducting Characteristics of GdBCO Coated Conductors: Preliminary Results. <i>IEEE Transactions on Applied Superconductivity</i> , 2013 , 23, 6600804-6600804	1.8	7

24	Ultrasonication-dry-based synthesis of gold nanoparticle-supported CuFe on rGO nanosheets for competent detection of biological molecules. <i>Applied Surface Science</i> , 2020 , 531, 147415	6.7	7
23	Effects of Stabilizer Thickness of 2G HTS Wire on the Design of a 1.5-MW-Class HTS Synchronous Machine. <i>IEEE Transactions on Applied Superconductivity</i> , 2016 , 26, 1-5	1.8	7
22	Design, analysis, and fabrication of salient field-pole for a 1-kW-class HTS rotating machine. <i>Cryogenics</i> , 2019 , 97, 126-132	1.8	7
21	Mixed cryogen cooling systems for HTS power applications: A status report of progress in Korea University. <i>Cryogenics</i> , 2012 , 52, 648-655	1.8	6
20	Development of vapor-cooled HTS-copper 6-kA current lead incorporating operation in the current-sharing mode. <i>Cryogenics</i> , 2004 , 44, 7-14	1.8	6
19	A solid-nitrogen cooled Nb/sub 3/Sn NMR magnet operating in the range 8-10 K. <i>IEEE Transactions on Applied Superconductivity</i> , 2003 , 13, 1636-1639	1.8	6
18	Study on Thermal-Quench Behaviors of GdBCO Coils Wound With Silicon Grease as an Insulation Material. <i>IEEE Transactions on Applied Superconductivity</i> , 2017 , 27, 1-5	1.8	5
17	Analytical Design Method of High-Tc Coated Conductor for a Resistive Superconducting Fault Current Limiter Using Finite Element Method. <i>IEEE Transactions on Applied Superconductivity</i> , 2010 , 20, 1172-1176	1.8	5
16	Cooling Performance and Thermal Characteristics of No-Insulation GdBCO Magnet Cooled by a Mixed Cryogen Cooling System. <i>IEEE Transactions on Applied Superconductivity</i> , 2016 , 26, 1-5	1.8	4
15	A Research About Bending Strain Effect on Splice Characteristics in $\text{YBa}_2\text{Cu}_3\text{O}_{7-x}$ Coated Conductors Under Various Pressures in Splicing. <i>IEEE Transactions on Applied Superconductivity</i> , 2011 , 21, 3001-3004	1.8	4
14	Synthesis of yttrium barium copper oxide-0.325Ag superconductors via intermediate precursor with overall composition Y:Ba:Cu:O=l:2:3:Y, Y>7 produced by high-energy attrition milling. <i>Metals and Materials International</i> , 2000 , 6, 473-489		4
13	Synthesis of Melted Yttrium Barium Copper Oxide-0.325Ag Superconductors Contained in a Solid Silver Cladding at Reduced Oxygen Partial Pressures. <i>Japanese Journal of Applied Physics</i> , 2003 , 42, 6841-6847	1.4	3
12	AMI-MIT 1-kA leads with high-temperature superconducting sections-design concept and key parameters. <i>IEEE Transactions on Applied Superconductivity</i> , 2001 , 11, 2539-2542	1.8	3
11	Fabrication and testing of high performance acoustic emission sensor with Ta-Doped lead zirconate titanate. <i>Journal of Electroceramics</i> , 2015 , 35, 53-58	1.5	2
10	A Study on Recovery Characteristics of Joined Tapes From the View of Thermal and Electrical Variation for Superconducting Magnets. <i>IEEE Transactions on Applied Superconductivity</i> , 2012 , 22, 4703505-4703505	1.8	3
9	Fabrication of a high performance acoustic emission (AE) sensor to monitor and diagnose disturbances in HTS tapes and magnet systems. <i>Metals and Materials International</i> , 2010 , 16, 109-113	2.4	2
8	3D Reconstruction of the Human Pallidothalamic and Nigrothalamic Pathways With Super-Resolution 7T MR Track Density Imaging and Fiber Tractography. <i>Frontiers in Neuroanatomy</i> , 2021 , 15, 739576	3.6	2
7	Oxygen out-diffusion in partially melted YBa ₂ Cu ₃ O _y 0.325Ag superconductor at reduced oxygen partial pressure 2008 , 14, 673		1

6	Future Prospects of Positron Emission Tomography/Magnetic Resonance Imaging Hybrid Systems and Applications in Psychiatric Disorders. <i>Pharmaceuticals</i> , 2022 , 15, 583	5.2	1
5	Magnetic Field Stability Analysis on No-Insulation and Turn-to-Turn Soldered HTS Magnets Under Sinusoidal Noise Operation. <i>IEEE Transactions on Applied Superconductivity</i> , 2016 , 26, 1-5	1.8	0
4	. <i>IEEE Transactions on Applied Superconductivity</i> , 2012 , 22, 5602504-5602504	1.8	0
3	Oxygen out-diffusion in partially melted YBa ₂ Cu ₃ O _y 0.325Ag superconductor at reduced oxygen partial pressure. <i>Metals and Materials International</i> , 2008 , 14, 673-678	2.4	
2	Thermal-quench behavior of non-insulated high-temperature superconducting (HTS) racetrack pancake coil with cooling channels through the epoxy surface. <i>Results in Physics</i> , 2021 , 24, 104131	3.7	
1	Micro-architecture embedding ultra-thin interlayer to bond diamond and silicon via direct fusion. <i>Applied Physics Letters</i> , 2018 , 112, 211601	3.4	