Samarshi Chakraborty

List of Publications by Year in Descending Order

Source: https://exaly.com/author-pdf/137953/samarshi-chakraborty-publications-by-year.pdf

Version: 2024-04-25

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

25 604 13 24 g-index

25 896 4.4 4.91 ext. papers ext. citations avg, IF L-index

| # | Paper | IF | Citations |
|----|---|------|-----------|
| 25 | Microalgae Coupled Biofuel Production and Carbon Capture from Thermal Power Plant: A Biorefinery Approach. <i>Energy, Environment, and Sustainability</i> , 2022 , 325-343 | 0.8 | |
| 24 | Synthesis of Cu-Al LDH nanofluid and effectiveness as a promoter for CO2 hydrate formation. <i>Chemical Engineering Journal</i> , 2022 , 435, 134786 | 14.7 | 1 |
| 23 | Thermophysical properties using ND/water nanofluids: An experimental study, ANFIS-based model and optimization. <i>Journal of Molecular Liquids</i> , 2021 , 330, 115659 | 6 | 22 |
| 22 | Role of anisotropic pinning and liquid properties during partial rebound of droplets on unidirectionally structured hydrophobic surfaces. <i>Chemical Engineering Science</i> , 2021 , 230, 116197 | 4.4 | 2 |
| 21 | Stability of nanofluid: A review. <i>Applied Thermal Engineering</i> , 2020 , 174, 115259 | 5.8 | 121 |
| 20 | Spray cooling of hot steel plate using aqueous solution of surfactant and polymer. <i>Thermal Science and Engineering Progress</i> , 2019 , 10, 217-231 | 3.6 | 14 |
| 19 | Effect of surfactant on thermo-physical properties and spray cooling heat transfer performance of Cu-Zn-Al LDH nanofluid. <i>Applied Clay Science</i> , 2019 , 168, 43-55 | 5.2 | 26 |
| 18 | Application of TiO2 nanofluid-based coolant for jet impingement quenching of a hot steel plate. <i>Experimental Heat Transfer</i> , 2019 , 32, 322-336 | 2.4 | 7 |
| 17 | Influence of Marangoni stress on the variation in number of coalescence cascade stages. <i>Canadian Journal of Chemical Engineering</i> , 2019 , 97, 983-994 | 2.3 | 6 |
| 16 | Synthesis of Cu-Al LDH nanofluid and its application in spray cooling heat transfer of a hot steel plate. <i>Powder Technology</i> , 2018 , 335, 285-300 | 5.2 | 28 |
| 15 | Morphological, mechanical, and thermal features of PMMA nanocomposites containing two-dimensional CoAl layered double hydroxide. <i>Journal of Applied Polymer Science</i> , 2018 , 135, 45774 | 2.9 | 7 |
| 14 | Comparative study on different additives with a jet array on cooling of a hot steel surface. <i>Applied Thermal Engineering</i> , 2018 , 137, 154-163 | 5.8 | 3 |
| 13 | Thermo-physical properties of Cu-Zn-Al LDH nanofluid and its application in spray cooling. <i>Applied Thermal Engineering</i> , 2018 , 141, 339-351 | 5.8 | 30 |
| 12 | Thermal reduction of graphene oxide: How temperature influences purity. <i>Journal of Materials Research</i> , 2018 , 33, 4113-4122 | 2.5 | 84 |
| 11 | Ultrafast cooling of a hot steel plate using Cu-Al layered double hydroxide nanofluid jet. <i>International Journal of Thermal Sciences</i> , 2017 , 116, 52-62 | 4.1 | 13 |
| 10 | Heat transfer from a hot moving steel plate by using Cu-Al layered double hydroxide nanofluid based air atomized spray. <i>Experimental Heat Transfer</i> , 2017 , 30, 500-516 | 2.4 | 7 |
| 9 | Synthesis and characterization of Zn-Al layered double hydroxide nanofluid and its application as a coolant in metal quenching. <i>Applied Clay Science</i> , 2017 , 143, 241-249 | 5.2 | 8 |

LIST OF PUBLICATIONS

| 8 | Heat transfer enhancement using surfactant based alumina nanofluid jet from a hot steel plate. <i>Experimental Thermal and Fluid Science</i> , 2017 , 89, 295-303 | 3 | 27 |
|---|---|-----|----|
| 7 | Effect of alumina nanofluid jet on the enhancement of heat transfer from a steel plate. <i>Heat and Mass Transfer</i> , 2017 , 53, 2187-2197 | 2.2 | 9 |
| 6 | Experimental investigation on the effect of dispersant addition on thermal and rheological characteristics of TiO2 nanofluid. <i>Powder Technology</i> , 2017 , 307, 10-24 | 5.2 | 46 |
| 5 | Heat transfer in jet impingement on a hot steel surface using surfactant based CuAl layered double hydroxide nanofluid. <i>International Journal of Heat and Mass Transfer</i> , 2016 , 101, 825-833 | 4.9 | 11 |
| 4 | Investigation of structural, rheological and thermal properties of PMMA/ONi-Al LDH nanocomposites synthesized via solvent blending method: Effect of LDH loading. <i>Chinese Journal of Polymer Science (English Edition)</i> , 2016 , 34, 739-754 | 3.5 | 14 |
| 3 | Synthesis of CuAl layered double hydroxide nanofluid and characterization of its thermal properties. <i>Applied Clay Science</i> , 2015 , 107, 98-108 | 5.2 | 47 |
| 2 | Heat transfer enhancement using air-atomized spray cooling with waterAl2O3 nanofluid. <i>International Journal of Thermal Sciences</i> , 2015 , 96, 85-93 | 4.1 | 39 |
| 1 | Influence of organically modified NiAl layered double hydroxide (LDH) loading on the rheological properties of poly (methyl methacrylate) (PMMA)/LDH blend solution. <i>Powder Technology</i> , 2014 , 256, 196-203 | 5.2 | 32 |