## Enrique Mariano Castrodeza

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/1419879/publications.pdf

Version: 2024-02-01

27 papers

393 citations

759233 12 h-index 19 g-index

27 all docs 27 docs citations

times ranked

27

365 citing authors

| #  | Article  | IF  | Citations |
|----|--|-----|-----------|
| 1  | Effect of heat treatments and loading orientation on the tensile properties and fracture toughness of AlSi7Mg alloy produced by Laser Powder Bed Fusion. International Journal of Fracture, 2022, 235, 145-157.                  | 2.2 | 6         |
| 2  | Analysis of the S method for geometries where $\hat{\textbf{l}}$ depends on a/W. Engineering Fracture Mechanics, 2021, 241, 107416.  | 4.3 | 0         |
| 3  | Influence of microstructure and porosity on the fracture toughness of Al-Si-Mg alloy. Journal of Materials Research and Technology, 2020, 9, 1286-1295.  | 5.8 | 15        |
| 4  | Fatigue crack growth behavior of a selective laser melted AlSi10Mg. Engineering Fracture Mechanics, 2019, 217, 106564.   | 4.3 | 38        |
| 5  | Effect of build orientation on fracture and tensile behavior of A357 Al alloy processed by Selective Laser Melting. Materials Science & Diplication (1383) and Diplication (1383) and Diplication (1383) and Diplication (1383). | 5.6 | 39        |
| 6  | Determination of mode I dynamic fracture toughness of IM7-8552 composites by digital image correlation and machine learning. Composite Structures, 2019, 210, 707-714.   | 5.8 | 14        |
| 7  | Fracture toughness of high strength seamless pipe steel from SE(T) and SE(B) specimens evaluated by different standards. Fatigue and Fracture of Engineering Materials and Structures, 2019, 42, 572-582.                        | 3.4 | 1         |
| 8  | Effect of displacement rate and subcritical crack growth on J-R curves of API X65 steels in sour environment. Engineering Fracture Mechanics, 2018, 190, 134-145.  | 4.3 | 3         |
| 9  | Normalization method for J-R curve determination using SENT specimens. Engineering Fracture Mechanics, 2018, 199, 658-671.   | 4.3 | 10        |
| 10 | Comparison of J–R curves and JC values of C(T) and M(T) specimens of bidirectional GLARE 3 5/4 0.3 fiber-metal laminates. Engineering Fracture Mechanics, 2016, 159, 79-89.  | 4.3 | 5         |
| 11 | Production of 17CrMoV5-11 steel sponges utilising powder metallurgical replication technique with SiC as space holder. Powder Metallurgy, 2016, 59, 95-99.   | 1.7 | 2         |
| 12 | CTODâ€R curves of the metalâ€clad interface of API X52 pipes cladded with an Inconel 625 alloy by welding overlay. Fatigue and Fracture of Engineering Materials and Structures, 2016, 39, 1477-1487.                            | 3.4 | 10        |
| 13 | Crack growth resistance curves of GLARE 3 5/4 0.3 fiber–metal laminates at low temperature. Fatigue and Fracture of Engineering Materials and Structures, 2015, 38, 268-275.   | 3.4 | 10        |
| 14 | Performance of stainless steel foams produced by infiltration casting techniques. Journal of Materials Processing Technology, 2013, 213, 1846-1854.  | 6.3 | 28        |
| 15 | Cyclic pseudoelastic behavior and energy dissipation in as-cast Cu-Zn-Al foams of different densities. Intermetallics, 2011, 19, 577-585.  | 3.9 | 20        |
| 16 | Fatigue crack propagation in API 5L X-70 pipeline steel longitudinal welded joints under constant and variable amplitudes. Fatigue and Fracture of Engineering Materials and Structures, 2011, 34, 321-328.                      | 3.4 | 15        |
| 17 | Processing and Characterization of Dual Phase Steel Foams Featured by Different Pore Distribution. Steel Research International, 2011, 82, 918-925.  | 1.8 | 10        |
| 18 | Mechanical properties of martensitic Cu–Zn–Al foams in the pseudoelastic regime. Materials Letters, 2010, 64, 1448-1450.   | 2.6 | 26        |

## ENRIQUE MARIANO

| #  | Article  | IF          | CITATION |
|----|--|-------------|----------|
| 19 | Processing of Shape Memory CuZnAl Open-cell Foam by Molten Metal Infiltration. Journal of Materials Engineering and Performance, 2009, 18, 484-489.  | 2.5         | 28       |
| 20 | Processing of brass open-cell foam by silica-gel beads replication. Journal of Materials Processing Technology, 2009, 209, 4958-4962.  | 6.3         | 25       |
| 21 | Crack resistance curves of GLARE laminates by elastic compliance. Engineering Fracture Mechanics, 2006, 73, 2292-2303.   | 4.3         | 12       |
| 22 | Residual strength of unidirectional fibreâ€metal laminates based on J C toughness of C(T) and SE(B) specimens: comparison with M(T) test results. Fatigue and Fracture of Engineering Materials and Structures, 2004, 27, 923-929. | 3.4         | 7        |
| 23 | Fracture toughness evaluation of unidirectional fibre metal laminates using traditional CTOD (Î) and Schwalbe (Î'5) methodologies. Engineering Fracture Mechanics, 2004, 71, 1107-1118.  | 4.3         | 17       |
| 24 | Critical fracture toughness, JC and δ5C, of unidirectional fibre–metal laminates. Thin-Walled Structures, 2003, 41, 1089-1101.   | <b>5.</b> 3 | 21       |
| 25 | Fracture Micromechanisms of Fibre-Metal Laminates: In-Situ SEM Observations. Journal of Composite Materials, 2002, 36, 387-400.  | 2.4         | 10       |
| 26 | Experimental techniques for fracture instability toughness determination of unidirectional fibre metal laminates. Fatigue and Fracture of Engineering Materials and Structures, 2002, 25, 999-1008.                                | 3.4         | 20       |
| 27 | Characterization and Comparative Study of Pseudo-Elastic Cu-Zn-Al Foams Synthesized by Two Different Methods. Materials Science Forum, 0, 738-739, 172-176.  | 0.3         | 1        |