

# Jianyin Xiong

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/1464694/publications.pdf>

Version: 2024-02-01

58  
papers

1,864  
citations

218381

26  
h-index

276539

41  
g-index

60  
all docs

60  
docs citations

60  
times ranked

1195  
citing authors

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 1  | Predicting the concentrations of VOCs in a controlled chamber and an occupied classroom via a deep learning approach. <i>Building and Environment</i> , 2022, 207, 108525.   | 3.0 | 14        |
| 2  | Residential building materials: An important source of ambient formaldehyde in mainland China. <i>Environment International</i> , 2022, 158, 106909.   | 4.8 | 17        |
| 3  | Characterization of the off-body squalene ozonolysis on indoor surfaces. <i>Chemosphere</i> , 2022, 291, 132772.   | 4.2 | 7         |
| 4  | Study on the Effect of an Intermittent Ventilation Strategy on Controlling Formaldehyde Concentrations in Office Rooms. <i>Atmosphere</i> , 2022, 13, 102.   | 1.0 | 3         |
| 5  | Interpretation of standard effective temperature (SET) and explorations on its modification and development. <i>Building and Environment</i> , 2022, 210, 108714.  | 3.0 | 18        |
| 6  | Predicting the emissions of VOCs/SVOCs in source and sink materials: Development of analytical model and determination of the key parameters. <i>Environment International</i> , 2022, 160, 107064.  | 4.8 | 12        |
| 7  | Highly efficient hydrogen production via a zinc-carbon @ nickel system. <i>International Journal of Hydrogen Energy</i> , 2022, 47, 5354-5360.   | 3.8 | 5         |
| 8  | Determination of the key parameters of VOCs emitted from multi-layer leather furniture using a region traversal approach. <i>Science of the Total Environment</i> , 2022, 819, 153126.   | 3.9 | 8         |
| 9  | A rapid and robust method to determine the key parameters of formaldehyde emissions from building and vehicle cabin materials: Principle, multi-source application and exposure assessment. <i>Journal of Hazardous Materials</i> , 2022, 430, 128422. | 6.5 | 19        |
| 10 | The association between daily-diagnosed COVID-19 morbidity and short-term exposure to PM1 is larger than associations with PM2.5 and PM10. <i>Environmental Research</i> , 2022, 210, 113016.  | 3.7 | 8         |
| 11 | Investigation on the Direct Transfer of SVOCs from Source to Settled Dust: Analytical Model and Key Parameter Determination. <i>Environmental Science &amp; Technology</i> , 2022, 56, 5489-5496.  | 4.6 | 9         |
| 12 | Physical-Chemical Coupling Model for Characterizing the Reaction of Ozone with Squalene in Realistic Indoor Environments. <i>Environmental Science &amp; Technology</i> , 2021, 55, 1690-1698.   | 4.6 | 33        |
| 13 | Using a machine learning approach to predict the emission characteristics of VOCs from furniture. <i>Building and Environment</i> , 2021, 196, 107786.   | 3.0 | 20        |
| 14 | Selection of hydrogel electrolytes for flexible zinc-air batteries. <i>Materials Today Chemistry</i> , 2021, 21, 100538.   | 1.7 | 30        |
| 15 | Measurement of the key parameters of VOC emissions from wooden furniture, and the impact of temperature. <i>Atmospheric Environment</i> , 2021, 259, 118510.   | 1.9 | 35        |
| 16 | Zn-Ni reaction in the alkaline zinc-air battery using a nickel-supported air electrode. <i>Materials Today Energy</i> , 2021, 21, 100823.  | 2.5 | 4         |
| 17 | VOC emissions from two-layer building and vehicle cabin materials: Measurements and independent validation. <i>Atmospheric Environment</i> , 2021, 267, 118772.  | 1.9 | 10        |
| 18 | High Volatility Organic Compounds (VOCs)., 2021, , 1-34.   |     | 0         |

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 19 | Characterization of phthalates in sink and source materials: Measurement methods and the impact on exposure assessment. <i>Journal of Hazardous Materials</i> , 2020, 396, 122689.   | 6.5 | 19        |
| 20 | A general regression method for accurately determining the key parameters of VOC emissions from building materials/furniture in a ventilated chamber. <i>Atmospheric Environment</i> , 2020, 231, 117527.                  | 1.9 | 11        |
| 21 | Predicting the emission characteristics of VOCs in a simulated vehicle cabin environment based on small-scale chamber tests: Parameter determination and validation. <i>Environment International</i> , 2020, 142, 105817. | 4.8 | 51        |
| 22 | Short-term exposure to ambient particle gamma radioactivity is associated with increased risk for all-cause non-accidental and cardiovascular mortality. <i>Science of the Total Environment</i> , 2020, 721, 137793.      | 3.9 | 7         |
| 23 | Emissions of DEHP from vehicle cabin materials: parameter determination, impact factors and exposure analysis. <i>Environmental Sciences: Processes and Impacts</i> , 2019, 21, 1323-1333.                                 | 1.7 | 6         |
| 24 | Characterization of VOC emissions from composite wood furniture: Parameter determination and simplified model. <i>Building and Environment</i> , 2019, 161, 106237.  | 3.0 | 23        |
| 25 | An improved mechanism-based model for predicting the long-term formaldehyde emissions from composite wood products with exposed edges and seams. <i>Environment International</i> , 2019, 132, 105086.                     | 4.8 | 34        |
| 26 | Modeling the Time-Dependent Concentrations of Primary and Secondary Reaction Products of Ozone with Squalene in a University Classroom. <i>Environmental Science &amp; Technology</i> , 2019, 53, 8262-8270.               | 4.6 | 35        |
| 27 | Characterizing sources and emissions of volatile organic compounds in a northern California residence using space- and time-resolved measurements. <i>Indoor Air</i> , 2019, 29, 630-644.                                  | 2.0 | 70        |
| 28 | Association between the emissions of volatile organic compounds from vehicular cabin materials and temperature: Correlation and exposure analysis. <i>Indoor and Built Environment</i> , 2019, 28, 362-371.                | 1.5 | 11        |
| 29 | Detailed investigation of ventilation rates and airflow patterns in a northern California residence. <i>Indoor Air</i> , 2018, 28, 572-584.  | 2.0 | 50        |
| 30 | Fluorescent biological aerosol particles: Concentrations, emissions, and exposures in a northern California residence. <i>Indoor Air</i> , 2018, 28, 559-571.  | 2.0 | 22        |
| 31 | Air quality inside motor vehicles' cabins: A review. <i>Indoor and Built Environment</i> , 2018, 27, 452-465.  | 1.5 | 80        |
| 32 | Predicting Indoor Emissions of Cyclic Volatile Methylsiloxanes from the Use of Personal Care Products by University Students. <i>Environmental Science &amp; Technology</i> , 2018, 52, 14208-14215.                       | 4.6 | 40        |
| 33 | Predicting VOC emissions from materials in vehicle cabins: Determination of the key parameters and the influence of environmental factors. <i>International Journal of Heat and Mass Transfer</i> , 2017, 110, 671-679.    | 2.5 | 51        |
| 34 | Influence of humidity on the initial emittable concentration of formaldehyde and hexaldehyde in building materials: experimental observation and correlation. <i>Scientific Reports</i> , 2016, 6, 23388.                  | 1.6 | 31        |
| 35 | Understanding and controlling airborne organic compounds in the indoor environment: mass transfer analysis and applications. <i>Indoor Air</i> , 2016, 26, 39-60.  | 2.0 | 65        |
| 36 | Comprehensive influence of environmental factors on the emission rate of formaldehyde and VOCs in building materials: Correlation development and exposure assessment. <i>Environmental Research</i> , 2016, 151, 734-741. | 3.7 | 84        |

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 37 | Transient Method for Determining Indoor Chemical Concentrations Based on SPME: Model Development and Calibration. <i>Environmental Science &amp; Technology</i> , 2016, 50, 9452-9459.  | 4.6 | 24        |
| 38 | Early stage C-history method: Rapid and accurate determination of the key SVOC emission or sorption parameters of indoor materials. <i>Building and Environment</i> , 2016, 95, 314-321.  | 3.0 | 25        |
| 39 | The Impact of Relative Humidity on the Emission Behaviour of Formaldehyde in Building Materials. <i>Procedia Engineering</i> , 2015, 121, 59-66.  | 1.2 | 8         |
| 40 | Thermodynamic analysis of an idealised solar tower thermal power plant. <i>Applied Thermal Engineering</i> , 2015, 81, 271-278.   | 3.0 | 23        |
| 41 | Impact of Temperature on the Ratio of Initial Emittable Concentration to Total Concentration for Formaldehyde in Building Materials: Theoretical Correlation and Validation. <i>Environmental Science &amp; Technology</i> , 2015, 49, 1537-1544.                           | 4.6 | 86        |
| 42 | The analytical solutions for the stress distributions within elastic hollow spheres under the diametrical point loads. <i>Archive of Applied Mechanics</i> , 2015, 85, 817-830.   | 1.2 | 12        |
| 43 | Experimental and numerical investigation on a novel solar still with vertical ripple surface. <i>Energy Conversion and Management</i> , 2015, 98, 151-160.  | 4.4 | 31        |
| 44 | Characterization of VOC Emission from Materials in Vehicular Environment at Varied Temperatures: Correlation Development and Validation. <i>PLoS ONE</i> , 2015, 10, e0140081.  | 1.1 | 23        |
| 45 | Experimental and numerical study on the self-balancing heating performance of a thermosyphon during the process of oil production. <i>Applied Thermal Engineering</i> , 2014, 73, 1270-1278.  | 3.0 | 11        |
| 46 | Experimental and numerical study on a new multi-effect solar still with enhanced condensation surface. <i>Energy Conversion and Management</i> , 2013, 73, 176-185.   | 4.4 | 90        |
| 47 | Measuring the characteristic parameters of VOC emission from paints. <i>Building and Environment</i> , 2013, 66, 65-71.   | 3.0 | 27        |
| 48 | A rapid and accurate method, ventilated chamber C-history method, of measuring the emission characteristic parameters of formaldehyde/VOCs in building materials. <i>Journal of Hazardous Materials</i> , 2013, 261, 542-549.   | 6.5 | 61        |
| 49 | Association between the Emission Rate and Temperature for Chemical Pollutants in Building Materials: General Correlation and Understanding. <i>Environmental Science &amp; Technology</i> , 2013, 47, 130709124156006.  | 4.6 | 32        |
| 50 | Influence of Precision of Emission Characteristic Parameters on Model Prediction Error of VOCs/Formaldehyde from Dry Building Material. <i>PLoS ONE</i> , 2013, 8, e80736.  | 1.1 | 11        |
| 51 | A Novel Method for Measuring the Diffusion, Partition and Convective Mass Transfer Coefficients of Formaldehyde and VOC in Building Materials. <i>PLoS ONE</i> , 2012, 7, e49342.   | 1.1 | 16        |
| 52 | A general analytical model for formaldehyde and VOC emission/sorption in single-layer building materials and its application in determining the characteristic parameters. <i>Atmospheric Environment</i> , 2012, 47, 288-294.  | 1.9 | 50        |
| 53 | Variable Volume Loading Method: A Convenient and Rapid Method for Measuring the Initial Emittable Concentration and Partition Coefficient of Formaldehyde and Other Aldehydes in Building Materials. <i>Environmental Science &amp; Technology</i> , 2011, 45, 10111-10116. | 4.6 | 38        |
| 54 | C-History Method: Rapid Measurement of the Initial Emittable Concentration, Diffusion and Partition Coefficients for Formaldehyde and VOCs in Building Materials. <i>Environmental Science &amp; Technology</i> , 2011, 45, 3584-3590.                                      | 4.6 | 111       |

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 55 | Determination of the equivalent emission parameters of wood-based furniture by applying C-history method. <i>Atmospheric Environment</i> , 2011, 45, 5602-5611.                                       | 1.9 | 29        |
| 56 | Impact of temperature on the initial emittable concentration of formaldehyde in building materials: experimental observation. <i>Indoor Air</i> , 2010, 20, 523-529.                                  | 2.0 | 63        |
| 57 | An improved extraction method to determine the initial emittable concentration and the partition coefficient of VOCs in dry building materials. <i>Atmospheric Environment</i> , 2009, 43, 4102-4107. | 1.9 | 34        |
| 58 | Macro-meso two-scale model for predicting the VOC diffusion coefficients and emission characteristics of porous building materials. <i>Atmospheric Environment</i> , 2008, 42, 5278-5290.             | 1.9 | 73        |