Guiying Xu

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/1528827/publications.pdf

Version: 2024-02-01

840776 794594 29 388 11 19 citations h-index g-index papers 30 30 30 466 docs citations times ranked citing authors all docs

#	Article	IF	Citations
1	Locally ordered nano-domains as novel microstructure defects suppressing the phonon transport in SnTe thermoelectrics. Journal of the European Ceramic Society, 2022, 42, 1001-1006.	5.7	1
2	High thermoelectric performance of PNP abrupt heterostructures by independent regulation of the electrical conductivity and Seebeck coefficient. Materials Today Communications, 2022, 31, 103343.	1.9	1
3	Enabling High Quality Factor and Enhanced Thermoelectric Performance in BiBr ₃ -Doped Sn _{0.93} Mn _{0.1} Te via Band Convergence and Band Sharpening. ACS Applied Materials & Samp; Interfaces, 2022, 14, 32236-32243.	8.0	9
4	Enhancing thermoelectric performance of Sn1-Sb2/3Te via synergistic charge balanced compensation doping. Chemical Engineering Journal, 2021, 404, 126925.	12.7	16
5	Realizing widespread resonance effects to enhance thermoelectric performance of SnTe. Journal of Alloys and Compounds, 2021, 852, 156989.	5.5	12
6	Anion exchanged Cl doping achieving band sharpening and low lattice thermal conductivity for improving thermoelectric performance in SnTe. Inorganic Chemistry Frontiers, 2021, 8, 4666-4675.	6.0	5
7	Effect of excess Ge and Te on thermoelectric performance of GeTe. International Journal of Applied Ceramic Technology, 2021, 18, 1144-1152.	2.1	1
8	Fine-grained polycrystalline MoTe2 with enhanced thermoelectric properties through iodine doping. Journal of Materials Science: Materials in Electronics, 2021, 32, 20093-20103.	2.2	2
9	High thermoelectric performance of (Bi 1―x Pr x) 2 (Te 0.9 Se 0.1) 3 alloys prepared by highâ€pressure sintering method. International Journal of Applied Ceramic Technology, 2021, 18, 2075.	2.1	O
10	Synergistic regulation of electrical-thermal effect leading to an optimized thermoelectric performance in Co doping n-type Bi2(Te0.97Se0.03)3. Intermetallics, 2020, 118, 106683.	3.9	10
11	Low Expression of Smurf1 Enhances the Chemosensitivity of Human Colorectal Cancer to Gemcitabine and Cisplatin in Patient-Derived Xenograft Models. Translational Oncology, 2020, 13, 100804.	3.7	6
12	Transcriptomic analysis reveals that IL-1R8/Sigirr is a novel macrophage migration regulator and suppresses macrophage proliferation through p38 MAPK signaling pathway. Biomedicine and Pharmacotherapy, 2020, 124, 109846.	5.6	6
13	Improving thermoelectric performance of (Bi0.2Sb0.8)2(Te0.97Se0.03)3 via Sm-doping. Journal of Alloys and Compounds, 2019, 787, 909-917.	5.5	7
14	Thermoelectric performance of (GeTe) _{1â^'x} (Sb ₂ Te ₃) _x fabricated by high pressure sintering method. Materials Research Express, 2019, 6, 1250h5.	1.6	4
15	Mechanism and application method to analyze the carrier scattering factor by electrical conductivity ratio based on thermoelectric property measurement. Journal of Applied Physics, 2018, 123, .	2.5	13
16	Recent advances in inorganic material thermoelectrics. Inorganic Chemistry Frontiers, 2018, 5, 2380-2398.	6.0	63
17	Thermoelectric performance of n-type (PbTe)1â^'x(CoTe)x composite prepared by high pressure sintering method. Journal of Materials Science: Materials in Electronics, 2018, 29, 5327-5336.	2.2	8
18	Thermoelectric performance of p-type Nd1â^'In Te3 fabricated by high pressure sintering method. Journal of Alloys and Compounds, 2017, 696, 648-654.	5.5	4

#	Article	IF	CITATION
19	Fracture behaviour and microstructure of refractory materials for steel ladle purging plugs in the system Al2O3-MgO-CaO. Ceramics International, 2017, 43, 9679-9685.	4.8	33
20	The effect of Sm doping on the transport and thermoelectric properties of SnSe. Materials Research Bulletin, 2017, 93, 366-372.	5.2	34
21	Thermoelectric performance of polycrystalline Sn 1-x Cu x Se (x Â=Â0–0.03) prepared by high pressure method. Intermetallics, 2017, 89, 40-45.	3.9	37
22	Thermoelectric transport properties of Sn _{1â^'<i>x</i>} Ge _{<i>x</i>} Se (<i>x</i> =0â€0.03) prepared by melting synthesis method. International Journal of Applied Ceramic Technology, 2017, 14, 963-968.	2.1	7
23	Thermodynamic evaluation and properties of refractory materials for steel ladle purging plugs in the system Al2O3-MgO-CaO. Ceramics International, 2016, 42, 11930-11940.	4.8	42
24	Phase transformations and electrochemical characterizations of electrodeposited amorphous Fe–W coatings. Surface and Coatings Technology, 2016, 286, 36-41.	4.8	27
25	Thermoelectric Properties of Nanocrystalline Bi2(Te1â^'x Se x)3 Prepared by High-Pressure Sintering. Journal of Electronic Materials, 2015, 44, 1592-1598.	2.2	4
26	Enhanced thermoelectric performance in n -type Bi 2 Te 2.95 Se 0.05 bulks fabricated by high pressure sintering technique. Materials Research Bulletin, 2014, 60, 808-813.	5.2	10
27	Bonding tungsten, W–Cu-alloy and copper with amorphous Fe–W alloy transition. Fusion Engineering and Design, 2013, 88, 248-252.	1.9	11
28	Effects of Various Reductants and Surfactants on the Nanostructure of Bi2Te3 Synthesized by a Hydrothermal Process. Journal of Electronic Materials, 2011, 40, 835-839.	2.2	13
29	The heat capacity measurements of CoSb ₃ -based Skutterudite compounds. International Journal of Materials Research, 2010, 101, 808-811.	0.3	2