Mazidah Mukri

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/1543422/publications.pdf

Version: 2024-02-01

2258059 2053705 16 36 3 5 citations h-index g-index papers 16 16 16 30 all docs docs citations times ranked citing authors

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 1 | Practicability and effectiveness of flood disaster standard operating procedures (SOPs) in Malaysia. IOP Conference Series: Earth and Environmental Science, 2021, 685, 012004. | 0.3 | O |
| 2 | INFLUENCE OF DIFFERENT PERCENTAGE BOILER ASH-BASED GEOPOLYMER IN LATERITE SOIL. IIUM Engineering Journal, 2021, 22, 67-82. | 0.8 | 1 |
| 3 | Effect of compaction characteristics on hydraulic conductivity performance for sedimentary residual soil mixed bentonite as compacted liners. IOP Conference Series: Earth and Environmental Science, 2020, 498, 012003. | 0.3 | 7 |
| 4 | A dataset of visualization methods to assessing soil profile using RES2DINV and VOXLER software. Data in Brief, 2019, 24, 103821. | 1.0 | 5 |
| 5 | Effect on Salak Tinggi residual soil mixed Bentonite as compacted clay liner. IOP Conference Series: Materials Science and Engineering, 2019, 513, 012024. | 0.6 | 5 |
| 6 | The Estimation of Hydraulic Properties from Geophysical Measurement of Subsoil Depend on Regression Equation. Modern Applied Science, 2019, 13, 12. | 0.6 | 0 |
| 7 | The Significant Effect of Interface Shear Strength Between Soil Liner and Geotextile with Different Percentages of Bentonite and Sodium Bentonite with Geosynthetic. MATEC Web of Conferences, 2018, 150, 02009. | 0.2 | 1 |
| 8 | Performance of different percentage on nano-kaolin as additives in soil liner application. Materials Today: Proceedings, 2018, 5, 21604-21611. | 1.8 | 2 |
| 9 | Geophysical measurement for estimation of groundwater hydraulic properties. Data in Brief, 2018, 21, 907-910. | 1.0 | 1 |
| 10 | Effect on physical properties of laterite soil with difference percentage of sodium bentonite. AIP Conference Proceedings, 2017, , . | 0.4 | 3 |
| 11 | Prediction of settlement by using finite element simulation 2D program at Seksyen 7, Shah Alam. AIP Conference Proceedings, 2017, , . | 0.4 | 1 |
| 12 | Study of Nano-Kaolinite Properties in Clay Liner Application. Materials Science Forum, 2017, 889, 239-242. | 0.3 | 2 |
| 13 | Understanding of outcome-based education (OBE) implementation by civil engineering students in Malaysia. , $2017, $, . | | 6 |
| 14 | Compaction characteristics of banting soft soil subgrade stabilized using waste paper sludge ash (WPSA). AIP Conference Proceedings, $2016, \ldots$ | 0.4 | 2 |
| 15 | The correlation between internal erosion resistances with the hydraulic conductivity of residual soil., 2012,,. | | O |
| 16 | The Influence of Compaction Effort in Laterite Soil with the Appearance of Sodium Bentonite as a Soil Liner. Applied Mechanics and Materials, 0, 873, 198-202. | 0.2 | 0 |