

Zhonglei Li

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/1811597/zhonglei-li-publications-by-year.pdf>

Version: 2024-04-19

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

118
papers

1,209
citations

20
h-index

28
g-index

192
ext. papers

1,745
ext. citations

2.6
avg. IF

5.35
L-index

#	Paper	IF	Citations
118	Effects of Pre-Crosslinking on Space Charge and Breakdown Characteristics of XLPE Cable Insulation. <i>Energies</i> , 2022 , 15, 2360	3.1	0
117	Semi-conductive Polymer Composites for Power Cables 2021 , 153-178		
116	Electric Ageing and Breakdown Phenomenon in Polypropylene Under Complex DC Operating Condition 2021 , 173-214		
115	Conduction and Charge Transport Characteristics of Silicone Rubber Composites with Nonlinear Conductivity 2021 , 215-242		1
114	The Insulating Properties of Polypropylene Blends Modified by ULDPPE and Graphene for HVDC Cables 2021 , 97-126		
113	Molecule diffusion behaviours of waterproof sealants into silicone rubber insulation for submarine cable joint based on molecular dynamics simulations. <i>High Voltage</i> , 2021 , 6, 230-241	4.1	3
112	An investigation on discharge fault in buffer layer of 220kV XLPE AC cable. <i>IET Science, Measurement and Technology</i> , 2021 , 15, 508-516	1.5	5
111	Improved Breakdown Strength of Polypropylene Film by Polycyclic Compounds Addition for Power Capacitors. <i>Materials</i> , 2021 , 14,	3.5	4
110	Crystallization Morphology-Dependent Breakdown Strength of Polypropylene Films for Converter Valve Capacitor. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2021 , 28, 964-971	2.3	1
109	Effect of polarity-reversal voltage on charge accumulation and carrier mobility in silicone rubber/silicon carbide composites. <i>IET Science, Measurement and Technology</i> , 2021 , 15, 184-192	1.5	1
108	Electric Field Optimization of 1MV DC-GIL Spacer With Surface Conductivity Gradient for ITER NBI. <i>IEEE Transactions on Applied Superconductivity</i> , 2021 , 1-1	1.8	0
107	Dynamic Interface Charge Behaviors in HVDC Cable Terminal Considering Carrier Dynamic Equilibrium. <i>IEEJ Transactions on Fundamentals and Materials</i> , 2021 , 141, 567-573	0.2	0
106	Effect of Electrical Aging On PPLP Insulation Characteristics in LN2. <i>IEEE Transactions on Applied Superconductivity</i> , 2021 , 31, 1-4	1.8	0
105	Effects of High Magnetic Field on Partial Discharge and Flashover Behavior of Epoxy Resin. <i>IEEE Transactions on Applied Superconductivity</i> , 2021 , 31, 1-4	1.8	1
104	Effect of Harmonic Voltage On Partial Discharge Properties of LN2/PPLP Insulation for HTS DC Cable. <i>IEEE Transactions on Applied Superconductivity</i> , 2021 , 31, 1-4	1.8	
103	Effects of Temperature Gradient on Electrical Tree Initiation and Breakdown Phenomenon in XLPE Under Harmonic Superimposed DC Voltage. <i>IEEE Access</i> , 2021 , 9, 7586-7596	3.5	1
102	Effects of Magnetic field on Partial Discharge in Epoxy Resin for Superconducting Coil Insulation. <i>IEEE Transactions on Applied Superconductivity</i> , 2021 , 1-1	1.8	2

101	Study on Improving Interface Performance of HVDC Composite Insulators by Plasma Etching. <i>Coatings</i> , 2020 , 10, 1036	2.9	3
100	Non-Intrusive Measurement of Transient Electric Field Distribution Under AC and Impulse Voltages. <i>IEEE Sensors Journal</i> , 2020 , 20, 10898-10902	4	1
99	Effects of high temperature and high electric field on the space charge behavior in epoxy resin for power modules. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2020 , 27, 882-890	2.3	14
98	Coupling Effect of Molecular Chain Displacement and Carrier Trap Characteristics on DC Breakdown of HDPE/LDPE Blend Insulation. <i>Polymers</i> , 2020 , 12,	4.5	4
97	Effect of Crystalline Morphology on Electrical Tree Growth Characteristics of High-Density and Low-Density Polyethylene Blend Insulation. <i>IEEE Access</i> , 2020 , 8, 114413-114421	3.5	2
96	Molecular Structure Modulated Trap Distribution and Carrier Migration in Fluorinated Epoxy Resin. <i>Molecules</i> , 2020 , 25,	4.8	7
95	Electric-Field- and Temperature-Dependent Nonlinear Conductivity of SiC/Epoxy Resin Composites at Cryogenic Temperature. <i>IEEE Transactions on Applied Superconductivity</i> , 2020 , 30, 1-6	1.8	1
94	Polycyclic Compounds Affecting Electrical Tree Growth in Polypropylene Under Ambient Temperature. <i>IEEE Access</i> , 2020 , 8, 8886-8898	3.5	2
93	Temperature-dependent DC conductivity and space charge distribution of XLPE/GO nanocomposites for HVDC cable insulation. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2020 , 27, 418-426	2.3	13
92	Improved space charge transport model in bi-layer dielectrics considering carrier dynamic equilibrium. <i>High Voltage</i> , 2020 , 5, 176-183	4.1	10
91	Promising functional graded materials for compact gaseous insulated switchgears/pipelines. <i>High Voltage</i> , 2020 , 5, 231-240	4.1	30
90	Electrical tree degradation in high-voltage cable insulation: progress and challenges. <i>High Voltage</i> , 2020 , 5, 353-364	4.1	22
89	Deep trap sites suppressing space charge injection in polycyclic aromatic compounds doped XLPE composite. <i>IET Nanodielectrics</i> , 2020 , 3, 10-13	2.8	6
88	Electrical Treeing Characteristics in Epoxy under Electro-magnetic Coupled Field. <i>Journal of Physics: Conference Series</i> , 2020 , 1559, 012089	0.3	6
87	Improved Electric Field Distribution Within Bushing Insulation by EP/GO Nanocomposites With Reduced Temperature Coefficient of Conductivity. <i>IEEE Access</i> , 2020 , 8, 176864-176872	3.5	5
86	Investigation of charge transport and breakdown properties in XLPE/GO nanocomposites part 2: Effect of polarity reversal. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2020 , 27, 1213-1221	2.3	5
85	Effect of micro-HO and micro-O on the decomposition characteristics of insulating medium CFCN gas using molecular dynamics and transition state method. <i>Journal of Molecular Modeling</i> , 2020 , 26, 252 ²		3
84	Non-Linear Conductivity Epoxy/SiC Composites for Emerging Power Module Packaging: Fabrication, Characterization and Application. <i>Materials</i> , 2020 , 13,	3.5	2

83	Investigation of charge transport and breakdown properties in XLPE/GO nanocomposites part 1: The role of functionalized GO quantum wells. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2020 , 27, 1204-1212	2.3	11
82	Trap Level Characteristics and DC Breakdown Performance of Isotactic/Syndiotactic/Atactic Polypropylene Blend Insulation. <i>IEEE Access</i> , 2020 , 8, 220840-220847	3.5	
81	Effect of Fullerene Nanoparticle on Tuning Trap Level Distribution of Fullerene/Polyethylene Nanocomposites 2019 ,		2
80	Effect of voltage stabilizers on the space charge behavior of XLPE for HVDC cable application. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2019 , 26, 34-42	2.3	25
79	Surface FGM Insulator Based on BaTiO ₃ Magnetron Sputtering for Electric Field Grading of AC Gas Insulated Power Apparatus. <i>IEEE Access</i> , 2019 , 7, 62681-62688	3.5	11
78	Inhibition Effect of Graphene Nanoplatelets on Electrical Degradation in Silicone Rubber. <i>Polymers</i> , 2019 , 11,	4.5	7
77	Electrical Tree Characteristics in Polypropylene Under Impulse Superimposed DC Voltage in LN ₂ . <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-3	1.8	2
76	Multistep and Multiscale Electron Trapping for High-Efficiency Modulation of Electrical Degradation in Polymer Dielectrics. <i>Journal of Physical Chemistry C</i> , 2019 , 123, 7045-7053	3.8	15
75	Temperature-dependent surface charge and discharge behaviour of converter transformer oil/paper insulation under DC voltage. <i>IET Science, Measurement and Technology</i> , 2019 , 13, 29-34	1.5	5
74	Space charge accumulation in double-layer dielectric systems: measurement methods and quantum chemical calculations. <i>IEEE Electrical Insulation Magazine</i> , 2019 , 35, 36-46	2.1	22
73	Improved DC Conductivity and Space Charge Characteristics of XLPE for HVDC Cable Application: Effect of Voltage Stabilizers. <i>IEEE Access</i> , 2019 , 7, 66576-66583	3.5	13
72	Numerical Investigation on Collision of Pollution Particles on Outdoor Insulators. <i>IEEE Access</i> , 2019 , 7, 56974-56985	3.5	4
71	Effect of Polycyclic Compounds Fillers on Electrical Treeing Characteristics in XLPE with DC-Impulse Voltage. <i>Energies</i> , 2019 , 12, 2767	3.1	4
70	Electronic and optical properties of C-doped BN nanotubes by adsorption of typical decomposition products of C ₃ F ₇ CN gas. <i>Applied Surface Science</i> , 2019 , 491, 698-706	6.7	4
69	Nanoscale-trap-modulated electrical degradation in polymer dielectric composites using antioxidants as voltage stabilizers. <i>Composites Part B: Engineering</i> , 2019 , 178, 107434	10	5
68	Dielectric relaxation and trap-modulated DC breakdown of polypropylene blend insulation. <i>Polymer</i> , 2019 , 185, 121935	3.9	12
67	Mechanism of deep trap sites in epoxy/graphene nanocomposite using quantum chemical calculation. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2019 , 26, 1577-1580	2.3	25
66	Effects of Antioxidant Additives on Electrical Tree Characteristics in EPDM Under Liquid Nitrogen. <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-5	1.8	2

65	Electric Field Regulation of Insulator Interface by FGM With Conductivity for Superconducting-GIL. <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-5	1.8	10
64	Application of E-Field Adaptive Insulator for DC GHe-Insulated Pipeline. <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-3	1.8	2
63	Effects of ZnO magnetron sputtering on surface charge and flashover voltage of oil-impregnated paper. <i>High Voltage</i> , 2019 , 4, 308-315	4.1	20
62	Surface Functional Graded Material Considered for DC Gas-Insulated Pipeline 2019 ,		1
61	Mechanical stress distribution and risk assessment of 110kV GIS insulator considering Al ₂ O ₃ settlement. <i>High Voltage</i> , 2019 , 4, 65-71	4.1	23
60	Surface Charge Transport Characteristics of ZnO/Silicone Rubber Composites Under Impulse Superimposed on DC Voltage. <i>IEEE Access</i> , 2019 , 7, 3008-3017	3.5	12
59	Surface Discharge Property of Polypropylene/BN Nanocomposite for HTS Apparatus Application. <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-4	1.8	1
58	. <i>IEEE Transactions on Applied Superconductivity</i> , 2019 , 29, 1-5	1.8	3
57	Evaluation of high-voltage AC cable grounding systems based on the real-time monitoring and theoretical calculation of grounding currents. <i>High Voltage</i> , 2018 , 3, 38-43	4.1	6
56	Carrier mobility and trap distribution dependent flashover characteristics of epoxy resin. <i>IET Generation, Transmission and Distribution</i> , 2018 , 12, 466-471	2.5	40
55	Effects of non-linear conductivity on charge trapping and de-trapping behaviours in epoxy/SiC composites under DC stress. <i>IET Science, Measurement and Technology</i> , 2018 , 12, 83-89	1.5	27
54	Improved carrier mobility dependent surface charge am flashover voltage of polypropylene film under DC and pulse voltages. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2018 , 25, 1014-1021	2.3	8
53	Surface Layer Fluorination-Modulated Space Charge Behaviors in HVDC Cable Accessory. <i>Polymers</i> , 2018 , 10,	4.5	18
52	Temperature dependent surface charge and discharge behavior of epoxy/AlN nanocomposites. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2018 , 25, 1300-1307	2.3	10
51	Understanding Trap Effects on Electrical Treeing Phenomena in EPDM/POSS Composites. <i>Scientific Reports</i> , 2018 , 8, 8481	4.9	26
50	Electrical Field Distribution in 600 kV Converter Transformer Bushing Core with the Application of Epoxy Resin with Nonlinear Conductivity 2018 ,		4
49	Inhibition Effect of Graphene on Space Charge Injection and Accumulation in Low-Density Polyethylene. <i>Nanomaterials</i> , 2018 , 8,	5.4	8
48	Coupling Effects of Ambient Temperature and Filler Contents on Surface Charge and Discharge Behavior of Epoxy/AlN Nanocomposites 2018 ,		1

47	Temperature-Dependent Surface Charge and Flashover Behaviors of Oil-Paper Insulation Under Impulse With Superimposed DC Voltage. <i>IEEE Access</i> , 2018 , 6, 63087-63093	3.5	8
46	Numerical simulation on the surface charge accumulation process of epoxy insulator under needle-plane corona discharge in air. <i>IET Science, Measurement and Technology</i> , 2018 , 12, 9-16	1.5	9
45	Simulation of Interface Charge Behaviors in HVDC Cable Accessory Based on Bipolar Carrier Transportation Model 2018 ,		1
44	Trap Distribution and Dielectric Breakdown of Isotactic Polypropylene/Propylene Based Elastomer With Improved Flexibility for DC Cable Insulation. <i>IEEE Access</i> , 2018 , 6, 58645-58661	3.5	27
43	Electrical Tree in Epoxy Resin under Combined DC-harmonic Voltage 2018 ,		1
42	Simulation of Interface Charge Behaviors in HVDC Cable Accessory Based on Bipolar Carrier Transportation Model 2018 ,		3
41	Suppressing Space Charge in LDPE/GO Nanocomposites for HVDC Cable Application 2018 ,		1
40	Electrical Tree Initiation and Growth in Silicone Rubber under Combined DC-Pulse Voltage. <i>Energies</i> , 2018 , 11, 764	3.1	14
39	. <i>IEEE Electrical Insulation Magazine</i> , 2018 , 34, 30-43	2.1	54
38	. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2018 , 25, 1479-1486	2.3	18
37	Surface charge coupling behavior of fluorinated polyimide film under DC and pulse voltage. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 567-573	2.3	21
36	Temperature-dependent surface charge behavior of polypropylene film under DC and pulse voltages. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 774-783	2.3	12
35	Trap Modulated Charge Carrier Transport in Polyethylene/Graphene Nanocomposites. <i>Scientific Reports</i> , 2017 , 7, 4015	4.9	53
34	Investigation of electrification and breakdown strength about transformer oil/pressboard. <i>IET Electric Power Applications</i> , 2017 , 11, 386-392	1.8	9
33	Trap distribution of electron beam irradiated epoxy resin under repetitive pulse voltage. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 3869-3877	2.3	17
32	Suppressing interface charge between LDPE and EPDM for HVDC cable accessory insulation. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 1331-1339	2.3	35
31	Effects of mechanical stretching on space charge behaviors of PP/POE blend for HVDC cables. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 1438-1445	2.3	22
30	Effects of mechanical stress on treeing growth characteristics in HTV silicone rubber. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 1547-1556	2.3	18

29	Nonlinear conductivity and interface charge behaviors between LDPE and EPDM/SiC composite for HVDC cable accessory. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 1566-1573	2.3	41
28	Effects of nonlinear conductivity on interface charge in HVDC cable accessories 2017 ,		2
27	Trap dependent interface charge behaviors of fluorinated HVDC cable accessories 2017 ,		1
26	Improved ampacity of buried HVDC cable with high thermal conductivity LDPE/BN insulation. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2017 , 24, 2667-2676	2.3	17
25	Effects of multiple parameters on static electrification and breakdown strength of transformer oil. <i>IET Science, Measurement and Technology</i> , 2016 , 10, 597-601	1.5	8
24	Discharge Breakdown Characteristics With Fluorinated Polyimide Films in High-Temperature Superconducting Cable Insulation. <i>IEEE Transactions on Applied Superconductivity</i> , 2016 , 26, 1-5	1.8	5
23	Effects of direct fluorination on space charge accumulation in HTV silicone rubber. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2016 , 23, 2353-2360	2.3	13
22	Effect of direct fluorination on partial discharge characteristics of polyimide film used as magnet wire insulation of generator. <i>IET Generation, Transmission and Distribution</i> , 2016 , 10, 2251-2258	2.5	2
21	Space charge behaviors of PP/POE/ZnO nanocomposites for HVDC cables. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2016 , 23, 3165-3174	2.3	56
20	Trap Distribution and Flashover Characteristics of Carbon-Black-Filled EPDM in Low Temperature. <i>IEEE Transactions on Applied Superconductivity</i> , 2016 , 26, 1-5	1.8	3
19	Effects of AC and pulse voltage combination on surface charge accumulation and decay of epoxy resin. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2016 , 23, 2368-2376	2.3	22
18	Effects of ambient temperature on surface charge and flashover of heat-shrinkable polymer under polarity reversal voltage. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2016 , 23, 1190-1197	2.3	52
17	Interface charge behaviors between LDPE and EPDM filled with carbon black nanoparticles. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2016 , 23, 3696-3703	2.3	6
16	Surface charge and flashover voltage of EVA/CB nanocomposite under mechanical stresses. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2016 , 23, 3734-3741	2.3	13
15	Reduction of vibration noise for amorphous metal alloy core distribution transformer. <i>Transactions of Tianjin University</i> , 2015 , 21, 289-298	2.9	3
14	Effect of external magnetic fields on the breakdown and partial discharge characteristics of vegetable oil 2015 ,		1
13	Electrical and mechanical ageing behaviors of used heat-shrinkable insulation tubes. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2014 , 21, 1875-1881	2.3	13
12	Effects of nano-SiO ₂ particles on surface tracking characteristics of silicone rubber composites. <i>Applied Physics Letters</i> , 2014 , 105, 102905	3.4	24

11	Effects of low temperature on treeing phenomena of silicone rubber 2013 ,		3
10	Surface charge accumulate and decay of direct-fluorinated RTV silicone rubber 2013 ,		2
9	Tracking and erosion resistance of silicone rubber/BN nanocomposites under DC voltage 2013 ,		9
8	Acoustic Characteristic of Surface Discharge for Hydrophobicity Evaluation of HVDC Silicone Rubber Insulator. <i>IEEJ Transactions on Fundamentals and Materials</i> , 2013 , 133, 121-122	0.2	1
7	Effects of Al ₂ O ₃ Particles on Surface Charge of Epoxy Nanocomposites. <i>IEEJ Transactions on Fundamentals and Materials</i> , 2013 , 133, 224-230	0.2	
6	The calculation of circulating current for the single-core cables in Smart Grid 2012 ,		9
5	Chaos analysis of discharge current based on tracking test of phenolic resin. <i>Transactions of Tianjin University</i> , 2009 , 15, 1-6	2.9	
4	Chaos existence in surface discharge of tracking test. <i>Transactions of Tianjin University</i> , 2009 , 15, 168-172.	0.9	2
3	Effect of gamma-ray irradiation on surface charge behavior of polybutylene naphthalate. <i>Journal of Electrostatics</i> , 2009 , 67, 22-26	1.7	9
2	Dynamic behavior of surface charge on gamma-ray irradiated polybutylene naphthalate. <i>Polymer Degradation and Stability</i> , 2009 , 94, 139-143	4.7	16
1	Effects of Atmospheric Pressure on Insulation Breakdown of Gamma-ray Irradiated Polyphenylene Oxide. <i>IEEJ Transactions on Fundamentals and Materials</i> , 2004 , 124, 271-276	0.2	