

# Jiwei Zhai

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/2404211/publications.pdf>

Version: 2024-02-01

244  
papers

13,469  
citations

21215

62  
h-index

33145

104  
g-index

244  
all docs

244  
docs citations

244  
times ranked

5058  
citing authors

#	ARTICLE	IF	CITATIONS
1	Realizing high-performance capacitive energy storage in lead-free relaxor ferroelectrics via synergistic effect design. <i>Journal of the European Ceramic Society</i> , 2022, 42, 129-139.	2.8	39
2	Non-volatile multi-level cell storage via sequential phase transition in $\text{Sb}_{7-x}\text{Te}_3/\text{GeSb}_6\text{Te}$ multilayer thin film. <i>Nanotechnology</i> , 2022, 33, 075701.	1.3	6
3	Achieving synergistic electromechanical and electrocaloric responses by local structural evolution in lead-free BNT-based relaxor ferroelectrics. <i>Chemical Engineering Journal</i> , 2022, 431, 133386.	6.6	13
4	Simultaneously achieving high energy-storage efficiency and density in Bi-modified $\text{SrTiO}_3$ -based relaxor ferroelectrics by ion selective engineering. <i>Composites Part B: Engineering</i> , 2022, 230, 109493.	5.9	52
5	Isothermal phase transition across phase boundary in $(\text{Pb}_{0.95}\text{Ba}_{0.05})\text{ZrO}_3$ ceramics. <i>Applied Physics Letters</i> , 2022, 120, 023902.	1.5	2
6	Eco-friendly cooling materials with synergistic behavior of electromechanical and electrocaloric effects based on constructing B-site defect field. <i>Applied Materials Today</i> , 2022, 26, 101332.	2.3	2
7	Three-dimensional polypyrrole induced high-performance flexible piezoelectric nanogenerators for mechanical energy harvesting. <i>Composites Science and Technology</i> , 2022, 219, 109260.	3.8	22
8	Composition and Structure Optimized $\text{BiFeO}_3/\text{SrTiO}_3$ Lead-Free Ceramics with Ultrahigh Energy Storage Performance. <i>Small</i> , 2022, 18, e2106515.	5.2	82
9	Piezoelectric enhancement and vacancy defect reduction of lead-free $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ -based thin films. <i>Ceramics International</i> , 2022, 48, 12601-12607.	2.3	7
10	Interfacial polarization regulation of ultrathin 2D nanosheets inducing high energy storage density of polymer-based nanocomposite with opposite gradient architecture. <i>Energy Storage Materials</i> , 2022, 46, 503-511.	9.5	23
11	One doping strategy to simultaneously lower the sintering temperature and increase the energy storage properties. <i>Chemical Engineering Journal</i> , 2022, 434, 134660.	6.6	7
12	Intelligent self-actuating lead-free cooling ceramics based on A-site defect engineering. <i>Acta Materialia</i> , 2022, 227, 117750.	3.8	17
13	Two-Dimensional Fillers Induced Superior Electrostatic Energy Storage Performance in Trilayered Architecture Nanocomposites. <i>ACS Applied Materials &amp; Interfaces</i> , 2022, 14, 8448-8457.	4.0	30
14	Chemical nature of the enhanced energy storage in A-site defect engineered $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ -based relaxor ferroelectrics. <i>Journal of Alloys and Compounds</i> , 2022, 905, 164183.	2.8	15
15	Morphotropic Relaxor Boundary Construction Highly Boosts the Piezoelectric Properties of Bi-Based Lead-Free Thin Films. <i>ACS Applied Materials &amp; Interfaces</i> , 2022, 14, 8115-8125.	4.0	17
16	Ultrahigh energy harvesting properties in temperature-insensitive eco-friendly high-performance KNN-based textured ceramics. <i>Journal of Materials Chemistry A</i> , 2022, 10, 7978-7988.	5.2	58
17	Superior energy storage performance in $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3$ -based lead-free relaxor ferroelectrics for dielectric capacitor application via multiscale optimization design. <i>Journal of Materials Chemistry A</i> , 2022, 10, 9535-9546.	5.2	70
18	Uncovering the physical properties, structural characteristics, and electronic application of superlattice-like Ti/Sb phase-change thin films. <i>Journal Physics D: Applied Physics</i> , 2022, 55, 245102.	1.3	3

#	ARTICLE	IF	CITATIONS
19	Excellent energy storage performance of niobate-based glass-ceramics via introduction of nucleating agent. <i>Journal of Materiomics</i> , 2022, 8, 763-771.	2.8	18
20	Tunable Domain Switching Features of Incommensurate Antiferroelectric Ceramics Realizing Excellent Energy Storage Properties. <i>Advanced Materials</i> , 2022, 34, e2201333.	11.1	62
21	Synergy of a Stabilized Antiferroelectric Phase and Domain Engineering Boosting the Energy Storage Performance of $\text{NaNbO}_3$ -Based Relaxor Antiferroelectric Ceramics. <i>ACS Applied Materials &amp; Interfaces</i> , 2022, 14, 17662-17673.	4.0	48
22	Crystallization-temperature controlled alkali-free niobate glass-ceramics with high energy storage density and actual discharge energy density. <i>Journal of Alloys and Compounds</i> , 2022, 910, 164923.	2.8	7
23	Semiconducting piezoelectric heterostructures for piezo- and piezophotocatalysis. <i>Nano Energy</i> , 2022, 96, 107141.	8.2	69
24	Constructing novel binary $\text{Bi}_0.5\text{Na}_0.5\text{TiO}_3$ -based composite ceramics for excellent energy storage performances via defect engineering. <i>Chemical Engineering Journal</i> , 2022, 439, 135762.	6.6	28
25	Achieving ultrahigh discharge energy and power density in niobate-based glass ceramics via A-site substitution modulation during crystallization. <i>Journal of Materials Chemistry A</i> , 2022, 10, 11535-11541.	5.2	13
26	Efficient Production of Solar Hydrogen Peroxide Using Piezoelectric Polarization and Photoinduced Charge Transfer of Nanopiezoelectrics Sensitized by Carbon Quantum Dots. <i>Advanced Science</i> , 2022, 9, e2105792.	5.6	26
27	Superior energy storage properties in $\text{NaNbO}_3$ -based ceramics via synergistically optimizing domain and band structures. <i>Journal of Materials Chemistry A</i> , 2022, 10, 11613-11624.	5.2	40
28	High depolarization temperature and superior piezoelectric performance with complex structural evolution in $\text{BiFeO}_3\text{PbTiO}_3$ -( $\text{Sr}_{0.7}\text{Bi}_{0.2}$ - $\text{Ti}_{0.1}$ ) $\text{TiO}_3$ systems. <i>Journal of Materiomics</i> , 2022, 8, 1260-1268.	2.8	3
29	Simultaneously achieving high performance of energy storage and transparency via A-site non-stoichiometric defect engineering in KNN-based ceramics. <i>Chemical Engineering Journal</i> , 2022, 444, 136538.	6.6	42
30	Tailoring micro-structure of eco-friendly temperature-insensitive transparent ceramics achieving superior piezoelectricity. <i>Acta Materialia</i> , 2022, 235, 118061.	3.8	12
31	Ultra-sensitive flexible piezoelectric energy harvesters inspired by pine branches for detection. <i>Nano Energy</i> , 2022, 99, 107422.	8.2	11
32	Hidden piezoelectric performances of $\text{BiFeO}_3$ -based textured ceramics. <i>Inorganic Chemistry Frontiers</i> , 2022, 9, 3636-3642.	3.0	1
33	Polarization Rotation Control Domain Dynamic Response Modulates Piezoelectric Properties of Lead-Free Thin Films. <i>Advanced Electronic Materials</i> , 2022, 8, .	2.6	1
34	Enhancement of recoverable energy density and efficiency of lead-free relaxor-ferroelectric BNT-based ceramics. <i>Chemical Engineering Journal</i> , 2021, 406, 126818.	6.6	123
35	Optimization the energy density and efficiency of $\text{BaTiO}_3$ -based ceramics for capacitor applications. <i>Chemical Engineering Journal</i> , 2021, 409, 127375.	6.6	83
36	Enhanced piezoelectricity and reduced leakage current of a novel $(1-x)\text{TjETQqO}_0\text{O}_0\text{rgBT}$ /Overlock 10 Tf 50 67 Td ( $x$ ) $\text{Bi}$ -based thin film. <i>Inorganic Chemistry Frontiers</i> , 2021, 8, 700-710.	3.0	17

#	ARTICLE	IF	CITATIONS
37	Revisiting structural evolution, dielectric and ferroelectric properties in (Pb Ba <sub>1-x</sub> )ZrO <sub>3</sub> system (0.5 ≤ x ≤ 1.0). <i>Ceramics International</i> , 2021, 47, 7430-7437.	2.3	6
38	A superior stable interlayer for dendrite-free solid-state lithium metal batteries. <i>Chemical Engineering Journal</i> , 2021, 421, 127727.	6.6	20
39	Significantly Improvement of Comprehensive Energy Storage Performances with Lead-free Relaxor Ferroelectric Ceramics for High-temperature Capacitors Applications. <i>Acta Materialia</i> , 2021, 203, 116484.	3.8	149
40	Synergistic optimization of antiferroelectric ceramics with superior energy storage properties via phase structure engineering. <i>Energy Storage Materials</i> , 2021, 35, 114-121.	9.5	50
41	Effects of crystalline temperature on microstructures and dielectric properties in BaO-Na <sub>2</sub> O-Bi <sub>2</sub> O <sub>3</sub> -Nb <sub>2</sub> O <sub>5</sub> -Al <sub>2</sub> O <sub>3</sub> -SiO <sub>2</sub> glass-ceramics. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2021, 263, 114885.	1.7	12
42	Improved piezoelectricity and energy storage performance simultaneously achieved in [001]-preferentially oriented Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> â€“BaTiO <sub>3</sub> â€“BiMnO <sub>3</sub> thin films grown on Nb-doped SrTiO <sub>3</sub> single-crystalline substrates. <i>Journal of the European Ceramic Society</i> , 2021, 41, 2539-2547.	2.8	16
43	Substantially improved energy storage capability of ferroelectric thin films for application in high-temperature capacitors. <i>Journal of Materials Chemistry A</i> , 2021, 9, 9281-9290.	5.2	27
44	Fatigue-less relaxor ferroelectric thin films with high energy storage density via defect engineer. <i>Journal of Materials Science and Technology</i> , 2021, 77, 178-186.	5.6	31
45	Realizing high comprehensive energy storage performances of BNT-based ceramics for application in pulse power capacitors. <i>Journal of the European Ceramic Society</i> , 2021, 41, 2548-2558.	2.8	72
46	Optimization of polarization and electric field of bismuth ferrite-based ceramics for capacitor applications. <i>Chemical Engineering Journal</i> , 2021, 417, 127945.	6.6	100
47	Ameliorative energy-storage properties stemmed from the refined grains in PBLZS antiferroelectric ceramics via introducing liquid phase sintering. <i>Journal of the European Ceramic Society</i> , 2021, 41, 2450-2457.	2.8	32
48	Ferroelectric-relaxor crossover induce large electrocaloric effect with ultrawide temperature span in NaNbO <sub>3</sub> -based lead-free ceramics. <i>Applied Physics Letters</i> , 2021, 118, .	1.5	20
49	Ultrahigh energy storage performance of a polymer-based nanocomposite <i>via</i> interface engineering. <i>Journal of Materials Chemistry A</i> , 2021, 9, 3530-3539.	5.2	29
50	High energy storage density with high power density in Bi <sub>0.2</sub> Sr <sub>0.7</sub> TiO <sub>3</sub> /BiFeO <sub>3</sub> multilayer thin films. <i>Journal of Materials Chemistry C</i> , 2021, 9, 4652-4660.	2.7	20
51	Simultaneously improved transparency, photochromic contrast and Curie temperature<i>via</i> rare-earth ion modification in KNN-based ceramics. <i>Inorganic Chemistry Frontiers</i> , 2021, 8, 2027-2035.	3.0	30
52	Performances variations of BiFeO <sub>3</sub> -based ceramics induced by additives with diverse phase structures. <i>CrystEngComm</i> , 2021, 23, 1596-1603.	1.3	9
53	Expedient Red Emitting and Transparency Dual Modulation in KNN-Based Transparent Ceramics via Sensitive Photothermochromic Behavior. <i>ACS Applied Electronic Materials</i> , 2021, 3, 1394-1402.	2.0	19
54	Physical properties and structure characteristics of titanium-modified antimony-selenium phase change thin film. <i>Applied Physics Letters</i> , 2021, 118, .	1.5	12

#	ARTICLE	IF	CITATIONS
55	Potential High-Temperature Piezoelectric Ceramics with Remarkable Performances Enhanced by the Second-Order Jahn-Teller Effect. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 14385-14393.	4.0	17
56	High Performance Generation of $\text{H}_2\text{O}_2$ under Piezophototronic Effect with Multi-Layer $\text{In}_2\text{S}_3$ Nanosheets Modified by Spherical ZnS and $\text{BaTiO}_3$ Nanopiezoelectrics. <i>Small Methods</i> , 2021, 5, e2100269.	4.6	34
57	Simultaneously Realizing Superior Energy Storage Properties and Outstanding Charge-Discharge Performances in Tungsten Bronze-Based Ceramic for Capacitor Applications. <i>Inorganic Chemistry</i> , 2021, 60, 6559-6568.	1.9	46
58	Crystallization characteristic and structure of hafnium addition in germanium antimony thin films for phase change memory. <i>Journal of Alloys and Compounds</i> , 2021, 864, 158893.	2.8	3
59	Enhanced Sunlight-Driven Reactive Species Generation via Polarization Field in Nanopiezoelectric Heterostructures. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 29691-29707.	4.0	8
60	Significantly Photo-Thermochromic KNN-Based "Smart Window" for Sustainable Optical Data Storage and Anti-Counterfeiting. <i>Advanced Optical Materials</i> , 2021, 9, 2100580.	3.6	39
61	$\text{Cr}_7\text{Ge}_{33}\text{Te}_{60}/\text{Hf}_{16}\text{Ge}_6\text{Sb}_{78}$ Superlattice-Like Thin Film with Triple-Phase Transitions for Multilevel Phase-Change Memory. <i>Physica Status Solidi - Rapid Research Letters</i> , 2021, 15, 2100222.	1.2	4
62	2D Fillers Highly Boost the Discharge Energy Density of Polymer-Based Nanocomposites with Trilayered Architecture. <i>Advanced Functional Materials</i> , 2021, 31, 2102646.	7.8	56
63	Simultaneously ultra-low dielectric loss and rapid discharge time in Ta <sub>2</sub> O <sub>5</sub> doped niobate-based glass-ceramics. <i>Journal of Materials Science</i> , 2021, 56, 16278-16289.	1.7	7
64	Relaxor ferroelectric (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -based ceramic with remarkable comprehensive energy storage performance under low electric field for capacitor applications. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 21164-21177.	1.1	9
65	Cu-Doped Alloy Layer Guiding Uniform Li Deposition on a Li-LLZO Interface under High Current Density. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 42212-42219.	4.0	23
66	Defect Management and Multi-Mode Optoelectronic Manipulations via Photo-Thermochromism in Smart Windows. <i>Laser and Photonics Reviews</i> , 2021, 15, 2100211.	4.4	66
67	Performance Improvement of Sb Phase Change Thin Film by Y Doping. <i>ECS Journal of Solid State Science and Technology</i> , 2021, 10, 093002.	0.9	6
68	Ultrahigh Energy Storage Performance of Layered Polymer Nanocomposites over a Broad Temperature Range. <i>Advanced Materials</i> , 2021, 33, e2103338.	11.1	96
69	(Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -based relaxor ferroelectrics with simultaneous high energy storage properties and remarkable charge-discharge performances under low working electric fields for dielectric capacitor applications. <i>Ceramics International</i> , 2021, 47, 25800-25809.	2.3	25
70	Comparative study of phase structure, dielectric properties and electrocaloric effect in novel high-entropy ceramics. <i>Journal of Materials Science</i> , 2021, 56, 18417-18429.	1.7	16
71	Construction of multi-domain coexistence enhanced piezoelectric properties of Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -based thin films. <i>Journal of the European Ceramic Society</i> , 2021, 41, 6456-6464.	2.8	11
72	Macrodomain structure formed in (Sr <sub>0.7</sub> Bi <sub>0.2</sub> -i0.1)TiO <sub>3</sub> -modified Bi <sub>0.5</sub> Na <sub>0.4</sub> K <sub>0.1</sub> TiO <sub>3</sub> thin film. <i>Ceramics International</i> , 2021, 47, 26955-26962.	2.3	3

#	ARTICLE	IF	CITATIONS
73	Ta-doped Ge <sub>5</sub> Sb <sub>95</sub> phase change thin films for high speed and low power application. <i>Journal of Non-Crystalline Solids</i> , 2021, 571, 121069.	1.5	6
74	High breakdown strength and enhanced energy storage performance of niobate-based glass-ceramics via glass phase structure optimization. <i>Ceramics International</i> , 2021, 47, 31229-31237.	2.3	10
75	Sandwich structured lead-free ceramics based on Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> for high energy storage. <i>Chemical Engineering Journal</i> , 2021, 425, 130669.	6.6	49
76	Significantly enhanced energy storage performances and power density in (1-x)BCZT-xSBT lead-free ceramics via synergistic optimization strategy. <i>Chemical Engineering Journal</i> , 2021, 426, 130800.	6.6	42
77	Rapid poling under low direct current field of [001] oriented BiFeO <sub>3</sub> -based lead-free ceramics. <i>Scripta Materialia</i> , 2021, 205, 114181.	2.6	8
78	High capacitive performance at moderate operating field in (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -based dielectric ceramics via synergistic effect of site engineering strategy. <i>Chemical Engineering Journal</i> , 2021, 426, 130811.	6.6	45
79	Excellent energy storage properties and superior stability achieved in lead-free ceramics via a spatial sandwich structure design strategy. <i>Journal of Materials Chemistry A</i> , 2021, 9, 15827-15835.	5.2	44
80	Optimizing the energy storage properties of antiferroelectric ceramics by modulating the phase structure via constructing a novel binary composite. <i>Journal of Materials Chemistry A</i> , 2021, 9, 11291-11299.	5.2	16
81	Achieving Superior Energy Storage Properties and Ultrafast Discharge Speed in Environment-Friendly Niobate-Based Glass Ceramics. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 4236-4243.	4.0	32
82	Reactive Oxygenated Species Generated on Iodide-Doped BiVO <sub>4</sub> /BaTiO <sub>3</sub> Heterostructures with Ag/Cu Nanoparticles by Coupled Piezophototronic Effect and Plasmonic Excitation. <i>Advanced Functional Materials</i> , 2021, 31, 2009594.	7.8	80
83	Coexistence of excellent piezoelectric performance and thermal stability in KNN-based lead-free piezoelectric ceramics. <i>Ceramics International</i> , 2020, 46, 1390-1395.	2.3	33
84	Electrocaloric effect in BNT-based lead-free ceramics by local-structure and phase-boundary evolution. <i>Journal of Alloys and Compounds</i> , 2020, 817, 152794.	2.8	20
85	Reduced leakage current and enhanced piezoelectricity of BNT-BT-BMO thin films. <i>Journal of the American Ceramic Society</i> , 2020, 103, 1219-1229.	1.9	16
86	Greatly enhanced discharge energy density and efficiency of novel relaxation ferroelectric BNT-BKT-based ceramics. <i>Journal of Materials Chemistry C</i> , 2020, 8, 591-601.	2.7	224
87	Zn-doped Sb <sub>70</sub> Se <sub>30</sub> thin films with multiple phase transition for high storage density and low power consumption phase change memory applications. <i>Scripta Materialia</i> , 2020, 178, 324-328.	2.6	13
88	High energy storage performance and fast discharging speed in dense 0.7Bi <sub>0.5</sub> K <sub>0.5</sub> TiO <sub>3</sub> -0.3SrTiO <sub>3</sub> ceramics via a novel rolling technology. <i>Ceramics International</i> , 2020, 46, 6995-6998.	2.3	23
89	High piezoelectricity and stable output in BaHfO <sub>3</sub> and (Bi <sub>0.5</sub> Na <sub>0.5</sub> )ZrO <sub>3</sub> modified (K <sub>0.5</sub> Na <sub>0.5</sub> )(Nb <sub>0.96</sub> Sb <sub>0.04</sub> )O <sub>3</sub> textured ceramics. <i>Acta Materialia</i> , 2020, 199, 542-550.	3.8	36
90	The optimization effect of titanium on the phase change properties of SnSb <sub>4</sub> thin films for phase change memory applications. <i>CrystEngComm</i> , 2020, 22, 5002-5009.	1.3	4

#	ARTICLE	IF	CITATIONS
91	Multi-domain BNiT modification enhanced the piezoelectric properties of BNT-based lead-free thin films. <i>Journal of Materials Chemistry C</i> , 2020, 8, 17114-17121.	2.7	17
92	Giant Field-Induced Strain with Low Hysteresis and Boosted Energy Storage Performance under Low Electric Field in (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -Based Grain Orientation-Controlled Ceramics. <i>Advanced Electronic Materials</i> , 2020, 6, 2000332.	2.6	59
93	Remarkable Piezophoto Coupling Catalysis Behavior of BiOX/BaTiO <sub>3</sub> (X = Cl, Br). <i>TJ ETQq1 1 0.784314 rgBT /Overlock 10</i>	5.2	133
94	Ultrahigh breakdown strength and energy density of polymer nanocomposite containing surface insulated BCZT@BN nanofibers. <i>Composites Science and Technology</i> , 2020, 195, 108209.	3.8	24
95	Normal-relaxor ferroelectric phase transition induced morphotropic phase boundary accompanied by enhanced piezoelectric and electrostrain properties in strontium modulated Bi <sub>0.5</sub> K <sub>0.5</sub> TiO <sub>3</sub> lead-free ceramics. <i>Journal of the European Ceramic Society</i> , 2020, 40, 3918-3927.	2.8	23
96	Tailoring high energy density with superior stability under low electric field in novel (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -based relaxor ferroelectric ceramics. <i>Journal of the European Ceramic Society</i> , 2020, 40, 4475-4486.	2.8	123
97	Superior energy storage properties and excellent stability achieved in environment-friendly ferroelectrics via composition design strategy. <i>Nano Energy</i> , 2020, 75, 105012.	8.2	205
98	Integrating chemical engineering and crystallographic texturing design strategy for the realization of practically viable lead-free sodium bismuth titanate-based incipient piezoceramics. <i>Dalton Transactions</i> , 2020, 49, 8661-8671.	1.6	10
99	Significantly enhanced energy storage density and efficiency of BNT-based perovskite ceramics via A-site defect engineering. <i>Energy Storage Materials</i> , 2020, 30, 392-400.	9.5	298
100	Influences of rare earth site engineering on piezoelectric and electromechanical response of (Ba <sub>0.85</sub> Ca <sub>0.15</sub> )(Zr <sub>0.1</sub> Ti <sub>0.9</sub> )O <sub>3</sub> lead-free ceramics. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 6560-6573.	1.1	9
101	Improving electromechanical properties in KNANS-BNZ ceramics by the synergy between phase structure modification and grain orientation. <i>Journal of Materials Chemistry C</i> , 2020, 8, 6149-6158.	2.7	14
102	Enhanced piezoelectric properties of (1 - x)BiFe <sub>0.98</sub> (Zn <sub>0.5</sub> Hf <sub>0.5</sub> ) <sub>0.02</sub> O <sub>3</sub> -xBaTiO <sub>3</sub> ceramics near the morphotropic phase boundary. <i>Dalton Transactions</i> , 2020, 49, 5573-5580.	1.6	9
103	Enhanced energy storage capability of (1-x)Na <sub>0.5</sub> Bi <sub>0.5</sub> TiO <sub>3</sub> -xSr <sub>0.7</sub> Bi <sub>0.2</sub> TiO <sub>3</sub> free-lead relaxor ferroelectric thin films. <i>Ceramics International</i> , 2020, 46, 14816-14821.	2.3	29
104	Revealing the relationship between morphotropic phase boundary and tolerance factor of Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -based thin films. <i>Journal of the European Ceramic Society</i> , 2020, 40, 2954-2963.	2.8	16
105	Fatigue-Free Aurivillius Phase Ferroelectric Thin Films with Ultrahigh Energy Storage Performance. <i>Advanced Energy Materials</i> , 2020, 10, 2001536.	10.2	114
106	B-site-doped BiFeO <sub>3</sub> -based piezoceramics with enhanced ferro/piezoelectric properties and good temperature stability. <i>Journal of the American Ceramic Society</i> , 2020, 103, 6245-6254.	1.9	33
107	Ultralow Electrical Hysteresis along with High Energy Storage Density in Lead-Based Antiferroelectric Ceramics. <i>Advanced Electronic Materials</i> , 2020, 6, 1901366.	2.6	81
108	Realizing superior energy storage properties in lead-free ceramics via a macro-structure design strategy. <i>Journal of Materials Chemistry A</i> , 2020, 8, 11656-11664.	5.2	82

#	ARTICLE	IF	CITATIONS
109	Enhanced energy-storage density in sodium-barium-niobate based glass-ceramics realized by doping CaF <sub>2</sub> nucleating agent. Journal of Materials Science: Materials in Electronics, 2019, 30, 15277-15284.	1.1	8
110	SbSe/ZnSb stacked thin films with multi-level phase transition for high density phase change memory applications. Journal of Materials Science: Materials in Electronics, 2019, 30, 15024-15030.	1.1	4
111	<i>In-situ</i> investigation on the crystallization property and microstructure evolution induced by thermal annealing and electron beam irradiation of titanium antimony thin film. Applied Physics Letters, 2019, 115, .	1.5	11
112	Excellent energy storage density and charge-discharge performance of a novel Bi <sub>0.2</sub> Sr <sub>0.7</sub> TiO <sub>3</sub> BiFeO <sub>3</sub> thin film. Journal of Materials Chemistry C, 2019, 7, 10891-10900.	2.7	42
113	A Study on the Relationship Between Grain Size and Electrical Properties in (K,Na)NbO <sub>3</sub> -Based Lead-Free Piezoelectric Ceramics. Advanced Electronic Materials, 2019, 5, 1900570.	2.6	50
114	Improvement of phase change speed and thermal stability in Ge <sub>5</sub> Sb <sub>95</sub> /ZnSb multilayer thin films for phase change memory application. Semiconductor Science and Technology, 2019, 34, 105022.	1.0	4
115	Ultrahigh Energy Storage Density and Excellent Charge-Discharge Properties of Bi <sub>2</sub> O <sub>3</sub> -Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub> Glass Ceramic with CeO <sub>2</sub> Doping. Journal of Electronic Materials, 2019, 48, 6183-6188.	1.0	5
116	Fine-grain induced outstanding energy storage performance in novel Bi <sub>0.5</sub> K <sub>0.5</sub> TiO <sub>3</sub> Ba(Mg <sub>1/3</sub> Nb <sub>2/3</sub> )O <sub>3</sub> ceramics <i>via</i> a hot-pressing strategy. Journal of Materials Chemistry C, 2019, 7, 12127-12138.		119
117	Piezophototronic effect in enhancing charge carrier separation and transfer in ZnO/BaTiO <sub>3</sub> heterostructures for high-efficiency catalytic oxidation. Nano Energy, 2019, 66, 104127.	8.2	163
118	Excellent energy storage and charge-discharge performances in sodium-barium-niobium based glass ceramics. Ceramics International, 2019, 45, 19429-19434.	2.3	14
119	Multifunctionality of lead-free BiFeO <sub>3</sub> -based ergodic relaxor ferroelectric ceramics: High energy storage performance and electrocaloric effect. Journal of Alloys and Compounds, 2019, 803, 185-192.	2.8	79
120	Tailoring frequency-insensitive large field-induced strain and energy storage properties in (Ba <sub>0.85</sub> Ca <sub>0.15</sub> )(Zr <sub>0.1</sub> Ti <sub>0.9</sub> )O <sub>3</sub> -modified (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> lead-free ceramics. Dalton Transactions, 2019, 48, 10160-10173.	1.6	59
121	Highly enhanced discharged energy density of polymer nanocomposites <i>via</i> a novel hybrid structure as fillers. Journal of Materials Chemistry A, 2019, 7, 15347-15355.	5.2	89
122	Simultaneously enhanced discharge energy density and efficiency in nanocomposite film capacitors utilizing two-dimensional NaNbO <sub>3</sub> @Al <sub>2</sub> O <sub>3</sub> platelets. Nanoscale, 2019, 11, 10546-10554.	2.8	93
123	Flexible antiferroelectric thick film deposited on nickel foils for high energy storage capacitor. Journal of the American Ceramic Society, 2019, 102, 6107-6114.	1.9	28
124	Designing novel sodium bismuth titanate lead-free incipient perovskite for piezoactuator applications. Journal of the American Ceramic Society, 2019, 102, 6751-6759.	1.9	12
125	Achieving high discharge energy density and efficiency with NBT-based ceramics for application in capacitors. Journal of Materials Chemistry C, 2019, 7, 4072-4078.	2.7	291
126	Structure-design strategy of 0-3 type (Bi <sub>0.32</sub> Sr <sub>0.42</sub> Na <sub>0.20</sub> )TiO <sub>3</sub> /MgO composite to boost energy storage density, efficiency and charge-discharge performance. Journal of the European Ceramic Society, 2019, 39, 2889-2898.	2.8	100



#	ARTICLE	IF	CITATIONS
127	Novel bismuth ferrite-based lead-free incipient piezoceramics with high electromechanical response. <i>Journal of Materials Chemistry C</i> , 2019, 7, 5122-5130.	2.7	63
128	Glass-ceramic dielectric materials with high energy density and ultra-fast discharge speed for high power energy storage applications. <i>Journal of Materials Chemistry C</i> , 2019, 7, 15118-15135.	2.7	70
129	High-performance potassium-sodium niobate lead-free piezoelectric ceramics based on polymorphic phase boundary and crystallographic texture. <i>Acta Materialia</i> , 2019, 165, 486-495.	3.8	61
130	Superior discharge energy density and efficiency in polymer nanocomposites induced by linear dielectric core-shell nanofibers. <i>Journal of Materials Chemistry C</i> , 2019, 7, 405-413.	2.7	92
131	Enhanced piezoelectric performance and thermal stability of alkali niobate-based ceramics. <i>Ceramics International</i> , 2019, 45, 2275-2280.	2.3	21
132	Grain size dependent physical properties in lead-free multifunctional piezoceramics: A case study of NBT-xST system. <i>Acta Materialia</i> , 2019, 164, 12-24.	3.8	98
133	Dielectric characterization of a novel Bi <sub>2</sub> O <sub>3</sub> -Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub> glass-ceramic with excellent charge-discharge properties. <i>Journal of the European Ceramic Society</i> , 2019, 39, 1164-1169.	2.8	21
134	Progress in high-strain perovskite piezoelectric ceramics. <i>Materials Science and Engineering Reports</i> , 2019, 135, 1-57.	14.8	530
135	High-energy-density with polymer nanocomposites containing of SrTiO <sub>3</sub> nanofibers for capacitor application. <i>Composites Part A: Applied Science and Manufacturing</i> , 2018, 109, 48-54.	3.8	145
136	Simultaneously high-energy storage density and responsivity in quasi-hysteresis-free Mn-doped Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -BaTiO <sub>3</sub> -(Sr <sub>0.7</sub> Bi <sub>0.2</sub> Ag <sub>0.1</sub> ) <sub>1-x</sub> ergodic relaxor ceramics. <i>Materials Research Letters</i> , 2018, 6, 345-352.	2.1	168
137	Interfacial Coupling Effect in Organic/Inorganic Nanocomposites with High Energy Density. <i>Advanced Materials</i> , 2018, 30, e1705662.	11.1	245
138	Crystallization kinetics behavior and dielectric energy storage properties of strontium potassium niobate glass-ceramics with different nucleating agents. <i>Ceramics International</i> , 2018, 44, 8528-8533.	2.3	38
139	Giant electrostrain accompanying structural evolution in lead-free NBT-based piezoceramics. <i>Journal of Materials Chemistry C</i> , 2018, 6, 814-822.	2.7	68
140	The phase formation process of Bi <sub>0.5</sub> (Na <sub>0.8</sub> K <sub>0.2</sub> ) <sub>0.5</sub> TiO <sub>3</sub> thin films prepared using the sol-gel method. <i>Ceramics International</i> , 2018, 44, 6402-6408.	2.3	5
141	Effects of crystallization temperature on phase evolution and energy storage properties of BaO-Na <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub> glass-ceramics. <i>Journal of the European Ceramic Society</i> , 2018, 38, 2312-2317.	2.8	26
142	Ultrahigh Piezoelectric Properties in Textured (K,Na)NbO <sub>3</sub> -Based Lead-Free Ceramics. <i>Advanced Materials</i> , 2018, 30, 1705171.	11.1	361
143	Effects of TiO <sub>2</sub> addition on dielectric and energy storage properties of BaO-K <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> glass ceramics. <i>Ceramics International</i> , 2018, 44, 6181-6185.	2.3	28
144	Crystallization characteristic and scaling behavior of germanium antimony thin films for phase change memory. <i>Nanoscale</i> , 2018, 10, 7228-7237.	2.8	33

#	ARTICLE	IF	CITATIONS
145	Mechanism of significantly enhanced piezoelectric performance and stability in textured potassium-sodium niobate piezoelectric ceramics. <i>Journal of the European Ceramic Society</i> , 2018, 38, 75-83.	2.8	31
146	Enhancement of Dielectric Breakdown Strength and Energy Conversion Efficiency of Niobate Glass-Ceramics by Sc <sub>2</sub> O <sub>3</sub> Doping. <i>Journal of Electronic Materials</i> , 2018, 47, 834-842.	1.0	7
147	High energy storage density and rapid discharge speed of niobosilicate glasses. <i>Materials Chemistry and Physics</i> , 2018, 206, 29-34.	2.0	12
148	Superlattice-like Sb-Ge thin films for high thermal stability and low power phase change memory. <i>Journal of Alloys and Compounds</i> , 2018, 738, 145-150.	2.8	11
149	Ultrahigh energy storage density and instantaneous discharge power density in BaO-PbO-Na <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub> glass-ceramics. <i>Journal of Materials Chemistry C</i> , 2018, 6, 12608-12614.	2.3	34
150	Crystallization Mechanisms and Energy-Storage Performances in BaO-SrO-Na <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> Based Glass-Ceramics. <i>Journal of Electronic Materials</i> , 2018, 47, 7429-7434.	1.0	6
151	Atomistic insights toward strengthening of GeTe phase change material by impurity doping and grain boundary engineering. <i>Journal of Applied Physics</i> , 2018, 124, .	1.1	3
152	Recent progress of ecofriendly perovskite-type dielectric ceramics for energy storage applications. <i>Journal of Advanced Dielectrics</i> , 2018, 08, 1830005.	1.5	84
153	Influence of structural evolution on electrocaloric effect in Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -SrTiO <sub>3</sub> ferroelectric ceramics. <i>Journal of Applied Physics</i> , 2018, 124, .	1.1	40
154	Effect of phase structures on dielectric properties and energy storage performances in Na <sub>2</sub> O-BaO-PbO-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> -Al <sub>2</sub> O <sub>3</sub> glass-ceramics. <i>Ceramics International</i> , 2018, 44, 23109-23115.	2.3	22
155	Enhanced energy storage properties of BaO-K <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> glass ceramics obtained through microwave crystallization. <i>Ceramics International</i> , 2018, 44, 15490-15494.	2.3	7
156	Enhanced piezoelectric properties and electrocaloric effect in novel lead-free (Bi <sub>0.5</sub> K <sub>0.5</sub> )TiO <sub>3</sub> -La(Mg <sub>0.5</sub> Ti <sub>0.5</sub> )O <sub>3</sub> ceramics. <i>Journal of the American Ceramic Society</i> , 2018, 101, 5503-5513.	1.9	20
157	Great enhancement of energy storage density and power density in BNBT/xBFO multilayer thin film hetero-structures. <i>Inorganic Chemistry Frontiers</i> , 2018, 5, 2300-2305.	3.0	39
158	High-performance capacitors based on NaNbO <sub>3</sub> nanowires/poly(vinylidene fluoride) nanocomposites. <i>Journal of Materials Chemistry A</i> , 2018, 6, 14614-14622.	5.2	94
159	Novel barium titanate based ferroelectric relaxor ceramics with superior charge-discharge performance. <i>Journal of the European Ceramic Society</i> , 2018, 38, 4646-4652.	2.8	161
160	High recoverable energy storage density in (1-x)Bi <sub>0.5</sub> (Na <sub>0.8</sub> K <sub>0.2</sub> ) <sub>0.5</sub> TiO <sub>3</sub> -xSrZrO <sub>3</sub> thin films prepared by a sol-gel method. <i>Journal of the European Ceramic Society</i> , 2018, 38, 4640-4645.	2.8	38
161	Understanding the crystallization behavior and structure of titanium addition in germanium antimony phase change thin films. <i>Journal of Materials Chemistry C</i> , 2018, 6, 9081-9092.	2.7	28
162	Improvement of energy storage properties in niobate glass-ceramics via the adjustment of glass/ceramic ratios. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 16758-16764.	1.1	6

#	ARTICLE	IF	CITATIONS
163	Exploring novel bismuth-based materials for energy storage applications. <i>Journal of Materials Chemistry C</i> , 2018, 6, 7976-7981.	2.7	93
164	Largely enhanced energy storage capability of a polymer nanocomposite utilizing a core-satellite strategy. <i>Nanoscale</i> , 2018, 10, 16621-16629.	2.8	70
165	Microscopic Insight into Electric Fatigue Resistance and Thermally Stable Piezoelectric Properties of (K,Na)NbO <sub>3</sub> -Based Ceramics. <i>ACS Applied Materials &amp; Interfaces</i> , 2018, 10, 28772-28779.	4.0	71
166	Enhanced piezoelectricity and energy storage performances of Fe-doped BNT <sub>1-x</sub> BKT <sub>x</sub> ST thin films. <i>Ceramics International</i> , 2018, 44, 21289-21294.	2.3	35
167	Local phenomena in bismuth sodium titanate perovskite studied by Raman spectroscopy. <i>Journal of the American Ceramic Society</i> , 2018, 101, 5604-5614.	1.9	34
168	Electric-field-induced local distortion and large electrostrictive effects in lead-free NBT-based relaxor ferroelectrics. <i>Journal of the European Ceramic Society</i> , 2018, 38, 4631-4639.	2.8	49
169	Improved dielectric breakdown strength and suppressed energy loss in niobate glass-ceramics crystallized by microwave process. <i>Materials Letters</i> , 2017, 190, 154-156.	1.3	11
170	High-Energy-Density Polymer Nanocomposites Composed of Newly Structured One-Dimensional BaTiO <sub>3</sub> @Al <sub>2</sub> O <sub>3</sub> Nanofibers. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 4024-4033.	4.0	241
171	Novel design of highly [110]-oriented barium titanate nanorod array and its application in nanocomposite capacitors. <i>Nanoscale</i> , 2017, 9, 4255-4264.	2.8	53
172	Study of temperature-induced structural evolution in (Na <sub>0.5</sub> Bi <sub>0.5</sub> )TiO <sub>3</sub> -(K <sub>0.5</sub> Bi <sub>0.5</sub> )TiO <sub>3</sub> -(K <sub>0.5</sub> Na) <sub>1-x</sub> Bi <sub>x</sub> TiO <sub>3</sub> relaxor ferroelectrics. <i>Journal of Applied Physics</i> , 2017, 121, .	1.1	15
173	NaNbO <sub>3</sub> templates-induced phase evolution and enhancement of electromechanical properties in grain oriented lead-free BNT-based piezoelectric materials. <i>Journal of the European Ceramic Society</i> , 2017, 37, 2591-2604.	2.8	84
174	Influence of structural evolution on energy storage properties in Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -SrTiO <sub>3</sub> -NaNbO <sub>3</sub> lead-free ferroelectric ceramics. <i>Journal of Applied Physics</i> , 2017, 121, .	1.1	111
175	Effect of crystallization temperature on dielectric and energy-storage properties in SrO-Na <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> glass-ceramics. <i>Ceramics International</i> , 2017, 43, 8898-8904.	2.3	25
176	High recoverable energy storage density and large piezoelectric response in (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -PbTiO <sub>3</sub> thin films prepared by a sol-gel method. <i>Journal of the European Ceramic Society</i> , 2017, 37, 3319-3327.	2.8	35
177	Ultrafast Discharge and High-Energy-Density of Polymer Nanocomposites Achieved via Optimizing the Structure Design of Barium Titanates. <i>ACS Sustainable Chemistry and Engineering</i> , 2017, 5, 4707-4717.	3.2	102
178	Investigation on the crystallization properties and structure of oxygen-doped Ge <sub>8</sub> Sb <sub>92</sub> phase change thin films. <i>Journal Physics D: Applied Physics</i> , 2017, 50, 095602.	1.3	20
179	Ti <sub>x</sub> Sb <sub>100-x</sub> thin films as candidates for phase-change memory application. <i>Applied Physics Letters</i> , 2017, 110, .	1.5	25
180	Significantly improved dielectric properties and energy density of polymer nanocomposites via small loaded of BaTiO <sub>3</sub> nanotubes. <i>Composites Science and Technology</i> , 2017, 147, 30-38.	3.8	139

#	ARTICLE	IF	CITATIONS
181	Effects of Sr substitution for Ba on dielectric and energy-storage properties of SrO-BaO-K <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> glass-ceramics. <i>Journal of the European Ceramic Society</i> , 2017, 37, 3917-3925.	2.8	40
182	Type-II pseudo-first-order phase transition induced electrocaloric effect in lead-free Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -0.06BaTiO <sub>3</sub> ceramics. <i>Applied Physics Letters</i> , 2017, 110, .	1.5	73
183	Crystallization kinetics, breakdown strength, and energy-storage properties in niobate-based glass-ceramics. <i>Journal of Alloys and Compounds</i> , 2017, 722, 212-218.	2.8	51
184	The Structure, Dielectric and Energy Storage Properties of Strontium Barium Niobate-Based Glass-Ceramics Doped with La <sub>2</sub> O <sub>3</sub> . <i>Journal of Electronic Materials</i> , 2017, 46, 4557-4561.	1.0	9
185	Ultrafast Discharge and Enhanced Energy Density of Polymer Nanocomposites Loaded with 0.5(Ba <sub>0.7</sub> Ca <sub>0.3</sub> )TiO <sub>3</sub> -0.5Ba(Zr <sub>0.2</sub> Ti <sub>0.8</sub> )O <sub>4</sub> Nanofibers. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 14337-14346.	4.3	120
186	Effect of K <sub>2</sub> O content on breakdown strength and energy-storage density in K <sub>2</sub> O-BaO-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> glass-ceramics. <i>Ceramics International</i> , 2017, 43, 4183-4187.	2.3	25
187	Improving piezoelectric properties by controlling phase structure and crystal orientation. <i>RSC Advances</i> , 2017, 7, 41788-41795.	1.7	17
188	Multi-level storage and ultra-high speed of superlattice-like Ge <sub>50</sub> Te <sub>50</sub> /Ge <sub>8</sub> Sb <sub>92</sub> thin film for phase-change memory application. <i>Nanotechnology</i> , 2017, 28, 405206.	1.3	22
189	NaNbO <sub>3</sub> two-dimensional platelets induced highly energy storage density in trilayered architecture composites. <i>Nano Energy</i> , 2017, 40, 587-595.	8.2	247
190	Temperature induced high charge-discharge performances in lead-free Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -based ergodic relaxor ferroelectric ceramics. <i>Scripta Materialia</i> , 2017, 141, 15-19.	2.6	155
191	Enhanced dielectric and energy-storage properties in BiFeO <sub>3</sub> -modified Bi <sub>0.5</sub> (Na <sub>0.8</sub> K <sub>0.2</sub> ) <sub>0.5</sub> TiO <sub>3</sub> thin films. <i>Ceramics International</i> , 2017, 43, 13371-13376.	2.3	46
192	Multilayer SnSb <sub>4</sub> -SbSe Thin Films for Phase Change Materials Possessing Ultrafast Phase Change Speed and Enhanced Stability. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 27004-27013.	4.0	21
193	Study on the physical properties and structure of titanium antimony thin films for phase change memory application. <i>Journal of Materials Science</i> , 2017, 52, 11598-11607.	1.7	21
194	The effects of MnO <sub>2</sub> addition on the structure and dielectric properties of the strontium barium niobate glass-ceramics. <i>Materials Research Bulletin</i> , 2017, 95, 349-353.	2.7	17
195	Phase-composition and temperature dependence of electrocaloric effect in lead-free Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -BaTiO <sub>3</sub> (Sr <sub>0.7</sub> Bi <sub>0.2</sub> -i <sub>0.1</sub> )TiO <sub>3</sub> ceramics. <i>Journal of the European Ceramic Society</i> , 2017, 37, 4732-4740.	2.8	76
196	Large improvement on energy storage and charge-discharge properties of Gd <sub>2</sub> O <sub>3</sub> -doped BaO-K <sub>2</sub> O-Nb <sub>2</sub> O <sub>5</sub> -SiO <sub>2</sub> glass-ceramic dielectrics. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2017, 223, 178-184.	1.7	28
197	Multilayer hierarchical interfaces with high energy density in polymer nanocomposites composed of BaTiO <sub>3</sub> @TiO <sub>2</sub> @Al <sub>2</sub> O <sub>3</sub> nanofibers. <i>Journal of Materials Chemistry A</i> , 2017, 5, 15217-15226.	5.2	221
198	Significantly enhanced energy-storage density in the strontium barium niobate-based/titanate-based glass-ceramics. <i>Journal of the American Ceramic Society</i> , 2017, 100, 506-510.	1.9	22

#	ARTICLE	IF	CITATIONS
199	Tuning the ferroelectric-relaxor transition temperature in NBT-based lead-free ceramics by Bi nonstoichiometry. Journal of the European Ceramic Society, 2017, 37, 4585-4595.	2.8	64
200	Microstructure evolution and energy storage properties of potassium strontium niobate boronaluminosilicate glass-ceramics by microwave crystallization. Journal of the European Ceramic Society, 2016, 36, 4071-4076.	2.8	31
201	Composition- and temperature-driven phase transition characteristics and associated electromechanical properties in $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ -based lead-free ceramics. Dalton Transactions, 2016, 45, 8573-8586.	1.6	84
202	Phase evolution and correlation between tolerance factor and electromechanical properties in BNT-based ternary perovskite compounds with calculated end-member $\text{Bi}(\text{Me}_{0.5}\text{Ti}_{0.5})\text{O}_3$ (Me = Zn, Mg, Ni, Co). Dalton Transactions, 2016, 45, 14141-14153.	1.6	47
203	Surface-modified $\text{Ba}(\text{Zr}_{0.3}\text{Ti}_{0.7})\text{O}_3$ nanofibers by polyvinylpyrrolidone filler for poly(vinylidene fluoride) thin films. Reports, 2016, 6, 26198.	1.6	105
204	Improvement of phase change properties of stacked $\text{Ge}_2\text{Sb}_2\text{Te}_5/\text{ZnSb}$ thin films for phase change memory application. Materials Letters, 2016, 185, 399-402.	1.3	12
205	Ultra High Energy Storage Density in the Barium Potassium Niobate-Based Glass-Ceramics for Energy Storage Applications. Journal of the American Ceramic Society, 2016, 99, 2909-2912.	1.9	56
206	Enhanced energy storage density and discharge efficiency in the strontium sodium niobate-based glass-ceramics. Journal of Alloys and Compounds, 2016, 687, 280-285.	2.8	37
207	Crystallization kinetics behaviour and dielectric properties of strontium barium niobate-based glass-ceramics. Journal of Materials Science: Materials in Electronics, 2016, 27, 5324-5330.	1.1	19
208	Effect of Different Al/Si Ratios on the Structure and Energy Storage Properties of Strontium Barium Niobate-Based Glass-Ceramics. Journal of Electronic Materials, 2016, 45, 1017-1022.	1.0	9
209	Optimization of the dielectric properties and energy storage density in $(\text{K}_2\text{O})_x(\text{Ba}_{1-x}\text{TiO}_3)$ thin films. Journal of Materials Science: Materials in Electronics, 2016, 27, 5331-5336.	1.7	11
210	Superlattice-like $\text{SnSb}_4/\text{Ge}$ thin films for ultra-high speed phase change memory applications. CrystEngComm, 2016, 18, 1230-1234.	1.3	22
211	Temperature-insensitive large strain response with a low hysteresis behavior in BNT-based ceramics. Ceramics International, 2016, 42, 7669-7680.	2.3	97
212	Effect of rare-earth additions on the structure and dielectric energy storage properties of $\text{Ba}_x\text{Sr}_{1-x}\text{TiO}_3$ -based barium boronaluminosilicate glass-ceramics. Journal of Alloys and Compounds, 2016, 670, 217-221.	2.8	37
213	Structural modification and piezoelectric properties in $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ -based $\text{BaTiO}_3$ - $\text{SrTiO}_3$ thin films. Journal of Materials Science: Materials in Electronics, 2016, 27, 215-220.	1.1	11
214	Structure and electromechanical properties in $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$ -based lead-free piezoceramics with calculated end-member $\text{Bi}(\text{Ni}_{0.5}\text{Ti}_{0.5})\text{O}_3$ . Journal of the European Ceramic Society, 2015, 35, 3457-3466.	2.8	35
215	Effect of $\text{CeO}_2$ Addition on the Structure and Dielectric Properties of $\text{Ba}_x\text{Sr}_{1-x}\text{TiO}_3$ -Based Glass Ceramics. Ferroelectrics, 2015, 488, 71-78.	0.3	4
216	Crystallization and Properties of Strontium Barium Niobate-Based Glass-Ceramics for Energy-Storage Applications. Journal of Electronic Materials, 2015, 44, 227-234.	1.0	25

#	ARTICLE	IF	CITATIONS
217	Crystallization behavior and dielectric properties of $K_2O\text{-}SrO\text{-}Nb_2O_5\text{-}B_2O_3\text{-}Al_2O_3\text{-}SiO_2$ glass-ceramic for energy storage. <i>Journal of Alloys and Compounds</i> , 2015, 648, 745-750.	2.8	19
218	Composition dependence of phase structure and electrical properties of $BiMnO_3$ -modified $Bi_{0.5}(Na_{0.8}K_{0.2})_{0.5}TiO_3$ thin films. <i>RSC Advances</i> , 2015, 5, 62713-62718.	1.7	17
219	Reduced leakage current, enhanced ferroelectric and dielectric properties of (La, Fe)-codoped $Bi_{0.5}Na_{0.5}TiO_3$ -based thin films. <i>Ceramics International</i> , 2015, 41, S344-S348.	2.3	28
220	Effect of different templates on structure evolution and large strain response under a low electric field in <math>\text{BiMnO}_3</math>-textured lead-free BNT-based piezoelectric ceramics. <i>Journal of the European Ceramic Society</i> , 2015, 35, 2489-2499.	2.8	79
221	Femtosecond laser-induced crystallization of amorphous N-doped $Ge_8Sb_{92}$ films and <i>in situ</i> characterization by coherent phonon spectroscopy. <i>Journal of Applied Physics</i> , 2015, 117, .	1.1	17
222	Reduced energy loss in poly(vinylidene fluoride) nanocomposites by filling with a small loading of core-shell structured $BaTiO_3/SiO_2$ nanofibers. <i>Applied Physics Letters</i> , 2015, 107, .	1.5	67
223	High speed and high reliability in $Ge_8Sb_{92}/Ga_{30}Sb_{70}$ stacked thin films for phase change memory applications. <i>Journal of Alloys and Compounds</i> , 2015, 653, 334-337.	2.8	15
224	Ferroelectric and piezoelectric properties of La-modified lead-free $(Bi_{0.5}Na_{0.5})TiO_3\text{-}(Bi_{0.5}K_{0.5})TiO_3\text{-}SrTiO_3$ thin films. <i>Ceramics International</i> , 2015, 41, 4479-4486.	2.3	24
225	Improving the dielectric constant and energy density of poly(vinylidene fluoride) composites induced by surface-modified $SrTiO_3$ nanofibers by polyvinylpyrrolidone. <i>Journal of Materials Chemistry A</i> , 2015, 3, 1511-1517.	5.2	231
226	The preparation and piezoelectric property of textured KNN-based ceramics with plate-like $NaNbO_3$ powders as template. <i>Journal of Alloys and Compounds</i> , 2015, 622, 137-142.	2.8	30
227	Superlattice-like $Ge_8Sb_{92}/Ge$ thin films for high speed and low power consumption phase change memory application. <i>Scripta Materialia</i> , 2014, 93, 4-7.	2.6	37
228	Effect of microwave processes on the energy-storage properties of barium strontium titanate glass ceramics. <i>Journal of Materials Research</i> , 2014, 29, 288-293.	1.2	23
229	Structural, dielectric and piezoelectric properties of $(Bi_{0.5}Na_{0.5})TiO_3\text{-}(Bi_{0.5}K_{0.5})TiO_3\text{-}Bi(Zn_{0.5}Ti_{0.5})O_3$ thin films prepared by sol-gel method. <i>Ceramics International</i> , 2014, 40, 7947-7951.	2.3	24
230	A comprehensive review on the progress of lead zirconate-based antiferroelectric materials. <i>Progress in Materials Science</i> , 2014, 63, 1-57.	16.0	584
231	Effect of $BiMeO_3$ on the Phase Structure, Ferroelectric Stability, and Properties of Lead-Free $Bi_{0.5}(Na_{0.8}K_{0.2})_{0.5}TiO_3$ Ceramics. <i>Journal of the American Ceramic Society</i> , 2014, 97, 1776-1784.	1.9	59
232	Phase Diagrams and Electromechanical Strains in Lead-Free BNT-Based Ternary Perovskite Compounds. <i>Journal of the American Ceramic Society</i> , 2014, 97, 3510-3518.	1.9	61
233	Structure and dielectric properties of $Ba_xSr_{1-x}TiO_3$ -based glass ceramics for energy storage. <i>Journal of Alloys and Compounds</i> , 2014, 617, 740-745.	2.8	46
234	Effect of the Ba/Na ratio on the microstructure and dielectric properties of $(BaO, Na_2O)\text{-}Nb_2O_5\text{-}SiO_2$ glass-ceramics. <i>Ceramics International</i> , 2014, 40, 7495-7499.	2.3	39

#	ARTICLE	IF	CITATIONS
235	The Composition and Temperature-Dependent Structure Evolution and Large Strain Response in $(1-x)(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3-x\text{SrTiO}_3$ Ceramics. Journal of the American Ceramic Society, 2013, 96, 246-252.	2.1	21
236	Al <sub>19</sub> Sb <sub>54</sub> Se <sub>27</sub> material for high stability and high-speed phase-change memory applications. Scripta Materialia, 2013, 69, 61-64.	2.6	48
237	Switching of morphotropic phase boundary and large strain response in lead-free ternary $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3-(\text{K}_{0.5}\text{Bi}_{0.5})\text{TiO}_3-(\text{K}_{0.5}\text{Na}_{0.5})\text{NbO}_3$ system. Journal of Applied Physics, 2013, 113, .	1.1	143
238	Large Strain Response in $0.99(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3-x(\text{K}_{0.5}\text{Bi}_{0.5})\text{TiO}_3-x(\text{K}_{0.5}\text{Na}_{0.5})\text{NbO}_3$ Lead-Free Ceramics Induced by the Change of $x$ Ratio in $(\text{K}_{0.5}\text{Na}_{0.5})\text{NbO}_3$ . Journal of the American Ceramic Society, 2013, 96, 3133-3140.	1.9	49
239	Superlattice-like $\text{Sb}_{50}\text{Se}_{50}/\text{Ga}_{30}\text{Sb}_{70}$ thin films for high-speed and high density phase change memory application. Applied Physics Letters, 2013, 103, .	1.5	31
240	Correlation Between the Microstructure and Electrical Properties in High-Performance $(\text{Ba}_{0.85}\text{Ca}_{0.15})(\text{Zr}_{0.9}\text{Sn}_{0.1})\text{O}_3$ Lead-Free Piezoelectric Ceramics. Journal of the American Ceramic Society, 2012, 95, 1998-2006.	1.9	33
241	Thickness-dependent dielectric and tunable properties of barium stannate titanate thin films. Journal of Applied Physics, 2009, 106, .	1.1	20
242	Phase transformation and electric field tunable pyroelectric behavior of $\text{Pb}(\text{Nb,Zr,Sn,Ti})\text{O}_3$ and $(\text{Pb,Lu})(\text{Zr,Sn,Ti})\text{O}_3$ antiferroelectric thin films. Applied Physics Letters, 2006, 88, 132908.	1.5	60
243	Uncooled tunable pyroelectric response of antiferroelectric $\text{Pb}_{0.97}\text{La}_{0.02}(\text{Zr}_{0.65}\text{Sn}_{0.22}\text{Ti}_{0.13})\text{O}_3$ perovskite. Applied Physics Letters, 2005, 87, 192904.	1.5	45
244	[001] Oriented $\text{BiFeO}_3$ -Based Lead-Free Ceramic with a Rapid Piezoelectric Response Under Low Poling Voltage. SSRN Electronic Journal, 0, , .	0.4	0