## Miriam Maria de Resende

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/2750990/publications.pdf

Version: 2024-02-01

47 papers

1,012 citations

430874 18 h-index 454955 30 g-index

51 all docs

51 docs citations

51 times ranked

1436 citing authors

| #  | Article  | IF  | CITATIONS |
|----|--|-----|-----------|
| 1  | Acid Phosphatase Immobilization and Production Study by <i>Trichoderma</i> spp. in Soybean Molasses. Chemical Engineering and Technology, 2022, 45, 979-984.   | 1.5 | 1         |
| 2  | Leaching with mixed organic acids and sulfuric acid to recover cobalt and lithium from lithium ion batteries. Environmental Technology (United Kingdom), 2021, 42, 4027-4037.  | 2.2 | 11        |
| 3  | Improvement of ethanol production in fed-batch fermentation using a mixture of sugarcane juice and molasse under very high-gravity conditions. Bioprocess and Biosystems Engineering, 2021, 44, 617-625.   | 3.4 | 19        |
| 4  | Synthesis and Immobilization of $\hat{l}^2$ -galactosidase from Kluyveromyces marxianus Using Ion Exchange Resin. Industrial Biotechnology, 2021, 17, 27-37.   | 0.8 | 2         |
| 5  | Very High Gravity Bioethanol Revisited: Main Challenges and Advances. Fermentation, 2021, 7, 38.   | 3.0 | 21        |
| 6  | Culture Medium Evaluation Using Lowâ€Cost Substrate for Biosurfactants Lipopeptides Production by <i>Bacillus amyloliquefaciens</i> in Pilot Bioreactor. Journal of Surfactants and Detergents, 2020, 23, 91-98.   | 2.1 | 11        |
| 7  | Alcoholic fermentation with high sugar and cell concentration at moderate temperatures using flocculant yeasts. Korean Journal of Chemical Engineering, 2020, 37, 1717-1725.   | 2.7 | 1         |
| 8  | Interference of a magnetic field generated by circular magnets in the retention of chromium by microbial cells and in the morphology of a mixed culture during the bio-removal of chromium from effluent. Chemical Engineering and Processing: Process Intensification, 2020, 154, 108019. | 3.6 | 4         |
| 9  | Removal and desorption of chromium in synthetic effluent by a mixed culture in a bioreactor with a magnetic field. Journal of Environmental Sciences, 2020, 91, 151-159.   | 6.1 | 7         |
| 10 | Immobilization of the enzyme invertase in SBA-15 with surfaces functionalized by different organic compounds. Journal of Porous Materials, 2019, 26, 77-89.  | 2.6 | 10        |
| 11 | Electrodialysis for removal of chromium (VI) from effluent: Analysis of concentrated solution saturation. Journal of Environmental Chemical Engineering, 2019, 7, 103380.  | 6.7 | 38        |
| 12 | An experimental and computational study of biosurfactant production from soy molasses. Reaction Kinetics, Mechanisms and Catalysis, 2019, 128, 847-865.  | 1.7 | 3         |
| 13 | Phosphorus Recovery from Phosphate Rocks Using Phosphate-Solubilizing Bacteria. Geomicrobiology Journal, 2019, 36, 195-203.  | 2.0 | 30        |
| 14 | Evaluation of process conditions in the performance of yeast on alcoholic fermentation. Chemical Engineering Communications, 2018, 205, 846-855.   | 2.6 | 13        |
| 15 | Production of omega-3 polyunsaturated fatty acids through hydrolysis of fish oil by Candida rugosa lipase immobilized and stabilized on different supports. Biocatalysis and Biotransformation, 2017, 35, 63-73.   | 2.0 | 14        |
| 16 | Solid-phase amination of Geotrichum candidum lipase: ionic immobilization, stabilization and fish oil hydrolysis for the production of Omega-3 polyunsaturated fatty acids. European Food Research and Technology, 2017, 243, 1375-1384.   | 3.3 | 12        |
| 17 | Soy molasses as a fermentation substrate for the production of biosurfactant using Pseudomonas aeruginosa ATCC 10145. Environmental Science and Pollution Research, 2017, 24, 18699-18709.   | 5.3 | 28        |
| 18 | Sucrose hydrolysis by invertase immobilized on Duolite A-568 employing a packed-bed reactor. Chemical Engineering Communications, 2017, 204, 1007-1019.  | 2.6 | 8         |

| #  | Article   | IF  | CITATIONS |
|----|---|-----|-----------|
| 19 | Improvement of recovered activity and stability of the Aspergillus oryzae $\hat{l}^2$ -galactosidase immobilized on duolite A568 by combination of immobilization methods. Chemical Industry and Chemical Engineering Quarterly, 2017, 23, 495-506. | 0.7 | 7         |
| 20 | Biodiesel dry purification with sugarcane bagasse. Industrial Crops and Products, 2016, 89, 119-127.  | 5.2 | 48        |
| 21 | Optimization of the production and characterization of lipase from Candida rugosa and Geotrichum candidum in soybean molasses by submerged fermentation. Protein Expression and Purification, 2016, 123, 26-34.                                     | 1.3 | 35        |
| 22 | Influence of Magnetic Field Frequency Generated by Permanent Magnets in Mixed Culture Used for the Treatment of Effluent Contaminated with Chromium. Water, Air, and Soil Pollution, 2016, 227, 1.  | 2.4 | 5         |
| 23 | Joint Assessment of Bioreduction of Chromium(VI) and of Removals of Both Total Chromium and Total Organic Carbon (TOC) in Sequential Hybrid Bioreactors. Water, Air, and Soil Pollution, 2016, 227, 1.  | 2.4 | 11        |
| 24 | Bio-oil production and removal of organic load by microalga Scenedesmus sp. using culture medium contaminated with different sugars, cheese whey and whey permeate. Journal of Environmental Management, 2016, 173, 134-140.                        | 7.8 | 5         |
| 25 | Alcoholic Fermentation with Selfâ€Flocculating Yeast in a Tower Upflow Reactor. Chemical Engineering and Technology, 2015, 38, 345-354.   | 1.5 | 5         |
| 26 | OPTIMIZATION OF THE OPERATING CONDITIONS FOR RHAMNOLIPID PRODUCTION USING SLAUGHTERHOUSE-GENERATED INDUSTRIAL FLOAT AS SUBSTRATE. Brazilian Journal of Chemical Engineering, 2015, 32, 357-365.   | 1.3 | 9         |
| 27 | Continuous ethanol fermentation in tower reactors with cell recycling using flocculent Saccharomyces cerevisiae. Process Biochemistry, 2015, 50, 1725-1729.   | 3.7 | 14        |
| 28 | Influence of an electromagnetic field on the bioreduction of chromium (VI) using a mixed culture of microorganisms. Environmental Progress and Sustainable Energy, 2015, 34, 88-98.   | 2.3 | 7         |
| 29 | Alcoholic Fermentation with Flocculant Saccharomyces cerevisiae in Fed-Batch Process. Applied Biochemistry and Biotechnology, 2014, 172, 1623-1638.   | 2.9 | 14        |
| 30 | Biohydrogen Production Through Dark Fermentation by a Microbial Consortium Using Whey Permeate as Substrate. Applied Biochemistry and Biotechnology, 2014, 172, 3670-3685.  | 2.9 | 41        |
| 31 | Evaluation of potential ethanol production and nutrients for four varieties of sweet sorghum during maturation. Renewable Energy, 2014, 71, 518-524.  | 8.9 | 37        |
| 32 | Evaluation of hop extract as a natural antibacterial agent in contaminated fuel ethanol fermentations. Fuel Processing Technology, 2013, 106, 611-618.  | 7.2 | 21        |
| 33 | Optimization and modeling of lactose hydrolysis in a packed bed system using immobilized $\hat{l}^2$ -galactosidase from Aspergillus oryzae. Journal of Molecular Catalysis B: Enzymatic, 2013, 85-86, 178-186.                                     | 1.8 | 22        |
| 34 | Ethanol Production from Hydrolyzed Soybean Molasses. Energy & Energy & 2012, 26, 2310-2316.   | 5.1 | 26        |
| 35 | Use of a greasy effluent floater treatment station from the slaughterhouse for biosurfactant production. Biotechnology and Applied Biochemistry, 2012, 59, 238-244.   | 3.1 | 10        |
| 36 | Evaluation of the bioremoval of Cr(VI) and TOC in biofilters under continuous operation using response surface methodology. Biodegradation, 2012, 23, 441-454.  | 3.0 | 6         |

| #  | Article  | IF   | CITATIONS |
|----|--|------|-----------|
| 37 | $\hat{l}^2$ -Galactosidase of Aspergillus oryzae immobilized in an ion exchange resin combining the ionic-binding and crosslinking methods: Kinetics and stability during the hydrolysis of lactose. Journal of Molecular Catalysis B: Enzymatic, 2011, 71, 139-145. | 1.8  | 31        |
| 38 | Characterization of xanthan gum produced from sugar cane broth. Carbohydrate Polymers, 2011, 86, 469-476.  | 10.2 | 203       |
| 39 | Evaluation of hexavalent chromium removal in a continuous biological filter with the use of central composite design (CCD). Journal of Environmental Management, 2011, 92, 1165-1173.  | 7.8  | 24        |
| 40 | Application of a model using the phenomenological approach for prediction of growth and xanthan gum production with sugar cane broth in a batch process. LWT - Food Science and Technology, 2010, 43, 498-506.   | 5.2  | 24        |
| 41 | Biosurfactant Production by Pseudomonas aeruginosa Grown in Residual Soybean Oil. Applied Biochemistry and Biotechnology, 2009, 152, 156-168.  | 2.9  | 66        |
| 42 | A Comparison Between Shaker and Bioreactor Performance Based on the Kinetic Parameters of Xanthan Gum Production. Applied Biochemistry and Biotechnology, 2009, 156, 45-58.  | 2.9  | 19        |
| 43 | Enhancement of rhamnoplipid production in residual soybean oil by an isolated strain of Pseudomonas aeruginosa. Applied Biochemistry and Biotechnology, 2007, 137-140, 463-470.  | 2.9  | 9         |
| 44 | Estimation of mass transfer parameters in a Taylor-Couette-Poiseuille heterogeneous reactor. Brazilian Journal of Chemical Engineering, 2004, 21, 175-184.   | 1.3  | 21        |
| 45 | Hybrid Model for an Enzymatic Reactor: Hydrolysis of Cheese Whey Proteins by Alcalase Immobilized in Agarose Gel Particles. Applied Biochemistry and Biotechnology, 2003, 106, 413-422.  | 2.9  | 9         |
| 46 | Simulating a ceramic membrane bioreactor for the production of penicillin: an example of the importance of consistent initialization for solving DAE systems. Process Biochemistry, 2002, 37, 1297-1305.   | 3.7  | 5         |
| 47 | Distribution of suspended particles in a Taylor–Poiseuille vortex flow reactor. Chemical Engineering Science, 2001, 56, 755-761.   | 3.8  | 26        |