Min-Suk Kwon

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/2768240/publications.pdf Version: 2024-02-01



MIN-SUK KWON

#	Article	IF	CITATIONS
1	Thermal Tuning of Plasmofluidic Disk Resonators Filled With a Liquid Crystal: Its Narrow-Trench Filling and Arrangement. Journal of Lightwave Technology, 2020, 38, 4419-4428.	4.6	0
2	Compact Low-Loss Electroabsorption Modulator Using a Graphene-Inserted Metal-Slot-Added Waveguide. IEEE Access, 2020, 8, 203309-203316.	4.2	2
3	Solid-Electrolyte-Gated Graphene-Covered Metal-Insulator-Silicon-Insulator-Metal Waveguide With a Remarkably Large Modulation Depth. IEEE Access, 2019, 7, 174312-174324.	4.2	3
4	Silicon photonic add-drop filter based on a grating-assisted co-directionally coupled vertical hybrid structure. Optics Express, 2019, 27, 11748.	3.4	7
5	Experimental Investigation of Intensity Modulation of a Graphene-covered Silicon-based Hybrid Plasmonic Waveguide. , 2019, , .		0
6	Theoretical Study of a Tunable Transmissive Subtractive Color Filter UsingThin Metal films and Transparent Conducting Oxide. , 2018, , .		0
7	Theoretical Investigation of a Plasmonic Waveguide Modulator Using Grating-Assisted Coupling to a Graphene Plasmon. , 2018, , .		0
8	Bulk-Silicon-Based Waveguides and Bends Fabricated Using Silicon Wet Etching: Properties and Limits. Journal of Lightwave Technology, 2017, 35, 3918-3923.	4.6	5
9	Mid-infrared subwavelength modulator based on grating-assisted coupling of a hybrid plasmonic waveguide mode to a graphene plasmon. Nanoscale, 2017, 9, 17429-17438.	5.6	13
10	Compact Silicon Slot Waveguide Intersection Based on Mode Transformation and Multimode Interference. IEEE Photonics Journal, 2017, 9, 1-10.	2.0	6
11	Plasmofluidic Disk Resonators. Scientific Reports, 2016, 6, 23149.	3.3	22
12	Theoretical Investigation of Intersections of Metal-Insulator-Silicon-Insulator-Metal Waveguides. IEEE Photonics Journal, 2016, 8, 1-10.	2.0	2
13	Discussion of Two Ways of Optically Modeling Indium–Tin–Oxide Layers in Slot Waveguides for Waveguide Analysis. IEEE Photonics Journal, 2016, 8, 1-9.	2.0	4
14	Theoretical investigation of graphene-based inverted rib-type silicon waveguides. , 2015, , .		0
15	Experimental investigation of plasmofluidic waveguides. Applied Physics Letters, 2015, 107, 201104.	3.3	5
16	Mid-infrared optical waveguide modulator based on the epsilon-near-zero effect of ITO. , 2015, , .		1
17	Metal–Insulator–Silicon–Insulator–Metal Waveguide Splitters With Large-Arm Separation. Journal of Lightwave Technology, 2015, 33, 3843-3849.	4.6	11
18	Metal-Insulator-Silicon-Insulator-Metal Waveguide with Its Insulator Replaced by Fluid. , 2015, , .		0

MIN-SUK KWON

#	Article	IF	CITATIONS
19	Discussion of the Epsilon-Near-Zero Effect of Graphene in a Horizontal Slot Waveguide. IEEE Photonics Journal, 2014, 6, 1-9.	2.0	55
20	Efficient Coupling Between Photonic and Dielectric-Loaded Surface Plasmon Polariton Waveguides With the Same Core Material. IEEE Photonics Journal, 2014, 6, 1-9.	2.0	9
21	Investigation of 90° submicrometer radius bends of metal-insulator-silicon-insulator-metal waveguides. Optics Letters, 2014, 39, 715.	3.3	9
22	Investigation and Improvement of 90\$^{circ}\$ Direct Bends of Metal–Insulator–Silicon–Insulator–Metal Waveguides. IEEE Photonics Journal, 2013, 5, 6601909-6601909.	2.0	6
23	Characterizations of realized metal-insulator-silicon-insulator-metal waveguides and nanochannel fabrication via insulator removal. Optics Express, 2012, 20, 21875.	3.4	25
24	Metal-insulator-silicon-insulator-metal waveguides compatible with standard CMOS technology. Optics Express, 2011, 19, 8379.	3.4	61
25	Theoretical Investigation of an Interferometer-type Plasmonic Biosensor Using a Metal-insulator-silicon Waveguide. Plasmonics, 2010, 5, 347-354.	3.4	19
26	Disposable and compact integrated plasmonic sensor using a long-period grating. Optics Letters, 2010, 35, 3835.	3.3	11
27	A Numerically Stable Analysis Method for Complex Multilayer Waveguides Based on Modified Transfer-Matrix Equations. Journal of Lightwave Technology, 2009, 27, 4407-4414.	4.6	14
28	Influence of the Parameters of a Heater Array Inducing a Thermooptic Long-Period Grating on Its Power Consumption. Journal of Lightwave Technology, 2009, 27, 1108-1113.	4.6	0
29	Microring-resonator-based sensor measuring both the concentration and temperature of a solution. Optics Express, 2008, 16, 9372.	3.4	89

30 Glucose senosr based on two distinct microring resonators. , 2008, , .

0