

Sofyan A Taya

List of Publications by Citations

Source: <https://exaly.com/author-pdf/28870/sofyan-a-taya-publications-by-citations.pdf>

Version: 2024-04-25

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

106
papers

1,193
citations

22
h-index

27
g-index

125
ext. papers

1,668
ext. citations

2.2
avg, IF

5.34
L-index

#	Paper	IF	Citations
106	Enhanced sensitivity of cancer cell using one dimensional nano composite material coated photonic crystal. <i>Microsystem Technologies</i> , 2019 , 25, 189-196	1.7	54
105	Metal-clad waveguide sensor using a left-handed material as a core layer. <i>Journal of the Optical Society of America B: Optical Physics</i> , 2012 , 29, 959	1.7	46
104	P-polarized surface waves in a slab waveguide with left-handed material for sensing applications. <i>Journal of Magnetism and Magnetic Materials</i> , 2015 , 377, 281-285	2.8	40
103	Design of one dimensional defect based photonic crystal by composited superconducting material for bio sensing applications. <i>Physica B: Condensed Matter</i> , 2019 , 572, 42-55	2.8	39
102	Enhancement of sensitivity in optical waveguide sensors using left-handed materials. <i>Optik</i> , 2009 , 120, 504-508	2.5	39
101	Slab waveguide with air core layer and anisotropic left-handed material claddings as a sensor. <i>Opto-electronics Review</i> , 2014 , 22,	2.4	37
100	Dye-Sensitized Solar Cells Using Fresh and Dried Natural Dyes. <i>International Journal of Materials Science and Applications</i> , 2013 , 2, 37	0.3	35
99	Dispersion properties of lossy, dispersive, and anisotropic left-handed material slab waveguide. <i>Optik</i> , 2015 , 126, 1319-1323	2.5	29
98	Transverse magnetic peak type metal-clad optical waveguide sensor. <i>Optik</i> , 2014 , 125, 97-100	2.5	29
97	Guided modes in slab waveguides with negative index cladding and substrate. <i>Optik</i> , 2013 , 124, 1431-1436	2.5	27
96	Goos-Hänchen shift as a probe in evanescent slab waveguide sensors. <i>AEU - International Journal of Electronics and Communications</i> , 2012 , 66, 204-210	2.8	27
95	Dye-Sensitized Solar Cells Based on ZnO Films and Natural Dyes. <i>International Journal of Materials and Chemistry</i> , 2012 , 2, 105-110	1	27
94	Optimization of transverse electric peak-type metal-clad waveguide sensor using double-negative materials. <i>Applied Physics A: Materials Science and Processing</i> , 2014 , 116, 1841-1846	2.6	26
93	Dispersion properties of slab waveguides with double negative material guiding layer and nonlinear substrate. <i>Journal of the Optical Society of America B: Optical Physics</i> , 2013 , 30, 2008	1.7	26
92	Properties of ternary photonic crystal consisting of dielectric/plasma/dielectric as a lattice period. <i>Optik</i> , 2019 , 185, 784-793	2.5	25
91	Temperature sensor utilizing a ternary photonic crystal with a polymer layer sandwiched between Si and SiO ₂ layers. <i>Journal of Theoretical and Applied Physics</i> , 2018 , 12, 293-298	1.4	25
90	Symmetric multilayer slab waveguide structure with a negative index material: TM case. <i>Optik</i> , 2012 , 123, 2264-2268	2.5	24

89	Dye-sensitized solar cells based on dyes extracted from dried plant leaves. <i>Turkish Journal of Physics</i> , 2015 , 39, 24-30	1.6	23
88	Excitation of TE surface polaritons on metal-NIM interfaces. <i>Optik</i> , 2014 , 125, 1401-1405	2.5	23
87	Nonlinear polarization in metal nanocomposite system based photonic crystals. <i>Optik</i> , 2019 , 176, 78-84	2.5	23
86	Photonic crystal as a refractometric sensor operated in reflection mode. <i>Superlattices and Microstructures</i> , 2017 , 101, 299-305	2.8	22
85	Peak type metal-clad waveguide sensor using negative index materials. <i>AEU - International Journal of Electronics and Communications</i> , 2013 , 67, 984-986	2.8	22
84	Optical sensors based on Fabry-Berot resonator and fringes of equal thickness structure. <i>Optik</i> , 2012 , 123, 417-421	2.5	20
83	Dye-sensitized solar cells with natural dyes extracted from plant seeds. <i>Materials Science-Poland</i> , 2014 , 32, 547-554	0.6	19
82	Nonlinear planar asymmetrical optical waveguides for sensing applications. <i>Optik</i> , 2010 , 121, 860-865	2.5	18
81	Rotating polarizer-analyzer scanning ellipsometer. <i>Thin Solid Films</i> , 2010 , 518, 5610-5614	2.2	18
80	Reflection and transmission from left-handed material structures using Lorentz and Drude medium models. <i>Opto-electronics Review</i> , 2015 , 23,	2.4	17
79	Development and construction of rotating polarizer analyzer ellipsometer. <i>Optics and Lasers in Engineering</i> , 2011 , 49, 507-513	4.6	17
78	Analysis of photonic band gap in photonic crystal with epsilon negative and double negative materials. <i>Optik</i> , 2019 , 183, 203-210	2.5	16
77	Ternary photonic crystal with left-handed material layer for refractometric application. <i>Opto-electronics Review</i> , 2018 , 26, 236-241	2.4	15
76	Analysis of the Sensitivity of Self-focused Nonlinear Optical Evanescent Waveguide Sensors. <i>International Journal of Optomechatronics</i> , 2007 , 1, 284-296	3.5	15
75	A reverse symmetry optical waveguide sensor using a plasma substrate. <i>Journal of Optics (United Kingdom)</i> , 2011 , 13, 075701	1.7	14
74	Theoretical analysis of TM nonlinear asymmetrical waveguide optical sensors. <i>Sensors and Actuators A: Physical</i> , 2008 , 147, 137-141	3.9	14
73	Extension of energy band gap in ternary photonic crystal using left-handed materials. <i>Superlattices and Microstructures</i> , 2018 , 120, 353-362	2.8	13
72	Photonic crystal with epsilon negative and double negative materials as an optical sensor. <i>Optical and Quantum Electronics</i> , 2018 , 50, 1	2.4	13

71	Highly Sensitive Refractive Index Sensor for Temperature and Salinity Measurement of Seawater. <i>Optik</i> , 2020 , 216, 164901	2.5	12
70	One-dimensional ring mirror-defect photonic crystal for detection of mycobacterium tuberculosis bacteria. <i>Optik</i> , 2020 , 219, 165097	2.5	12
69	Slab waveguide sensor utilizing left-handed material core and substrate layers. <i>Optik</i> , 2016 , 127, 7732-7739	2.39	11
68	Sensitivity enhancement in optical waveguide sensors using metamaterials. <i>Applied Physics A: Materials Science and Processing</i> , 2011 , 103, 611-614	2.6	11
67	An Improvement of Scanning Ellipsometer by Rotating a Polarizer and an Analyzer at a Speed Ratio of 1:3. <i>International Journal of Optomechatronics</i> , 2011 , 5, 51-67	3.5	11
66	Slab waveguide with conducting interfaces as an efficient optical sensor: TE case. <i>Journal of Modern Optics</i> , 2017 , 64, 836-843	1.1	10
65	Theoretical investigation of guided modes in planar waveguides having chiral negative index metamaterial core layer. <i>Optik</i> , 2017 , 131, 562-573	2.5	9
64	Reflection through a parallel-plate waveguide formed by two graphene sheets. <i>Photonics and Nanostructures - Fundamentals and Applications</i> , 2017 , 24, 53-57	2.6	9
63	Four-Layer Slab Waveguide Sensors Supported with Left Handed Materials. <i>Sensor Letters</i> , 2011 , 9, 1823-1829	1.29	9
62	Propagation of p-polarized light in photonic crystal for sensor application. <i>Chinese Journal of Physics</i> , 2017 , 55, 571-582	3.5	8
61	Aldimine derivatives as photosensitizers for dye-sensitized solar cells. <i>Turkish Journal of Physics</i> , 2014 , 38, 86-90	1.6	8
60	Spectroscopic ellipsometry time study of low-temperature plasma-polymerized plain trimethylsilane thin films deposited on silicon. <i>Physica Scripta</i> , 2011 , 84, 045302	2.6	8
59	Dyes Extracted from Safflower, Medicago Sativa, and Ros Marinus Oficinalis as Photosensitizers for Dye-sensitized Solar Cells. <i>Journal of Nano- and Electronic Physics</i> , 2016 , 8, 01026-1-01026-5	1.5	8
58	Investigation of bandgap properties in one-dimensional binary superconductor dielectric photonic crystal: TE case. <i>Indian Journal of Physics</i> , 2018 , 92, 519-527	1.4	7
57	Binary photonic crystal for refractometric applications (TE case). <i>Indian Journal of Physics</i> , 2018 , 92, 519-527	1.4	7
56	Metamaterial-based refractive index sensor using Ge 2 Sb 2 Te 5 substrate for glucose detection. <i>Microwave and Optical Technology Letters</i> , 2022 , 64, 867-872	1.2	7
55	Design of a slab waveguide using a graded index profile and a left hand material. <i>Physica B: Condensed Matter</i> , 2019 , 564, 59-63	2.8	6
54	Plasmon modes supported by left-handed material slab waveguide with conducting interfaces. <i>Photonics and Nanostructures - Fundamentals and Applications</i> , 2018 , 30, 39-44	2.6	6

53	Theoretical investigation of five-layer waveguide structure including two left-handed material layers for refractometric applications. <i>Journal of Magnetism and Magnetic Materials</i> , 2018 , 449, 395-400	2.8	6
52	Dyes extracted from Trigonella seeds as photosensitizers for dye-sensitized solar cells. <i>Iranian Physical Journal</i> , 2016 , 10, 265-270		6
51	A Fourier Ellipsometer Using Rotating Polarizer and Analyzer at a Speed Ratio 1 : 1. <i>Journal of Sensors</i> , 2010 , 2010, 1-7	2	6
50	Ellipsometry of anisotropic materials: A new efficient polynomial approach. <i>Optik</i> , 2011 , 122, 666-670	2.5	6
49	A comparative study: synthetic dyes as photosensitizers for dye-sensitized solar cells. <i>Turkish Journal of Physics</i> , 2015 , 39, 272-279	1.6	6
48	Optical fiber surrounded by a graphene layer as an optical sensor. <i>Optical and Quantum Electronics</i> , 2020 , 52, 1	2.4	5
47	Propagation of Electromagnetic Waves in Slab Waveguide Structure Consisting of Chiral Nihility Claddings and Negative-Index Material Core Layer. <i>Photonic Sensors</i> , 2018 , 8, 176-187	2.3	5
46	A spectroscopic ellipsometer using rotating polarizer and analyzer at a speed ratio 1:1 and a compensator. <i>Optical and Quantum Electronics</i> , 2014 , 46, 883-895	2.4	5
45	Ellipsometric configurations using a phase retarder and a rotating polarizer and analyzer at any speed ratio. <i>Chinese Physics B</i> , 2012 , 21, 110701	1.2	5
44	NONLINEAR OPTICAL WAVEGUIDE STRUCTURE FOR SENSOR APPLICATION: TM CASE. <i>International Journal of Modern Physics B</i> , 2007 , 21, 5075-5089	1.1	5
43	Surface plasmon resonance-based optical sensor using a thin layer of plasma. <i>Journal of the Optical Society of America B: Optical Physics</i> , 2021 , 38, 2362	1.7	5
42	Properties of defect modes and band gaps of mirror symmetric metal-dielectric 1D photonic crystals. <i>Optical and Quantum Electronics</i> , 2021 , 53, 1	2.4	5
41	Enhancement of optical visible wavelength region selective reflector for photovoltaic cell applications using a ternary photonic crystal. <i>Optik</i> , 2021 , 243, 167491	2.5	5
40	Rotating polarizer analyzer ellipsometer with a fixed compensator. <i>Optik</i> , 2013 , 124, 3379-3383	2.5	4
39	Aging of Oxygen-Treated Trimethylsilane Plasma-Polymerized Films Using Spectroscopic Ellipsometry. <i>Journal of Atomic, Molecular, and Optical Physics</i> , 2011 , 2011, 1-6		4
38	Surface plasmon resonance biosensor based on graphene layer for the detection of waterborne bacteria.. <i>Journal of Biophotonics</i> , 2022 , e202200001	3.1	4
37	Thin Film Characterization Using Rotating Polarizer Analyzer Ellipsometer with a Speed Ratio 1:3. <i>Journal of Electromagnetic Analysis and Applications</i> , 2011 , 03, 351-358	0.3	4
36	Three Fresh Plant Seeds as Natural Dye Sensitizers for Titanium Dioxide Based Dye Sensitized Solar Cells. <i>British Journal of Applied Science & Technology</i> , 2015 , 5, 380-386		4

35	Transverse magnetic mode slab waveguide optical sensor in the presence of conducting interfaces. <i>Optik</i> , 2019 , 178, 1090-1096	2.5	4
34	Universal dispersion curves of a planar waveguide with an exponential graded-index guiding layer and a nonlinear cladding. <i>Results in Physics</i> , 2021 , 20, 103734	3.7	4
33	Graphene-based metasurface solar absorber design for the visible and near-infrared region with behavior prediction using Polynomial Regression. <i>Optik</i> , 2022 , 169298	2.5	4
32	Characteristics of electromagnetic waves in slab waveguide structures comprising chiral nihility film and left-handed material claddings. <i>Optik</i> , 2017 , 149, 332-343	2.5	3
31	Design of a novel optical sensor for the detection of waterborne bacteria based on a photonic crystal with an ultra-high sensitivity. <i>Optical and Quantum Electronics</i> , 2022 , 54, 1	2.4	3
30	Characteristics of Symmetric Left-Handed Material Slab Waveguide. <i>IOSR Journal of Applied Physics</i> , 2016 , 08, 91-98		3
29	Analysis of proposed PCF with square air hole for revolutionary high birefringence and nonlinearity. <i>Photonics and Nanostructures - Fundamentals and Applications</i> , 2021 , 43, 100896	2.6	3
28	An ultra-high birefringent and nonlinear decahedron photonic crystal fiber employing molybdenum disulphide (MoS ₂): A numerical analysis. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2021 , 270, 115236	3.1	3
27	Properties of band gap for p-polarized wave propagating in a binary superconductor-dielectric photonic crystal. <i>Optik</i> , 2021 , 243, 167505	2.5	3
26	Propagation of p-polarized waves in a linearly graded index film surrounded by negative index materials. <i>Optical and Quantum Electronics</i> , 2017 , 49, 1	2.4	2
25	Effect of the orientation of the fixed analyzer on the ellipsometric parameters in rotating polarizer and compensator ellipsometer with speed ratio 1:1. <i>Optical and Quantum Electronics</i> , 2015 , 47, 2039-2053	2.4	2
24	Design of a spectroscopic ellipsometer by synchronous rotation of the polarizer and analyzer in opposite directions. <i>Microwave and Optical Technology Letters</i> , 2014 , 56, 2822-2826	1.2	2
23	Rotating polarizer, compensator, and analyzer ellipsometry. <i>Chinese Physics B</i> , 2013 , 22, 120703	1.2	2
22	A New Matrix Formulation for One-Dimensional Scattering in Dirac Comb (Electromagnetic Waves Approach). <i>Physica Scripta</i> , 2003 , 67, 147-152	2.6	2
21	Detection of water concentration in ethanol solution using a ternary photonic crystal-based sensor. <i>Materials Chemistry and Physics</i> , 2022 , 279, 125772	4.4	2
20	Highly sensitive nano-sensor based on a binary photonic crystal for the detection of mycobacterium tuberculosis bacteria. <i>Journal of Materials Science: Materials in Electronics</i> , 2021 , 32, 28406	2.1	2
19	Modelling of three tunable multichannel filters using Ag metal as a defect layer in a photonic crystal. <i>Optical and Quantum Electronics</i> , 2021 , 53, 1	2.4	2
18	Properties of a binary photonic crystal with an inverted symmetry and a defect layer. <i>European Physical Journal Plus</i> , 2020 , 135, 1	3.1	2

17	Cancer cell detector based on a slab waveguide of anisotropic, lossy, and dispersive left-handed material. <i>Applied Optics</i> , 2021 , 60, 8360-8367	1.7	2
16	Planar slab waveguide sensor with a left-handed material substrate 2011 ,		1
15	Effect of noise on the optical parameters extracted from different ellipsometric configurations. <i>Physica Scripta</i> , 2012 , 85, 045706	2.6	1
14	Sensitivity enhancement of an optical sensor based on a binary photonic crystal for the detection of Escherichia coli by controlling the central wavelength and the angle of incidence. <i>Optical and Quantum Electronics</i> , 2022 , 54, 1	2.4	1
13	Dispersion properties of slab waveguides with a linear graded-index film and a nonlinear substrate. <i>Microsystem Technologies</i> , 2021 , 27, 2589-2594	1.7	1
12	Dispersion curves of a slab waveguide with a nonlinear covering medium and an exponential graded-index thin film (TM case). <i>Journal of the Optical Society of America B: Optical Physics</i> ,	1.7	1
11	Ultra-High-Sensitive Sensor Based on Surface Plasmon Resonance Structure Having Si and Graphene Layers for the Detection of Chikungunya Virus. <i>Plasmonics</i> ,1	2.4	1
10	Design of a nano-sensor for cancer cell detection based on a ternary photonic crystal with high sensitivity and low detection limit. <i>Chinese Journal of Physics</i> , 2022 , 77, 1168-1181	3.5	1
9	Waveguides including negative permeability and simultaneously negative permittivity and permeability materials for sensing applications. <i>Optik</i> , 2021 , 228, 166147	2.5	0
8	A highly birefringent bend-insensitive porous core PCF for endlessly single-mode operation in THz regime: an analysis with core porosity. <i>Applied Nanoscience (Switzerland)</i> , 2021 , 11, 1021-1030	3.3	0
7	Multi-layered graphene silica-metasurface based infrared polarizer structure. <i>Optical and Quantum Electronics</i> , 2022 , 54, 1	2.4	0
6	An exact solution of a slab waveguide dispersion relation with a linear graded-index guiding layer (TM case). <i>Microsystem Technologies</i> ,1	1.7	0
5	Properties of the defect mode of a ternary photonic crystal having an n-doped semiconductor as a defect layer: TE case. <i>Materials Science in Semiconductor Processing</i> , 2022 , 144, 106626	4.3	0
4	Reflected and transmitted powers of p-polarized electromagnetic waves through a dielectric slab surrounded by double negative materials. <i>Journal of Electromagnetic Waves and Applications</i> , 2018 , 32, 1541-1559	1.3	
3	Transverse magnetic peak type metal-clad optical waveguide sensor. <i>Optik</i> , 2013 , 124, 7080-7084	2.5	
2	Refractometric sensor based on slab waveguides of simultaneously negative permittivity and permeability materials. <i>Optical and Quantum Electronics</i> , 2020 , 52, 1	2.4	
1	Wide-Angle Absorption Based on Angle-Insensitive Light Slowing Effect in Photonic Crystal Containing Hyperbolic Metamaterials. <i>Photonics</i> , 2022 , 9, 181	2.2	