Limin Sun

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/3355182/publications.pdf

Version: 2024-02-01

| | 933447 | 996975 |
|----------------|--------------|---------------------------------|
| 590 | 10 | 15 |
| citations | h-index | g-index |
| | | |
| | | |
| | | 0.45 |
| 15 | 15 | 945 |
| docs citations | times ranked | citing authors |
| | | |
| | citations 15 | 590 10 citations h-index 15 15 |

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 1 | Impaired Gamma-Band Activity during Perceptual Organization in Adults with Autism Spectrum Disorders: Evidence for Dysfunctional Network Activity in Frontal-Posterior Cortices. Journal of Neuroscience, 2012, 32, 9563-9573. | 3.6 | 139 |
| 2 | Deficits in high- (>60 Hz) gamma-band oscillations during visual processing in schizophrenia. Frontiers in Human Neuroscience, 2013, 7, 88. | 2.0 | 124 |
| 3 | Evidence for dysregulated high-frequency oscillations during sensory processing in medication-naÃ-ve, first episode schizophrenia. Schizophrenia Research, 2013, 150, 519-525. | 2.0 | 86 |
| 4 | BabyMEG: A whole-head pediatric magnetoencephalography system for human brain development research. Review of Scientific Instruments, 2016, 87, 094301. | 1.3 | 66 |
| 5 | Reorganization of the somatosensory cortex in hemiplegic cerebral palsy associated with impaired sensory tracts. Neurolmage: Clinical, 2018, 17, 198-212. | 2.7 | 46 |
| 6 | Moving average template subtraction to remove stimulation artefacts in EEGs and LFPs recorded during deep brain stimulation. Journal of Neuroscience Methods, 2016, 266, 126-136. | 2.5 | 24 |
| 7 | Simultaneously recorded EEG–fMRI: Removal of gradient artifacts by subtraction of head movement related average artifact waveforms. Human Brain Mapping, 2009, 30, 3361-3377. | 3.6 | 23 |
| 8 | Compact, ultra-low vibration, closed-cycle helium recycler for uninterrupted operation of MEG with SQUID magnetometers. Cryogenics, 2016, 76, 16-22. | 1.7 | 18 |
| 9 | Maximum noise fraction (MNF) transformation to remove ballistocardiographic artifacts in EEG signals recorded during fMRI scanning. NeuroImage, 2009, 46, 144-153. | 4.2 | 17 |
| 10 | MNE Scan: Software for real-time processing of electrophysiological data. Journal of Neuroscience Methods, 2018, 303, 55-67. | 2.5 | 17 |
| 11 | Removing Cardiac Artefacts in Magnetoencephalography with Resampled Moving Average Subtraction. Brain Topography, 2016, 29, 783-790. | 1.8 | 10 |
| 12 | Mne-X: MEG/EEG Real-Time Acquisition, Real-Time Processing, and Real-Time Source Localization Framework. Biomedizinische Technik, 2013, 58 Suppl 1, . | 0.8 | 7 |
| 13 | Noise cancellation for a whole-head magnetometer-based MEG system in hospital environment. Biomedical Physics and Engineering Express, 2018, 4, 055014. | 1.2 | 6 |
| 14 | Versatile synchronized real-time MEG hardware controller for large-scale fast data acquisition. Review of Scientific Instruments, 2017, 88, 055110. | 1.3 | 4 |
| 15 | Vibrotactile piezoelectric stimulation system with precise and versatile timing control for somatosensory research. Journal of Neuroscience Methods, 2019, 317, 29-36. | 2.5 | 3 |