## Mojtaba Joodaki

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/3467588/publications.pdf

Version: 2024-02-01

933447 888059 75 429 10 17 citations g-index h-index papers 76 76 76 393 docs citations times ranked citing authors all docs

| #  | Article   | IF  | Citations |
|----|---|-----|-----------|
| 1  | Tensile Mechanical Strain Effects on the Electrical Characteristics of Roll-to-Roll Printed OSC. IEEE Journal of Photovoltaics, 2022, 12, 737-743.  | 2,5 | 1         |
| 2  | An approach for one dimensional periodic arbitrary lithography based on Fourier series. Engineering Science and Technology, an International Journal, 2021, 24, 343-347.  | 3.2 | 0         |
| 3  | Decreasing the Loading Effect of the TVS Diode Using a Transmission Line for RF and Microwave Applications. IEEE Letters on EMC Practice and Applications, 2021, 3, 29-33.  | 1.1 | 3         |
| 4  | Odd-Mode Instability Analysis of <i>f</i> <sub>T</sub> -Doubler Hybrid Power Amplifiers Based on GaN-HEMT. IEEE Transactions on Circuits and Systems II: Express Briefs, 2021, 68, 1193-1197.                             | 3.0 | 4         |
| 5  | High on–off current ratio titanium oxynitride write-once-read-many-times memory. Semiconductor Science and Technology, 2021, 36, 06LT01.  | 2.0 | 1         |
| 6  | An extremely ultrathin flexible Huygens's transformer. AIP Advances, 2020, 10, 105201.  | 1.3 | 3         |
| 7  | A new compact dual-band perfect absorption ultrathin planar metasurface energy harvester in X- and V-bands with a wide incident angle. AIP Advances, 2020, 10, 085007.  | 1.3 | 10        |
| 8  | Performance dependence of self-aligned dual-gate poly-Si TFTs on localized defective regions. Semiconductor Science and Technology, 2020, 35, 085027.   | 2.0 | 1         |
| 9  | Analysis, Design, and Implementation of a New Extremely Ultrathin 2-D-Isotropic Flexible Energy Harvester Using Symmetric Patch FSS. IEEE Transactions on Microwave Theory and Techniques, 2020, 68, 2108-2115.           | 4.6 | 24        |
| 10 | A Distributed Power Amplifier Design with a High Power Gain. , 2020, , .  |     | 2         |
| 11 | Design and Implementation of SIW Cavity Oscillators for Humidity Sensing Applications. , 2020, , .  |     | O         |
| 12 | Investigation of Electrical Characteristics Dependency of Roll-to-Roll Printed Solar Cells With Silver Electrodes on Mechanical Tensile Strain. IEEE Transactions on Device and Materials Reliability, 2019, 19, 718-722. | 2.0 | 5         |
| 13 | Extracting voltage-dependent series resistance of single diode model for organic solar cells. SN Applied Sciences, 2019, 1, 1.  | 2.9 | 7         |
| 14 | Probe-induced resistive switching memory based on organic-inorganic lead halide perovskite materials. Organic Electronics, 2019, 69, 106-113.   | 2.6 | 13        |
| 15 | Realization of a broadband hybrid X-band power amplifier based on f-doubler technique. AEU - International Journal of Electronics and Communications, 2019, 104, 119-127.   | 2.9 | 9         |
| 16 | Design and fabrication of a 2D-isotropic flexible ultra-thin metasurface for ambient electromagnetic energy harvesting. AIP Advances, 2019, 9, .  | 1.3 | 34        |
| 17 | UV and IR cut-off filters based on plasmonic crossed-shaped nano-antennas for solar cell applications. Optics Communications, 2019, 433, 275-282.   | 2.1 | 20        |
| 18 | Shielding Effectiveness Measurement for Extremely Small Dimension Enclosures. IEEE Transactions on Electromagnetic Compatibility, 2019, 61, 1740-1745.  | 2.2 | 5         |

| #  | Article   | IF  | CITATIONS |
|----|---|-----|-----------|
| 19 | Using a network of ports for shielding effectiveness optimization of an enclosure with arbitrary shape apertures. International Journal of Numerical Modelling: Electronic Networks, Devices and Fields, 2018, 31, e2334.                 | 1.9 | 1         |
| 20 | An Angular Displacement Sensor With a Curved Two-Metal-Layer CPW Loaded by an EBG Structure. IEEE Sensors Journal, 2018, 18, 2335-2341.   | 4.7 | 8         |
| 21 | Efficiency enhancement by employing the transistor nonlinear capacitors effects in a 6W hybrid X-band Class-J power amplifier. International Journal of RF and Microwave Computer-Aided Engineering, 2018, 28, e21187.                    | 1.2 | 3         |
| 22 | Experimental investigation of tensile mechanical strain influence on the dark current of organic solar cells. Organic Electronics, 2018, 54, 192-196.   | 2.6 | 4         |
| 23 | Using Aperture Impedance for Shielding Effectiveness Estimation of a Metallic Enclosure With Multiple Apertures on Different Walls Considering Higher Order Modes. IEEE Transactions on Electromagnetic Compatibility, 2018, 60, 629-637. | 2.2 | 7         |
| 24 | Systematic design of hybrid high power microwave amplifiers using large gate periphery GaN HEMTs. AEU - International Journal of Electronics and Communications, 2018, 84, 225-233.   | 2.9 | 17        |
| 25 | Design of X-band Power Amplifier Based on the Partitioning Design Approach. , 2018, , .   |     | 1         |
| 26 | Thermal analysis of microwave GaN-HEMTs in conventional and flip-chip assemblies. International Journal of RF and Microwave Computer-Aided Engineering, 2018, 28, e21513.   | 1.2 | 9         |
| 27 | Investigation of the tensile strain influence on flicker noise of organic solar cells under dark condition. Organic Electronics, 2018, 59, 230-235.   | 2.6 | 10        |
| 28 | Microstrip differential passband filter with high commonâ€mode suppression using periodically loaded stubs and coupled resonators. Journal of Engineering, 2018, 2018, 242-247.   | 1.1 | 2         |
| 29 | Realization of a Low-Cost Displacement Sensor on PCB With Two-Metal-Layer Coplanar Waveguide<br>Loaded by an EBG Structure. IEEE Sensors Journal, 2017, 17, 4797-4804.  | 4.7 | 6         |
| 30 | Two-Dimensional Displacement Sensor Based on CPW Line Loaded by Defected Ground Structure With Two Separated Transmission Zeroes. IEEE Sensors Journal, 2017, 17, 994-999.  | 4.7 | 31        |
| 31 | Shielding Effectiveness Estimation of a Metallic Enclosure With an Aperture Using S-Parameter<br>Analysis: Analytic Validation and Experiment. IEEE Transactions on Electromagnetic Compatibility, 2017,<br>59, 537-540.                  | 2.2 | 19        |
| 32 | Shielding effectiveness estimation of an enclosure with an arbitrary shape aperture. , 2017, , .  |     | 2         |
| 33 | Electromagnetic modeling of an enclosure with an aperture excited by an external thin wire. , 2017, , .   |     | 0         |
| 34 | Design and fabrication of hybrid 30-watt X-band GaN-based amplifier. , 2016, , .  |     | 4         |
| 35 | High efficiency 8.8–9.6 GHz class J power amplifier. , 2016, , .  |     | 4         |
| 36 | A network of ports to estimate shielding effectiveness of an enclosure with apertures. , 2016, , .  |     | 5         |

| #  | Article  | IF  | Citations |
|----|--|-----|-----------|
| 37 | Uprising nano memories: Latest advances in monolithic three dimensional (3D) integrated Flash memories. Microelectronic Engineering, 2016, 164, 75-87.                                   | 2.4 | 14        |
| 38 | A wide differential passband filter with common-mode suppression property based on left handed metamaterial transmission line. , 2016, , .   |     | 2         |
| 39 | Coplanar Waveguide (CPW) Loaded With an Electromagnetic Bandgap (EBG) Structure: Modeling and Application to Displacement Sensor. IEEE Sensors Journal, 2016, 16, 3034-3040.             | 4.7 | 22        |
| 40 | On the extraction of the external drain and source resistors and effective channel length in Si-MOSFET. Solid-State Electronics, 2015, 111, 1-6.   | 1.4 | 4         |
| 41 | Thermal analysis of organic solar cells using an enhanced opto-thermal model. Organic Electronics, 2015, 25, 184-192.  | 2.6 | 4         |
| 42 | An 8.8–9.8 GHz 100W hybrid solid state power amplifier for high power applications. , 2014, , .  |     | 4         |
| 43 | A radiated EMI measurement setup for un-buffered DRAM PCBs. , 2014, , .  |     | 2         |
| 44 | A fast method for estimating shielding effectiveness of an enclosure with apertures. , 2014, , .   |     | 7         |
| 45 | A computational study of solvent effects on polymer photovoltaics considering the field dependendent series resistance. , 2014, , .  |     | 1         |
| 46 | In-depth analysis of solvent effects on bulk heterojunction solar cell performance. Proceedings of SPIE, $2014, $ , .  | 0.8 | 1         |
| 47 | Future Prospect of Nanoelectronic Devices. Lecture Notes in Electrical Engineering, 2013, , 171-279.   | 0.4 | 1         |
| 48 | Selected Advances in Nanoelectronic Devices. Lecture Notes in Electrical Engineering, 2013, , .  | 0.4 | 5         |
| 49 | Radio Frequency Devices. Lecture Notes in Electrical Engineering, 2013, , 159-170.   | 0.4 | 9         |
| 50 | Memory Devices. Lecture Notes in Electrical Engineering, 2013, , 29-157.   | 0.4 | 1         |
| 51 | Logic Devices. Lecture Notes in Electrical Engineering, 2013, , 5-28.  | 0.4 | 0         |
| 52 | An extended drain current conductance extraction method and its application to DRAM support and array devices. Solid-State Electronics, 2009, 53, 1020-1031.                             | 1.4 | 5         |
| 53 | Quasi-monolithic integration of high-power GaN-based HEMTs for high-frequency applications. Semiconductor Science and Technology, 2007, 22, 1245-1248.                                   | 2.0 | 8         |
| 54 | Application of neural networks for extraction of distance and reflectance in pulsed laser radar. Measurement: Journal of the International Measurement Confederation, 2007, 40, 724-736. | 5.0 | 5         |

| #  | Article  | lF  | CITATIONS |
|----|--|-----|-----------|
| 55 | Interconnects Analyses in Quasi-Monolithic Integration Technology (QMIT)., 2006,,.   |     | 2         |
| 56 | A voltage-dependent channel length extraction method for MOSFET's. Solid-State Electronics, 2006, 50, 1787-1795.   | 1.4 | 3         |
| 57 | Technological requirements for a self-aligned lateral SiGe HBT with the SiGe layer formed by Ge ion implantation in Si including theoretical performance. , 2006, , .                    |     | 2         |
| 58 | Small-Signal Characterization of SiGe-HBT < tex> $f_T$ \$ < /tex>-Doubler up to 120 GHz. IEEE Transactions on Electron Devices, 2005, 52, 2108-2111.                                     | 3.0 | 10        |
| 59 | Heat transfer improvement in quasi-monolithic integration technology. Journal of Micro/<br>Nanolithography, MEMS, and MOEMS, 2005, 4, 033011.  | 0.9 | 1         |
| 60 | Application of a Scanning Thermal Nano-Probe for Thermal Imaging of High Frequency Active devices. Japanese Journal of Applied Physics, 2005, 44, 6823-6825.                             | 1.5 | 5         |
| 61 | Thermomechanical stress analysis and measurement in quasi-monolithic integration technology (QMIT). IEEE Transactions on Device and Materials Reliability, 2005, 5, 581-594.             | 2.0 | 4         |
| 62 | An enhanced quasi-monolithic integration technology for microwave and millimeter wave applications. IEEE Transactions on Advanced Packaging, 2003, 26, 402-409.                          | 1.6 | 10        |
| 63 | Reliable neural modeling of pHEMT from a smaller number of measurement data. , 2002, , .   |     | 1         |
| 64 | Thermal imaging of microwave power GaAs-FET with scanning thermal nanoprobe. , 2002, , .   |     | 2         |
| 65 | <title>Using a neural networks algorithm for high-resolution imaging in pulsed laser radar</title> ., 2001, , .  |     | 0         |
| 66 | <title>Using scanning probe microscopy and nanomoter surface profiler of DEKTAK for determination of thermal stress in quasi-monolithic integration technology (QMIT)</title> ., 2001,,. |     | 0         |
| 67 | Neural Method for Two Dimensional (2D) High Contrast Imaging in Pulsed Laser Radar. , 2001, , .  |     | 0         |
| 68 | Static thermal design of quasi monolithic integration technology (QMIT). , 0, , .  |     | 1         |
| 69 | Static thermal design of quasi monolithic technology (QMT) for realization of power microwave and millimeter wave circuits. , 0, , .   |     | 1         |
| 70 | Simulation and measurement of thermal stress in quasi-monolithic integration technology (QMIT). , 0, , .   |     | 4         |
| 71 | Optimization of thermal resistance in quasi monolithic integration technology (QMIT) structure. , 0, , .   |     | 3         |
| 72 | Using neural networks for high resolution distance measurements in pulsed laser radar. , 0, , .  |     | 3         |

| #  | Article  | IF | CITATIONS |
|----|--|----|-----------|
| 73 | Heat transfer and thermal stress analysis in the new generation quasi-monolithic integration technology (QMIT). , 0, , . |    | 4         |
| 74 | New generation quasi-monolithic integration technology (QMIT)., 0,,.   |    | 1         |
| 75 | A systematic approach to a reliable neural model for pHEMT using different numbers of training data. , 0, , .            |    | 2         |