

Leiming Wu

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/3616441/publications.pdf>

Version: 2024-02-01

72
papers

5,277
citations

94269

37
h-index

85405

71
g-index

72
all docs

72
docs citations

72
times ranked

4556
citing authors

#	ARTICLE	IF	CITATIONS
1	Ultrasensitive detection of miRNA with an antimonene-based surface plasmon resonance sensor. <i>Nature Communications</i> , 2019, 10, 28.	5.8	475
2	Sensitivity enhancement by using few-layer black phosphorus-graphene/TMDCs heterostructure in surface plasmon resonance biochemical sensor. <i>Sensors and Actuators B: Chemical</i> , 2017, 249, 542-548.	4.0	322
3	Few-layer Bismuthene: Sonochemical Exfoliation, Nonlinear Optics and Applications for Ultrafast Photonics with Enhanced Stability. <i>Laser and Photonics Reviews</i> , 2018, 12, 1700221.	4.4	311
4	MXene-enabled Electrochemical Microfluidic Biosensor: Applications toward Multicomponent Continuous Monitoring in Whole Blood. <i>Advanced Functional Materials</i> , 2019, 29, 1807326.	7.8	301
5	Broadband Nonlinear Optical Response in Few-layer Antimonene and Antimonene Quantum Dots: A Promising Optical Kerr Media with Enhanced Stability. <i>Advanced Optical Materials</i> , 2017, 5, 1700301.	3.6	269
6	Few-layer Tin Sulfide: A Promising Black-phosphorus-analogue 2D Material with Exceptionally Large Nonlinear Optical Response, High Stability, and Applications in All-optical Switching and Wavelength Conversion. <i>Advanced Optical Materials</i> , 2018, 6, 1700985.	3.6	212
7	Kerr Nonlinearity in 2D Graphdiyne for Passive Photonic Diodes. <i>Advanced Materials</i> , 2019, 31, e1807981.	11.1	187
8	Graphdiyne-based Flexible Photodetectors with High Responsivity and Detectivity. <i>Advanced Materials</i> , 2020, 32, e2001082.	11.1	171
9	Facile fabrication and characterization of two-dimensional bismuth(<i>iii</i>) sulfide nanosheets for high-performance photodetector applications under ambient conditions. <i>Nanoscale</i> , 2018, 10, 2404-2412.	2.8	166
10	Sensitivity Improved SPR Biosensor Based on the MoS ₂ /Graphene-Aluminum Hybrid Structure. <i>Journal of Lightwave Technology</i> , 2017, 35, 82-87.	2.7	165
11	All-optical Switching of Two Continuous Waves in Few Layer Bismuthene Based on Spatial Cross-Phase Modulation. <i>ACS Photonics</i> , 2017, 4, 2852-2861.	3.2	164
12	Few-layer Ti ₃ C ₂ T _x MXene: A promising surface plasmon resonance biosensing material to enhance the sensitivity. <i>Sensors and Actuators B: Chemical</i> , 2018, 277, 210-215.	4.0	163
13	All-optical Phosphorene Phase Modulator with Enhanced Stability Under Ambient Conditions. <i>Laser and Photonics Reviews</i> , 2018, 12, 1800016.	4.4	155
14	Enhanced Photodetection Properties of Tellurium@Selenium Roll-to-roll Nanotube Heterojunctions. <i>Small</i> , 2019, 15, e1900902.	5.2	120
15	MXene-based Nonlinear Optical Information Converter for All-optical Modulator and Switcher. <i>Laser and Photonics Reviews</i> , 2018, 12, 1800215.	4.4	117
16	Nonlinear Few-layer Antimonene-based All-optical Signal Processing: Ultrafast Optical Switching and High-speed Wavelength Conversion. <i>Advanced Optical Materials</i> , 2018, 6, 1701287.	3.6	97
17	Ultrasensitive biosensors based on long-range surface plasmon polariton and dielectric waveguide modes. <i>Photonics Research</i> , 2016, 4, 262.	3.4	93
18	Perovskite CsPbX ₃ : A Promising Nonlinear Optical Material and Its Applications for Ambient All-optical Switching with Enhanced Stability. <i>Advanced Optical Materials</i> , 2018, 6, 1800400.	3.6	90

#	ARTICLE	IF	CITATIONS
19	MZI-Based All-Optical Modulator Using MXene $\text{Ti}_3\text{C}_2\text{T}_x$ ($T = \text{O}$) EIOq110.784314 87	3.0	87
20	Tuning and Sensitivity Enhancement of Surface Plasmon Resonance Biosensor With Graphene Covered Au-MoS ₂ -Au Films. <i>IEEE Photonics Journal</i> , 2016, 8, 1-8.	1.0	85
21	Refractive Index Sensors Based on $\text{Ti}_3\text{C}_2\text{T}_x$ MXene Fibers. <i>ACS Applied Nano Materials</i> , 2020, 3, 303-311.	2.4	74
22	Nonlinear optical response, all optical switching, and all optical information conversion in NbSe_2 nanosheets based on spatial self-phase modulation. <i>Nanoscale</i> , 2019, 11, 4515-4522.	2.8	61
23	A self-powered photodetector based on two-dimensional boron nanosheets. <i>Nanoscale</i> , 2020, 12, 5313-5323.	2.8	60
24	Ultrasensitive Terahertz Biosensors Based on Fano Resonance of a Graphene/Waveguide Hybrid Structure. <i>Sensors</i> , 2017, 17, 1924.	2.1	52
25	Broadband nonlinear optical resonance and all-optical switching of liquid phase exfoliated tungsten diselenide. <i>Photonics Research</i> , 2018, 6, 1040.	3.4	52
26	Engineering ultrafast charge transfer in a bismuthene/perovskite nanohybrid. <i>Nanoscale</i> , 2019, 11, 2637-2643.	2.8	51
27	An ultra-high sensitivity surface plasmon resonance sensor based on graphene-aluminum-graphene sandwich-like structure. <i>Journal of Applied Physics</i> , 2016, 120, .	1.1	50
28	Two-dimensional beta-lead oxide quantum dots. <i>Nanoscale</i> , 2018, 10, 20540-20547.	2.8	49
29	Self-Healable Black Phosphorus Photodetectors. <i>Advanced Functional Materials</i> , 2019, 29, 1906610.	7.8	48
30	High-Performance Lossy-Mode Resonance Sensor Based on Few-Layer Black Phosphorus. <i>Journal of Physical Chemistry C</i> , 2018, 122, 7368-7373.	1.5	47
31	Two-Dimensional Black Arsenic Phosphorus for Ultrafast Photonics in Near- and Mid-Infrared Regimes. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 46509-46518.	4.0	47
32	Highly Sensitive Terahertz Gas Sensor Based on Surface Plasmon Resonance With Graphene. <i>IEEE Photonics Journal</i> , 2018, 10, 1-7.	1.0	46
33	Sensitivity Enhanced by MoS ₂ -Graphene Hybrid Structure in Guided-Wave Surface Plasmon Resonance Biosensor. <i>Plasmonics</i> , 2018, 13, 281-285.	1.8	46
34	Epitaxial Growth of Topological Insulators on Semiconductors ($\text{Bi}_2\text{Se}_3/\text{Te@Se}$) toward High-Performance Photodetectors. <i>Small Methods</i> , 2019, 3, 1900349.	4.6	45
35	Van der Waals Integration of Bismuth Quantum Dots-Decorated Tellurium Nanotubes (Te@Bi) Heterojunctions and Plasma-Enhanced Optoelectronic Applications. <i>Small</i> , 2019, 15, e1903233.	5.2	45
36	Tunable terahertz/infrared coherent perfect absorption in a monolayer black phosphorus. <i>Optics Express</i> , 2018, 26, 5488.	1.7	44

#	ARTICLE	IF	CITATIONS
37	Long-Range Surface Plasmon With Graphene for Enhancing the Sensitivity and Detection Accuracy of Biosensor. <i>IEEE Photonics Journal</i> , 2016, 8, 1-9.	1.0	41
38	A promising nonlinear optical material and its applications for all-optical switching and information converters based on the spatial self-phase modulation (SSPM) effect of TaSe ₂ nanosheets. <i>Journal of Materials Chemistry C</i> , 2019, 7, 3811-3816.	2.7	41
39	Fano resonance in double waveguides with graphene for ultrasensitive biosensor. <i>Optics Express</i> , 2018, 26, 16884.	1.7	40
40	Spatial self-phase modulation and all-optical switching of graphene oxide dispersions. <i>Journal of Alloys and Compounds</i> , 2019, 771, 900-904.	2.8	35
41	Recent Advances of Spatial Self-Phase Modulation in 2D Materials and Passive Photonic Device Applications. <i>Small</i> , 2020, 16, e2002252.	5.2	35
42	Theoretical Investigation of Multilayer Ti ₃ C ₂ T _x MXene as the Plasmonic Material for Surface Plasmon Resonance Sensors in Near Infrared Region. <i>IEEE Sensors Journal</i> , 2019, 19, 11834-11838.	2.4	34
43	Absorption enhancement and total absorption in a graphene-waveguide hybrid structure. <i>AIP Advances</i> , 2017, 7, .	0.6	33
44	Ultrathin boron nanosheets as an emerging two-dimensional photoluminescence material for bioimaging. <i>Nanoscale Horizons</i> , 2020, 5, 705-713.	4.1	33
45	Manipulating the optical bistability at terahertz frequency in the Fabry-Perot cavity with graphene. <i>Optics Express</i> , 2015, 23, 31181.	1.7	32
46	Improving the Performance of an SPR Biosensor Using Long-Range Surface Plasmon of Ga-Doped Zinc Oxide. <i>Sensors</i> , 2018, 18, 2098.	2.1	31
47	Tunable polaritonic metasurface absorbers in mid-IR based on hexagonal boron nitride and vanadium dioxide layers. <i>Journal Physics D: Applied Physics</i> , 2019, 52, 164002.	1.3	30
48	Synthesis and optoelectronics of mixed-dimensional Bi/Te binary heterostructures. <i>Nanoscale Horizons</i> , 2020, 5, 847-856.	4.1	28
49	All-optical logic devices based on black arsenic phosphorus with strong nonlinear optical response and high stability. <i>Opto-Electronic Advances</i> , 2022, 5, 200046-200046.	6.4	25
50	GeSe nanosheets modified surface plasmon resonance sensors for enhancing sensitivity. <i>Nanophotonics</i> , 2020, 9, 327-336.	2.9	24
51	Enhancement of photonic spin Hall effect via bound states in the continuum. <i>Journal Physics D: Applied Physics</i> , 2019, 52, 045401.	1.3	23
52	Liquid-Exfoliated Few-Layer InSe Nanosheets for Broadband Nonlinear All-Optical Applications. <i>Advanced Optical Materials</i> , 2020, 8, 1901862.	3.6	20
53	High Sensitivity Intensity-Interrogated Bloch Surface Wave Biosensor With Graphene. <i>IEEE Sensors Journal</i> , 2018, 18, 106-110.	2.4	19
54	Broadband nonlinear optical response in Bi ₂ Se ₃ -Bi ₂ Te ₃ heterostructure and its application in all-optical switching. <i>AIP Advances</i> , 2019, 9, .	0.6	19

#	ARTICLE	IF	CITATIONS
55	1D@0D hybrid dimensional heterojunction-based photonics logical gate and isolator. Applied Materials Today, 2020, 19, 100589.	2.3	19
56	Terahertz Biochemical Sensor Based on Strong Coupling Between Waveguide Mode and Surface Plasmons of Double-Layer Graphene. IEEE Sensors Journal, 2018, 18, 7436-7441.	2.4	18
57	Topological insulator overlayer to enhance the sensitivity and detection limit of surface plasmon resonance sensor. Nanophotonics, 2020, 9, 1941-1951.	2.9	18
58	Giant tunable Goos-Hänchen shifts based on surface plasmon resonance with Dirac semimetal films. Journal Physics D: Applied Physics, 2019, 53, 015107.	1.3	14
59	Application of Few-Layer Transition Metal Dichalcogenides to Detect the Refractive Index Variation in Lossy-Mode Resonance Sensors With High Figure of Merit. IEEE Sensors Journal, 2019, 19, 5030-5034.	2.4	14
60	High Figure of Merit Lossy Mode Resonance Sensor with Graphene. Plasmonics, 2019, 14, 929-934.	1.8	13
61	Ultrasensitive Multiple Guided-Mode Biosensor With Few-Layer Black Phosphorus. Journal of Lightwave Technology, 2020, 38, 1564-1571.	2.7	11
62	2D BP/InSe Heterostructures as a Nonlinear Optical Material for Ultrafast Photonics. Nanomaterials, 2022, 12, 1809.	1.9	11
63	Lossy-mode-resonance sensor based on perovskite nanomaterial with high sensitivity. Optics Express, 2021, 29, 17602.	1.7	10
64	Multifunctional VI-VI binary heterostructure-based self-powered pH-sensitive photo-detector. Journal of Materials Chemistry C, 2020, 8, 5991-6000.	2.7	8
65	Enhancement of Sensitivity with High Reflective Index Guided-Wave Nanomaterials for a Long-Range Surface Plasmon Resonance Sensor. Nanomaterials, 2022, 12, 168.	1.9	6
66	Photodetectors: Graphdiyne-Based Flexible Photodetectors with High Responsivity and Detectivity (Adv. Mater. 23/2020). Advanced Materials, 2020, 32, 2070175.	11.1	5
67	CH ₃ NH ₃ PbBr ₃ Thin Film Served as Guided-Wave Layer for Enhancing the Angular Sensitivity of Plasmon Biosensor. Biosensors, 2021, 11, 415.	2.3	5
68	Quantum Dots: Broadband Nonlinear Optical Response in Few-Layer Antimonene and Antimonene Quantum Dots: A Promising Optical Kerr Media with Enhanced Stability (Advanced Optical Materials) Tj ETQq0 0 0 3gBT /Overclock 10 Tf		
69	Fano Resonance in Waveguide Coupled Surface Exciton Polaritons: Theory and Application in Biosensor. Sensors, 2018, 18, 4437.	2.1	3
70	Tunable Nonlinearity in 2D Graphdiyne Oxide for High-Performance All-Optical Modulation. Advanced Optical Materials, 2022, 10, .	3.6	3
71	Double Perovskite Ba ₂ LaTaO ₆ for Ultrafast Fiber Lasers in Anomalous and Normal Net Dispersion Regime. Nanomaterials, 2022, 12, 2112.	1.9	3
72	Ultrasensitive Terahertz Imaging Sensors Based on the Strong Coupling of Surface Phonon Polariton and Graphene Surface Plasmon Polariton. IEEE Photonics Journal, 2018, 10, 1-9.	1.0	2