

Jeremie Soulestin

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/363978/publications.pdf>

Version: 2024-02-01

64
papers

2,135
citations

201385

27
h-index

233125

45
g-index

64
all docs

64
docs citations

64
times ranked

2424
citing authors

#	ARTICLE	IF	CITATIONS
1	Rheological Considerations in Processing Self-Reinforced Thermoplastic Polymer Nanocomposites: A Review. <i>Polymers</i> , 2022, 14, 637.	2.0	8
2	(Nano)Fibrillar morphology development in biobased poly(butylene succinate-co-adipate)/poly(amide-11) blown films. <i>Polymer Engineering and Science</i> , 2021, 61, 1324-1337.	1.5	4
3	Fused filament fabrication of polypropylene: Influence of the bead temperature on adhesion and porosity. <i>Additive Manufacturing</i> , 2021, 38, 101838.	1.7	7
4	Fused filament fabrication of scaffolds for tissue engineering; how realistic is shape-memory? A review. <i>Polymer</i> , 2021, 217, 123440.	1.8	14
5	In-situ nano-fibrillation of poly(butylene succinate-co-adipate) in isosorbide-based polycarbonate matrix. Relationship between rheological parameters and induced morphological and mechanical properties. <i>Polymer</i> , 2021, 217, 123445.	1.8	7
6	Minimise thermo-mechanical batch variations when processing medical grade lactide based copolymers in additive manufacturing. <i>Polymer Degradation and Stability</i> , 2020, 181, 109372.	2.7	8
7	Beta Phase Crystallization and Ferro- and Piezoelectric Performances of Melt-Processed Poly(vinylidene difluoride) Blends with Poly(methyl methacrylate) Copolymers Containing Ionizable Moieties. <i>ACS Applied Polymer Materials</i> , 2020, 2, 3766-3780.	2.0	12
8	Biodegradable PLA/PBSA Multinanolayer Nanocomposites: Effect of Nanoclays Incorporation in Multinanolayered Structure on Mechanical and Water Barrier Properties. <i>Nanomaterials</i> , 2020, 10, 2561.	1.9	6
9	Thermal and geometry impacts on the structure and mechanical properties of part produced by polymer additive manufacturing. <i>Journal of Applied Polymer Science</i> , 2020, 137, 49038.	1.3	16
10	Poly(ethylene oxide)/Poly(3,4-ethylenedioxythiophene):Poly(styrene sulfonate) (PEDOT:PSS) Blends: An Efficient Route to Highly Conductive Thermoplastic Materials for Melt-State Extrusion Processing ?. <i>ACS Applied Polymer Materials</i> , 2020, 2, 2366-2379.	2.0	16
11	Optimization of the UV stabilization of a plasticized PVC film for exterior automotive applications. <i>AIP Conference Proceedings</i> , 2020, , .	0.3	2
12	Melt compatibility between polyolefins: Evaluation and reliability of interfacial/surface tensions obtained by various techniques. <i>Polymer Testing</i> , 2019, 78, 105995.	2.3	9
13	Effect of clay particles size and location on coalescence in PMMA/PS blends. <i>Journal of Rheology</i> , 2019, 63, 883-893.	1.3	6
14	Thermal and dielectric behavior of polyamide-6/clay nanocomposites. <i>Materials Chemistry and Physics</i> , 2019, 232, 99-108.	2.0	16
15	Optimization of mechanical properties of printed acrylonitrile butadiene styrene using RSM design. <i>International Journal of Advanced Manufacturing Technology</i> , 2019, 100, 1363-1372.	1.5	18
16	Processing of PVDF-based electroactive/ferroelectric films: importance of PMMA and cooling rate from the melt state on the crystallization of PVDF beta-crystals. <i>Soft Matter</i> , 2018, 14, 4591-4602.	1.2	36
17	Influence of the molar masses on compatibilization mechanism induced by two block copolymers in PMMA/PS blends. <i>Journal of Rheology</i> , 2018, 62, 681-693.	1.3	6
18	How does temperature govern mechanisms of starch changes during extrusion?. <i>Carbohydrate Polymers</i> , 2018, 184, 57-65.	5.1	30

#	ARTICLE	IF	CITATIONS
19	Development of nanofibrillar morphologies in poly(ϵ -lactide)/poly(amide) blends: role of the matrix elasticity and identification of the critical shear rate for the nodular/fibrillar transition. RSC Advances, 2018, 8, 22023-22041.	1.7	25
20	Compatibilization mechanism induced by organoclay in PMMA/PS blends. Journal of Rheology, 2017, 61, 613-626.	1.3	23
21	Water Transport Properties of Poly(butylene succinate) and Poly[(butylene) Tj ETQq1 1 0.784314 rgBT /Overlock 10 Tf 50 667 Td (su Extrusion Process. Journal of Physical Chemistry C, 2017, 121, 918-930.	1.5	15
22	Influence of crystallinity on the dielectric relaxations of poly(butylene succinate) and poly[(butylene) Tj ETQq0 0 0 rgBT /Overlock 10 Tf 50 667 Td (su	2.6	21
23	New Melting Data of the Two Polymorphs of Prednisolone. Journal of Physical Chemistry B, 2016, 120, 10839-10843.	1.2	14
24	Poly[(butylene succinate)- <i>co</i> -(butylene adipate)]-Montmorillonite Nanocomposites Prepared by Water-Assisted Extrusion: Role of the Dispersion Level and of the Structure-Microstructure on the Enhanced Barrier Properties. Journal of Physical Chemistry C, 2016, 120, 13234-13248.	1.5	27
25	<i>In situ</i> fibrillation of polypropylene/polyamide 6 blends: Effect of organoclay addition. Journal of Applied Polymer Science, 2015, 132, .	1.3	9
26	Structure- ϵ barrier property relationship of biodegradable poly(butylene succinate) and poly[(butylene succinate)- <i>co</i> -(butylene adipate)] nanocomposites: influence of the rigid amorphous fraction. Physical Chemistry Chemical Physics, 2015, 17, 29918-29934.	1.3	32
27	Improvement of barrier properties of bio-based polyester nanocomposite membranes by water-assisted extrusion. Journal of Membrane Science, 2015, 496, 185-198.	4.1	29
28	Using water to modify the localization of clay in immiscible polymer blends. RSC Advances, 2015, 5, 75311-75324.	1.7	6
29	Poly(3-hydroxybutyrate- <i>co</i> -4-hydroxybutyrate) based nanocomposites: influence of the microstructure on the barrier properties. Physical Chemistry Chemical Physics, 2015, 17, 11313-11323.	1.3	17
30	Melt-blended halloysite nanotubes/wheat starch nanocomposites as drug delivery system. Polymer Engineering and Science, 2015, 55, 573-580.	1.5	32
31	Preparation and characterization of plasticized starch/halloysite porous nanocomposites possibly suitable for biomedical applications. Journal of Applied Polymer Science, 2015, 132, .	1.3	34
32	Studies on the effect of storage time and plasticizers on the structural variations in thermoplastic starch. Carbohydrate Polymers, 2015, 115, 364-372.	5.1	93
33	Processing and Characterization of Polypropylene Filled with Multiwalled Carbon Nanotube and Clay Hybrid Nanocomposites. International Journal of Polymer Analysis and Characterization, 2014, 19, 363-371.	0.9	18
34	Processing- ϵ induced degradation of nanoclay organic modifier in melt- ϵ mixed PET/PE blends during twin screw extrusion at industrial scale: Effect on morphology and mechanical behavior. Journal of Applied Polymer Science, 2014, 131, .	1.3	4
35	Deformation mechanisms of plasticized starch materials. Carbohydrate Polymers, 2014, 114, 450-457.	5.1	43
36	Evaluation of rheological properties of non-Newtonian fluids in micro rheology compounder: Experimental procedures for a reliable polymer melt viscosity measurement. Polymer Testing, 2014, 40, 207-217.	2.3	32

#	ARTICLE	IF	CITATIONS
37	Microstructure and barrier properties of PHBV/organoclays bionanocomposites. <i>Journal of Membrane Science</i> , 2014, 467, 56-66.	4.1	54
38	Structural evolution of poly(lactic acid)/poly(ethylene oxide)/unmodified clay upon ambient ageing. <i>Journal of Applied Polymer Science</i> , 2014, 131, .	1.3	4
39	Active pseudo-multilayered films from polycaprolactone and starch based matrix for food-packaging applications. <i>European Polymer Journal</i> , 2013, 49, 1234-1242.	2.6	66
40	Emission of volatile organic compounds during processing and use of organoclay-based nanocomposites. <i>Polymer Degradation and Stability</i> , 2013, 98, 557-565.	2.7	12
41	Plasticized-starch/poly(ethylene oxide) blends prepared by extrusion. <i>Carbohydrate Polymers</i> , 2013, 91, 253-261.	5.1	53
42	Effect of Nanoclay Hydration on Barrier Properties of PLA/Montmorillonite Based Nanocomposites. <i>Journal of Physical Chemistry C</i> , 2013, 117, 12117-12135.	1.5	85
43	Compatibilization of Immiscible Polymer Blends by Organoclay: Effect of Nanofiller or Organo-Modifier?. <i>Macromolecular Materials and Engineering</i> , 2013, 298, 757-770.	1.7	30
44	Morphology and mechanical properties of PET/PE blends compatibilized by nanoclays: Effect of thermal stability of nanofiller organic modifier. <i>Journal of Applied Polymer Science</i> , 2013, 128, 2766-2778.	1.3	29
45	Water Diffusion Mechanisms in New Bio-Nanocomposites Based on Polyhydroxyalkanoates/Nanoclays. <i>Advanced Materials Research</i> , 2013, 747, 682-685.	0.3	1
46	Effect of injection molding parameters on nanofillers dispersion in masterbatch based PP-clay nanocomposites. <i>EXPRESS Polymer Letters</i> , 2012, 6, 237-248.	1.1	28
47	Effect of Highly Exfoliated and Oriented Organoclays on the Barrier Properties of Polyamide 6 Based Nanocomposites. <i>Journal of Physical Chemistry C</i> , 2012, 116, 4937-4947.	1.5	61
48	Tailoring the properties of thermoplastic starch by blending with cinnamyl alcohol and radiation processing: An insight into the competitive grafting and scission reactions. <i>Radiation Physics and Chemistry</i> , 2012, 81, 986-990.	1.4	8
49	Preparation and properties of novel melt-blended halloysite nanotubes/wheat starch nanocomposites. <i>Carbohydrate Polymers</i> , 2012, 89, 920-927.	5.1	84
50	Mechanical and Optical Properties of Polyamide 6/Clay Nanocomposite Cast Films: Influence of the Degree of Exfoliation. <i>Macromolecular Materials and Engineering</i> , 2012, 297, 444-454.	1.7	41
51	One-step water-assisted melt-compounding of polyamide 6/pristine clay nanocomposites: An efficient way to prevent matrix degradation. <i>Polymer Degradation and Stability</i> , 2011, 96, 1890-1900.	2.7	35
52	Efficient one-step melt-compounding of copolyetheramide/pristine clay nanocomposites using water-injection as intercalating/exfoliating aid. <i>EXPRESS Polymer Letters</i> , 2011, 5, 1085-1101.	1.1	22
53	Electrical and Dielectric Properties of Multi-Walled Carbon Nanotube Filled Polypropylene Nanocomposites. <i>Polymers and Polymer Composites</i> , 2010, 18, 489-494.	1.0	21
54	Present Status and Key Challenges of Carbon Nanotubes Reinforced Polyolefins: A Review on Nanocomposites Manufacturing and Performance Issues. <i>Polymers and Polymer Composites</i> , 2009, 17, 205-245.	1.0	30

#	ARTICLE	IF	CITATIONS
55	Intumescent Biobased-Polylactide Films to Flame Retard Nonwovens. <i>Journal of Engineered Fibers and Fabrics</i> , 2009, 4, 155892500900400.	0.5	9
56	Masterbatch-based multi-walled carbon nanotube filled polypropylene nanocomposites: Assessment of rheological and mechanical properties. <i>Composites Science and Technology</i> , 2009, 69, 1756-1763.	3.8	341
57	A new elaboration concept of polypropylene/unmodified Montmorillonite nanocomposites by reactive extrusion based on direct injection of polypropylene aqueous suspensions. <i>Polymer Engineering and Science</i> , 2009, 49, 2276-2285.	1.5	19
58	Segmental Dynamics of Poly(ethylene oxide) Chains in a Model Polymer/Clay Intercalated Phase: Solid-State NMR Investigation. <i>Macromolecules</i> , 2009, 42, 218-230.	2.2	36
59	Taguchi analysis of shrinkage and warpage of injection-moulded polypropylene/multiwall carbon nanotubes nanocomposites. <i>EXPRESS Polymer Letters</i> , 2009, 3, 630-638.	1.1	36
60	Multi-walled carbon nanotube filled polypropylene nanocomposites based on masterbatch route: Improvement of dispersion and mechanical properties through PP-g-MA addition. <i>EXPRESS Polymer Letters</i> , 2008, 2, 735-745.	1.1	185
61	Polyolefins biofibre composites: A new way for an industrial production. <i>Polymer Engineering and Science</i> , 2007, 47, 467-476.	1.5	30
62	Comparison of the photochemical and thermal degradation of bisphenol-A polycarbonate and trimethylcyclohexane polycarbonate. <i>Polymer Degradation and Stability</i> , 2002, 75, 17-33.	2.7	81
63	Influence of the chemical structure of polycarbonates on the contribution of crosslinking and chain scissions to the photothermal ageing. <i>European Polymer Journal</i> , 2002, 38, 1349-1363.	2.6	35
64	Processing and Mechanical Behaviour of Halloysite Filled Starch Based Nanocomposites. <i>Advanced Materials Research</i> , 0, 584, 445-449.	0.3	4