

List of Publications by Citations

Source: <https://exaly.com/author-pdf/3712375/jasmina-anojcic-publications-by-citations.pdf>
Version: 2024-04-27

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.
The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

16 papers	193 citations	7 h-index	13 g-index
16 ext. papers	212 ext. citations	4.7 avg, IF	2.73 L-index

#	Paper	IF	Citations
16	Voltammetric behavior of doxorubicin at a renewable silver-amalgam film electrode and its determination in human urine. <i>Electrochimica Acta</i> , 2014 , 132, 49-57	6.7	43
15	Bismuth modified carbon-based electrodes for the determination of selected neonicotinoid insecticides. <i>Molecules</i> , 2011 , 16, 4451-66	4.8	39
14	Hydrodynamic chronoamperometric determination of hydrogen peroxide using carbon paste electrodes coated by multiwalled carbon nanotubes decorated with MnO ₂ or Pt particles. <i>Sensors and Actuators B: Chemical</i> , 2016 , 233, 83-92	8.5	30
13	Hydrodynamic chronoamperometric method for the determination of H ₂ O ₂ using MnO ₂ -based carbon paste electrodes in groundwater treated by Fenton and Fenton-like reagents for natural organic matter removal. <i>Journal of Hazardous Materials</i> , 2015 , 283, 292-301	12.8	18
12	Screen-printed enzymatic glucose biosensor based on a composite made from multiwalled carbon nanotubes and palladium containing particles. <i>Mikrochimica Acta</i> , 2017 , 184, 1987-1996	5.8	15
11	Voltammetric behavior of erythromycin ethylsuccinate at a renewable silver-amalgam film electrode and its determination in urine and in a pharmaceutical preparation. <i>Electrochimica Acta</i> , 2016 , 191, 44-54	6.7	15
10	Amperometric Determination of Glucose in White Grape and in Tablets as Ingredient by Screen-Printed Electrode Modified with Glucose Oxidase and Composite of Platinum and Multiwalled Carbon Nanotubes. <i>Food Analytical Methods</i> , 2019 , 12, 570-580	3.4	8
9	Rapid, trace-level direct cathodic voltammetric determination of dopamine by oxidized multiwalled carbon nanotube-modified carbon paste electrode in selected samples of pharmaceutical importance. <i>Ionics</i> , 2019 , 25, 6093-6106	2.7	7
8	Imidazolium-based ionic liquids as modifiers of carbon paste electrodes for trace-level voltammetric determination of dopamine in pharmaceutical preparations. <i>Journal of Molecular Liquids</i> , 2020 , 306, 112900	6	7
7	Use of carbon paste electrode and modified by gold nanoparticles for selected macrolide antibiotics determination as standard and in pharmaceutical preparations. <i>Journal of Electroanalytical Chemistry</i> , 2020 , 873, 114324	4.1	5
6	Rapid amperometric determination of H ₂ O ₂ by a Pt nanoparticle/Vulcan XC72 composite-coated carbon paste electrode in disinfection and contact lens solutions. <i>Monatshefte für Chemie</i> , 2018 , 149, 1727-1738	1.4	4
5	Tetrabutylammonium Chloride Modified Carbon Paste Electrode for Rapid and Highly Sensitive Voltammetric Determination of Carbendazim. <i>Journal of the Electrochemical Society</i> , 2020 , 167, 137504	3.9	1
4	Electroanalytical performance of a β -cyclodextrin and ionic liquid modified carbon paste electrode for the determination of verapamil in urine and pharmaceutical formulation. <i>Analytical Methods</i> , 2021 , 13, 2963-2973	3.2	1
3	Self-assembled iridium(III) complex microspheres on the carbon paste electrode surface for signal enhanced amperometric determination of H ₂ O ₂ in color cream developers. <i>Journal of Electroanalytical Chemistry</i> , 2021 , 904, 115873	4.1	
2	The analysis of chromatographic behavior of homoandrostane derivatives in reversed-phase ultra-high performance liquid chromatography. <i>Acta Periodica Technologica</i> , 2021 , 147-158	0.8	
1	Rapid direct cathodic voltammetric determination of insecticide flonicamid by renewable silver-amalgam film electrode. <i>International Journal of Environmental Analytical Chemistry</i> , 1-15	1.8	