

Yanjun Xie

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/3869329/publications.pdf>

Version: 2024-02-01

105
papers

5,082
citations

136940

32
h-index

95259

68
g-index

107
all docs

107
docs citations

107
times ranked

5052
citing authors

#	ARTICLE	IF	CITATIONS
1	Characterization of the structural rheological properties of wood flour/polyethylene composites with ultrahigh filling on the basis of uniaxial cyclic compression method. <i>Composites Part A: Applied Science and Manufacturing</i> , 2022, 153, 106724.	7.6	5
2	Cellulose-derived solid-solid phase change thermal energy storage membrane with switchable optical transparency. <i>Chemical Engineering Journal</i> , 2022, 435, 134851.	12.7	17
3	Aliphatic chains grafted cellulose nanocrystals with core-corona structures for efficient toughening of PLA composites. <i>Carbohydrate Polymers</i> , 2022, 285, 119200.	10.2	18
4	Low-value wood for sustainable high-performance structural materials. <i>Nature Sustainability</i> , 2022, 5, 628-635.	23.7	72
5	Multifunctional Reversible Self-Assembled Structures of Cellulose-Derived Phase-Change Nanocrystals. <i>Advanced Materials</i> , 2021, 33, e2005263.	21.0	21
6	Magnetically Driven 3D Cellulose Film for Improved Energy Efficiency in Solar Evaporation. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 7756-7765.	8.0	38
7	Developing a Superhydrophobic Absorption-Dominated Electromagnetic Shielding Material by Building Clustered Fe ₃ O ₄ Nanoparticles on the Copper-Coated Cellulose Paper. <i>ACS Sustainable Chemistry and Engineering</i> , 2021, 9, 6574-6585.	6.7	29
8	Carbonized Wood Decorated with Cobalt-Nickel Binary Nanoparticles as a Low-Cost and Efficient Electrode for Water Splitting. <i>Advanced Functional Materials</i> , 2021, 31, 2010951.	14.9	54
9	Sandwich-structural Ni/Fe ₃ O ₄ /Ni/cellulose paper with a honeycomb surface for improved absorption performance of electromagnetic interference. <i>Carbohydrate Polymers</i> , 2021, 260, 117840.	10.2	32
10	Multifunctional composite film based on biodegradable grape skin and polyvinyl alcohol. <i>Cellulose</i> , 2021, 28, 6467-6479.	4.9	8
11	Compression rheological behavior of ultrahighly filled wood flour-polyethylene composites. <i>Composites Part B: Engineering</i> , 2021, 215, 108766.	12.0	7
12	HTO/Cellulose Aerogel for Rapid and Highly Selective Li ⁺ Recovery from Seawater. <i>Molecules</i> , 2021, 26, 4054.	3.8	14
13	Flexible cellulose-based material with a higher conductivity and electromagnetic shielding performance from electroless nickel plating. <i>Wood Science and Technology</i> , 2021, 55, 1693-1710.	3.2	12
14	Superhydrophobic Hierarchical Structures from Self-Assembly of Cellulose-Based Nanoparticles. <i>ACS Sustainable Chemistry and Engineering</i> , 2021, 9, 14101-14111.	6.7	23
15	Conductive and fire-retardant wood/polyethylene composites based on a continuous honeycomb-like nanoscale carbon black network. <i>Construction and Building Materials</i> , 2020, 233, 117369.	7.2	26
16	Sulfhydryl-Modified Chitosan Aerogel for the Adsorption of Heavy Metal Ions and Organic Dyes. <i>Industrial & Engineering Chemistry Research</i> , 2020, 59, 14531-14536.	3.7	40
17	A Coral Reef-like Structure Fabricated on Cellulose Paper for Simultaneous Oil/Water Separation and Electromagnetic Shielding Protection. <i>ACS Omega</i> , 2020, 5, 18105-18113.	3.5	8
18	Transparent wood with thermo-reversible optical properties based on phase-change material. <i>Composites Science and Technology</i> , 2020, 200, 108407.	7.8	32

#	ARTICLE	IF	CITATIONS
19	Cellulose-Based Superhydrophobic Surface Decorated with Functional Groups Showing Distinct Wetting Abilities to Manipulate Water Harvesting. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 40968-40978.	8.0	49
20	Sustainable and antibacterial sandwich-like Ag-Pulp/CNF composite paper for oil/water separation. <i>Carbohydrate Polymers</i> , 2020, 245, 116587.	10.2	34
21	Cellulose nanocrystal reinforced poly(lactic acid) nanocomposites prepared by a solution precipitation approach. <i>Cellulose</i> , 2020, 27, 7489-7502.	4.9	21
22	The influence of double-layered distribution of fire retardants on the fire retardancy and mechanical properties of wood fiber polypropylene composites. <i>Construction and Building Materials</i> , 2020, 242, 118047.	7.2	23
23	Highly Efficient, Stable, and Recyclable Hydrogen Manganese Oxide/Cellulose Film for the Extraction of Lithium from Seawater. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 9775-9781.	8.0	59
24	Fabrication of a laminated felt-like electromagnetic shielding material based on nickel-coated cellulose fibers via self-foaming effect in electroless plating process. <i>International Journal of Biological Macromolecules</i> , 2020, 154, 954-961.	7.5	8
25	Anodic oxidation growth of lanthanum/manganese-doped TiO ₂ nanotube arrays for photocatalytic degradation of various organic dyes. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 8844-8851.	2.2	9
26	Enhanced Weathering Resistance of Radiata Pine Wood by Treatment with an Aqueous Styrene/Acrylic Acid Copolymer Dispersion. <i>Journal of Wood Chemistry and Technology</i> , 2019, 39, 421-435.	1.7	6
27	Thermal, antioxidant and swelling behaviour of transparent polyvinyl (alcohol) films in presence of hydrophobic citric acid-modified lignin nanoparticles. <i>International Journal of Biological Macromolecules</i> , 2019, 127, 665-676.	7.5	100
28	Lightweight, Flexible, Thermally-Stable, and Thermally-Insulating Aerogels Derived from Cotton Nanofibrillated Cellulose. <i>ACS Sustainable Chemistry and Engineering</i> , 2019, 7, 9202-9210.	6.7	52
29	Combustion behavior of poplar (<i>Populus adenopoda</i> Maxim.) and radiata pine (<i>Pinus radiata</i> Don.) treated with a combination of styrene-acrylic copolymer and sodium silicate. <i>European Journal of Wood and Wood Products</i> , 2019, 77, 439-452.	2.9	6
30	Enhanced heavy metal adsorption ability of lignocellulosic hydrogel adsorbents by the structural support effect of lignin. <i>Cellulose</i> , 2019, 26, 4005-4019.	4.9	27
31	Effects of modification with a combination of styrene-acrylic copolymer dispersion and sodium silicate on the mechanical properties of wood. <i>Journal of Wood Science</i> , 2019, 65, .	1.9	19
32	Wood-Based Mesoporous Filter Decorated with Silver Nanoparticles for Water Purification. <i>ACS Sustainable Chemistry and Engineering</i> , 2019, 7, 5134-5141.	6.7	85
33	Reinforcement of wood flour/HDPE composite with a copolyester of <i>p</i> -hydroxy benzoic acid and <i>o</i> -hydroxy-naphthoic acid. <i>Journal of Applied Polymer Science</i> , 2019, 136, 47338.	2.6	2
34	Transparent wood bearing a shielding effect to infrared heat and ultraviolet via incorporation of modified antimony-doped tin oxide nanoparticles. <i>Composites Science and Technology</i> , 2019, 172, 43-48.	7.8	77
35	Activation of glucose with Fenton's reagent: chemical structures of activated products and their reaction efficacy toward cellulosic material. <i>Holzforschung</i> , 2019, 73, 579-587.	1.9	2
36	Coating performance on glutaraldehyde-modified wood. <i>Journal of Forestry Research</i> , 2019, 30, 353-361.	3.6	1

#	ARTICLE	IF	CITATIONS
37	Mechanical reinforcement and creep resistance of coextruded wood flour/polyethylene composites by shell layer treatment with nano- and micro-SiO ₂ particles. <i>Polymer Composites</i> , 2019, 40, 1576-1584.	4.6	16
38	Modification of Scots pine with activated glucose and citric acid: Physical and mechanical properties. <i>BioResources</i> , 2019, 14, 3445-3458.	1.0	19
39	Reinforcing 3D print methacrylate resin/cellulose nanocrystal composites: Effect of cellulose nanocrystal modification. <i>BioResources</i> , 2019, 14, 3701-3716.	1.0	10
40	End effect on determining shear modulus of timber beams in torsion tests. <i>Construction and Building Materials</i> , 2018, 164, 442-450.	7.2	10
41	Radiata pine wood treatment with a dispersion of aqueous styrene/acrylic acid copolymer. <i>Holzforschung</i> , 2018, 72, 387-396.	1.9	15
42	Sandwich-structured wood flour/HDPE composite panels: Reinforcement using a linear low-density polyethylene core layer. <i>Construction and Building Materials</i> , 2018, 164, 489-496.	7.2	33
43	Fire retardancy of an aqueous, intumescent, and translucent wood varnish based on guanylurea phosphate and melamine-urea-formaldehyde resin. <i>Progress in Organic Coatings</i> , 2018, 121, 64-72.	3.9	44
44	Reinforcing 3D printed acrylonitrile butadiene styrene by impregnation of methacrylate resin and cellulose nanocrystal mixture: Structural effects and homogeneous properties. <i>Materials and Design</i> , 2018, 138, 62-70.	7.0	20
45	The reinforcement efficacy of nano- and microscale silica for extruded wood flour/HDPE composites: the effects of dispersion patterns and interfacial modification. <i>Journal of Materials Science</i> , 2018, 53, 1899-1910.	3.7	27
46	Vaporization heat of bound water in wood chemically modified via grafting and crosslinking patterns by DSC and NMR analysis. <i>Holzforschung</i> , 2018, 72, 1043-1049.	1.9	10
47	Citric Acid as Green Modifier for Tuned Hydrophilicity of Surface Modified Cellulose and Lignin Nanoparticles. <i>ACS Sustainable Chemistry and Engineering</i> , 2018, 6, 9966-9978.	6.7	72
48	Functional nanomaterials through esterification of cellulose: a review of chemistry and application. <i>Cellulose</i> , 2018, 25, 3703-3731.	4.9	160
49	A Comparative Study of Self-Assembled Superstructures from Cellulose Stearoyl Ester and Poly(Vinyl Tj ETQq1 1 0,784314,rgBT /O 2,2 5	10.2	10
50	Structural, mechanical, and thermal properties of 3D printed Lâ€CNC/acrylonitrile butadiene styrene nanocomposites. <i>Journal of Applied Polymer Science</i> , 2017, 134, 45082.	2.6	26
51	Lignin-coated cellulose nanocrystal filled methacrylate composites prepared via 3D stereolithography printing: Mechanical reinforcement and thermal stabilization. <i>Carbohydrate Polymers</i> , 2017, 169, 272-281.	10.2	89
52	Improved Acetylation Efficacy of Wood Fibers by Ionic Liquid Pretreatment. <i>BioResources</i> , 2016, 12, .	1.0	2
53	Rheological behavior and mechanical properties of wood flour/high density polyethylene blends: Effects of esterification of wood with citric acid. <i>Polymer Composites</i> , 2016, 37, 553-560.	4.6	17
54	Thermal degradation and flammability behavior of fire-retarded wood flour/polypropylene composites. <i>Journal of Fire Sciences</i> , 2016, 34, 226-239.	2.0	11

#	ARTICLE	IF	CITATIONS
55	Thermo-oxidative decomposition and combustion behavior of Scots pine (<i>Pinus sylvestris</i> L.) sapwood modified with phenol- and melamine-formaldehyde resins. <i>Wood Science and Technology</i> , 2016, 50, 1125-1143.	3.2	23
56	Combustion behavior of Scots pine (<i>Pinus sylvestris</i> L.) sapwood treated with a dispersion of aluminum oxychloride-modified silica. <i>Holzforschung</i> , 2016, 70, 1165-1173.	1.9	16
57	Incorporation effect of enzymatic hydrolysis lignin on the mechanical and rheological properties of the resulting wood flour/high density polyethylene composites. <i>Polymer Composites</i> , 2016, 37, 379-384.	4.6	5
58	Thermal degradation and flammability properties of multilayer structured wood fiber and polypropylene composites with fire retardants. <i>RSC Advances</i> , 2016, 6, 13890-13897.	3.6	21
59	Thermal decomposition of fire-retarded wood flour/polypropylene composites. <i>Journal of Thermal Analysis and Calorimetry</i> , 2016, 123, 309-318.	3.6	28
60	Modification of poplar wood with glucose crosslinked with citric acid and 1,3-dimethylol-4,5-dihydroxy ethyleneurea. <i>Holzforschung</i> , 2016, 70, 47-53.	1.9	25
61	Coupling pattern and efficacy of organofunctional silanes in wood flour-filled polypropylene or polyethylene composites. <i>Journal of Composite Materials</i> , 2015, 49, 677-684.	2.4	13
62	Material pocket dynamic mechanical analysis: a novel tool to study thermal transition in wood fibers plasticized by an ionic liquid (IL). <i>Holzforschung</i> , 2015, 69, 223-232.	1.9	11
63	Degradation of chemically modified Scots pine (<i>Pinus sylvestris</i> L.) with Fenton reagent. <i>Holzforschung</i> , 2015, 69, 153-161.	1.9	13
64	Impact of Dmdheu Resin Treatment on the Mechanical Properties of Poplar. <i>Polymers and Polymer Composites</i> , 2014, 22, 669-674.	1.9	14
65	Thermoplastic deformation of poplar wood plasticized by ionic liquids measured by a nonisothermal compression technique. <i>Holzforschung</i> , 2014, 68, 555-566.	1.9	28
66	Thermal, crystallization, and dynamic rheological behavior of wood particle/HDPE composites: Effect of removal of wood cell wall composition. <i>Journal of Applied Polymer Science</i> , 2014, 131, .	2.6	14
67	Esterification of wood with citric acid: The catalytic effects of sodium hypophosphite (SHP). <i>Holzforschung</i> , 2014, 68, 427-433.	1.9	47
68	Combustion behavior of oak wood (<i>Quercus mongolica</i> L.) modified by 1,3-dimethylol-4,5-dihydroxyethyleneurea (DMDHEU). <i>Holzforschung</i> , 2014, 68, 881-887.	1.9	19
69	The water vapour sorption behaviour of acetylated birch wood: how acetylation affects the sorption isotherm and accessible hydroxyl content. <i>Journal of Materials Science</i> , 2014, 49, 2362-2371.	3.7	108
70	Morphology, mechanical properties, and dimensional stability of wood particle/high density polyethylene composites: Effect of removal of wood cell wall composition. <i>Materials & Design</i> , 2014, 58, 339-345.	5.1	97
71	Effects of ionic liquid on the rheological properties of wood flour/high density polyethylene composites. <i>Composites Part A: Applied Science and Manufacturing</i> , 2014, 61, 134-140.	7.6	34
72	Effects of use of coupling agents on the properties of microfibrillar composite based on high-density polyethylene and polyamide-6. <i>Polymer Bulletin</i> , 2014, 71, 685-703.	3.3	18

#	ARTICLE	IF	CITATIONS
73	Effect of wood cell wall composition on the rheological properties of wood particle/high density polyethylene composites. <i>Composites Science and Technology</i> , 2014, 93, 68-75.	7.8	84
74	Effects of chemical modification of wood flour on the rheological properties of high-density polyethylene blends. <i>Journal of Applied Polymer Science</i> , 2014, 131, .	2.6	9
75	Fire performance of oak wood modified with N-methylol resin and methylolated guanylurea phosphate/boric acid-based fire retardant. <i>Construction and Building Materials</i> , 2014, 72, 1-6.	7.2	39
76	Wood Protection with Dimethyloldihydroxy-Ethyleneurea and Its Derivatives. <i>ACS Symposium Series</i> , 2014, , 287-299.	0.5	4
77	Impacts of freezing and thermal treatments on dimensional and mechanical properties of wood flour-HDPE composite. <i>Journal of Forestry Research</i> , 2013, 24, 143-147.	3.6	9
78	Reinforcing effects of modified Kevlar® fiber on the mechanical properties of wood-flour/polypropylene composites. <i>Journal of Forestry Research</i> , 2013, 24, 149-153.	3.6	15
79	Effects of chemical modification on the mechanical properties of wood. <i>European Journal of Wood and Wood Products</i> , 2013, 71, 401-416.	2.9	126
80	Effects of hydrophobation treatments of wood particles with an amino alkylsiloxane co-oligomer on properties of the ensuing polypropylene composites. <i>Composites Part A: Applied Science and Manufacturing</i> , 2013, 44, 32-39.	7.6	20
81	The fungal resistance of wood modified with glutaraldehyde. <i>Holzforschung</i> , 2012, 66, 237-243.	1.9	20
82	Degradation of wood veneers by Fenton reagents: Effects of 2,3-dihydroxybenzoic acid on mineralization of wood. <i>Polymer Degradation and Stability</i> , 2012, 97, 1270-1277.	5.8	8
83	Grafting effects of polypropylene/polyethylene blends with maleic anhydride on the properties of the resulting wood-plastic composites. <i>Composites Part A: Applied Science and Manufacturing</i> , 2012, 43, 150-157.	7.6	123
84	Isothermal crystallization kinetics of Kevlar fiber-reinforced wood flour/high-density polyethylene composites. <i>Journal of Applied Polymer Science</i> , 2012, 126, E2.	2.6	8
85	Solid biopolymer electrolytes based on all-cellulose composites prepared by partially dissolving cellulosic fibers in the ionic liquid 1-butyl-3-methylimidazolium chloride. <i>Journal of Materials Science</i> , 2012, 47, 5978-5986.	3.7	34
86	Effects of chemical modification with glutaraldehyde on the weathering performance of Scots pine sapwood. <i>Wood Science and Technology</i> , 2012, 46, 749-767.	3.2	21
87	Study of Vinyltrimethoxysilane Modified Wood Flour/HDPE Composites. <i>Advanced Materials Research</i> , 2011, 183-185, 2148-2153.	0.3	0
88	The dynamic water vapour sorption behaviour of natural fibres and kinetic analysis using the parallel exponential kinetics model. <i>Journal of Materials Science</i> , 2011, 46, 479-489.	3.7	102
89	The dynamic water vapour sorption properties of natural fibres and viscoelastic behaviour of the cell wall: is there a link between sorption kinetics and hysteresis?. <i>Journal of Materials Science</i> , 2011, 46, 3738-3748.	3.7	26
90	The water vapour sorption behaviour of three celluloses: analysis using parallel exponential kinetics and interpretation using the Kelvin-Voigt viscoelastic model. <i>Cellulose</i> , 2011, 18, 517-530.	4.9	57

#	ARTICLE	IF	CITATIONS
91	Distribution of blue stain in untreated and DMDHEU treated Scots pine sapwood panels after six years of outdoor weathering. <i>European Journal of Wood and Wood Products</i> , 2011, 69, 333-336.	2.9	6
92	Dynamic water vapour sorption properties of wood treated with glutaraldehyde. <i>Wood Science and Technology</i> , 2011, 45, 49-61.	3.2	66
93	Water vapor sorption kinetics of wood modified with glutaraldehyde. <i>Journal of Applied Polymer Science</i> , 2010, 117, 1674-1682.	2.6	23
94	Effects of chemical modification of wood particles with glutaraldehyde and 1,3-dimethylol-4,5-dihydroxyethyleneurea on properties of the resulting polypropylene composites. <i>Composites Science and Technology</i> , 2010, 70, 2003-2011.	7.8	67
95	Effects of Geometrical Shapes of Wood Particles on the Mechanical and Water-Uptake Properties of the Resulting Wood/High Density Polyethylene Composites. <i>Advanced Materials Research</i> , 2010, 113-116, 674-678.	0.3	1
96	Effects of modification with glutaraldehyde on the mechanical properties of wood. <i>Holzforschung</i> , 2010, 64, .	1.9	13
97	Effect of glutaraldehyde on water related properties of solid wood. <i>Holzforschung</i> , 2010, 64, .	1.9	28
98	Analysis of water vapour sorption of oleo-thermal modified wood of <i>Acacia mangium</i> and <i>Endospermum malaccense</i> by a parallel exponential kinetics model and according to the Hailwood-Horrobin model. <i>Holzforschung</i> , 2010, 64, .	1.9	31
99	Degradation of wood veneers by Fenton's reagents: Effects of wood constituents and low molecular weight phenolic compounds on hydrogen peroxide decomposition and wood tensile strength loss. <i>Holzforschung</i> , 2010, 64, .	1.9	18
100	Silane coupling agents used for natural fiber/polymer composites: A review. <i>Composites Part A: Applied Science and Manufacturing</i> , 2010, 41, 806-819.	7.6	1,677
101	Analysis of the water vapour sorption isotherms of thermally modified acacia and sesendok. <i>Wood Material Science and Engineering</i> , 2010, 5, 194-203.	2.3	56
102	Weathering of uncoated and coated wood treated with methylated 1,3-dimethylol-4,5-dihydroxyethyleneurea (mDMDHEU). <i>European Journal of Wood and Wood Products</i> , 2008, 66, 455-464.	2.9	46
103	Effect of treatments with 1,3-dimethylol-4,5-dihydroxy-ethyleneurea (DMDHEU) on the tensile properties of wood. <i>Holzforschung</i> , 2007, 61, 43-50.	1.9	64
104	Coating performance of finishes on wood modified with an N-methylol compound. <i>Progress in Organic Coatings</i> , 2006, 57, 291-300.	3.9	32
105	Weathering of wood modified with the N-methylol compound 1,3-dimethylol-4,5-dihydroxyethyleneurea. <i>Polymer Degradation and Stability</i> , 2005, 89, 189-199.	5.8	86