

# Peter E Andersen

## List of Publications by Year in Descending Order

**Source:** <https://exaly.com/author-pdf/3896424/peter-e-andersen-publications-by-year.pdf>

**Version:** 2024-04-29

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

117  
papers

1,969  
citations

23  
h-index

40  
g-index

175  
ext. papers

2,422  
ext. citations

3.5  
avg, IF

4.42  
L-index

#	Paper	IF	Citations
117	360 optoacoustic capsule endoscopy at 50 Hz for esophageal imaging.. <i>Photoacoustics</i> , <b>2022</b> , 25, 1003339		0
116	Pedestal High-Contrast Gratings for Biosensing. <i>Nanomaterials</i> , <b>2022</b> , 12, 1748	5.4	
115	Guided-mode resonance on pedestal and half-buried high-contrast gratings for biosensing applications. <i>Nanophotonics</i> , <b>2021</b> ,	6.3	5
114	Selecting optimal spectral bands for improved detection of autofluorescent biomarkers in multiphoton microscopy. <i>Journal of Biomedical Optics</i> , <b>2020</b> , 25, 1-13	3.5	9
113	Morpho-molecular ex vivo detection and grading of non-muscle-invasive bladder cancer using forward imaging probe based multimodal optical coherence tomography and Raman spectroscopy. <i>Analyst, The</i> , <b>2020</b> , 145, 1445-1456	5	13
112	Optical Radiomic Signatures Derived from Optical Coherence Tomography Images Improve Identification of Melanoma. <i>Cancer Research</i> , <b>2019</b> , 79, 2021-2030	10.1	62
111	2.7 W diffraction-limited yellow lasers by efficient frequency doubling of high-brightness tapered diode lasers. <i>Optics Communications</i> , <b>2019</b> , 435, 145-149	2	6
110	Intensity Noise Transfer Through a Diode-Pumped Titanium Sapphire Laser System. <i>IEEE Journal of Quantum Electronics</i> , <b>2018</b> , 54, 1-9	2	15
109	MCmatlab: an open-source, user-friendly, MATLAB-integrated three-dimensional Monte Carlo light transport solver with heat diffusion and tissue damage. <i>Journal of Biomedical Optics</i> , <b>2018</b> , 23, 1-6	3.5	28
108	Efficient generation of 3.5 W laser light at 515 nm by frequency doubling a single-frequency high power DBR tapered diode laser. <i>Optics Communications</i> , <b>2017</b> , 392, 167-170	2	5
107	Integrated single- and two-photon light sheet microscopy using accelerating beams. <i>Scientific Reports</i> , <b>2017</b> , 7, 1435	4.9	22
106	Epi-detecting label-free multimodal imaging platform using a compact diode-pumped femtosecond solid-state laser. <i>Journal of Biomedical Optics</i> , <b>2017</b> , 22, 1	3.5	7
105	Multi-photon microscope driven by novel green laser pump <b>2016</b> ,		1
104	Efficient generation of 509 nm light by sum-frequency mixing between two tapered diode lasers. <i>Optics Communications</i> , <b>2015</b> , 339, 137-140	2	9
103	Computationally effective solution of the inverse problem in time-of-flight spectroscopy. <i>Optics Express</i> , <b>2015</b> , 23, 6937-45	3.3	6
102	Concept for power scaling second harmonic generation using a cascade of nonlinear crystals. <i>Optics Express</i> , <b>2015</b> , 23, 15921-34	3.3	21
101	Sensitivity analysis for oblique incidence reflectometry using Monte Carlo simulations. <i>Applied Optics</i> , <b>2015</b> , 54, 7099-105	0.2	6

100	Non-invasive assessment of dairy products using spatially resolved diffuse reflectance spectroscopy. <i>Applied Spectroscopy</i> , <b>2015</b> , 69, 1096-105	3.1	18
99	Multiphoton imaging with a novel compact diode-pumped Ti:sapphire oscillator. <i>Microscopy Research and Technique</i> , <b>2015</b> , 78, 1154-8	2.8	6
98	Highly efficient single-pass sum frequency generation by cascaded nonlinear crystals. <i>Optics Letters</i> , <b>2015</b> , 40, 5526-9	3	11
97	Transmission near-infrared (NIR) and photon time-of-flight (PTOF) spectroscopy in a comparative analysis of pharmaceuticals. <i>Applied Spectroscopy</i> , <b>2015</b> , 69, 389-97	3.1	6
96	Modeling Light-Tissue Interaction in Optical Coherence Tomography Systems <b>2015</b> , 95-140		
95	Power Scaling of Nonlinear Frequency Converted Tapered Diode Lasers for Biophotonics. <i>IEEE Journal of Selected Topics in Quantum Electronics</i> , <b>2014</b> , 20, 307-321	3.8	10
94	Generation of 3.5 W of diffraction-limited green light from SHG of a single tapered diode laser in a cascade of nonlinear crystals <b>2014</b> ,		1
93	Deep tissue optical imaging of upconverting nanoparticles enabled by exploiting higher intrinsic quantum yield through use of millisecond single pulse excitation with high peak power. <i>Nanoscale</i> , <b>2013</b> , 5, 10034-40	7.7	51
92	Diode laser based light sources for biomedical applications. <i>Laser and Photonics Reviews</i> , <b>2013</b> , 7, 605-628.	3	39
91	Optical Coherence Tomography: Advanced Modeling <b>2013</b> , 743-798		
90	Retinal polarization-sensitive optical coherence tomography at 1060 nm with 350 kHz A-scan rate using an Fourier domain mode locked laser. <i>Journal of Biomedical Optics</i> , <b>2013</b> , 18, 26008	3.5	19
89	Simultaneous dual wavelength eye-tracked ultrahigh resolution retinal and choroidal optical coherence tomography. <i>Optics Letters</i> , <b>2013</b> , 38, 4312-5	3	14
88	Frequency-doubled diode laser for direct pumping of Ti:sapphire lasers <b>2012</b> ,		1
87	Investigation of the impact of water absorption on retinal OCT imaging in the 1060 nm range. <i>Biomedical Optics Express</i> , <b>2012</b> , 3, 1620-31	3.5	10
86	Efficient concept for generation of diffraction-limited green light by sum-frequency generation of spectrally combined tapered diode lasers. <i>Optics Letters</i> , <b>2012</b> , 37, 3753-5	3	14
85	High-speed polarization-sensitive OCT at 1060 nm using a Fourier domain mode-locked swept source <b>2012</b> ,		1
84	Special section guest editorial: selected topics in biophotonics: optical coherence tomography and medical imaging using diffuse optics. <i>Journal of Biomedical Optics</i> , <b>2012</b> , 17, 071301	3.5	
83	Broadband Fourier domain mode-locked laser for optical coherence tomography at 1060 nm <b>2012</b> ,		6

82	16 W output power by high-efficient spectral beam combining of DBR-tapered diode lasers. <i>Optics Express</i> , <b>2011</b> , 19, 1228-35	3-3	22
81	Frequency-doubled DBR-tapered diode laser for direct pumping of Ti:sapphire lasers generating sub-20 fs pulses. <i>Optics Express</i> , <b>2011</b> , 19, 12156-63	3-3	25
80	Supercontinuum generation for coherent anti-Stokes Raman scattering microscopy with photonic crystal fibers. <i>Optics Express</i> , <b>2011</b> , 19, 26672-83	3-3	19
79	Experimental investigation of relative timing jitter in passively synchronized Q-switched lasers. <i>Optics Letters</i> , <b>2011</b> , 36, 415-7	3	7
78	Optical coherence tomography-current technology and applications in clinical and biomedical research. <i>Analytical and Bioanalytical Chemistry</i> , <b>2011</b> , 400, 2699-720	4-4	57
77	How histological features of basal cell carcinomas influence image quality in optical coherence tomography. <i>Journal of Biophotonics</i> , <b>2011</b> , 4, 544-51	3-1	26
76	Drug quantification in turbid media by fluorescence imaging combined with light-absorption correction using white Monte Carlo simulations. <i>Journal of Biomedical Optics</i> , <b>2011</b> , 16, 066002	3-5	9
75	Physical limits of semiconductor laser operation: A time-resolved analysis of catastrophic optical damage. <i>Applied Physics Letters</i> , <b>2010</b> , 97, 021110	3-4	21
74	High-power FDML laser for swept source-OCT at 1060 nm <b>2010</b> ,		1
73	Fourier domain mode-locked swept source at 1050 nm based on a tapered amplifier. <i>Optics Express</i> , <b>2010</b> , 18, 15820-31	3-3	40
72	All passive synchronized Q-switching of a quasi-three-level and a four-level Nd:YAG laser. <i>Optics Express</i> , <b>2010</b> , 18, 23987-93	3-3	11
71	High-power green light generation by second harmonic generation of single-frequency tapered diode lasers <b>2010</b> ,		3
70	Efficient quasi-three-level Nd:YAG laser at 946nm pumped by a tunable external cavity tapered diode laser. <i>Optics Communications</i> , <b>2010</b> , 283, 4717-4721	2	2
69	OCT imaging of skin cancer and other dermatological diseases. <i>Journal of Biophotonics</i> , <b>2009</b> , 2, 442-51	3-1	128
68	Threshold for strong thermal dephasing in periodically poled KTP in external cavity frequency doubling. <i>Applied Physics B: Lasers and Optics</i> , <b>2009</b> , 96, 827-831	1-9	7
67	Catastrophic optical mirror damage in diode lasers monitored during single-pulse operation. <i>Applied Physics Letters</i> , <b>2009</b> , 94, 191101	3-4	21
66	Optical coherence tomography for imaging of skin and skin diseases. <i>Seminars in Cutaneous Medicine and Surgery</i> , <b>2009</b> , 28, 196-202	1-4	86
65	1.5 W green light generation by single-pass second harmonic generation of a single-frequency tapered diode laser. <i>Optics Express</i> , <b>2009</b> , 17, 6532-9	3-3	53

64	Frequency-swept laser light source at 1050 nm with higher bandwidth due to multiple semiconductor optical amplifiers in series <b>2009</b> ,		1
63	Broadband light generation at approximately 1300 nm through spectrally recoiled solitons and dispersive waves. <i>Optics Letters</i> , <b>2008</b> , 33, 621-3	3	19
62	High power 404 nm source based on second harmonic generation in PPKTP of a tapered external feedback diode laser. <i>Optics Express</i> , <b>2008</b> , 16, 2486-93	3.3	28
61	Optical Doppler tomography for monitoring vascularization during photodynamic therapy of skin cancer lesions <b>2008</b> ,		1
60	Optical Doppler tomography based on a field programmable gate array. <i>Biomedical Signal Processing and Control</i> , <b>2008</b> , 3, 102-106	4.9	2
59	Wavelength stabilization of extended-cavity tapered lasers with volume Bragg gratings. <i>Applied Physics B: Lasers and Optics</i> , <b>2008</b> , 91, 493-498	1.9	13
58	Imaging of cutaneous larva migrans by optical coherence tomography. <i>Travel Medicine and Infectious Disease</i> , <b>2007</b> , 5, 243-6	8.4	15
57	Semiconductor optical amplifier based swept wavelength source at 1060 nm using a scanning Fabry-Pérot filter and an YDFA-based booster amplifier. <i>Optics Communications</i> , <b>2007</b> , 271, 197-202	2	5
56	808 nm tapered diode lasers optimised for high output power and nearly diffraction-limited beam quality in pulse mode operation <b>2007</b> , 6456, 88		
55	Speckle reduction in optical coherence tomography images of human skin by a spatial diversity method <b>2007</b> , 6627, 128		3
54	Generation of more than 300 mW diffraction-limited light at 405 nm by second-harmonic generation of a tapered diode laser with external cavity feedback <b>2007</b> ,		1
53	The free NADH concentration is kept constant in plant mitochondria under different metabolic conditions. <i>Plant Cell</i> , <b>2006</b> , 18, 688-98	11.6	78
52	Highly sensitive biosensing based on interference from light scattering in capillary tubes. <i>Applied Physics Letters</i> , <b>2006</b> , 89, 151108	3.4	10
51	Near-diffraction-limited segmented broad area diode laser based on off-axis spectral beam combining. <i>Applied Physics B: Lasers and Optics</i> , <b>2006</b> , 83, 225-228	1.9	16
50	Guiding of laser modes based on self-pumped four-wave mixing in a semiconductor amplifier. <i>Optics Express</i> , <b>2005</b> , 13, 3340-7	3.3	3
49	Swept wavelength source in the 1 microm range. <i>Optics Express</i> , <b>2005</b> , 13, 4096-106	3.3	13
48	Tunable high-power narrow-linewidth semiconductor laser based on an external-cavity tapered amplifier. <i>Optics Express</i> , <b>2005</b> , 13, 10589-96	3.3	52
47	Infrared thermography and ultrasonography to indirectly monitor the influence of liner type and overmilking on teat tissue recovery. <i>Acta Veterinaria Scandinavica</i> , <b>2005</b> , 46, 137-47	2	35

46	Analysis of multiple scattering effects in optical Doppler tomography <b>2005</b> ,		1
45	Extraction of tissue optical properties from optical coherence tomography images for diagnostic purposes (Invited Paper) <b>2005</b> ,		5
44	An external-cavity laser diode at 635 nm for laser display applications. <i>Optics Communications</i> , <b>2005</b> , 245, 333-339	2	5
43	Second-harmonic generation of 405-nm light using periodically poled KTiOPO <sub>4</sub> pumped by external-cavity laser diode with double grating feedback. <i>Applied Physics B: Lasers and Optics</i> , <b>2005</b> , 80, 861-864	1.9	3
42	Optical Doppler coherence tomography based on a field-programmable gate array <b>2005</b> , 5690, 263		1
41	An experimental study of language intensity and response rate in e mail surveys. <i>Communication Reports</i> , <b>2004</b> , 17, 73-84	2	18
40	Advanced modelling of optical coherence tomography systems. <i>Physics in Medicine and Biology</i> , <b>2004</b> , 49, 1307-27	3.8	28
39	Determination of optical scattering properties of highly-scattering media in optical coherence tomography images. <i>Optics Express</i> , <b>2004</b> , 12, 249-59	3.3	152
38	Improvement of spatial and temporal coherence of a broad area laser diode using an external-cavity design with double grating feedback. <i>Optics Express</i> , <b>2004</b> , 12, 609-16	3.3	12
37	Extraction of optical scattering parameters and attenuation compensation in optical coherence tomography images of multilayered tissue structures. <i>Optics Letters</i> , <b>2004</b> , 29, 1641-3	3	41
36	Quantitative distinction between bound and free NADH in biological systems <b>2004</b> ,		1
35	Optical Coherence Tomography: Advanced Modeling <b>2004</b> , 594-651		1
34	Assessing blood vessel abnormality via extracting scattering coefficients from OCT images <b>2003</b> , 5140, 12		5
33	Modeling the optical coherence tomography geometry using the extended Huygens-Fresnel principle and Monte Carlo simulations <b>2003</b> , 5068, 170		
32	Improvement of brightness and output power of high-power laser diodes in the visible spectral region. <i>Optics Communications</i> , <b>2003</b> , 219, 369-375	2	5
31	Absolute refractive index determination by microinterferometric backscatter detection. <i>Analytical Chemistry</i> , <b>2003</b> , 75, 1946-53	7.8	25
30	Spatial frequency mixing by nonlinear charge transport in photorefractive materials. <i>Physical Review B</i> , <b>2002</b> , 65,	3.3	3
29	Fourier transform infrared spectroscopy of aqueous solutions using optical subtraction <b>2002</b> ,		1

28	True-reflection OCT imaging <b>2002</b> , 4619, 36		4
27	Derivation of a Monte Carlo method for modeling heterodyne detection in optical coherence tomography systems. <i>Applied Optics</i> , <b>2002</b> , 41, 6676-91	1.7	42
26	Optical coherence tomography: new analytical model and the shower curtain effect <b>2000</b> ,		3
25	Calculation of the maximum obtainable probing depth of optical coherence tomography in tissue <b>2000</b> ,		6
24	Modeling the optical coherence tomography geometry using the extended Huygens-Fresnel principle and Monte Carlo simulations <b>2000</b> ,		3
23	Nonlinear cross talk between gratings recorded in BaTiO <sub>3</sub> by mutually incoherent beam pairs. <i>Journal of Applied Physics</i> , <b>2000</b> , 88, 5527-5533	2.5	3
22	Analysis of optical coherence tomography systems based on the extended Huygens-Fresnel principle. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , <b>2000</b> , 17, 484-90	1.8	157
21	Closed-form solution for the Wigner phase-space distribution function for diffuse reflection and small-angle scattering in a random medium. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , <b>2000</b> , 17, 2464-74	1.8	17
20	Nonlinear grating interactions in multibeam photorefractive recording: theoretical investigation. <i>Journal of the Optical Society of America B: Optical Physics</i> , <b>1999</b> , 16, 414	1.7	4
19	Photoacoustic imaging of buried objects using an all-optical detection scheme <b>1999</b> , 3601, 303		
18	Determination of tissue optical properties from diffuse reflectance profiles by multivariate calibration. <i>Applied Optics</i> , <b>1998</b> , 37, 772-8	1.7	35
17	Kinetics of higher-order combinational gratings in photorefractive media: diffusion regime. <i>Journal of the Optical Society of America B: Optical Physics</i> , <b>1998</b> , 15, 2032	1.7	4
16	Noncontact detection of laser-induced acoustic waves from buried absorbing objects using a dual-beam common-path interferometer <b>1998</b> , 3254, 307		4
15	Local diffuse reflectance from three-layered skin tissue structures <b>1997</b> , 2979, 515		2
14	Theory of nonlinear multiple-grating interaction in diffusion-dominated photorefractive media: errata. <i>Journal of the Optical Society of America B: Optical Physics</i> , <b>1997</b> , 14, 989	1.7	
13	Spectral dependence of cross-talk between photorefractive gratings in Bi <sub>12</sub> SiO <sub>20</sub> in diffusion regime. <i>Applied Physics B: Lasers and Optics</i> , <b>1997</b> , 65, 523-526	1.9	3
12	Theory of nonlinear multiple-grating interaction in diffusion-dominated photorefractive media. <i>Journal of the Optical Society of America B: Optical Physics</i> , <b>1996</b> , 13, 2569	1.7	7
11	Strong coupling between coherent gratings due to nonlinear spatial frequency mixing in Bi <sub>12</sub> SiO <sub>20</sub> . <i>Optics Communications</i> , <b>1996</b> , 128, 185-192	2	6

10	Nonlinear grating interaction in photorefractive Bi <sub>12</sub> SiO <sub>20</sub> . <i>Applied Physics Letters</i> , <b>1995</b> , 66, 792-794	3.4	10
9	Photorefractive devices. <i>Ferroelectrics</i> , <b>1995</b> , 174, 149-183	0.6	7
8	Observation of spontaneously frequency-shifted beam fanning in photorefractive Bi <sub>12</sub> SiO <sub>20</sub> . <i>Optics Letters</i> , <b>1995</b> , 20, 2475	3	7
7	Nonlinear combinations of gratings in Bi <sub>12</sub> SiO <sub>20</sub> : theory and experiments. <i>Journal of the Optical Society of America B: Optical Physics</i> , <b>1995</b> , 12, 1422	1.7	23
6	Nonlinear combinations of gratings in drift-dominated recording in Bi <sub>12</sub> SiO <sub>20</sub> . <i>Journal of the Optical Society of America B: Optical Physics</i> , <b>1995</b> , 12, 2453	1.7	11
5	Fundamental Properties of Nonlinear Combinations of Gratings in Bi <sub>12</sub> SiO <sub>20</sub> and Their Applications. <i>Journal of Optics (India)</i> , <b>1995</b> , 24, 185-225	1.3	
4	Crosstalk in dynamic optical interconnects in photorefractive crystals. <i>Applied Physics Letters</i> , <b>1994</b> , 65, 271-273	3.4	12
3	Noise-free holographic storage in iron-doped lithium niobate crystals. <i>Optics Letters</i> , <b>1994</b> , 19, 1583-5	3	5
2	Polarization properties of a photorefractive Bi <sub>12</sub> /SiO <sub>20</sub> crystal and their application in an optical correlator. <i>IEEE Journal of Quantum Electronics</i> , <b>1994</b> , 30, 1075-1089	2	6
1	Photorefractive particle image velocimetry: performance enhancement with bismuth silicon oxide crystals. <i>Optics Letters</i> , <b>1992</b> , 17, 619-21	3	7