

List of Publications by Year in  
Descending Order

**Source:** <https://exaly.com/author-pdf/4194067/bo-wei-publications-by-year.pdf>  
**Version:** 2024-04-10

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.  
The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

147 papers	3,439 citations	34 h-index	50 g-index
153 ext. papers	3,929 ext. citations	5.3 avg, IF	5.24 L-index

#	Paper	IF	Citations
147	In situ unraveling surface reconstruction of Ni <sub>5</sub> P <sub>4</sub> @FeP nanosheet array for superior alkaline oxygen evolution reaction. <i>Applied Catalysis B: Environmental</i> , <b>2022</b> , 305, 121033	21.8	6
146	Operando capturing of surface self-reconstruction of Ni <sub>3</sub> S <sub>2</sub> /FeNi <sub>2</sub> S <sub>4</sub> hybrid nanosheet array for overall water splitting. <i>Chemical Engineering Journal</i> , <b>2022</b> , 427, 131944	14.7	26
145	Synergistically improving electrocatalytic performance and CO <sub>2</sub> tolerance of Fe-based cathode catalysts for solid oxide fuel cells. <i>Energy</i> , <b>2022</b> , 124050	7.9	1
144	A SrCo <sub>0.9</sub> Ta <sub>0.1</sub> O <sub>3-δ</sub> -derived medium-entropy cathode with superior CO <sub>2</sub> poisoning tolerance for solid oxide fuel cells. <i>Journal of Power Sources</i> , <b>2022</b> , 540, 231661	8.9	0
143	In-situ probing the rapid reconstruction of FeOOH-decorated NiMoO <sub>4</sub> nanowires with boosted oxygen evolution activity. <i>Materials Today Energy</i> , <b>2021</b> , 23, 100887	7	4
142	A cobalt-free bismuth ferrite-based cathode for intermediate temperature solid oxide fuel cells. <i>Electrochemistry Communications</i> , <b>2021</b> , 125, 106978	5.1	8
141	In-situ self-reconstruction of Ni <sub>2</sub> BeAl hybrid phosphides nanosheet arrays enables efficient oxygen evolution in alkaline. <i>International Journal of Hydrogen Energy</i> , <b>2021</b> , 46, 25070-25080	6.7	8
140	In Situ Synthesis of FeO/FeO Heterojunction Photoanode via Fast Flame Annealing for Enhanced Charge Separation and Water Oxidation. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2021</b> , 13, 4785-4795	9.5	13
139	The electronic properties and structural stability of LaFeO <sub>3</sub> oxide by niobium doping: A density functional theory study. <i>International Journal of Hydrogen Energy</i> , <b>2021</b> , 46, 9193-9198	6.7	2
138	Efficient use of waste carton for power generation, tar and fertilizer through direct carbon solid oxide fuel cell. <i>Renewable Energy</i> , <b>2020</b> , 158, 410-420	8.1	12
137	Self-supported Reevesite Ni-Fe Layered Double Hydroxide Nanosheet Arrays for Efficient Water Oxidation. <i>ChemistrySelect</i> , <b>2020</b> , 5, 3062-3068	1.8	2
136	Novel cobalt-free layered perovskite LaBaFe <sub>2-x</sub> Nb <sub>x</sub> O <sub>6-δ</sub> (x=0.1) as cathode for solid oxide fuel cells. <i>Journal of Power Sources</i> , <b>2020</b> , 453, 227875	8.9	13
135	Self-supported phosphorus-doped CoMoO <sub>4</sub> rod bundles for efficient hydrogen evolution. <i>Journal of Materials Science</i> , <b>2020</b> , 55, 6502-6512	4.3	6
134	Investigations on sulfur poisoning mechanisms of a solid oxide fuel cell with niobium-doped ferrate perovskite anode. <i>Electrochimica Acta</i> , <b>2020</b> , 335, 135703	6.7	3
133	Self-supported Hierarchical Fe(PO <sub>3</sub> ) <sub>2</sub> @Cu <sub>3</sub> P nanotube arrays for efficient hydrogen evolution in alkaline media. <i>Journal of Alloys and Compounds</i> , <b>2020</b> , 820, 153185	5.7	10
132	Direct growth of Ni <sub>2</sub> Be phosphides nanohybrids on NiFe foam for highly efficient water oxidation. <i>Journal of Alloys and Compounds</i> , <b>2020</b> , 847, 156363	5.7	16
131	Heterostructural Ni <sub>3</sub> S <sub>2</sub> /Fe <sub>5</sub> Ni <sub>4</sub> S <sub>8</sub> hybrids for efficient electrocatalytic oxygen evolution. <i>Journal of Materials Science</i> , <b>2020</b> , 55, 15963-15974	4.3	3

130	Tailoring tantalum doping into a perovskite ferrite to obtain a highly active and stable anode for solid oxide fuel cells. <i>Journal of Materials Chemistry A</i> , <b>2020</b> , 8, 18778-18791	13	13
129	The electronic structure and the oxygen adsorption at BaO terminated surface of GdBaCo <sub>2</sub> O <sub>5.5</sub> : A first principles study. <i>Solid State Communications</i> , <b>2020</b> , 311, 113871	1.6	
128	The surface engineering of cobalt carbide spheres through N, B co-doping achieved by room-temperature in situ anchoring effects for active and durable multifunctional electrocatalysts. <i>Journal of Materials Chemistry A</i> , <b>2019</b> , 7, 14904-14915	13	53
127	Redox sculptured dual-scale porous nickel-iron foams for efficient water oxidation. <i>Electrochimica Acta</i> , <b>2019</b> , 309, 415-423	6.7	9
126	Mo-Doped Cobalt Phosphide Nanosheets for Efficient Hydrogen Generation in an Alkaline Media. <i>Energy Technology</i> , <b>2019</b> , 7, 1900021	3.5	13
125	Morphology evolution and exsolution mechanism of a partially decomposed anode for intermediate temperature-solid oxide fuel cells. <i>Electrochimica Acta</i> , <b>2019</b> , 304, 30-41	6.7	12
124	Effect of the angle between gas flow direction and electrode on single-chamber SOFC stacks. <i>Journal of Solid State Electrochemistry</i> , <b>2019</b> , 23, 1651-1657	2.6	3
123	Enhanced performance of a single-chamber solid oxide fuel cell with dual gas supply method. <i>Ionics</i> , <b>2019</b> , 25, 1281-1289	2.7	2
122	La <sub>1.7</sub> Sr <sub>0.3</sub> Co <sub>0.5</sub> Ni <sub>0.5</sub> O <sub>4+δ</sub> layered perovskite as an efficient bifunctional electrocatalyst for rechargeable zinc-air batteries. <i>Applied Surface Science</i> , <b>2019</b> , 464, 494-501	6.7	15
121	Surface Cation Segregation and Chromium Deposition on the Double-Perovskite Oxide PrBaCoO. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2018</b> , 10, 8621-8629	9.5	33
120	On the limiting factor of impregnation methods for developing Cu/CeO <sub>2</sub> anodes for solid oxide fuel cells. <i>Journal of Solid State Electrochemistry</i> , <b>2018</b> , 22, 1735-1743	2.6	7
119	Anodic polarization induced performance loss in GdBaCo <sub>2</sub> O <sub>5+δ</sub> oxygen electrode under solid oxide electrolysis cell conditions. <i>Journal of the European Ceramic Society</i> , <b>2018</b> , 38, 2396-2403	6	6
118	Cellular Structure Fabricated on Ni Wire by a Simple and Cost-Effective Direct-Flame Approach and Its Application in Fiber-Shaped Supercapacitors. <i>ChemSusChem</i> , <b>2018</b> , 11, 985-993	8.3	11
117	Niobium Doped Lanthanum Strontium Ferrite as A Redox-Stable and Sulfur-Tolerant Anode for Solid Oxide Fuel Cells. <i>ChemSusChem</i> , <b>2018</b> , 11, 254-263	8.3	43
116	High-performance and stable La <sub>0.8</sub> Sr <sub>0.2</sub> Fe <sub>0.9</sub> Nb <sub>0.1</sub> O <sub>3-δ</sub> anode for direct carbon solid oxide fuel cells fueled by activated carbon and corn straw derived carbon. <i>International Journal of Hydrogen Energy</i> , <b>2018</b> , 43, 12358-12367	6.7	25
115	Hierarchical Hollow Spheres Assembled with Ultrathin CoMn Double Hydroxide Nanosheets as Trifunctional Electrocatalyst for Overall Water Splitting and Zn Air Battery. <i>ACS Sustainable Chemistry and Engineering</i> , <b>2018</b> , 6, 14641-14651	8.3	34
114	In-situ reduction synthesis of La <sub>2</sub> O <sub>3</sub> /NiM-NCNTs (M = Fe, Co) as efficient bifunctional electrocatalysts for oxygen reduction and evolution reactions. <i>International Journal of Hydrogen Energy</i> , <b>2018</b> , 43, 21959-21968	6.7	7
113	A Highly Efficient and Robust Perovskite Anode with Iron-Palladium Co-exolutions for Intermediate-Temperature Solid-Oxide Fuel Cells. <i>ChemSusChem</i> , <b>2018</b> , 11, 2593-2603	8.3	21

112	Ag <sub>2</sub> O nanoparticles decorated hierarchical Bi <sub>2</sub> MoO <sub>6</sub> microspheres for efficient visible light photocatalysts. <i>Journal of Alloys and Compounds</i> , <b>2017</b> , 699, 783-787	5.7	18
111	Enhanced electrochemical performance of co-synthesized La <sub>2</sub> NiO <sub>4</sub> + $\lambda$ Ce <sub>0.55</sub> La <sub>0.45</sub> O <sub>2</sub> - $\lambda$ composite cathode for IT-SOFCs. <i>Journal of Alloys and Compounds</i> , <b>2017</b> , 705, 105-111	5.7	13
110	Performance degradation of double-perovskite PrBaCo <sub>2</sub> O <sub>5</sub> + $\lambda$ oxygen electrode in CO <sub>2</sub> containing atmospheres. <i>Applied Surface Science</i> , <b>2017</b> , 416, 649-655	6.7	17
109	Carbon dots/Cu <sub>2</sub> MoS <sub>4</sub> nanosheets hybrids with efficient photoelectrochemical performance. <i>Materials Letters</i> , <b>2017</b> , 197, 79-82	3.3	9
108	Strontium doped lanthanum manganite (LSM) effects on electrochemical performance of LSM/MnO <sub>2</sub> composites for supercapacitor. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2017</b> , 28, 17020-17025	2.1	7
107	A novel La <sub>2</sub> NiO <sub>4</sub> + $\lambda$ La <sub>3</sub> Ni <sub>2</sub> O <sub>7</sub> - $\lambda$ Ce <sub>0.55</sub> La <sub>0.45</sub> O <sub>2</sub> - $\lambda$ ternary composite cathode prepared by the co-synthesis method for IT-SOFCs. <i>International Journal of Hydrogen Energy</i> , <b>2017</b> , 42, 17202-17210	6.7	7
106	Ion Exchange Synthesis of Bi <sub>2</sub> MoO <sub>6</sub> /BiOI Heterojunctions for Photocatalytic Degradation and Photoelectrochemical Water Splitting. <i>Nano</i> , <b>2016</b> , 11, 1650095	1.1	10
105	Colored TiO <sub>2</sub> hollow spheres for efficient water-splitting photocatalysts. <i>RSC Advances</i> , <b>2016</b> , 6, 108969-108973	3.7	3
104	Investigation of a solid oxide fuel cells catalyst LaSrNiO <sub>4</sub> : Electronic structure, surface segregation, and oxygen adsorption. <i>International Journal of Hydrogen Energy</i> , <b>2016</b> , 41, 21497-21502	6.7	5
103	The comparative theoretical study of the LaBO <sub>3</sub> (001) (B = Mn, Fe, Co, and Ni) surface properties and oxygen adsorption mechanisms. <i>Ionics</i> , <b>2016</b> , 22, 1153-1158	2.7	6
102	Efficient electrolysis of CO <sub>2</sub> in symmetrical solid oxide electrolysis cell with highly active La <sub>0.3</sub> Sr <sub>0.7</sub> Fe <sub>0.7</sub> Ti <sub>0.3</sub> O <sub>3</sub> electrode material. <i>Electrochemistry Communications</i> , <b>2016</b> , 69, 80-83	5.1	69
101	Strontium doped lanthanum manganite/manganese dioxide composite electrode for supercapacitor with enhanced rate capability. <i>Electrochimica Acta</i> , <b>2016</b> , 222, 1585-1591	6.7	24
100	Multilayered MoS <sub>2</sub> coated TiO <sub>2</sub> hollow spheres for efficient photodegradation of phenol under visible light irradiation. <i>Materials Letters</i> , <b>2016</b> , 179, 42-46	3.3	30
99	Electrochemically Driven Deactivation and Recovery in PrBaCo <sub>2</sub> O <sub>5</sub> + $\lambda$ Oxygen Electrodes for Reversible Solid Oxide Fuel Cells. <i>ChemSusChem</i> , <b>2016</b> , 9, 2443-50	8.3	24
98	Chromium deposition and poisoning at La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3</sub> - $\lambda$ oxygen electrodes of solid oxide electrolysis cells. <i>Physical Chemistry Chemical Physics</i> , <b>2015</b> , 17, 1601-9	3.6	39
97	Nanosize $\lambda$ Bi <sub>2</sub> O <sub>3</sub> decorated Bi <sub>2</sub> MoO <sub>6</sub> via an alkali etching process for enhanced photocatalytic performance. <i>RSC Advances</i> , <b>2015</b> , 5, 12346-12353	3.7	36
96	Performance degradation of SmBaCo <sub>2</sub> O <sub>5</sub> + $\lambda$ cathode induced by chromium deposition for solid oxide fuel cells. <i>Electrochimica Acta</i> , <b>2015</b> , 174, 327-331	6.7	15
95	A preliminary study of the pseudo-capacitance features of strontium doped lanthanum manganite. <i>RSC Advances</i> , <b>2015</b> , 5, 5858-5862	3.7	35

94	Cr deposition on porous La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-δ</sub> electrodes of solid oxide cells under open circuit condition. <i>Solid State Ionics</i> , <b>2015</b> , 281, 29-37	3.3	22
93	Performance and stability of co-synthesized Sm <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> -Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> oxygen electrode for reversible solid oxide cells. <i>Electrochimica Acta</i> , <b>2015</b> , 180, 1085-1093	6.7	9
92	Performance and stability of co-synthesized Sm <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> -Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>1.9</sub> composite oxygen electrode for solid oxide electrolysis cells. <i>International Journal of Hydrogen Energy</i> , <b>2015</b> , 40, 561-567	6.7	15
91	La <sub>0.6</sub> PrSr <sub>0.4</sub> NiO <sub>4-δ</sub> -Ce <sub>0.8</sub> PrO <sub>2</sub> O <sub>2</sub> composite cathode for solid oxide fuel cell. <i>Materials Chemistry and Physics</i> , <b>2015</b> , 149-150, 617-621	4.4	4
90	Electronic structure and surface properties of PrMnO <sub>3</sub> (001): A density functional theory study. <i>Solid State Communications</i> , <b>2015</b> , 201, 31-35	1.6	9
89	Advanced Technologies for High-Temperature Solid Oxide Fuel Cells. <i>Electrochemical Energy Storage and Conversion</i> , <b>2015</b> , 307-337		
88	Generation of Oxygen Vacancy and OH Radicals: A Comparative Study of Bi <sub>2</sub> WO <sub>6</sub> and Bi <sub>2</sub> WO <sub>6-x</sub> Nanoplates. <i>ChemCatChem</i> , <b>2015</b> , 7, 4076-4084	5.2	83
87	Preparation and performance of solid oxide fuel cells with YSZ/SDC bilayer electrolyte. <i>Ceramics International</i> , <b>2015</b> , 41, 4410-4415	5.1	26
86	Investigation on a novel composite solid oxide fuel cell anode with La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-δ</sub> derived phases. <i>Electrochimica Acta</i> , <b>2015</b> , 160, 89-93	6.7	18
85	Facile synthesis of Bi <sub>2</sub> O <sub>3</sub> /Bi <sub>2</sub> O <sub>2</sub> CO <sub>3</sub> nanocomposite with high visible-light photocatalytic activity. <i>Materials Letters</i> , <b>2014</b> , 120, 1-4	3.3	39
84	Effect of temperature on the chromium deposition and poisoning of La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-δ</sub> cathodes of solid oxide fuel cells. <i>Electrochimica Acta</i> , <b>2014</b> , 139, 173-179	6.7	30
83	Functionally graded cathodes based on double perovskite type GdBaCo <sub>2</sub> O <sub>5+δ</sub> -oxide. <i>Electrochimica Acta</i> , <b>2014</b> , 134, 136-142	6.7	21
82	A rapid preparation of acicular Ni impregnated anode with enhanced conductivity and operational stability. <i>Journal of Power Sources</i> , <b>2014</b> , 256, 424-429	8.9	4
81	Co-synthesis of Sm <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> -Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> Composite Cathode with Enhanced Electrochemical Property for Intermediate Temperature SOFCs. <i>Fuel Cells</i> , <b>2014</b> , 14, 966-972	2.9	8
80	Sm <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> -Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> Composite Oxygen Electrodes for Solid Oxide Electrolysis Cells. <i>Fuel Cells</i> , <b>2014</b> , 14, 76-82	2.9	20
79	Enhanced photosensitization process induced by the p-n junction of Bi <sub>2</sub> O <sub>2</sub> CO <sub>3</sub> /BiOCl heterojunctions on the degradation of rhodamine B. <i>Applied Surface Science</i> , <b>2014</b> , 303, 360-366	6.7	129
78	Flowerlike C-doped BiOCl nanostructures: Facile wet chemical fabrication and enhanced UV photocatalytic properties. <i>Applied Surface Science</i> , <b>2013</b> , 284, 497-502	6.7	70
77	SmBaCo <sub>2</sub> O <sub>5+δ</sub> as High Efficient Oxygen Electrode of Solid Oxide Electrolysis Cells. <i>ECS Transactions</i> , <b>2013</b> , 57, 3189-3196	1	6

76	Flower-like ZnO-Ag <sub>2</sub> O composites: precipitation synthesis and photocatalytic activity. <i>Nanoscale Research Letters</i> , <b>2013</b> , 8, 536	5	44
75	Adsorption of Sulfur-Containing Species on LaCrO <sub>3</sub> (001) Surface: A First-Principles Study. <i>Fuel Cells</i> , <b>2013</b> , 13, 1040-1047	2.9	3
74	Effect of gas supply method on the performance of the single-chamber SOFC micro-stack and the single cells. <i>Journal of Solid State Electrochemistry</i> , <b>2013</b> , 17, 269-275	2.6	7
73	Redox Tolerance of Thin and Thick Ni/YSZ Anodes of Electrolyte-Supported Single-Chamber Solid Oxide Fuel Cells under Methane Oxidation Conditions. <i>Fuel Cells</i> , <b>2013</b> , 13, 1109-1115	2.9	7
72	Cation exchange synthesis of ZnS/Ag <sub>2</sub> S microspheric composites with enhanced photocatalytic activity. <i>Applied Surface Science</i> , <b>2013</b> , 270, 133-138	6.7	97
71	Enhanced density of sol-gel derived La <sub>0.8</sub> Sr <sub>0.2</sub> MnO <sub>3</sub> thin film with an electric field assisted deposition. <i>Materials Letters</i> , <b>2013</b> , 92, 192-194	3.3	2
70	The Effect of Adding Ce <sub>1-x</sub> Sm <sub>x</sub> O <sub>2-x/2</sub> with Different Sm Contents on the Electrochemical Performance of GdBaCo <sub>2</sub> O <sub>5+δ</sub> -Based Composite Cathode. <i>Fuel Cells</i> , <b>2013</b> , 13, 289-297	2.9	5
69	A direct flame solid oxide fuel cell for potential combined heat and power generation. <i>International Journal of Hydrogen Energy</i> , <b>2012</b> , 37, 8621-8629	6.7	35
68	Oxygen adsorption on the Ag/La <sub>1-x</sub> Sr <sub>x</sub> MnO <sub>3</sub> (001) catalysts surfaces: A first-principles study. <i>Journal of Power Sources</i> , <b>2012</b> , 209, 158-162	8.9	15
67	Structure, electrical and thermal properties of (Ba <sub>0.5</sub> Sr <sub>0.5</sub> ) <sub>1-x</sub> Gd <sub>x</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-δ</sub> perovskite as a solid-oxide fuel cell cathode. <i>Solid State Ionics</i> , <b>2012</b> , 207, 38-43	3.3	9
66	A Performance Study of Solid Oxide Fuel Cells With BaZr <sub>0.1</sub> Ce <sub>0.7</sub> Y <sub>0.2</sub> O <sub>3-δ</sub> Electrolyte Developed by Spray-Modified Pressing Method. <i>Fuel Cells</i> , <b>2012</b> , 12, 141-145	2.9	20
65	Study of a Single-Chamber Solid Oxide Fuel Cell Microstack with V-Shaped Congener-Electrode-Facing Configuration. <i>Fuel Cells</i> , <b>2012</b> , 12, 4-10	2.9	2
64	Enhanced Performance of Solid Oxide Fuel Cell by Manipulating the Orientation of Cylindrical Pores in Anode Substrate. <i>Fuel Cells</i> , <b>2012</b> , 12, 41-46	2.9	6
63	The Interaction of Noble Metal With La <sub>1-x</sub> Sr <sub>x</sub> MnO <sub>3</sub> (001) Surface and Catalytic Role for Oxygen Adsorption: A Density Functional Theory Study. <i>Fuel Cells</i> , <b>2012</b> , 12, 1048-1055	2.9	
62	Photocatalytic properties of hierarchical ZnO flowers synthesized by a sucrose-assisted hydrothermal method. <i>Applied Surface Science</i> , <b>2012</b> , 259, 557-561	6.7	22
61	Synthesis and characterization of La <sub>0.9</sub> Sr <sub>0.1</sub> Ga <sub>0.8</sub> Mg <sub>0.2</sub> O <sub>3-δ</sub> intermediate-temperature electrolyte using conventional solid state reaction. <i>Journal of Power Sources</i> , <b>2012</b> , 218, 233-236	8.9	13
60	Improved Electrodes/Electrolyte Interfaces for Solid Oxide Fuel Cell by Using Dual-Sized Powders in Electrolyte Slurry. <i>Fuel Cells</i> , <b>2012</b> , 12, 732-738	2.9	2
59	Performance evaluation of an anode-supported solid oxide fuel cell with Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>1.9</sub> impregnated GdBaCo <sub>2</sub> O <sub>5+δ</sub> -cathode. <i>International Journal of Hydrogen Energy</i> , <b>2012</b> , 37, 13491-13498	6.7	20



58	Ag <sub>2</sub> O/Bi <sub>2</sub> O <sub>3</sub> composites: synthesis, characterization and high efficient photocatalytic activities. <i>CrystEngComm</i> , <b>2012</b> , 14, 5705	3.3	42
57	Ba and Gd Doping Effect in (Ba <sub>x</sub> Sr <sub>1-x</sub> ) <sub>0.95</sub> Gd <sub>0.05</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\lambda</math></sub> (x = 0.10.9) Cathode on the Phase Structure and Electrochemical Performance. <i>Fuel Cells</i> , <b>2012</b> , 12, 633-641	2.9	3
56	Evaluation of a Non-sealed Solid Oxide Fuel Cell Stack with Cells Embedded in Plane Configuration. <i>Fuel Cells</i> , <b>2012</b> , 12, 523-529	2.9	4
55	Compaction pressure effect on microstructure and electrochemical performance of GdBaCo <sub>2</sub> O <sub>5</sub> + $\lambda$ cathode for IT-SOFCs. <i>Ceramics International</i> , <b>2012</b> , 38, 2159-2164	5.1	5
54	Evaluation of (Ba <sub>0.5</sub> Sr <sub>0.5</sub> ) <sub>0.85</sub> Gd <sub>0.15</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\lambda</math></sub> cathode for intermediate temperature solid oxide fuel cell. <i>Ceramics International</i> , <b>2012</b> , 38, 3039-3046	5.1	18
53	One-step hydrothermal synthesis and optical properties of aluminium doped ZnO hexagonal nanoplates on a zinc substrate. <i>CrystEngComm</i> , <b>2011</b> , 13, 1283-1286	3.3	41
52	GdBaCo <sub>2</sub> O <sub>5</sub> + $\lambda$ m <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> composite cathodes for intermediate temperature SOFCs. <i>Journal of Alloys and Compounds</i> , <b>2011</b> , 509, 3651-3655	5.7	26
51	Fabrication and performance test of solid oxide fuel cells with screen-printed yttria-stabilized zirconia electrolyte membranes. <i>Journal of Solid State Electrochemistry</i> , <b>2011</b> , 15, 2661-2665	2.6	6
50	A symmetrical solid oxide fuel cell prepared by dry-pressing and impregnating methods. <i>Journal of Power Sources</i> , <b>2011</b> , 196, 729-733	8.9	66
49	Paper-Fibres Used as a Pore-Former for Anode Substrate of Solid Oxide Fuel Cell. <i>Fuel Cells</i> , <b>2011</b> , 11, 172-177	2.9	14
48	Effect of adding urea on performance of Cu/CeO <sub>2</sub> /yttria-stabilized zirconia anodes for solid oxide fuel cells prepared by impregnation method. <i>Electrochimica Acta</i> , <b>2011</b> , 56, 2230-2236	6.7	20
47	Redox of Ni/YSZ anodes and oscillatory behavior in single-chamber SOFC under methane oxidation conditions. <i>Electrochimica Acta</i> , <b>2011</b> , 56, 6688-6695	6.7	26
46	A right-angular configuration for the single-chamber solid oxide fuel cell. <i>International Journal of Hydrogen Energy</i> , <b>2011</b> , 36, 3147-3152	6.7	3
45	Nanosized Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>1.9</sub> infiltrated GdBaCo <sub>2</sub> O <sub>5</sub> + $\lambda$ cathodes for intermediate-temperature solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , <b>2011</b> , 36, 6151-6159	6.7	35
44	A non-sealed solid oxide fuel cell micro-stack with two gas channels. <i>International Journal of Hydrogen Energy</i> , <b>2011</b> , 36, 7251-7256	6.7	8
43	Development of Single-Chamber Solid Oxide Fuel Cells: Performance Optimization and Micro-Stack Designs. <i>Ceramic Transactions</i> , <b>2010</b> , 173-177	0.1	1
42	Direct Flame SOFCs with La <sub>[sub 0.75]</sub> Sr <sub>[sub 0.25]</sub> Cr <sub>[sub 0.5]</sub> Mn <sub>[sub 0.5]</sub> O <sub>[sub 3-<math>\lambda</math></sub> Ni Coimpregnated Yttria-Stabilized Zirconia Anodes Operated on Liquefied Petroleum Gas Flame. <i>Journal of the Electrochemical Society</i> , <b>2010</b> , 157, B1838	3.9	15
41	A Configuration for Improving the Performance of Coplanar Single-Chamber Solid Oxide Fuel Cell. <i>Electrochemical and Solid-State Letters</i> , <b>2010</b> , 13, B14		10

40	Performance of the Single-Chamber Solid Oxide Fuel Cell with a $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Mn}_{0.5}\text{O}_{3-\delta}$ -Based Perovskite Anode. <i>Journal of the Electrochemical Society</i> , <b>2010</b> , 157, B691	3.9	8
39	Impregnated $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Fe}_{0.5}\text{O}_{3-\delta}$ -Based Anodes Operating on $\text{H}_2$ , $\text{CH}_4$ , and $\text{C}_2\text{H}_5\text{OH}$ Fuels. <i>Electrochemical and Solid-State Letters</i> , <b>2010</b> , 13, B91		10
38	Effects of the single chamber SOFC stack configuration on the performance of the single cells. <i>Solid State Ionics</i> , <b>2010</b> , 181, 939-942	3.3	9
37	Fabrication and performance of membrane solid oxide fuel cells with $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Mn}_{0.5}\text{O}_{3-\delta}$ impregnated anodes. <i>Journal of Power Sources</i> , <b>2010</b> , 195, 1793-1798	8.9	35
36	Performance of an annular solid-oxide fuel cell micro-stack array operating in single-chamber conditions. <i>Journal of Power Sources</i> , <b>2010</b> , 195, 4247-4251	8.9	5
35	Investigations on $\text{Pr}_{1.6}\text{Sr}_{0.4}\text{NiO}_{4-\delta}$ /YSZ/Ag composite cathode for solid oxide fuel cells. <i>Journal of Physics and Chemistry of Solids</i> , <b>2010</b> , 71, 230-234	3.9	5
34	Thermal expansion and electrochemical properties of Ni-doped $\text{GdBaCo}_2\text{O}_{5+\delta}$ -double-perovskite type oxides. <i>International Journal of Hydrogen Energy</i> , <b>2010</b> , 35, 3775-3782	6.7	45
33	Fabrication and evaluation of a $\text{Ni}/\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Fe}_{0.5}\text{O}_{3-\delta}$ -impregnated yttria-stabilized zirconia anode for single-chamber solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , <b>2010</b> , 35, 6897-6904	6.7	19
32	A comparison of $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Mn}_{0.5}\text{O}_{3-\delta}$ and Ni impregnated porous YSZ anodes fabricated in two different ways for SOFCs. <i>Electrochimica Acta</i> , <b>2010</b> , 55, 3932-3938	6.7	30
31	Novel polymer fibers prepared by electrospinning for use as the pore-former for the anode of solid oxide fuel cell. <i>Electrochimica Acta</i> , <b>2010</b> , 55, 5538-5544	6.7	31
30	High Temperature Electrical Relaxation Study of $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.2}\text{Fe}_{0.8}\text{O}_{3-\delta}/\text{Ce}_{0.9}\text{Gd}_{0.1}\text{O}_{1.95}$ Composite. <i>Wuji Cailiao Xuebao/Journal of Inorganic Materials</i> , <b>2010</b> , 25, 635-640	1	0
29	Ni/SDC Nanoparticles Modified $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Fe}_{0.5}\text{O}_{3-\delta}$ as Anodes for Solid Oxide Fuel Cells. <i>Electrochemical and Solid-State Letters</i> , <b>2009</b> , 12, B161		7
28	Effect of the Cell Distance on the Cathode in Single Chamber SOFC Short Stack. <i>Journal of the Electrochemical Society</i> , <b>2009</b> , 156, B1253	3.9	13
27	A Novel Cell-Array Design for Single Chamber SOFC Microstack. <i>Fuel Cells</i> , <b>2009</b> , 9, 717-721	2.9	15
26	Enhanced performance of solid oxide fuel cells with Ni/CeO <sub>2</sub> modified $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{0.5}\text{Mn}_{0.5}\text{O}_{3-\delta}$ anodes. <i>Journal of Power Sources</i> , <b>2009</b> , 190, 326-330	8.9	43
25	Study on impedance spectra of $\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ and $\text{Sm}_{0.2}\text{Ce}_{0.8}\text{O}_{1.9}$ -impregnated $\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ cathode in single chamber fuel cell condition. <i>Electrochimica Acta</i> , <b>2009</b> , 54, 4726-4730	6.7	11
24	NiO+YSZ anode substrate for screen-printing fabrication of YSZ electrolyte film in solid oxide fuel cell. <i>Journal of Physics and Chemistry of Solids</i> , <b>2009</b> , 70, 164-168	3.9	15
23	Preparation and characteristics of $\text{Pr}_{1.6}\text{Sr}_{0.4}\text{NiO}_{4-\delta}$ +YSZ as composite cathode of solid oxide fuel cells. <i>Journal of Physics and Chemistry of Solids</i> , <b>2009</b> , 70, 665-668	3.9	16



22	A novel design of single-chamber SOFC micro-stack operated in methane-oxygen mixture. <i>Electrochemistry Communications</i> , <b>2009</b> , 11, 347-350	5.1	27
21	Performances of Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.6</sub> Fe <sub>0.4</sub> O <sub>3-<math>\delta</math></sub> /Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>1.9</sub> composite cathode materials for IT-SOFC. <i>Journal of Alloys and Compounds</i> , <b>2008</b> , 448, 116-121	5.7	49
20	Characterization of GdBaCo <sub>2</sub> O <sub>5-<math>\delta</math></sub> cathode for IT-SOFCs. <i>Journal of Alloys and Compounds</i> , <b>2008</b> , 454, 274-279	5.7	84
19	Characteristics of NiO-YSZ anode based on NiO particles synthesized by the precipitation method. <i>Journal of Alloys and Compounds</i> , <b>2008</b> , 454, 447-453	5.7	30
18	Effects of sucrose concentration on morphology and luminescence performance of Gd <sub>2</sub> O <sub>3</sub> :Eu nanocrystals. <i>Journal of Alloys and Compounds</i> , <b>2008</b> , 460, 524-528	5.7	19
17	Study on Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> /Sm <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3-<math>\delta</math></sub> composite cathode materials for IT-SOFCs. <i>Journal of Alloys and Compounds</i> , <b>2008</b> , 465, 274-279	5.7	38
16	Synthesis, electrical and electrochemical properties of Ba <sub>0.5</sub> Sr <sub>0.5</sub> Zn <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-<math>\delta</math></sub> perovskite oxide for IT-SOFC cathode. <i>Journal of Power Sources</i> , <b>2008</b> , 176, 1-8	8.9	148
15	Oxygen pump method for leak rate testing of SiO <sub>2</sub> B <sub>2</sub> O <sub>3</sub> Al <sub>2</sub> O <sub>3</sub> BaO/BbO <sub>2</sub> ZnO glass sealant for SOFC. <i>Solid State Ionics</i> , <b>2008</b> , 179, 1286-1290	3.3	6
14	Novel in situ method (vacuum assisted electroless plating) modified porous cathode for solid oxide fuel cells. <i>Electrochemistry Communications</i> , <b>2008</b> , 10, 844-847	5.1	22
13	Electrical and thermal properties of (Ba <sub>0.5</sub> Sr <sub>0.5</sub> ) <sub>1-<math>x</math></sub> Sm <sub><math>x</math></sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> perovskite oxides. <i>Solid State Ionics</i> , <b>2007</b> , 178, 417-422	3.3	35
12	Thermal, electrical, and electrochemical properties of Lanthanum-doped Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> . <i>Journal of Physics and Chemistry of Solids</i> , <b>2007</b> , 68, 1707-1712	3.9	46
11	Ba <sub>0.5</sub> Sr <sub>0.5</sub> Zn <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-<math>\delta</math></sub> Perovskite Oxide as a Novel Cathode for Intermediate-Temperature Solid-Oxide Fuel Cells. <i>Journal of the American Ceramic Society</i> , <b>2007</b> , 90, 3364-3366	3.8	49
10	Enhanced performance of a single-chamber solid oxide fuel cell with an SDC-impregnated cathode. <i>Journal of Power Sources</i> , <b>2007</b> , 167, 58-63	8.9	34
9	Anode-Supported Micro-SOFC Stacks Operated under Single-Chamber Conditions. <i>Journal of the Electrochemical Society</i> , <b>2007</b> , 154, B588	3.9	22
8	Characteristics of a SiO <sub>2</sub> B <sub>2</sub> O <sub>3</sub> Al <sub>2</sub> O <sub>3</sub> BaCO <sub>3</sub> BbO <sub>2</sub> ZnO glass-ceramic sealant for SOFCs. <i>Journal of Alloys and Compounds</i> , <b>2007</b> , 432, 189-193	5.7	30
7	Electrochemical characteristics of Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> /Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> composite materials for low-temperature solid oxide fuel cell cathodes. <i>Materials Letters</i> , <b>2006</b> , 60, 3642-3646	3.3	28
6	Synthesis and luminescence of europium doped yttria nanophosphors via a sucrose-templated combustion method. <i>Nanotechnology</i> , <b>2006</b> , 17, 4327-4331	3.4	37
5	Fabrication and thermoelectric properties of highly textured NaCo <sub>2</sub> O <sub>4</sub> ceramic. <i>Journal of Alloys and Compounds</i> , <b>2006</b> , 407, 299-303	5.7	15

4	A study of $(\text{Ba}_{0.5}\text{Sr}_{0.5})_{1-x}\text{Sm}_x\text{Co}_{0.8}\text{Fe}_{0.2}\text{O}_{3-\delta}$ as a cathode material for IT-SOFCs. <i>Journal of Alloys and Compounds</i> , <b>2006</b> , 426, 408-414	5.7	57
3	Low temperature solid oxide fuel cells based on $\text{Sm}_{0.2}\text{Ce}_{0.8}\text{O}_{1.9}$ films fabricated by slurry spin coating. <i>Journal of Power Sources</i> , <b>2006</b> , 159, 637-640	8.9	53
2	Crystal structure, thermal expansion and electrical conductivity of perovskite oxides $\text{Ba}_x\text{Sr}_{1-x}\text{Co}_{0.8}\text{Fe}_{0.2}\text{O}_{3-\delta}$ ( $0.3 \leq x \leq 0.7$ ). <i>Journal of the European Ceramic Society</i> , <b>2006</b> , 26, 2827-2832	6	196
1	Thermal and Electrical Properties of New Cathode Material $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{Co}_{0.8}\text{Fe}_{0.2}\text{O}_{3-\delta}$ for Solid Oxide Fuel Cells. <i>Electrochemical and Solid-State Letters</i> , <b>2005</b> , 8, A428		123