

List of Publications by Citations

**Source:** <https://exaly.com/author-pdf/4212500/li-lu-publications-by-citations.pdf>  
**Version:** 2024-04-09

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.  
The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

|                    |                         |                |                 |
|--------------------|-------------------------|----------------|-----------------|
| 200<br>papers      | 7,523<br>citations      | 44<br>h-index  | 79<br>g-index   |
| 209<br>ext. papers | 8,789<br>ext. citations | 6.3<br>avg, IF | 6.43<br>L-index |

| #   | Paper  | IF   | Citations |
|-----|--|------|-----------|
| 200 | Review on solid electrolytes for all-solid-state lithium-ion batteries. <i>Journal of Power Sources</i> , <b>2018</b> , 389, 198-213   | 8.9  | 593       |
| 199 | The electrocapacitive properties of graphene oxide reduced by urea. <i>Energy and Environmental Science</i> , <b>2012</b> , 5, 6391-6399   | 35.4 | 410       |
| 198 | Nanoflaky MnO <sub>2</sub> /carbon nanotube nanocomposites as anode materials for lithium-ion batteries. <i>Journal of Materials Chemistry</i> , <b>2010</b> , 20, 6896  |      | 386       |
| 197 | Synthesis of porous hollow Fe <sub>3</sub> O <sub>4</sub> beads and their applications in lithium ion batteries. <i>Journal of Materials Chemistry</i> , <b>2012</b> , 22, 5006  |      | 215       |
| 196 | Anisotropic Co <sub>3</sub> O <sub>4</sub> porous nanocapsules toward high-capacity Li-ion batteries. <i>Journal of Materials Chemistry</i> , <b>2010</b> , 20, 1506   |      | 187       |
| 195 | A high-energy-density supercapacitor with graphene/MK-5 as the electrode and ionic liquid as the electrolyte. <i>Journal of Materials Chemistry A</i> , <b>2013</b> , 1, 2313  | 13   | 165       |
| 194 | Enhanced Multiferroic Properties and Valence Effect of Ru-Doped BiFeO <sub>3</sub> Thin Films. <i>Journal of Physical Chemistry C</i> , <b>2010</b> , 114, 6994-6998   | 3.8  | 162       |
| 193 | Harmonizing Energy and Power Density toward 2.7 V Asymmetric Aqueous Supercapacitor. <i>Advanced Energy Materials</i> , <b>2018</b> , 8, 1702630   | 21.8 | 158       |
| 192 | Fe <sub>3</sub> O <sub>4</sub> Nanoparticles Embedded in Uniform Mesoporous Carbon Spheres for Superior High-Rate Battery Applications. <i>Advanced Functional Materials</i> , <b>2014</b> , 24, 319-326   | 15.6 | 150       |
| 191 | High-energy density nonaqueous all redox flow lithium battery enabled with a polymeric membrane. <i>Science Advances</i> , <b>2015</b> , 1, e1500886   | 14.3 | 144       |
| 190 | Graphene-based surface modification on layered Li-rich cathode for high-performance Li-ion batteries. <i>Journal of Materials Chemistry A</i> , <b>2013</b> , 1, 9954  | 13   | 142       |
| 189 | Recent Progress in the Applications of Vanadium-Based Oxides on Energy Storage: from Low-Dimensional Nanomaterials Synthesis to 3D Micro/Nano-Structures and Free-Standing Electrodes Fabrication. <i>Advanced Energy Materials</i> , <b>2017</b> , 7, 1700547 | 21.8 | 117       |
| 188 | A Na(+) Superionic Conductor for Room-Temperature Sodium Batteries. <i>Scientific Reports</i> , <b>2016</b> , 6, 32330   | 4.9  | 110       |
| 187 | Lithium storage capability of lithium ion conductor Li <sub>1.5</sub> Al <sub>0.5</sub> Ge <sub>1.5</sub> (PO <sub>4</sub> ) <sub>3</sub> . <i>Journal of Alloys and Compounds</i> , <b>2010</b> , 501, 255-258  | 5.7  | 109       |
| 186 | Electrochemical Properties of Nonstoichiometric LiNi <sub>0.5</sub> Mn <sub>1.5</sub> O <sub>4</sub> Thin-Film Electrodes Prepared by Pulsed Laser Deposition. <i>Journal of the Electrochemical Society</i> , <b>2007</b> , 154, A737                         | 3.9  | 105       |
| 185 | Ru <sub>0.01</sub> Ti <sub>0.99</sub> Nb <sub>2</sub> O <sub>7</sub> as an intercalation-type anode material with a large capacity and high rate performance for lithium-ion batteries. <i>Journal of Materials Chemistry A</i> , <b>2015</b> , 3, 8627-8635   | 13   | 102       |
| 184 | Development of solid-state electrolytes for sodium-ion battery: A short review. <i>Nano Materials Science</i> , <b>2019</b> , 1, 91-100  | 10.2 | 99        |

|     |   |      |    |
|-----|---|------|----|
| 183 | One-step synthesis of hollow porous Fe <sub>3</sub> O <sub>4</sub> beads/reduced graphene oxide composites with superior battery performance. <i>Journal of Materials Chemistry</i> , <b>2012</b> , 22, 17656   |      | 99 |
| 182 | Polyvinylpyrrolidone-Induced Uniform Surface-Conductive Polymer Coating Endows Ni-Rich LiNiCoMnO with Enhanced Cyclability for Lithium-Ion Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2019</b> , 11, 12594-12604   | 9.5  | 94 |
| 181 | Advanced electrochemical performance of Li <sub>4</sub> Ti <sub>5</sub> O <sub>12</sub> -based materials for lithium-ion battery: Synergistic effect of doping and compositing. <i>Journal of Power Sources</i> , <b>2014</b> , 248, 1034-1041  | 8.9  | 89 |
| 180 | Li <sub>4</sub> Ti <sub>5</sub> O <sub>12</sub> -based anode materials with low working potentials, high rate capabilities and high cyclability for high-power lithium-ion batteries: a synergistic effect of doping, incorporating a conductive phase and reducing the particle size. <i>Journal of Materials Chemistry A</i> , <b>2014</b> , 2, 9982-9993 | 13   | 86 |
| 179 | A study of the superior electrochemical performance of 3 nm SnO <sub>2</sub> nanoparticles supported by graphene. <i>Journal of Materials Chemistry A</i> , <b>2014</b> , 2, 5688-5695  | 13   | 85 |
| 178 | Synthesis of SnO <sub>2</sub> /MoS <sub>2</sub> composites with different component ratios and their applications as lithium ion battery anodes. <i>Journal of Materials Chemistry A</i> , <b>2014</b> , 2, 17857-17866   | 13   | 80 |
| 177 | Composite Solid Polymer Electrolyte with Garnet Nanosheets in Poly(ethylene oxide). <i>ACS Sustainable Chemistry and Engineering</i> , <b>2019</b> , 7, 7163-7170   | 8.3  | 77 |
| 176 | Facile synthesis of chain-like LiCoO <sub>2</sub> nanowire arrays as three-dimensional cathode for microbatteries. <i>NPG Asia Materials</i> , <b>2014</b> , 6, e126-e126   | 10.3 | 76 |
| 175 | A hybrid polymer/oxide/ionic-liquid solid electrolyte for Na-metal batteries. <i>Journal of Materials Chemistry A</i> , <b>2017</b> , 5, 6424-6431  | 13   | 74 |
| 174 | X-ray diffraction and photoelectron spectroscopic studies of (001)-oriented Pb(Zr <sub>0.52</sub> Ti <sub>0.48</sub> )O <sub>3</sub> thin films prepared by laser ablation. <i>Journal of Applied Physics</i> , <b>2004</b> , 95, 241-247   | 2.5  | 68 |
| 173 | The influence of preparation conditions on electrochemical properties of LiNi <sub>0.5</sub> Mn <sub>1.5</sub> O <sub>4</sub> thin film electrodes by PLD. <i>Electrochimica Acta</i> , <b>2007</b> , 52, 2822-2828   | 6.7  | 63 |
| 172 | Hydrothermal synthesis of nanostructured graphene/polyaniline composites as high-capacitance electrode materials for supercapacitors. <i>Scientific Reports</i> , <b>2017</b> , 7, 44562  | 4.9  | 62 |
| 171 | On the fragmentation of active material secondary particles in lithium ion battery cathodes induced by charge cycling. <i>Extreme Mechanics Letters</i> , <b>2016</b> , 9, 449-458  | 3.9  | 62 |
| 170 | Monodisperse Li <sub>1.2</sub> Mn <sub>0.6</sub> Ni <sub>0.2</sub> O <sub>2</sub> microspheres with enhanced lithium storage capability. <i>Journal of Materials Chemistry A</i> , <b>2013</b> , 1, 5301  | 13   | 62 |
| 169 | Effect of Li <sub>3</sub> PO <sub>4</sub> coating of layered lithium-rich oxide on electrochemical performance. <i>Journal of Power Sources</i> , <b>2017</b> , 341, 147-155  | 8.9  | 61 |
| 168 | Ultrathin VO <sub>2</sub> nanosheets self-assembled into 3D micro/nano-structured hierarchical porous sponge-like micro-bundles for long-life and high-rate Li-ion batteries. <i>Journal of Materials Chemistry A</i> , <b>2017</b> , 5, 8307-8316  | 13   | 60 |
| 167 | Texture effect on the electrochemical properties of LiCoO <sub>2</sub> thin films prepared by PLD. <i>Electrochimica Acta</i> , <b>2007</b> , 52, 7014-7021   | 6.7  | 60 |
| 166 | The Solvent Induced Inter-Dimensional Phase Transformations of Cobalt Zeolitic-Imidazolate Frameworks. <i>Chemistry - A European Journal</i> , <b>2017</b> , 23, 10638-10643  | 4.8  | 57 |

|     |  |      |    |
|-----|--|------|----|
| 165 | Nano-structural changes in Li-ion battery cathodes during cycling revealed by FIB-SEM serial sectioning tomography. <i>Journal of Materials Chemistry A</i> , <b>2015</b> , 3, 18171-18179   | 13   | 56 |
| 164 | Influence of crystallization temperature on ionic conductivity of lithium aluminum germanium phosphate glass-ceramic. <i>Journal of Power Sources</i> , <b>2015</b> , 290, 123-129   | 8.9  | 54 |
| 163 | Failure Mechanism and Interface Engineering for NASICON-Structured All-Solid-State Lithium Metal Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2019</b> , 11, 20895-20904  | 9.5  | 51 |
| 162 | Study on Shrinkage Behaviour of Direct Laser Sintering Metallic Powder. <i>Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture</i> , <b>2006</b> , 220, 183-190   | 2.4  | 51 |
| 161 | Achieving high energy density in a 4.5 V all nitrogen-doped graphene based lithium-ion capacitor. <i>Journal of Materials Chemistry A</i> , <b>2019</b> , 7, 19909-19921   | 13   | 49 |
| 160 | Transport and electrochemical properties of high potentialavorite LiVPO <sub>4</sub> F. <i>Solid State Ionics</i> , <b>2013</b> , 242, 10-19   | 3.3  | 48 |
| 159 | High electric breakdown strength and energy density in vinylidene fluoride oligomer/poly(vinylidene fluoride) blend thin films. <i>Applied Physics Letters</i> , <b>2011</b> , 99, 142901  | 3.4  | 48 |
| 158 | Study on vacancy formation in ferroelectric PbTiO <sub>3</sub> from ab initio. <i>Applied Physics Letters</i> , <b>2006</b> , 88, 142902   | 3.4  | 46 |
| 157 | Hierarchical Porous Intercalation-Type V O as High-Performance Anode Materials for Li-Ion Batteries. <i>Chemistry - A European Journal</i> , <b>2017</b> , 23, 7538-7544   | 4.8  | 45 |
| 156 | Structure and properties of hot-pressed lead-free (Ba <sub>0.85</sub> Ca <sub>0.15</sub> )(Zr <sub>0.1</sub> Ti <sub>0.9</sub> )O <sub>3</sub> piezoelectric ceramics. <i>RSC Advances</i> , <b>2013</b> , 3, 20693  | 3.7  | 44 |
| 155 | Deactivation of a Single-Site Gold-on-Carbon Acetylene Hydrochlorination Catalyst: An X-ray Absorption and Inelastic Neutron Scattering Study. <i>ACS Catalysis</i> , <b>2018</b> , 8, 8493-8505   | 13.1 | 43 |
| 154 | Role of carbon coating in improving electrochemical performance of Li-rich Li(Li <sub>0.2</sub> Mn <sub>0.54</sub> Ni <sub>0.13</sub> Co <sub>0.13</sub> )O <sub>2</sub> cathode. <i>RSC Advances</i> , <b>2014</b> , 4, 44244-44252                                   | 3.7  | 43 |
| 153 | Intermolecular interactions and high dielectric energy storage density in poly(vinylidene fluoride-hexafluoropropylene)/poly(vinylidene fluoride) blend thin films. <i>Applied Physics Letters</i> , <b>2012</b> , 100, 252907   | 3.4  | 41 |
| 152 | Temperature-Dependent Lithium-Ion Diffusion and Activation Energy of LiCoNiMnO Thin-Film Cathode at Nanoscale by Using Electrochemical Strain Microscopy. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2017</b> , 9, 13999-14005                                 | 9.5  | 39 |
| 151 | Three-dimensional hierarchical nickel-cobalt-sulfide nanostructures for high performance electrochemical energy storage electrodes. <i>Journal of Materials Chemistry A</i> , <b>2016</b> , 4, 18335-18341   | 13   | 39 |
| 150 | Composite NASICON (NaZrSiPO) Solid-State Electrolyte with Enhanced Na Ionic Conductivity: Effect of Liquid Phase Sintering. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2019</b> , 11, 40125-40133  | 9.5  | 39 |
| 149 | 1.8 V symmetric supercapacitors developed using nanocrystalline Ru films as electrodes. <i>RSC Advances</i> , <b>2014</b> , 4, 11111   | 3.7  | 39 |
| 148 | Ultrathin Nanoribbons of in Situ Carbon-Coated VO <sub>2</sub> /HO for High-Energy and Long-Life Li-Ion Batteries: Synthesis, Electrochemical Performance, and Charge-Discharge Behavior. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2017</b> , 9, 17002-17012 | 9.5  | 38 |

|     |  |      |    |
|-----|--|------|----|
| 147 | Crystal structure, migration mechanism and electrochemical performance of Cr-stabilized garnet. <i>Solid State Ionics</i> , <b>2014</b> , 268, 135-139   | 3.3  | 38 |
| 146 | Cycling effects on surface morphology, nanomechanical and interfacial reliability of LiMn2O4 cathode in thin film lithium ion batteries. <i>Electrochimica Acta</i> , <b>2012</b> , 68, 52-59                          | 6.7  | 38 |
| 145 | Manganese oxide thin films prepared by pulsed laser deposition for thin film microbatteries. <i>Materials Chemistry and Physics</i> , <b>2014</b> , 143, 720-727   | 4.4  | 38 |
| 144 | NASICON-Structured LiGe2(PO4)3 with Improved Cyclability for High-Performance Lithium Batteries. <i>Journal of Physical Chemistry C</i> , <b>2009</b> , 113, 20514-20520   | 3.8  | 38 |
| 143 | Mesoporous Li4Ti5O(12-x)/C submicrospheres with comprehensively improved electrochemical performances for high-power lithium-ion batteries. <i>Physical Chemistry Chemical Physics</i> , <b>2014</b> , 16, 24874-24883 | 3.6  | 37 |
| 142 | Advances in lead-free pyroelectric materials: a comprehensive review. <i>Journal of Materials Chemistry C</i> , <b>2020</b> , 8, 1494-1516   | 7.1  | 37 |
| 141 | Recent advances of bismuth based anode materials for sodium-ion batteries. <i>Materials Technology</i> , <b>2018</b> , 33, 563-573   | 2.1  | 36 |
| 140 | One-pot high temperature hydrothermal synthesis of Fe3O4@C/graphene nanocomposite as anode for high rate lithium ion battery. <i>Electrochimica Acta</i> , <b>2015</b> , 180, 1041-1049                                | 6.7  | 35 |
| 139 | IMPROVED CAPACITIVE BEHAVIOR OF MnO2 THIN FILMS PREPARED BY ELECTRODEPOSITION ON THE PT SUBSTRATE WITH A MnOx BUFFER LAYER. <i>Functional Materials Letters</i> , <b>2009</b> , 02, 13-18                              | 1.2  | 35 |
| 138 | Pulsed laser deposition of lead-zirconate-titanate thin films and multilayered heterostructures. <i>Applied Physics A: Materials Science and Processing</i> , <b>2005</b> , 81, 701-714                                | 2.6  | 35 |
| 137 | Improvement of Li ion conductivity of Li 5 La 3 Ta 2 O 12 solid electrolyte by substitution of Ge for Ta. <i>Journal of Power Sources</i> , <b>2017</b> , 349, 105-110   | 8.9  | 33 |
| 136 | In-situ nanoscale mapping of surface potential in all-solid-state thin film Li-ion battery using Kelvin probe force microscopy. <i>Journal of Applied Physics</i> , <b>2012</b> , 111, 063723                          | 2.5  | 33 |
| 135 | Properties of nano-crystalline LiMn2O4 thin films deposited by pulsed laser deposition. <i>Electrochimica Acta</i> , <b>2006</b> , 52, 1161-1168   | 6.7  | 32 |
| 134 | Effect of bottom electrodes on nanoscale switching characteristics and piezoelectric response in polycrystalline BiFeO3 thin films. <i>Journal of Applied Physics</i> , <b>2011</b> , 110, 084102                      | 2.5  | 31 |
| 133 | Photocrosslinkable nanocomposite ink for printing strong, biodegradable and bioactive bone graft. <i>Biomaterials</i> , <b>2020</b> , 263, 120378  | 15.6 | 31 |
| 132 | Growth of layered LiNi0.5Mn0.5O2 thin films by pulsed laser deposition for application in microbatteries. <i>Applied Physics Letters</i> , <b>2008</b> , 92, 011912  | 3.4  | 30 |
| 131 | Thermal and compositional driven relaxor ferroelectric behaviours of lead-free Bi0.5Na0.5TiO3BrTiO3 ceramics. <i>Journal of Materials Chemistry C</i> , <b>2020</b> , 8, 2411-2418                                     | 7.1  | 29 |
| 130 | Nanoscale characterization of charged/discharged lithium-rich thin film cathode by scanning probe microscopy techniques. <i>Journal of Power Sources</i> , <b>2017</b> , 352, 9-17                                     | 8.9  | 28 |

|     |   |      |    |
|-----|---|------|----|
| 129 | Li-rich layer-structured cathode materials for high energy Li-ion batteries. <i>Functional Materials Letters</i> , <b>2014</b> , 07, 1430002  | 1.2  | 28 |
| 128 | Poly(vinylidene fluoride-co-hexafluoropropylene)-graft-poly(dopamine methacrylamide) copolymers: A nonlinear dielectric material for high energy density storage. <i>Applied Physics Letters</i> , <b>2013</b> , 103, 262904                      | 3.4  | 28 |
| 127 | Formation of Magnesium Silicide by Mechanical Alloying. <i>Materials Technology</i> , <b>1997</b> , 4, 275-283  |      | 28 |
| 126 | Grain boundary effects on Li-ion diffusion in a $\text{Li}_{1.2}\text{Co}_{0.13}\text{Ni}_{0.13}\text{Mn}_{0.54}\text{O}_2$ thin film cathode studied by scanning probe microscopy techniques. <i>RSC Advances</i> , <b>2016</b> , 6, 94000-94009 | 3.7  | 28 |
| 125 | Comparative study of $\text{LiMn}_2\text{O}_4$ thin film cathode grown at high, medium and low temperatures by pulsed laser deposition. <i>Journal of Solid State Chemistry</i> , <b>2006</b> , 179, 3831-3838                                    | 3.3  | 27 |
| 124 | Polyanion Sodium Vanadium Phosphate for Next Generation of Sodium-Ion Batteries: A Review. <i>Advanced Functional Materials</i> , <b>2020</b> , 30, 2001289   | 15.6 | 26 |
| 123 | Mitigated phase transition during first cycle of a Li-rich layered cathode studied by in operando synchrotron X-ray powder diffraction. <i>Physical Chemistry Chemical Physics</i> , <b>2016</b> , 18, 4745-52                                    | 3.6  | 26 |
| 122 | Local probing of magnetoelectric coupling and magnetoelastic control of switching in $\text{BiFeO}_3\text{-CoFe}_2\text{O}_4$ thin-film nanocomposite. <i>Applied Physics Letters</i> , <b>2013</b> , 103, 042906                                 | 3.4  | 26 |
| 121 | Grain growth and recrystallization of nanocrystalline $\text{Al}_3\text{Ti}$ prepared by mechanical alloying. <i>Journal of Materials Science</i> , <b>2003</b> , 38, 613-619   | 4.3  | 26 |
| 120 | Substantial doping engineering in $\text{Na}_3\text{V}_2\text{-xFe}_x(\text{PO}_4)_3$ ( $0 \leq x \leq 0.15$ ) as high-rate cathode for sodium-ion battery. <i>Materials and Design</i> , <b>2020</b> , 186, 108287                               | 8.1  | 25 |
| 119 | $\text{Li}_{1.5}\text{Al}_{0.5}\text{Ge}_{1.5}(\text{PO}_4)_3$ Li-ion conductor prepared by melt-quench and low temperature pressing. <i>Solid State Ionics</i> , <b>2015</b> , 278, 65-68  | 3.3  | 24 |
| 118 | Chemical Bonding Construction of Reduced Graphene Oxide-Anchored Few-Layer Bismuth Oxychloride for Synergistically Improving Sodium-Ion Storage. <i>Chemistry of Materials</i> , <b>2019</b> , 31, 7311-7319                                      | 8.6  | 24 |
| 117 | Ultrathin carbon nanopainting of $\text{LiFePO}_4$ by oxidative surface polymerization of dopamine. <i>Journal of Power Sources</i> , <b>2014</b> , 265, 239-245  | 8.9  | 24 |
| 116 | Operando X-ray Absorption Spectroscopy Study of Atomic Phase Reversibility with Wavelet Transform in the Lithium-Rich Manganese Based Oxide Cathode. <i>Chemistry of Materials</i> , <b>2016</b> , 28, 4191-4203                                  | 8.6  | 22 |
| 115 | Li diffusion in spinel $\text{LiNi}_{0.5}\text{Mn}_{1.5}\text{O}_4$ thin films prepared by pulsed laser deposition. <i>Physica Scripta</i> , <b>2007</b> , T129, 43-48  | 2.6  | 22 |
| 114 | Research Update: Ca doping effect on the Li-ion conductivity in NASICON-type solid electrolyte $\text{LiZr}_2(\text{PO}_4)_3$ : A first-principles molecular dynamics study. <i>APL Materials</i> , <b>2018</b> , 6, 060702                       | 5.7  | 22 |
| 113 | Li diffusion in $\text{LiNi}_{0.5}\text{Mn}_{0.5}\text{O}_2$ thin film electrodes prepared by pulsed laser deposition. <i>Electrochimica Acta</i> , <b>2009</b> , 54, 5986-5991   | 6.7  | 21 |
| 112 | Selective Laser Sintering of Porous Silica Enabled by Carbon Additive. <i>Materials</i> , <b>2017</b> , 10,   | 3.5  | 20 |



|     |  |      |    |
|-----|--|------|----|
| 111 | Structural and Electrochemical Properties of LiNi <sub>0.5</sub> Mn <sub>0.5</sub> O <sub>2</sub> Thin-Film Electrodes Prepared by Pulsed Laser Deposition. <i>Journal of the Electrochemical Society</i> , <b>2010</b> , 157, A348                          | 3.9  | 20 |
| 110 | Magnetic and Microstructural Properties of CoCrPt:Oxide Perpendicular Recording Media With Novel Intermediate Layers. <i>IEEE Transactions on Magnetics</i> , <b>2007</b> , 43, 633-638  | 2    | 20 |
| 109 | Inorganic sodium solid-state electrolyte and interface with sodium metal for room-temperature metal solid-state batteries. <i>Energy Storage Materials</i> , <b>2021</b> , 34, 28-44   | 19.4 | 20 |
| 108 | Li <sub>5</sub> Cr <sub>9</sub> Ti <sub>4</sub> O <sub>24</sub> : A new anode material for lithium-ion batteries. <i>Journal of Alloys and Compounds</i> , <b>2015</b> , 650, 616-621  | 5.7  | 19 |
| 107 | A facile strategy to achieve high conduction and excellent chemical stability of lithium solid electrolytes. <i>RSC Advances</i> , <b>2015</b> , 5, 6588-6594  | 3.7  | 19 |
| 106 | Roles of Alkaline Earth Ions in Garnet-Type Superionic Conductors. <i>ChemElectroChem</i> , <b>2017</b> , 4, 266-271   | 4.3  | 18 |
| 105 | Na-rich layered NaTiCrO (x = 0, 0.06): Na-ion battery cathode materials with high capacity and long cycle life. <i>Scientific Reports</i> , <b>2017</b> , 7, 373   | 4.9  | 18 |
| 104 | Preparation of thin solid electrolyte by hot-pressing and diamond wire slicing.. <i>RSC Advances</i> , <b>2019</b> , 9, 11670-11675  | 3.7  | 18 |
| 103 | In operando X-ray absorption spectroscopy study of charge rate effects on the atomic environment in graphene-coated Li-rich mixed oxide cathode. <i>Materials and Design</i> , <b>2016</b> , 98, 231-242   | 8.1  | 18 |
| 102 | Synergistic Effect for LiMn <sub>2</sub> O <sub>4</sub> Microcubes with Enhanced Rate Capability and Excellent Cycle Stability for Lithium Ion Batteries. <i>Journal of the Electrochemical Society</i> , <b>2016</b> , 163, A197-A202                       | 3.9  | 18 |
| 101 | Leakage behavior and conduction mechanisms of Ba(Ti <sub>0.85</sub> Sn <sub>0.15</sub> )O <sub>3</sub> /Bi <sub>1.5</sub> Zn <sub>1.0</sub> Nb <sub>1.5</sub> O <sub>7</sub> heterostructures. <i>Journal of Applied Physics</i> , <b>2010</b> , 107, 104104 | 2.5  | 18 |
| 100 | Influence of oxygen pressure on the ferroelectric properties of BiFeO <sub>3</sub> thin films on LaNiO <sub>3</sub> /Si substrates via laser ablation. <i>Applied Physics A: Materials Science and Processing</i> , <b>2010</b> , 101, 651-654               | 2.6  | 18 |
| 99  | Synthesis mechanism of an Al-Ti-C grain refiner master alloy prepared by a new method. <i>Metallurgical and Materials Transactions A: Physical Metallurgy and Materials Science</i> , <b>2003</b> , 34, 1727-1733 <sup>2,3</sup>                             |      | 18 |
| 98  | Microstructural and Electrochemical Properties of Al- and Ga-Doped Li <sub>7</sub> La <sub>3</sub> Zr <sub>2</sub> O <sub>12</sub> Garnet Solid Electrolytes. <i>ACS Applied Energy Materials</i> , <b>2020</b> , 3, 4708-4719                               | 6.1  | 17 |
| 97  | The role of oxygen pressure and thickness on structure and pyroelectric properties of Ba(Ti <sub>0.85</sub> Sn <sub>0.15</sub> )O <sub>3</sub> thin films grown by pulsed laser deposition. <i>Journal of Applied Physics</i> , <b>2009</b> , 105, 084102    | 2.5  | 17 |
| 96  | The manufacture of micromould and microparts by vacuum casting. <i>International Journal of Advanced Manufacturing Technology</i> , <b>2008</b> , 38, 944-948  | 3.2  | 17 |
| 95  | Deformation behaviour of ultrafine and nanosize-grained Mg alloy synthesized via mechanical alloying. <i>Philosophical Magazine</i> , <b>2006</b> , 86, 2919-2939  | 1.6  | 17 |
| 94  | Electronic Coupling of Cobalt Nanoparticles to Nitrogen-Doped Graphene for Oxygen Reduction and Evolution Reactions. <i>ChemSusChem</i> , <b>2016</b> , 9, 3067-3073   | 8.3  | 17 |

|    |   |     |    |
|----|---|-----|----|
| 93 | Flexible, stable, fast-ion-conducting composite electrolyte composed of nanostructured Na-super-ion-conductor framework and continuous Poly(ethylene oxide) for all-solid-state Na battery. <i>Journal of Power Sources</i> , <b>2020</b> , 454, 227949   | 8.9 | 16 |
| 92 | Role of Pb(Zr <sub>0.52</sub> Ti <sub>0.48</sub> )O <sub>3</sub> substitution in multiferroic properties of polycrystalline BiFeO <sub>3</sub> thin films. <i>Journal of Applied Physics</i> , <b>2011</b> , 110, 114116                                  | 2.5 | 16 |
| 91 | Abnormal grain growth of WC with small amount of cobalt. <i>Philosophical Magazine</i> , <b>2007</b> , 87, 5657-5671  | 1.6 | 16 |
| 90 | A new approach for synthesizing bulk-type all-solid-state lithium-ion batteries. <i>Journal of Materials Chemistry A</i> , <b>2019</b> , 7, 9748-9760   | 13  | 15 |
| 89 | Probing the Coexistence of Ferroelectric and Relaxor States in BiNaTiO-Based Ceramics for Enhanced Piezoelectric Performance. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2020</b> , 12, 30548-30556   | 9.5 | 15 |
| 88 | Revealing Mechanism of Li <sub>3</sub> PO <sub>4</sub> Coating Suppressed Surface Oxygen Release for Commercial Ni-Rich Layered Cathodes. <i>ACS Applied Energy Materials</i> , <b>2020</b> , 3, 7445-7455  | 6.1 | 15 |
| 87 | Study on stabilization of cubic Li <sub>7</sub> La <sub>3</sub> Zr <sub>2</sub> O <sub>12</sub> by Ge substitution in various atmospheres. <i>Functional Materials Letters</i> , <b>2016</b> , 09, 1642005  | 1.2 | 15 |
| 86 | Processing and characterization of laser-sintered Al <sub>2</sub> O <sub>3</sub> /ZrO <sub>2</sub> /SiO <sub>2</sub> . <i>International Journal of Advanced Manufacturing Technology</i> , <b>2013</b> , 68, 2565-2569                                    | 3.2 | 15 |
| 85 | Cycling Effect on Morphological and Interfacial Properties of RuO <sub>2</sub> Anode Film in Thin-Film Lithium Ion Microbatteries. <i>Metallurgical and Materials Transactions A: Physical Metallurgy and Materials Science</i> , <b>2013</b> , 44, 26-34 | 2.3 | 15 |
| 84 | ELECTROCHEMICAL PROPERTY OF LiMn <sub>2</sub> O <sub>4</sub> IN OVER-DISCHARGED CONDITIONS. <i>Functional Materials Letters</i> , <b>2012</b> , 05, 1250028   | 1.2 | 15 |
| 83 | Defect and electronic structures of acceptor substituted lead titanate. <i>Applied Physics Letters</i> , <b>2008</b> , 92, 112909   | 3.4 | 15 |
| 82 | ELECTROCHEMICAL PROPERTIES OF BiFeO <sub>3</sub> THIN FILMS PREPARED BY PULSED LASER DEPOSITION. <i>Functional Materials Letters</i> , <b>2009</b> , 02, 163-167  | 1.2 | 14 |
| 81 | Micro-rapid-prototyping via multi-layered photo-lithography. <i>International Journal of Advanced Manufacturing Technology</i> , <b>2006</b> , 29, 1026-1032  | 3.2 | 13 |
| 80 | Fractal-based description for the three-dimensional surface of materials. <i>Journal of Applied Physics</i> , <b>1999</b> , 86, 2526-2532   | 2.5 | 13 |
| 79 | Synthesis and properties of poly(1,3-dioxolane) quasi-solid-state electrolytes a rare-earth triflate catalyst. <i>Chemical Communications</i> , <b>2021</b> , 57, 7934-7937   | 5.8 | 13 |
| 78 | Fe <sub>3</sub> O <sub>4</sub> /rice husk-based macro-/mesoporous carbon bone nanocomposite as superior high-rate anode for lithium ion battery. <i>Journal of Solid State Electrochemistry</i> , <b>2017</b> , 21, 27-34                                 | 2.6 | 12 |
| 77 | Increasing the high rate performance of mixed metal phospho-olivine cathodes through collective and cooperative strategies. <i>Journal of Power Sources</i> , <b>2014</b> , 247, 273-279  | 8.9 | 12 |
| 76 | Orientation-dependent surface potential behavior in Nb-doped BiFeO <sub>3</sub> . <i>Applied Physics Letters</i> , <b>2012</b> , 100, 172901  | 3.4 | 12 |



|    |   |      |    |
|----|---|------|----|
| 75 | The role of amorphous Ni <sub>50</sub> P <sub>50</sub> precoating layer in CoCrPtTa thin film media. <i>Journal of Applied Physics</i> , <b>2000</b> , 87, 6346-6348  | 2.5  | 12 |
| 74 | Preparation of Nanocomposite Polymer Electrolyte via In Situ Synthesis of SiO Nanoparticles in PEO. <i>Nanomaterials</i> , <b>2020</b> , 10,  | 5.4  | 11 |
| 73 | Enhanced tunable and pyroelectric properties of Ba(Ti <sub>0.85</sub> Sn <sub>0.15</sub> )O <sub>3</sub> thin films with Bi <sub>1.5</sub> Zn <sub>1.0</sub> Nb <sub>1.5</sub> O <sub>7</sub> buffer layers. <i>Applied Physics Letters</i> , <b>2010</b> , 96, 082901                            | 3.4  | 11 |
| 72 | Vortex structure transformation of BaTiO <sub>3</sub> nanoparticles through the gradient function. <i>Journal of Applied Physics</i> , <b>2009</b> , 106, 024111  | 2.5  | 11 |
| 71 | Magnetic, ferroelectric, and dielectric properties of Bi(Sc <sub>0.5</sub> Fe <sub>0.5</sub> )O <sub>3</sub> PbTiO <sub>3</sub> thin films. <i>Journal of Applied Physics</i> , <b>2009</b> , 105, 074101   | 2.5  | 11 |
| 70 | Facile aqueous synthesis of high performance Na <sub>2</sub> FeM(SO <sub>4</sub> ) <sub>3</sub> (M = Fe, Mn, Ni) alluaudites for low cost Na-ion batteries. <i>Journal of Materials Chemistry A</i> , <b>2020</b> , 8, 2728-2740  | 13   | 11 |
| 69 | 3D Frameworks with Variable Magnetic and Electrical Features from Sintered Cobalt-Modified Carbon Nanotubes. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2018</b> , 10, 20983-20994  | 9.5  | 11 |
| 68 | Phase diagram of NaFe <sub>y</sub> Co <sub>1-y</sub> O <sub>2</sub> and evolution of its physico- and electrochemical properties with changing iron content. <i>Journal of Power Sources</i> , <b>2019</b> , 419, 42-51   | 8.9  | 10 |
| 67 | Hollow microspherical LiFePO <sub>4</sub> /C synthesized from a novel multidentate phosphonate complexing agent. <i>RSC Advances</i> , <b>2013</b> , 3, 5127  | 3.7  | 10 |
| 66 | Cycling effects on interfacial reliability of TiO <sub>2</sub> anode film in thin film lithium-ion microbatteries. <i>Journal of Solid State Electrochemistry</i> , <b>2012</b> , 16, 1877-1881   | 2.6  | 10 |
| 65 | The mechanical alloying of titanium aluminides. <i>Jom</i> , <b>2002</b> , 54, 62-64  | 2.1  | 10 |
| 64 | Decomposition failure of Li <sub>1.5</sub> Al <sub>0.5</sub> Ge <sub>1.5</sub> (PO <sub>4</sub> ) <sub>3</sub> solid electrolytes induced by electric field: A multi-scenario study using Scanning Probe Microscopy-based techniques. <i>Journal of Power Sources</i> , <b>2020</b> , 471, 228468 | 8.9  | 10 |
| 63 | All-Solid-State Thin Film Batteries for Microelectronics. <i>Advanced Science</i> , <b>2021</b> , 8, e2100774   | 13.6 | 10 |
| 62 | Dual-Carbon Network for the Effective Transport of Charged Species in a LiFePO <sub>4</sub> Cathode for Lithium-Ion Batteries. <i>Energy Technology</i> , <b>2015</b> , 3, 63-69  | 3.5  | 9  |
| 61 | Li <sub>3.33</sub> Cu <sub>1.005</sub> Ti <sub>4.665</sub> O <sub>12</sub> /CuO composite with P4332 space group for Li-ion batteries: synergistic effect of substituting and compositing. <i>RSC Advances</i> , <b>2014</b> , 4, 31196-31200   | 3.7  | 9  |
| 60 | Thickness dependence of structure, tunable and pyroelectric properties of laser-ablated Ba(Zr <sub>0.25</sub> Ti <sub>0.75</sub> )O <sub>3</sub> thin films. <i>Journal Physics D: Applied Physics</i> , <b>2010</b> , 43, 035402   | 3    | 9  |
| 59 | Rice Husk-Based 3D Porous Silicon/Carbon Nanocomposites as Anode for Lithium-Ion Batteries. <i>Energy Technology</i> , <b>2019</b> , 7, 1800787   | 3.5  | 9  |
| 58 | Composite Hybrid Quasi-Solid Electrolyte for High-Energy Lithium Metal Batteries. <i>ACS Applied Energy Materials</i> , <b>2021</b> , 4, 7973-7982  | 6.1  | 9  |

|    |   |      |   |
|----|---|------|---|
| 57 | Dual-Nitrogen-Doped Carbon Decorated on Na <sub>3</sub> V <sub>2</sub> (PO <sub>4</sub> ) <sub>3</sub> to Stabilize the Intercalation of Three Sodium Ions. <i>ACS Applied Energy Materials</i> , <b>2020</b> , 3, 6870-6879                              | 6.1  | 8 |
| 56 | Multi-substituted garnet-type electrolytes for solid-state lithium batteries. <i>Ceramics International</i> , <b>2020</b> , 46, 5489-5494   | 5.1  | 8 |
| 55 | Elevating the discharge plateau of prussian blue analogs through low-spin Fe redox induced intercalation pseudocapacitance. <i>Energy Storage Materials</i> , <b>2021</b> , 43, 182-189   | 19.4 | 8 |
| 54 | Dual Substitution and Spark Plasma Sintering to Improve Ionic Conductivity of Garnet LiLaZrO. <i>Nanomaterials</i> , <b>2019</b> , 9,   | 5.4  | 7 |
| 53 | Doping Induced Hierarchical Lattice Expansion of Cobalt Diselenide/Carbon Nanosheet Hybrid for Fast and Stable Sodium Storage. <i>Cell Reports Physical Science</i> , <b>2020</b> , 1, 100082   | 6.1  | 7 |
| 52 | Stabilization of cubic Li <sub>7</sub> La <sub>3</sub> Zr <sub>2</sub> O <sub>12</sub> by Al substitution in various atmospheres. <i>Solid State Ionics</i> , <b>2020</b> , 350, 115323   | 3.3  | 7 |
| 51 | Characterization of crystallized LiMn <sub>2</sub> O <sub>4</sub> thin films grown by pulsed laser deposition. <i>Philosophical Magazine</i> , <b>2007</b> , 87, 3249-3258  | 1.6  | 7 |
| 50 | A facile method for the synthesis of a sintering dense nano-grained NaZrSiPO Na-ion solid-state electrolyte. <i>Chemical Communications</i> , <b>2021</b> , 57, 4023-4026   | 5.8  | 7 |
| 49 | Insight into the structure-capacity relationship in biomass derived carbon for high-performance sodium-ion batteries. <i>Journal of Energy Chemistry</i> , <b>2021</b> , 62, 497-504  | 12   | 7 |
| 48 | Abnormal Ionic Conductivities in Halide NaBi O Cl Induced by Absorbing Water and a Derived Oxhydryl Group. <i>Angewandte Chemie - International Edition</i> , <b>2020</b> , 59, 8991-8997   | 16.4 | 6 |
| 47 | Laser induced transformation of TiSi <sub>2</sub> . <i>Journal of Applied Physics</i> , <b>2003</b> , 94, 4291-4295   | 2.5  | 6 |
| 46 | Solid-gas reactions driven by mechanical alloying of niobium and tantalum in nitrogen. <i>Metallurgical and Materials Transactions A: Physical Metallurgy and Materials Science</i> , <b>1999</b> , 30, 1097-1100   | 2.3  | 6 |
| 45 | Reactive Synthesis of NbAl <sub>3</sub> Matrix Composites. <i>Materials Research Society Symposia Proceedings</i> , <b>1990</b> , 194, 79   |      | 6 |
| 44 | Extra Sodiation Sites in Hard Carbon for High Performance Sodium Ion Batteries.. <i>Small Methods</i> , <b>2021</b> , 5, e2100580   | 12.8 | 6 |
| 43 | Intrinsic low sodium/NASICON interfacial resistance paving the way for room temperature sodium-metal battery. <i>Journal of Colloid and Interface Science</i> , <b>2021</b> , 601, 418-426  | 9.3  | 6 |
| 42 | Hierarchical porous CoO /carbon nanocomposite for enhanced lithium storage. <i>Journal of Electroanalytical Chemistry</i> , <b>2019</b> , 847, 113202   | 4.1  | 5 |
| 41 | Trap State Spectroscopy of LiMyMn <sub>2</sub> -yO <sub>4</sub> (M = Mn, Ni, Co): Guiding Principles for Electrochemical Performance. <i>Journal of Physical Chemistry C</i> , <b>2013</b> , 117, 3812-3817   | 3.8  | 5 |
| 40 | Highly (100) oriented Pb(Zr <sub>0.52</sub> Ti <sub>0.48</sub> )O <sub>3</sub> /LaNiO <sub>3</sub> films grown on amorphous substrates by pulsed laser deposition. <i>Applied Physics A: Materials Science and Processing</i> , <b>2007</b> , 88, 365-370 | 2.6  | 5 |

|    |  |      |   |
|----|--|------|---|
| 39 | Effect of Matrix Constitution on Microstructure and Mechanical Properties of Rheocast Metal Matrix Composites. <i>Materials and Manufacturing Processes</i> , <b>1998</b> , 13, 27-52  | 4.1  | 5 |
| 38 | Fe <sub>9</sub> S <sub>8</sub> electrodes for all-solid-state lithium secondary batteries using sulfide-based solid electrolytes. <i>Journal of Power Sources</i> , <b>2020</b> , 449, 227576  | 8.9  | 5 |
| 37 | Nanocomposite multilayer capacitors comprising BaTiO <sub>3</sub> @TiO <sub>2</sub> and poly(vinylidene fluoride-hexafluoropropylene) for dielectric-based energy storage. <i>Journal of Advanced Dielectrics</i> , <b>2014</b> , 04, 1450009  | 1.3  | 4 |
| 36 | Strain effect on the surface potential and nanoscale switching characteristics of multiferroic BiFeO <sub>3</sub> thin films. <i>Applied Physics Letters</i> , <b>2012</b> , 100, 132907   | 3.4  | 4 |
| 35 | ELECTRIC, MAGNETIC AND MECHANICAL COUPLING EFFECTS ON FERROELECTRIC PROPERTIES AND SURFACE POTENTIAL OF BiFeO <sub>3</sub> THIN FILM. <i>Functional Materials Letters</i> , <b>2011</b> , 04, 91-95  | 1.2  | 4 |
| 34 | STEP-FLOW GROWTH OF HETEROEPITAXIAL SrRuO <sub>3</sub> THIN FILMS ON 0.04° SrTiO <sub>3</sub> (001) VICINAL SUBSTRATES. <i>Functional Materials Letters</i> , <b>2008</b> , 01, 253-257  | 1.2  | 4 |
| 33 | Development of a drop-on-demand system for multiple material dispensing <b>2008</b> ,  |      | 4 |
| 32 | Effect of variation in physical properties of the metallic matrix on the microstructural characteristics and the ageing behaviour of Al-Cu/SiC metal matrix composites. <i>Journal of Materials Science</i> , <b>1999</b> , 34, 1681-1689  | 4.3  | 4 |
| 31 | Ultrathin, Compacted Gel Polymer Electrolytes Enable High-Energy and Stable-Cycling 4 V Lithium-Metal Batteries. <i>ChemElectroChem</i> , <b>2020</b> , 7, 3656-3662   | 4.3  | 4 |
| 30 | A Robust Solid-Solid Interface Using Sodium-In Alloy Modified Metallic Sodium Anode Paving Way for All-Solid-State Battery. <i>Advanced Energy Materials</i> , <b>2021</b> , 11, 2101228   | 21.8 | 4 |
| 29 | Gallium-substituted Nasicon Na <sub>3</sub> Zr <sub>2</sub> Si <sub>2</sub> PO <sub>12</sub> solid electrolytes. <i>Journal of Alloys and Compounds</i> , <b>2021</b> , 855, 157501  | 5.7  | 4 |
| 28 | Electromechanical Failure of NASICON-Type Solid-State Electrolyte-Based All-Solid-State Li-Ion Batteries. <i>Chemistry of Materials</i> , <b>2021</b> , 33, 6841-6852  | 9.6  | 4 |
| 27 | Alleviating mechanical degradation of hexacyanoferrate via strain locking during Na <sup>+</sup> insertion/extraction for full sodium ion battery. <i>Nano Research</i> , 1  | 10   | 4 |
| 26 | Controllable 3D Porous Ni Current Collector Coupled with Surface Phosphorization Enhances Na Storage of Ni S Nanosheet Arrays.. <i>Small</i> , <b>2021</b> , e2106161  | 11   | 4 |
| 25 | High-Power and High-Energy Cu-Substituted Li <sub>x</sub> Ni <sub>0.88</sub> Co <sub>y</sub> Mn <sub>0.1</sub> Cu <sub>0.02</sub> O <sub>2</sub> Cathode Material for Li-Ion Batteries. <i>Physica Status Solidi (A) Applications and Materials Science</i> , <b>2020</b> , 217, 1900951 | 1.6  | 3 |
| 24 | Formation of Micromoulds via UV Lithography of SU8 Photoresist and Nickel Electrodeposition. <i>Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture</i> , <b>2006</b> , 220, 329-333  | 2.4  | 3 |
| 23 | Ultrathin, dense, hybrid polymer/ceramic gel electrolyte for high energy lithium metal batteries. <i>Materials Letters</i> , <b>2020</b> , 279, 128480   | 3.3  | 3 |
| 22 | Abnormal Phenomena of Multi-Way Sodium Storage in Selenide Electrode. <i>Advanced Functional Materials</i> , <b>2021</b> , 31, 2102406   | 15.6 | 3 |

|    |   |      |   |
|----|---|------|---|
| 21 | ACCEPTOR MODULATED DEFECT AND ELECTRONIC STRUCTURES IN FERROELECTRIC LEAD TITANATE: AN AB INITIO STUDY. <i>Functional Materials Letters</i> , <b>2008</b> , 01, 121-126   | 1.2  | 2 |
| 20 | Mechanochemical Activation of Solid State Reaction between Mg and TiO <sub>2</sub> . <i>JSME International Journal Series A-Solid Mechanics and Material Engineering</i> , <b>2003</b> , 46, 251-254  |      | 2 |
| 19 | The effect of O <sub>3</sub> P <sub>2</sub> phases coexistence in Na <sub>x</sub> Fe <sub>0.3</sub> Co <sub>0.7</sub> O <sub>2</sub> cathode material on its electronic and electrochemical properties. Experimental and theoretical studies. <i>Journal of Power Sources</i> , <b>2020</b> , 449, 227471 | 8.9  | 2 |
| 18 | Understanding and Preventing Dendrite Growth in Lithium Metal Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2021</b> , 13, 34320-34331  | 9.5  | 2 |
| 17 | Porous Li <sub>2</sub> O Al <sub>2</sub> O <sub>3</sub> SiO <sub>2</sub> (LAS) Glass-Ceramics Prepared by Selective Laser Melting and Annealing. <i>Ceramic Engineering and Science Proceedings</i> , 523-528   | 0.1  | 2 |
| 16 | Ferroelectric Engineered Electrode-Composite Polymer Electrolyte Interfaces for All-Solid-State Sodium Metal Battery.. <i>Advanced Science</i> , <b>2022</b> , e2105849   | 13.6 | 2 |
| 15 | Low temperature sintering of crystallized Li <sub>1.5</sub> Al <sub>0.5</sub> Ge <sub>1.5</sub> (PO <sub>4</sub> ) <sub>3</sub> using hot-press technique. <i>Materials Today: Proceedings</i> , <b>2019</b> , 17, 408-415  | 1.4  | 1 |
| 14 | Scalable Li <sub>1.5</sub> Al <sub>0.5</sub> Ge <sub>1.5</sub> (PO <sub>4</sub> ) <sub>3</sub> thin membrane prepared by tape-casting for large-scale lithium-ion battery application. <i>Materials Technology</i> , <b>2020</b> , 35, 572-579  | 2.1  | 1 |
| 13 | THE BEHAVIOR OF ELECTRODEPOSITED NANOCRYSTALLINE Co-Ni ALLOYS SUBJECTED TO MAGNETIC AND STRESS FIELDS. <i>Surface Review and Letters</i> , <b>2010</b> , 17, 129-134  | 1.1  | 1 |
| 12 | ELECTROCHEMICAL PERFORMANCE OF MICROBATTERIES USING CRYSTALLIZED LiCoO <sub>2</sub> AND NANO-CRYSTALLINE LiMn <sub>2</sub> O <sub>4</sub> FILM AS CATHODES AND AMORPHOUS LiNiVO <sub>4</sub> AS ANODE. <i>Surface Review and Letters</i> , <b>2008</b> , 15, 169-174                                      | 1.1  | 1 |
| 11 | Excimer laser-induced transformation in laser ablated Pb(Zr <sub>0.52</sub> Ti <sub>0.48</sub> )O <sub>3</sub> amorphous thin films. <i>Philosophical Magazine</i> , <b>2004</b> , 84, 3729-3739  | 1.6  | 1 |
| 10 | Supercapacitors Based on Activated Carbons, Products of Rice Hull Processing. <i>Russian Journal of Physical Chemistry A</i> , <b>2021</b> , 95, 818-826  | 0.7  | 1 |
| 9  | Ammonium Escorted Chloride Chemistry in Stabilizing Aqueous Chloride Ion Battery. <i>Materials Today Energy</i> , <b>2022</b> , 101020  | 7    | 1 |
| 8  | Structural, thermal, and electrochemical studies of biodegradable gel polymer electrolyte for electric double layer capacitor. <i>High Performance Polymers</i> , 095400832211017   | 1.6  | 1 |
| 7  | Abnormal Ionic Conductivities in Halide NaBi <sub>3</sub> O <sub>4</sub> Cl <sub>2</sub> Induced by Absorbing Water and a Derived Oxhydryl Group. <i>Angewandte Chemie</i> , <b>2020</b> , 132, 9076-9082   | 3.6  | 0 |
| 6  | Fast discharge-charge properties of FePS <sub>3</sub> electrode for all-solid-state batteries using sulfide electrolytes and its stable diffusion path. <i>Functional Materials Letters</i> , <b>2021</b> , 14, 2141005   | 1.2  | 0 |
| 5  | Kinetics of $\beta$ -phase transformation in the heat treatment of FeSi <sub>2</sub> - and Fe <sub>2</sub> Si <sub>5</sub> -based thermoelectric alloys. <i>Philosophical Magazine</i> , <b>2003</b> , 83, 2865-2873  | 1.6  |   |
| 4  | Effect of silicon substrate amorphization on the kinetics of reaction between a titanium thin film and silicon. <i>Philosophical Magazine A: Physics of Condensed Matter, Structure, Defects and Mechanical Properties</i> , <b>2002</b> , 82, 2923-2934  |      |   |

- 3 In-Situ Synthesis of AL-TI-C Master Alloy Grain Refiners by Different Methods193-201
- 2 Response and Implication of NASICON Solid-State Electrolytes to Local Electrical Stimulation: From Surface Engineering to Interfacial Manipulation. *ACS Applied Materials & Interfaces*, **2021**, 13, 46588-46597
- 1 Growth of Lanthanum Oxide Films by Pulsed Laser Deposition. *Ceramic Engineering and Science Proceedings*,51-55