

# Jin-Ping Qu

## List of Publications by Year in Descending Order

**Source:** <https://exaly.com/author-pdf/4216917/jin-ping-qu-publications-by-year.pdf>

**Version:** 2024-04-19

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

132  
papers

1,921  
citations

25  
h-index

36  
g-index

142  
ext. papers

2,516  
ext. citations

4.2  
avg, IF

5.48  
L-index

#	Paper	IF	Citations
132	Toward high dielectric constant and low dielectric loss nanocomposite via kinetical migration. <i>Composites Science and Technology</i> , <b>2022</b> , 221, 109310	8.6	0
131	Efficient fabrication of flame-retarding silicone rubber/hydroxylated boron nitride nanocomposites based on volumetric extensional rheology. <i>Chemical Engineering Journal</i> , <b>2022</b> , 435, 135154	14.7	2
130	Biomass porous potatoes/MXene encapsulated PEG-based PCMs with improved photo-to-thermal conversion capability. <i>Solar Energy Materials and Solar Cells</i> , <b>2022</b> , 237, 111559	6.4	6
129	Manufacturing High-Performance Polylactide by Constructing 3D Network Crystalline Structure with Adding Self-Assembly Nucleator. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2022</b> , 61, 4567-4578	3.9	0
128	Cost-Effective Fabrication of Micro-Nanostructured Superhydrophobic Polyethylene/Graphene Foam with Self-Floating, Optical Trapping, Acid-/Alkali Resistance for Efficient Photothermal Deicing and Interfacial Evaporation.. <i>Small</i> , <b>2022</b> , e2200175	11	13
127	Poly (ethylene-butylacrylate-glycidyl methacrylate) reaction compatibilized poly (lactic acid)/poly (3-hydroxybutyrate-4-hydroxybutyrate) blends with enhanced mechanical property, biodegradability and thermal stability. <i>Polymer Testing</i> , <b>2022</b> , 111, 107610	4.5	1
126	Scalable Fabrication of High-enthalpy Polyethylene/Carbon Nanotubes/Paraffin Wax Nanocomposite with Flexibility and Superhydrophobicity for Efficient Thermal Management. <i>Composites Part A: Applied Science and Manufacturing</i> , <b>2022</b> , 107006	8.4	3
125	Microstructure evolution and mechanism of PLA/PVDF hybrid dielectrics fabricated under elongational flow. <i>Polymer</i> , <b>2021</b> , 224, 123719	3.9	9
124	Supertough, Ultrastrong, and Transparent Poly(lactic acid) via Directly Hot Pressing under Cyclic CompressingReleasing. <i>Macromolecules</i> , <b>2021</b> , 54, 4847-4853	5.5	8
123	Ultrafast Fabrication of Graphene-Reinforced Nanocomposites via Synergy of Steam Explosion and Alternating Convergent-Divergent Flow. <i>Small</i> , <b>2021</b> , 17, e2100017	11	6
122	Improving thermal conductivity of ethylene propylene diene monomer/paraffin/expanded graphite shape-stabilized phase change materials with great thermal management potential via green steam explosion. <i>Advanced Composites and Hybrid Materials</i> , <b>2021</b> , 4, 478-491	8.7	24
121	Fabrication of iron oxide nanoparticle decorated boron nitride nanosheet for flame-retarding silicone rubber. <i>Materials Letters</i> , <b>2021</b> , 283, 128712	3.3	5
120	Efficient fabrication of lightweight polyethylene foam with robust and durable superhydrophobicity for self-cleaning and anti-icing applications. <i>Chemical Engineering Journal</i> , <b>2021</b> , 407, 127100	14.7	28
119	Effect of series explosion effects on the fiber length, fiber dispersion and structure properties in glass fiber reinforced polyamide 66. <i>Polymers for Advanced Technologies</i> , <b>2021</b> , 32, 505-513	3.2	4
118	Efficient fabrication of highly exfoliated and evenly dispersed high-density polyethylene/expanded graphite nanocomposite with enhanced dielectric constant and extremely low dielectric loss. <i>Composites Part A: Applied Science and Manufacturing</i> , <b>2021</b> , 142, 106242	8.4	4
117	Controlled localizing multi-wall carbon nanotubes in polyvinylidene fluoride/acrylonitrile butadiene styrene blends to achieve balanced dielectric constant and dielectric loss. <i>Composites Science and Technology</i> , <b>2021</b> , 212, 108874	8.6	8
116	High Thermal Conductivity and Mechanical Strength Phase Change Composite with Double Supporting Skeletons for Industrial Waste Heat Recovery. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2021</b> , 13, 47174-47184	9.5	23

115	Novel flexible polyurethane/MXene composites with sensitive solar thermal energy storage behavior. <i>Composites Part A: Applied Science and Manufacturing</i> , <b>2021</b> , 149, 106505	8.4	16
114	Synergistic Effect Based on Enhanced Local Shear Forces in PVDF/TiO <sub>2</sub> /CNT Ternary Composites. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2020</b> , 59, 18887-18897	3.9	9
113	Self-reinforced polyethylene enabled by cyclic pulsating pressure. <i>Polymer</i> , <b>2020</b> , 202, 122665	3.9	4
112	Constructing Bone-Mimicking High-Performance Structured Poly(lactic acid) by an Elongational Flow Field and Facile Annealing Process. <i>ACS Applied Materials &amp; Interfaces</i> , <b>2020</b> , 12, 13411-13420	9.5	21
111	Phase Formation of Polyvinylidene Fluoride via Hot Pressing under Cyclic Pulsating Pressure. <i>Macromolecules</i> , <b>2020</b> , 53, 8494-8501	5.5	6
110	Polyethylene-Based Single Polymer Composites Prepared under Elongational Flow for High-Voltage Applications. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2020</b> , 59, 18607-18615	3.9	3
109	One-Step and Solvent-Free Synthesis of Polyethylene Glycol-Based Polyurethane As Solid-Solid Phase Change Materials for Solar Thermal Energy Storage. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2019</b> , 58, 3024-3032	3.9	48
108	Properties of compression molded ultra-high molecular weight polyethylene products pretreated by eccentric rotor extrusion. <i>Polymer International</i> , <b>2019</b> , 68, 862-870	3.3	5
107	Preparation and properties of biodegradable poly (lactic acid)/ethylene butyl acrylate glycidyl methacrylate blends via novel vane extruder. <i>Plastics, Rubber and Composites</i> , <b>2019</b> , 48, 364-373	1.5	4
106	Enhancing Impact Toughness of Renewable Poly(lactic acid)/Thermoplastic Polyurethane Blends via Constructing Cocontinuous-like Phase Morphology Assisted by Ethylene-Methyl Acrylate-Glycidyl Methacrylate Copolymer. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2019</b> , 58, 10894-10907	3.9	32
105	A novel bio-based polyurethane/wood powder composite as shape-stable phase change material with high relative enthalpy efficiency for solar thermal energy storage. <i>Solar Energy Materials and Solar Cells</i> , <b>2019</b> , 200, 109987	6.4	26
104	Super-Toughened Poly(lactic Acid) with Poly( $\epsilon$ -caprolactone) and Ethylene-Methyl Acrylate-Glycidyl Methacrylate by Reactive Melt Blending. <i>Polymers</i> , <b>2019</b> , 11,	4.5	15
103	Super-Tough and Highly-Ductile Poly(L-lactic acid)/Thermoplastic Polyurethane/Epoxy-Containing Ethylene Copolymer Blends Prepared by Reactive Blending. <i>Macromolecular Materials and Engineering</i> , <b>2019</b> , 304, 1900020	3.9	5
102	Improved heat shrinkage and mechanical performances of polyethylene trilayer blown film prepared via novel multilayer coextrusion method. <i>Packaging Technology and Science</i> , <b>2019</b> , 32, 309-321	2.3	2
101	Short-time fabrication of well-mixed high-density polyethylene/ultrahigh-molecular-weight polyethylene blends under elongational flow: morphology, mechanical properties and mechanism. <i>Polymer International</i> , <b>2019</b> , 68, 904-914	3.3	7
100	Effect of continuous elongational flow on structure and properties of poly(L-lactic acid)/poly(ethylene glycol) blend and its organo-modified montmorillonite nanocomposites. <i>Polymer Composites</i> , <b>2019</b> , 40, E617	3	3
99	Structure and properties of Polylactide/Poly(butylene succinate)/Organically Modified Montmorillonite nanocomposites with high-efficiency intercalation and exfoliation effect manufactured via volume pulsating elongation flow. <i>Polymer</i> , <b>2019</b> , 180, 121656	3.9	23
98	Effect of continuous elongational flow on structure and properties of short glass fiber reinforced polyamide 6 composites. <i>Advanced Industrial and Engineering Polymer Research</i> , <b>2019</b> , 2, 93-101	7.3	9

97	A single step fabrication of bio-inspired high efficiency and durable water harvester made of polymer membranes. <i>Polymer</i> , <b>2019</b> , 183, 121843	3.9	3
96	UHMWPE/organoclay nanocomposites fabricated by melt intercalation under continuous elongational flow: Dispersion, thermal behaviors and mechanical properties. <i>Polymer Engineering and Science</i> , <b>2019</b> , 59, 547-554	2.3	9
95	Phase Morphology and Performance of Supertough PLA/EMA-GMA/ZrP Nanocomposites Prepared through Reactive Melt-Blending. <i>ACS Omega</i> , <b>2019</b> , 4, 19046-19053	3.9	6
94	Super-toughened poly(lactic acid)/thermoplastic poly(ether)urethane nanofiber composites with in-situ formation of aligned nanofibers prepared by an innovative eccentric rotor extruder. <i>Composites Science and Technology</i> , <b>2019</b> , 169, 135-141	8.6	40
93	A novel method for industrial manufacturing of thermoplastic multilayer films: Processing, microstructure, and properties. <i>Polymer Engineering and Science</i> , <b>2019</b> , 59, E339-E349	2.3	3
92	Formation of polypropylene/functional graphene oxide nanocomposites with Different FGs loading in elongation flow condition. <i>Polymer Engineering and Science</i> , <b>2019</b> , 59, 830-837	2.3	7
91	Preparation of poly(L-lactide)/poly(ethylene glycol)/organo-modified montmorillonite nanocomposites via melt intercalation under continuous elongation flow. <i>Journal of Polymer Engineering</i> , <b>2018</b> , 38, 449-460	1.4	6
90	Structure-property relationships in polypropylene/poly(ethylene-co-octene)/multiwalled carbon nanotube nanocomposites prepared via a novel eccentric rotor extruder. <i>Journal of Polymer Engineering</i> , <b>2018</b> , 38, 427-435	1.4	4
89	Role of In situ thermal-reduced graphene oxide on the morphology and properties of biodegradable poly(Lactic acid)/poly(butylene succinate) blends. <i>Polymer Composites</i> , <b>2018</b> , 39, 3057-3065	3.5	11
88	The technique of electrospinning for manufacturing core-shell nanofibers. <i>Materials and Manufacturing Processes</i> , <b>2018</b> , 33, 202-219	4.1	18
87	Electrospun poly(vinylidene fluoride) membranes functioning as static charge storage device with controlled crystalline phase by inclusions of nanoscale graphite platelets. <i>Journal of Materials Science</i> , <b>2018</b> , 53, 3038-3048	4.3	6
86	Electrospinning water harvesters inspired by spider silk and beetle. <i>Materials Letters</i> , <b>2018</b> , 211, 28-31	3.3	21
85	Mechanical and thermal properties of polybutylene terephthalate/ethylene-vinyl acetate blends using vane extruder. <i>E-Polymers</i> , <b>2018</b> , 18, 67-73	2.7	4
84	Dimensional impact of nanofillers on the micromorphology and rheology of PP/PS composites under continuous elongation flow. <i>Polymers for Advanced Technologies</i> , <b>2018</b> , 29, 2952-2962	3.2	6
83	Properties and Morphology of Poly(Lactic Acid)/Calcium Carbonate Whiskers Composites Prepared by a Vane Mixer based on an Extensional Flow Field. <i>Journal of Macromolecular Science - Physics</i> , <b>2018</b> , 57, 418-436	1.4	5
82	Preparation and characterization of poly(lactic acid)/sisal fiber bio-composites under continuous elongation flow. <i>Journal of Polymer Engineering</i> , <b>2018</b> , 39, 76-84	1.4	2
81	Morphology, rheology property, and crystallization behavior of PLLA/OMMT nanocomposites prepared by an innovative eccentric rotor extruder. <i>Polymers for Advanced Technologies</i> , <b>2018</b> , 29, 41-51	3.2	35
80	Investigation on Properties of Polypropylene/Multi-walled Carbon Nanotubes Nanocomposites Prepared by a Novel Eccentric Rotor Extruder Based on Elongational Rheology. <i>Journal of Macromolecular Science - Physics</i> , <b>2018</b> , 57, 348-363	1.4	8

79	Electric field-induced alignment of MWCNTs during the processing of PP/MWCNT composites: effects on electrical, dielectric, and rheological properties. <i>Journal of Polymer Engineering</i> , <b>2018</b> , 38, 881-889	1.4	4
78	Chemical structure and thermal properties of lignin modified with polyethylene glycol during steam explosion. <i>Wood Science and Technology</i> , <b>2017</b> , 51, 135-150	2.5	9
77	Preparation of polymer/clay nanocomposites via melt intercalation under continuous elongation flow. <i>Composites Science and Technology</i> , <b>2017</b> , 145, 157-164	8.6	76
76	Electrospinning polyvinylidene fluoride/expanded graphite composite membranes as high efficiency and reusable water harvester. <i>Materials Letters</i> , <b>2017</b> , 202, 78-81	3.3	12
75	Electrospun polyvinylidene fluoride containing nanoscale graphite platelets as electret membrane and its application in air filtration under extreme environment. <i>Polymer</i> , <b>2017</b> , 131, 143-150	3.9	26
74	Polypropylene/polystyrene/clay blends prepared by an innovative eccentric rotor extruder based on continuous elongational flow: Analysis of morphology, rheology property, and crystallization behavior. <i>Polymer Testing</i> , <b>2017</b> , 63, 73-83	4.5	31
73	Manufacturing polymer/clay nanocomposites through elongational flow technique. <i>Materials and Manufacturing Processes</i> , <b>2017</b> , 32, 1409-1415	4.1	11
72	Preparation and characterization of carbon fiber/polylactic acid/thermoplastic polyurethane (CF/PLA/TPU) composites prepared by a vane mixer. <i>Journal of Polymer Engineering</i> , <b>2017</b> , 37, 355-364	1.4	7
71	Polyvinyl alcohol-modified Pithecellobium Clypearia Benth herbal residue fiber/polypropylene composites. <i>Polymer Composites</i> , <b>2016</b> , 37, 915-924	3	52
70	Mechanical, thermal and rheological properties and morphology of poly (lactic acid)/poly (propylene carbonate) blends prepared by vane extruder. <i>Polymers for Advanced Technologies</i> , <b>2016</b> , 27, 1430-1437	3.2	21
69	A promising screw-extrusion steam explosion pretreatment process: effects on the morphological and structural features of Eucalyptus woodchips. <i>RSC Advances</i> , <b>2016</b> , 6, 109657-109663	3.7	8
68	Pithecellobium Clypearia Benth Fiber/Recycled Acrylonitrile-Butadiene-Styrene (ABS) Composites Prepared in a Vane Extruder: Analysis of Mechanical Properties and Morphology. <i>Journal of Macromolecular Science - Physics</i> , <b>2015</b> , 54, 1-16	1.4	4
67	Effect of vibration parameters in plasticizing process on properties of polypropylene by dynamic injection molding. <i>Journal of Thermoplastic Composite Materials</i> , <b>2015</b> , 28, 806-817	1.9	6
66	Poly(lactic acid)/polypropylene and compatibilized poly(lactic acid)/polypropylene blends prepared by a vane extruder: analysis of the mechanical properties, morphology and thermal behavior. <i>Journal of Polymer Engineering</i> , <b>2015</b> , 35, 753-764	1.4	4
65	Properties of heat-treated sisal fiber/polylactide composites. <i>Journal of Thermoplastic Composite Materials</i> , <b>2015</b> , 28, 777-790	1.9	14
64	Study on the properties of polyethylene/montmorillonite nanocomposites prepared by a novel vane mixer. <i>Journal of Applied Polymer Science</i> , <b>2015</b> , 132, n/a-n/a	2.9	6
63	Solids conveying in the solids compaction zone of vane extruder. <i>Polymer Engineering and Science</i> , <b>2015</b> , 55, 719-728	2.3	5
62	Preparation, characterization and properties of PLA/TiO <sub>2</sub> nanocomposites based on a novel vane extruder. <i>RSC Advances</i> , <b>2015</b> , 5, 4639-4647	3.7	74

61	Thermal behavior, dynamic mechanical properties and rheological properties of poly(butylene succinate) composites filled with nanometer calcium carbonate. <i>Polymer Testing</i> , <b>2015</b> , 42, 160-167	4.5	65
60	Flammable and mechanical effects of silica on intumescent flame retardant/ethylene terephthalate copolymer/polypropylene composites. <i>Journal of Thermoplastic Composite Materials</i> , <b>2015</b> , 28, 981-994	1.9	14
59	Effects of dynamic elongational flow on the dispersion and mechanical properties of low-density polyethylene/nanoprecipitated calcium carbonate composites. <i>Polymer Composites</i> , <b>2014</b> , 35, 884-891	3	12
58	Poly(lactic acid)/poly(butylene succinate)/calcium sulfate whiskers biodegradable blends prepared by vane extruder: Analysis of mechanical properties, morphology, and crystallization behavior. <i>Polymer Testing</i> , <b>2014</b> , 34, 1-9	4.5	44
57	Thermoplastic polyurethane/polypropylene blends based on novel vane extruder: A study of morphology and mechanical properties. <i>Polymer Engineering and Science</i> , <b>2014</b> , 54, 716-724	2.3	22
56	Effects of eccentricity, temperature, velocity, and polymer properties on solids compressibility in vane extruder. <i>Polymer Engineering and Science</i> , <b>2014</b> , 54, 1403-1411	2.3	3
55	Study on the properties of nano-TiO <sub>2</sub> /polybutylene succinate composites prepared by vane extruder. <i>Polymer Composites</i> , <b>2014</b> , 35, 53-59	3	26
54	Influences of dicumyl peroxide on morphology and mechanical properties of polypropylene/poly(styrene-b-butadiene-b-styrene) blends via vane-extruder. <i>Journal of Applied Polymer Science</i> , <b>2014</b> , 132, n/a-n/a	2.9	3
53	Morphology, mechanical, and rheological properties of poly(lactic acid)/ethylene acrylic acid copolymer blends processing via vane extruder. <i>Journal of Applied Polymer Science</i> , <b>2014</b> , 131, n/a-n/a	2.9	5
52	Supertoughened Poly(lactic acid)/Polyurethane Blend Material by in Situ Reactive Interfacial Compatibilization via Dynamic Vulcanization. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2014</b> , 53, 17386-17393	3.9	64
51	In-situ thermal reduction and effective reinforcement of graphene nanosheet/poly (ethylene glycol)/poly (lactic acid) nanocomposites. <i>Polymers for Advanced Technologies</i> , <b>2014</b> , 25, 1515-1522	3.2	23
50	Influences of ethylene butylacrylate/glycidyl methacrylate on morphology and mechanical properties of poly(butylene terephthalate)/polyolefin elastomer blends. <i>Journal of Applied Polymer Science</i> , <b>2014</b> , 131, n/a-n/a	2.9	9
49	Total Strain of Newtonian Fluids in a Vane Extruder. <i>Journal of Macromolecular Science - Physics</i> , <b>2014</b> , 53, 800-812	1.4	2
48	Caulis spatholobi residue fiber reinforced biodegradable poly (propylene carbonate) composites: The effect of fiber content on mechanical and morphological properties. <i>Polymer Composites</i> , <b>2014</b> , 35, 208-216	3	10
47	Effects of thermoplastic polyurethane on the properties of poly(lactic acid)/organo-montmorillonite nanocomposites based on novel vane extruder. <i>Polymer Engineering and Science</i> , <b>2014</b> , 54, 2292-2300	2.3	14
46	Numerical Simulation of Mixing Characteristics in a Vane Extruder. <i>Journal of Macromolecular Science - Physics</i> , <b>2014</b> , 53, 358-369	1.4	3
45	Power consumption in the compacting process of polymer particulate solids in a vane extruder. <i>Journal of Applied Polymer Science</i> , <b>2013</b> , 127, 3923-3932	2.9	25
44	Preparation and Characterization of Cross-Linked Poly(butylene succinate) by Multifunctional Toluene Diisocyanate/Trimethylolpropane Polyurethane Prepolymer. <i>Industrial &amp; Engineering Chemistry Research</i> , <b>2013</b> , 52, 13677-13684	3.9	28

43	Novel dynamic elongational flow procedure for reinforcing strong, tough, thermally stable polypropylene/thermoplastic polyurethane blends. <i>Langmuir</i> , <b>2013</b> , 29, 13509-17	4	24
42	Non-isothermal crystallization kinetics and morphology of mica particles filled biodegradable poly(butylene succinate). <i>Journal of Applied Polymer Science</i> , <b>2013</b> , 130, 2544-2556	2.9	7
41	Morphology study of immiscible polymer blends in a vane extruder. <i>Journal of Applied Polymer Science</i> , <b>2013</b> , 128, 3576-3585	2.9	42
40	Multifractal analysis on dispersion of immiscible high-density polyethylene/polystyrene blends processed via polymer vane plasticating extruder. <i>Journal of Applied Polymer Science</i> , <b>2013</b> , 130, 2328-2333	2.9	12
39	Mechanical and thermal properties of epoxidized soybean oil plasticized polybutylene succinate blends. <i>Polymers for Advanced Technologies</i> , <b>2012</b> , 23, 632-638	3.2	30
38	Solid conveying in vane extruder for polymer processing: Effects on pressure establishment. <i>Polymer Engineering and Science</i> , <b>2012</b> , 52, 2147-2156	2.3	50
37	Mechanical Properties of Poly(Butylene Succinate) Reinforced with Continuously Steam-Exploded Cotton Stalk Bast. <i>Polymer-Plastics Technology and Engineering</i> , <b>2011</b> , 50, 1405-1411		11
36	Effect of initial fiber length on the rheological properties of sisal fiber/polylactic acid composites. <i>Polymer Composites</i> , <b>2011</b> , 32, 1218-1224	3	9
35	Preparation and properties of PBS/sisal-fiber composites. <i>Polymer Engineering and Science</i> , <b>2011</b> , 51, 474-481	2.3	20
34	Theoretical and experimental study of the melting process of high-density polyethylene for multidimensional vibration equipment. <i>Journal of Applied Polymer Science</i> , <b>2011</b> , 120, 2912-2920	2.9	
33	The Effects of Temperature and Roll Pressing on the Properties of iPP Sheets. <i>Polymer-Plastics Technology and Engineering</i> , <b>2010</b> , 49, 1108-1113		1
32	Multivariable fuzzy decoupling control of the polymer electromagnetism dynamic extrusion process. <i>Journal of Applied Polymer Science</i> , <b>2010</b> , 116, 568-576	2.9	26
31	Effects of the vibration parameters of a hydraulic, dynamic injection-molding machine on the properties of low-density polyethylene samples in a plasticating process. <i>Journal of Applied Polymer Science</i> , <b>2010</b> , 117, 1208-1212	2.9	9
30	Mechanical and rheological properties of epoxidized soybean oil plasticized poly(lactic acid). <i>Journal of Applied Polymer Science</i> , <b>2009</b> , 112, 3185-3191	2.9	98
29	Predictability of apparent viscosity in a vibratory shearing flow field. <i>Journal of Applied Polymer Science</i> , <b>2009</b> , 113, 1560-1565	2.9	1
28	Melt rheology of poly (lactic acid) plasticized by epoxidized soybean oil. <i>Wuhan University Journal of Natural Sciences</i> , <b>2009</b> , 14, 349-354	0.4	18
27	Computer-aided experiment of using real-time small angle light scattering image processing technique for visual characterization flow field of polymer melts. <i>Polymer Bulletin</i> , <b>2009</b> , 62, 345-354	2.4	1
26	The Preparation of Polypropylene/Wollastonite Composites with Tri-screw Dynamic Compounding Extruder. <i>Polymer-Plastics Technology and Engineering</i> , <b>2009</b> , 48, 260-264		5

25	Characteristics Study of Polymer Melt Conveying Capacity in Vane Plasticization Extruder. <i>Polymer-Plastics Technology and Engineering</i> , <b>2009</b> , 48, 1269-1274		40
24	Orientation Kinetics of Screw-Axial Vibration on Glass Fiber Reinforced Polypropylene Composites. <i>Polymer-Plastics Technology and Engineering</i> , <b>2008</b> , 47, 186-198		3
23	Extrusion Characteristics of Round-Section Dies with VFF. <i>Polymer-Plastics Technology and Engineering</i> , <b>2008</b> , 47, 203-208		
22	Modeling of coat-hanger die under vibrational extrusion. <i>Journal of Applied Polymer Science</i> , <b>2008</b> , 107, 1006-1019	2.9	2
21	Effect of the axial vibration of screw on total shear strain distribution of melt in single-screw extruders. <i>Journal of Applied Polymer Science</i> , <b>2008</b> , 108, 3917-3926	2.9	2
20	Melting process and mechanism for vibration induced single-screw extruder. <i>Journal of Applied Polymer Science</i> , <b>2007</b> , 104, 2504-2514	2.9	5
19	Rheological behavior of a polymer melt under the impact of a vibration force field. <i>Journal of Applied Polymer Science</i> , <b>2007</b> , 106, 1152-1159	2.9	9
18	Optimization of water absorption of starch/PVA composites. <i>Polymer Composites</i> , <b>2007</b> , 28, 674-679	3	28
17	The Effect of Vibration on Mechanical Properties of Blends of EPDM/PP in a Tri-screw Dynamic Mixing Extruder. <i>Polymer-Plastics Technology and Engineering</i> , <b>2007</b> , 46, 795-799		
16	Influence of Vibration on Density of Polymer Solid Granules in Single Screw Extruder. <i>Polymer-Plastics Technology and Engineering</i> , <b>2007</b> , 46, 233-237		5
15	Experimental Study on the Influence of Pulsatile Injection Pressure on Filling Pressure and Filling Time. <i>Polymer-Plastics Technology and Engineering</i> , <b>2007</b> , 46, 709-712		
14	Effect of screw axial vibration on polymer melting process in single-screw extruders. <i>Journal of Applied Polymer Science</i> , <b>2006</b> , 100, 3860-3876	2.9	10
13	Effect of vibration parameters of electromagnetic dynamic plastics injection molding machine on mechanical properties of polypropylene samples. <i>Journal of Applied Polymer Science</i> , <b>2006</b> , 102, 972-976	2.9	13
12	Phase morphology control of immiscible polymer blends under vibration force field. <i>Journal of Applied Polymer Science</i> , <b>2006</b> , 102, 2299-2307	2.9	4
11	Simulation of nonisothermal flow of melt during melting process of vibration-induced polymer extruder. <i>Journal of Applied Polymer Science</i> , <b>2006</b> , 102, 5825-5840	2.9	1
10	Study on Energy Ratio Model for Phase Morphology of Immiscible Polymer Blends. <i>Polymer-Plastics Technology and Engineering</i> , <b>2006</b> , 45, 971-977		2
9	Effect of Vibrating Extrusion on the Structure and Mechanical Properties of Isotactic Polypropylene. <i>Polymer-Plastics Technology and Engineering</i> , <b>2006</b> , 45, 1065-1071		8
8	Experimental Studies and Mathematical Modeling of Melt-Pulsed Conveying in Screw Extruders. <i>Polymer-Plastics Technology and Engineering</i> , <b>2006</b> , 45, 1137-1142		3



7	Effect of the axial vibration of screw on residence time distribution in single-screw extruders. <i>Polymer Engineering and Science</i> , <b>2006</b> , 46, 198-204	2.3	4
6	Mechanical properties and morphological behavior of calcium carbonate-filled polypropylene in dynamic injection molding. <i>Polymer International</i> , <b>2006</b> , 55, 1330-1335	3.3	15
5	Nonaffine network structural model for molten Low-Density polyethylene and High-Density Polyethylene in oscillatory shear. <i>Journal of Shanghai University</i> , <b>2002</b> , 6, 292-296		9
4	Study on the pulsating extrusion characteristics of polymer melt through round-sectioned die. <i>Polymer-Plastics Technology and Engineering</i> , <b>2002</b> , 41, 115-132		38
3	Isogeometric analysis based on geometric reconstruction models. <i>Frontiers of Mechanical Engineering</i> , 1	3.3	2
2	A synergistic photothermal and photocatalytic membrane for efficient solar-driven contaminated water treatment. <i>Sustainable Energy and Fuels</i> ,	5.8	3
1	A Multifunctional Flexible Composite Film with Excellent Multi-Source Driven Thermal Management, Electromagnetic Interference Shielding, and Fire Safety Performance, Inspired by a Brick-Mortar-Sandwich Structure. <i>Advanced Functional Materials</i> , 2200570	15.6	14