## Chairul Hudaya

## List of Publications by Citations

Source: https://exaly.com/author-pdf/4335583/chairul-hudaya-publications-by-citations.pdf

Version: 2024-04-10

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

37 papers	471	11	<b>21</b>
	citations	h-index	g-index
53	557 ext. citations	5.4	3.74
ext. papers		avg, IF	L-index

#	Paper	IF	Citations
37	Phenyl-rich silicone oil as a precursor for SiOC anode materials for long-cycle and high-rate lithium ion batteries. <i>Journal of Materials Chemistry A</i> , <b>2016</b> , 4, 2651-2656	13	66
36	Oxidation-resistant hybrid metal oxides/metal nanodots/silver nanowires for high performance flexible transparent heaters. <i>Nanoscale</i> , <b>2016</b> , 8, 3307-13	7.7	48
35	Self-Relaxant Superelastic Matrix Derived from C Incorporated Sn Nanoparticles for Ultra-High-Performance Li-Ion Batteries. <i>ACS Nano</i> , <b>2018</b> , 12, 5588-5604	16.7	45
34	High thermal performance of SnO2:F thin transparent heaters with scattered metal nanodots. <i>ACS Applied Materials &amp; District Sciences</i> , <b>2015</b> , 7, 57-61	9.5	44
33	Pseudocapacitive Characteristics of Low-Carbon Silicon Oxycarbide for Lithium-Ion Capacitors. <i>ACS Applied Materials &amp; Discourse (Materials &amp; Discourse)</i> , 9, 20566-20576	9.5	41
32	Al-C hybrid nanoclustered anodes for lithium ion batteries with high electrical capacity and cyclic stability. <i>Chemical Communications</i> , <b>2014</b> , 50, 2837-40	5.8	40
31	An elastic carbon layer on echeveria-inspired SnO2 anode for long-cycle and high-rate lithium ion batteries. <i>Carbon</i> , <b>2015</b> , 94, 539-547	10.4	34
30	SnO2-coated LiCoO2 cathode material for high-voltage applications in lithium-ion batteries. <i>Solid State Ionics</i> , <b>2014</b> , 256, 89-92	3.3	27
29	Plasma-polymerized C60 as a functionalized coating layer on fluorine-doped tin oxides for anode materials of lithium-ion batteries. <i>Carbon</i> , <b>2015</b> , 81, 835-838	10.4	20
28	Effects of process parameters on sheet resistance uniformity of fluorine-doped tin oxide thin films. <i>Nanoscale Research Letters</i> , <b>2012</b> , 7, 17	5	20
27	A polymerized C60 coating enhancing interfacial stability at three-dimensional LiCoO2 in high-potential regime. <i>Journal of Power Sources</i> , <b>2015</b> , 298, 1-7	8.9	18
26	Characteristics of Fluorine-Doped Tin Oxide as a Transparent Heater on PET Prepared by ECR-MOCVD. <i>ECS Transactions</i> , <b>2013</b> , 53, 161-166	1	7
25	Effects of annealing temperature on the electrochemical characteristics of ZnO microrods as anode materials of lithium-ion battery using chemical bath deposition. <i>Jonics</i> , <b>2019</b> , 25, 457-466	2.7	7
24	Electrochemical performance of low concentration Al doped-lithium titanate anode synthesized via sol-gel for lithium ion capacitor applications. <i>Journal of Energy Storage</i> , <b>2020</b> , 29, 101480	7.8	6
23	Electrochemical characteristics of ZnO patterned column/SnO2 films for anodic electrodes of lithium ion batteries. <i>Thin Solid Films</i> , <b>2013</b> , 546, 404-409	2.2	5
22	Implementation of talis and dc house system for rural areas in indonesia. <i>MATEC Web of Conferences</i> , <b>2018</b> , 218, 01006	0.3	5
21	Solar-Powered Base Transceiver Station <b>2018</b> ,		4

20	Antiglare and antireflective coating of layer-by-layer SiO2 and TiZrO2 on surface-modified glass. <i>Applied Surface Science</i> , <b>2019</b> , 490, 278-282	6.7	3
19	The characteristics of heat inside a parked car as energy source for thermoelectric generators. <i>International Journal of Energy and Environmental Engineering</i> , <b>2019</b> , 10, 347-356	4	3
18	Nanostructural Growth Investigation of ZnO Nanorods Derived from Chemical Bath Deposition for Transparent Heater Application <b>2018</b> , 9, 1216		3
17	Pilot-scale electron cyclotron resonance-metal organic chemical vapor deposition system for the preparation of large-area fluorine-doped SnO2 thin films. <i>Journal of Vacuum Science and Technology A: Vacuum, Surfaces and Films</i> , <b>2016</b> , 34, 031501	2.9	3
16	Analysis of Power Transformer WLifetime Using Health Index Transformer Method Based on Artificial Neural Network Modeling <b>2019</b> ,		3
15	Building Integrated Photovoltaic for Rooftop and Facade Application in Indonesia 2018,		2
14	NaCrO2/Coffee Wastederived Nitrogen-doped Carbon Composite as High-Performance Cathode Material for Sodium Ion Batteries. <i>Bulletin of the Korean Chemical Society</i> , <b>2019</b> , 40, 857-862	1.2	2
13	Total cost of ownership analysis of 60 MVA 150/120 kV power transformer <b>2017</b> ,		2
12	The Influence of Deposition Time and Substrate Temperature during the Spray Pyrolysis Process on the Electrical Resistivity and Optical Transmittance of 2 wt% Fluorine-doped Tin Oxide Conducting Glass <b>2016</b> , 7, 1335		2
11	Design and Implementation Study of 3.12 kWp On Grid Rooftop Solar PV System <b>2019</b> ,		2
10	Effects of Harmonic Distortions on the Accuracy of Energy and Power Losses Measurements in a Water Treatment Industry <b>2019</b> ,		1
9	Simultaneous etching and transfer IFree multilayer graphene sheets derived from C60 thin films. <i>Journal of Industrial and Engineering Chemistry</i> , <b>2018</b> , 64, 70-75	6.3	1
8	Electricity price and subsidy scenario for hybrid power generations on off-grid system 2017,		1
7	Characteristics of Disturbance in Frequency 9 -150 kHz of Photovoltaic System under Fluctuated Solar Irradiance <b>2019</b> ,		1
6	The effect of activated carbon and silicon oxycarbide as anode materials on lithium-ion battery. <i>E3S Web of Conferences</i> , <b>2018</b> , 67, 03027	0.5	1
5	The effects of drying time during manufacturing process on partial discharge of 83.3 mva 275/160 kv power transformer. <i>MATEC Web of Conferences</i> , <b>2018</b> , 218, 04008	0.3	1
4	Labeling and Grouping of Light Emitting Diode Lamps based on Its Power Quality and Efficacy Level <b>2018</b> ,		1
3	The design of alternative electric energy utilizes solar heat in the vehicle cabin with thermoelectric module <b>2017</b> ,		O

2	Comparison of characteristics of fluorine doped zinc and gallium tin oxide composite thin films deposited on stainless steel 316 bipolar plate by electron cyclotron resonance-metal organic chemical vapor deposition for proton exchange membrane fuel cells. <i>Journal of Nanoscience and</i>	1.3
1	Nanotechnology, <b>2011</b> , 11, 7999-8003  Electrical discharge phenomenon of electrode gaps in oil insulation. <i>MATEC Web of Conferences</i> , <b>2018</b> , 197, 11005	0.3