

Hongtao Yu

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/4444238/publications.pdf>

Version: 2024-02-01

37
papers

761
citations

623734

14
h-index

526287

27
g-index

37
all docs

37
docs citations

37
times ranked

690
citing authors

#	ARTICLE	IF	CITATIONS
1	Phase composition and microwave dielectric properties of $\text{Ca}_{0.128}\text{Ba}_{0.032}\text{Sm}_{0.46}\text{Li}_{0.3}\text{TiO}_3$ ceramics with alumina addition. <i>Journal of the European Ceramic Society</i> , 2022, 42, 1480-1485.	5.7	9
2	Ultra-high quality factor of $\text{Mg}_6\text{Ti}_5\text{O}_{16}$ -based microwave dielectric ceramics with temperature stability. <i>Journal of Materials Science: Materials in Electronics</i> , 2021, 32, 2547-2556.	2.2	8
3	NiNb_2O_6 /poly(arylene ether nitriles) composite film dielectrics with excellent flexibility and high permittivity for organic film capacitors. <i>Polymer Composites</i> , 2020, 41, 94-101.	4.6	5
4	Formation mechanism and microstructure evolution of $\text{Ba}_2\text{Ti}_9\text{O}_{20}$ ceramics by reaction sintering method. <i>Journal of the American Ceramic Society</i> , 2020, 103, 1079-1087.	3.8	13
5	Improvement of microwave dielectric properties of $\text{Ba}_2\text{Ti}_9\text{O}_{20}$ ceramics using $[\text{Zn}_{1/3}\text{Nb}_{2/3}]^{4+}$ substitution for Ti^{4+} . <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 15184-15191.	2.2	3
6	Phase evolution and microwave dielectric properties of BaTi_4O_9 ceramics prepared by reaction sintering method. <i>International Journal of Applied Ceramic Technology</i> , 2019, 16, 146-151.	2.1	15
7	Low dielectric constant benzocyclobutene organosilicon resins constructed from cyclotetrasiloxane. <i>Journal of Applied Polymer Science</i> , 2019, 136, 47465.	2.6	13
8	Improvement of quality factor of SrTi_3O_3 dielectric ceramics with high dielectric constant using Sm_{2}O_3 . <i>Journal of the American Ceramic Society</i> , 2019, 102, 3849-3853.	3.8	13
9	Stabilizing temperature capacitance dependence of $(\text{Sr}, \text{Pb})_{1-x}\text{Ti}_x\text{O}_3$ relaxor ceramics. <i>Journal of the American Ceramic Society</i> , 2019, 102, 4029-4037.	3.8	13
10	Effect of ZnO on Mg_2Ti_4 based microwave dielectric ceramics prepared by reaction sintering route. <i>Advances in Applied Ceramics</i> , 2019, 118, 98-105.	1.1	24
11	Polyethylene/silica nanorod composites with reduced dielectric constant and enhanced mechanical strength. <i>Journal of Applied Polymer Science</i> , 2019, 136, 47143.	2.6	15
12	Phase compositions and microwave dielectric properties of MgTiO_3 -based ceramics obtained by reaction-sintering method. <i>Journal of Electroceramics</i> , 2018, 40, 360-364.	2.0	12
13	NiNb_2O_6 / BaTiO_3 Ceramics for Energy Storage Capacitors. <i>Energy Technology</i> , 2018, 6, 899-905.	3.8	15
14	High discharge efficiency of $(\text{Sr}, \text{Pb}, \text{Bi})\text{TiO}_3$ relaxor ceramics for energy-storage application. <i>Applied Physics Letters</i> , 2018, 112, .	3.3	29
15	$0.73\text{ZrTi}_2\text{O}_6$ / $0.27\text{MgNb}_2\text{O}_6$ microwave dielectric ceramics modified by Al_2O_3 addition. <i>Journal of the American Ceramic Society</i> , 2018, 101, 5110-5119.	3.8	18
16	Hydrofluoric Acid Modified Porous Magnesia Fibers as Immobilizing Agent for Molten Electrolyte in Thermal Battery. <i>Electrochemistry</i> , 2017, 85, 451-455.	1.4	5
17	Using MgO fibers to immobilize molten electrolyte in thermal batteries. <i>Journal of Solid State Electrochemistry</i> , 2016, 20, 1355-1360.	2.5	13
18	Low temperature sintering of $\text{Zn}_{1.8}\text{SiO}_{3.8}$ dielectric ceramics containing $3\text{ZnO} \cdot 2\text{B}_2\text{O}_3$ glass. <i>Materials Letters</i> , 2016, 179, 150-153.	2.6	9

#	ARTICLE	IF	CITATIONS
19	Dielectric characteristics of B-site-modified hexagonal-barium titanate. Journal of Materials Science: Materials in Electronics, 2016, 27, 2836-2840.	2.2	4
20	Structure and dielectric properties of zinc borate glass-ceramics modified by magnesium. Journal of Materials Science: Materials in Electronics, 2016, 27, 7109-7114.	2.2	14
21	Ultra-low sintering temperature ceramics for LTCC applications: a review. Journal of Materials Science: Materials in Electronics, 2015, 26, 9414-9423.	2.2	85
22	Tape casting and dielectric properties of SiO ₂ -filled glass composite ceramic with an ultra-low sintering temperature. Journal of Materials Science: Materials in Electronics, 2014, 25, 5114-5118.	2.2	9
23	Magnetic and microwave absorption properties of BaMn _x Co _{1-x} TiFe ₁₀ O ₁₉ . Journal of Alloys and Compounds, 2014, 588, 212-216.	5.5	85
24	A Novel Glass-Ceramic with Ultra-Low Sintering Temperature for LTCC Application. Journal of the American Ceramic Society, 2014, 97, 704-707.	3.8	28
25	Phase composition and microwave dielectric properties of Mg-excess MgTiO ₃ ceramics. Journal of Materials Science: Materials in Electronics, 2013, 24, 1287-1291.	2.2	31
26	Ultra-Low Temperature Sintering and Dielectric Properties of SiO ₂ -Filled Glass Composites. Journal of the American Ceramic Society, 2013, 96, 3563-3568.	3.8	30
27	Correlation between Sn substitution for Ti and Microwave Dielectric Properties of Magnesium Titanate Ceramics. International Journal of Applied Ceramic Technology, 2013, 10, E186.	2.1	4
28	Effect of interface layer on dielectric and magnetic properties of 2 nd type Ba ₂ Ti ₉ O ₂₀ -BaFe ₁₂ O ₁₉ composite ceramics. Ceramics International, 2012, 38, 4407-4410.	4.8	5
29	Microwave dielectric properties of Mg(Zr _{0.05} Ti _{0.95})O ₃ -SrTiO ₃ ceramics. Journal of Materials Science: Materials in Electronics, 2012, 23, 572-575.	2.2	4
30	Synthesis of nanocrystalline yttrium iron garnet by low temperature solid state reaction. Materials Characterization, 2011, 62, 378-381.	4.4	26
31	The microstructures and dielectric properties of xSrZrO ₃ -(1-x)SrTiO ₃ ceramics. Journal of Electroceramics, 2008, 21, 210-213.	2.0	11
32	Microwave synthesis of high dielectric constant CaCu ₃ Ti ₄ O ₁₂ . Journal of Materials Processing Technology, 2008, 208, 145-148.	6.3	47
33	Dielectric properties of CaCu ₃ Ti ₄ O ₁₂ ceramics modified by SrTiO ₃ . Materials Letters, 2008, 62, 1353-1355.	2.6	65
34	Grain size dependence of relaxor behavior in CaCu ₃ Ti ₄ O ₁₂ ceramics. Applied Physics Letters, 2007, 91, 222911.	3.3	52
35	Effect of B-Site Bond Valence on Microwave Dielectric Properties of Ca[(Zn _{1/3} Nb _{2/3})(1-x)Ti _x] ₂ O ₉ . Journal of Applied Physics, 2006, 100, 064101.	0.6	5
36	Effect of CuO on Microstructure and Microwave Dielectric Properties of CaTiO ₃ -Ca(Zn _{1/3} Nb _{2/3})O ₃ Ceramics System. Materials Research Society Symposia Proceedings, 2006, 966, 1.	0.1	0

#	ARTICLE	IF	CITATIONS
37	Dielectric Properties of (1-x)CaTiO ₃ -xCa(Zn _{1/3} Nb _{2/3})O ₃ Ceramic System at Microwave Frequency. Journal of the American Ceramic Society, 2005, 88, 453-455.	3.8	24