

# Radosław Mirski

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/4732619/publications.pdf>

Version: 2024-02-01

53  
papers

556  
citations

623734  
14  
h-index

713466  
21  
g-index

53  
all docs

53  
docs citations

53  
times ranked

365  
citing authors

#	ARTICLE	IF	CITATIONS
1	Possibility to Use Short Sawn Timber in the Production of Glued Laminated Beams. <i>Materials</i> , 2022, 15, 2992.	2.9	4
2	The Possibility to Use Pine Timber Pieces with Small Size in the Production of Glulam Beams. <i>Materials</i> , 2022, 15, 3154.	2.9	3
3	The Effect of Periodic Loading of Glued Laminated Beams on Their Static Bending Strength. <i>Materials</i> , 2022, 15, 3928.	2.9	2
4	The Strength of Pine ( <i>Pinus sylvestris</i> L.) Sawn Timber in Correlation with Selected Wood Defects. <i>Materials</i> , 2022, 15, 3974.	2.9	5
5	GL Beams Reinforced with Plywood in the Outer Layer. <i>Materials</i> , 2022, 15, 3976.	2.9	3
6	Quality and Dimensional Parameters of Large-Sized Pine Timber in View of Expectations of Polish Sawmill Industry. <i>Drvena Industrija</i> , 2022, 73, 335-340.	0.6	0
7	The reduction of adhesive application in plywood manufacturing by using nanocellulose reinforced urea-formaldehyde resin. <i>Journal of Applied Polymer Science</i> , 2021, 138, 49834.	2.6	22
8	The possibility to use a side-timber in glulam beams manufacturing for structural applications. <i>Annals of WULS Forestry and Wood Technology</i> , 2021, 113, 65-73.	0.2	2
9	Selected Properties of Formaldehyde-Free Polymer-Straw Boards Made from Different Types of Thermoplastics and Different Kinds of Straw. <i>Materials</i> , 2021, 14, 1216.	2.9	7
10	Efficiency of Machine Sanding of Wood. <i>Applied Sciences (Switzerland)</i> , 2021, 11, 2860.	2.5	15
11	Strength Properties of Structural Glulam Elements from Pine ( <i>Pinus sylvestris</i> L.) Timber Reinforced in the Tensile Zone with Steel and Basalt Rods. <i>Materials</i> , 2021, 14, 2574.	2.9	14
12	Lightweight Insulation Boards Based on Lignocellulosic Particles Glued with Agents of Natural Origin. <i>Materials</i> , 2021, 14, 3219.	2.9	3
13	Pine Logs Sorting as a Function of Bark Thickness. <i>Forests</i> , 2021, 12, 893.	2.1	4
14	Waste Wood Particles from Primary Wood Processing as a Filler of Insulation PUR Foams. <i>Materials</i> , 2021, 14, 4781.	2.9	14
15	Properties of Eco-Friendly Particleboards Bonded with Lignosulfonate-Urea-Formaldehyde Adhesives and pMDI as a Crosslinker. <i>Materials</i> , 2021, 14, 4875.	2.9	50
16	Influence of the Structure of Lattice Beams on Their Strength Properties. <i>Materials</i> , 2021, 14, 5765.	2.9	1
17	Strength Properties of Structural Glulam Manufactured from Pine ( <i>Pinus sylvestris</i> L.) Side Boards. <i>Materials</i> , 2021, 14, 7312.	2.9	4
18	The Usefulness of Pine Timber ( <i>Pinus sylvestris</i> L.) for the Production of Structural Elements. Part I: Evaluation of the Quality of the Pine Timber in the Bending Test. <i>Materials</i> , 2020, 13, 3957.	2.9	19

#	ARTICLE	IF	CITATIONS
19	A Qualitative Analysis of Sawn Timber Obtained from Various Sites Throughout Poland in the Aspect of Polish and European Standards of Quality. <i>Forests</i> , 2020, 11, 713.	2.1	1
20	The Usefulness of Pine Timber ( <i>Pinus sylvestris</i> L.) for the Production of Structural Elements. Part II: Strength Properties of Glued Laminated Timber. <i>Materials</i> , 2020, 13, 4029.	2.9	16
21	The Application of Oak Bark Powder as a Filler for Melamine-Urea-Formaldehyde Adhesive in Plywood Manufacturing. <i>Forests</i> , 2020, 11, 1249.	2.1	32
22	By-products of sawmill industry as raw materials for manufacture of chip-sawdust boards. <i>Journal of Building Engineering</i> , 2020, 32, 101460.	3.4	16
23	Effects of Chip Type on the Properties of Chipboard Sawdust Boards Glued with Polymeric Diphenyl Methane Diisocyanate. <i>Materials</i> , 2020, 13, 1329.	2.9	11
24	Properties of Plywood Produced with Urea-Formaldehyde Adhesive Modified with Nanocellulose and Microcellulose. <i>Drvna Industrija</i> , 2020, 71, 61-67.	0.6	15
25	Hemp flour as a formaldehyde scavenger for melamine-urea-formaldehyde adhesive in plywood production. <i>BioResources</i> , 2020, 15, 4052-4064.	1.0	20
26	The effect of nanocellulose addition to phenol-formaldehyde adhesive in water-resistant plywood manufacturing. <i>BioResources</i> , 2020, 15, 5388-5401.	1.0	20
27	The possible reduction of phenol-formaldehyde resin spread rate by its nanocellulose-reinforcement in plywood manufacturing process. <i>Annals of WULS Forestry and Wood Technology</i> , 2020, 111, 21-26.	0.2	0
28	Construction board resistance to accelerated aging. <i>BioResources</i> , 2020, 15, 2680-2690.	1.0	2
29	Effects of a Chipboard Structure on Its Physical and Mechanical Properties. <i>Materials</i> , 2019, 12, 3777.	2.9	11
30	Relationships between Thermoplastic Type and Properties of Polymer-Triticale Boards. <i>Polymers</i> , 2019, 11, 1750.	4.5	9
31	The effect of phenol-formaldehyde adhesive modification with fire retardant on the properties of birch plywood. <i>Annals of WULS Forestry and Wood Technology</i> , 2019, 106, 197-113.	0.2	0
32	Raw material factors affecting the quota of structural wood in sawmill production. <i>Annals of WULS Forestry and Wood Technology</i> , 2019, 107, 124-130.	0.2	0
33	Influence of qualitative and dimensional classification of Pinewood raw material as an efficiency indicator in the production of selected timber assortments. <i>Annals of WULS Forestry and Wood Technology</i> , 2019, 107, 72-79.	0.2	0
34	Possibility of Using Fine Wood Strands for the Production of P5 Type Building Boards. <i>BioResources</i> , 2018, 13, .	1.0	5
35	Properties of Particleboards Produced from Various Lignocellulosic Particles. <i>BioResources</i> , 2018, 13, .	1.0	15
36	Construction particleboards made from rapeseed straw glued with hybrid pMDI/PF resin. <i>European Journal of Wood and Wood Products</i> , 2017, 75, 175-184.	2.9	35

#	ARTICLE	IF	CITATIONS
37	The Possibility to Use Long Fibres from Fast Growing Hemp ( <i>Cannabis sativa</i> L.) for the Production of Boards for the Building and Furniture Industry. <i>BioResources</i> , 2017, 12, .	1.0	16
38	Dimensional stability of oriented strand boards with external layers made of non-strand chips: Changes in board length. <i>BioResources</i> , 2017, 12, 7107-7117.	1.0	1
39	The Possibility of Replacing Strands in the Core Layer of Oriented Strand Board by Particles from the Stems of Rape ( <i>Brassica napus</i> L. var. <i>napus</i> ). <i>BioResources</i> , 2016, 11, .	1.0	4
40	Properties of Oriented Strand Boards with External Layers made of Non-Strand Chips. <i>BioResources</i> , 2016, 11, .	1.0	3
41	Possibility of using the expanded polystyrene and rape straw to the manufacture of lightweight particleboards. <i>Maderas: Ciencia Y Tecnologia</i> , 2015, , 0-0.	0.7	9
42	Low-Density Oriented Strand Boards. <i>BioResources</i> , 2015, 10, .	1.0	5
43	Sound absorption of wood-based materials. <i>Holzforschung</i> , 2015, 69, 431-439.	1.9	37
44	Possibility of Using Accelerated Aging Tests to Assess the Performance of OSBs Exposed to Environmental Conditions. <i>BioResources</i> , 2014, 9, .	1.0	4
45	Properties of Liquid and Polycondensed UF Resin Modified with pMDI. <i>Drvna Industrija</i> , 2014, 65, 115-119.	0.6	19
46	Experimental study of wood acoustic absorption characteristics. <i>Holzforschung</i> , 2014, 68, 467-476.	1.9	27
47	The Influence of Microfungi on Physicomechanical Properties of Particleboards. <i>BioResources</i> , 2014, 9, .	1.0	1
48	Lightweight boards from wood and rape straw particles. , 2013, 56, 19-31.		3
49	Dimensional Stability of OSB Panels Subjected to Variable Relative Humidity: Core Layer Made with Fine Wood Chips. <i>BioResources</i> , 2013, 8, .	1.0	2
50	The Effect of Residual Swelling after Drying on Internal Bond in OSB. <i>Drvna Industrija</i> , 2012, 63, 241-247.	0.6	0
51	Potential of shortening pressing time or reducing pressing temperature for plywood resinated with PF resin modified using Alcohols and esters. <i>European Journal of Wood and Wood Products</i> , 2011, 69, 317-323.	2.9	20
52	The Utilization of Chips from Comminuted Wood Waste as a Substitute for Flakes in the Oriented Strand Board Core. <i>Forest Products Journal</i> , 2011, 61, 473-477.	0.4	8
53	Properties of phenol-formaldehyde resin modified with organic acid esters. <i>Journal of Applied Polymer Science</i> , 2008, 107, 3358-3366.	2.6	17