

List of Publications by Citations

Source: <https://exaly.com/author-pdf/4774303/jiyong-publications-by-citations.pdf>
Version: 2024-04-09

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.
The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

79 papers	1,767 citations	22 h-index	40 g-index
92 ext. papers	2,118 ext. citations	3.8 avg, IF	5.06 L-index

#	Paper	IF	Citations
79	Improved Synaptic Behavior Under Identical Pulses Using AlOx/HfO2 Bilayer RRAM Array for Neuromorphic Systems. <i>IEEE Electron Device Letters</i> , 2016 , 37, 994-997	4.4	253
78	HfZrOx-Based Ferroelectric Synapse Device With 32 Levels of Conductance States for Neuromorphic Applications. <i>IEEE Electron Device Letters</i> , 2017 , 38, 732-735	4.4	140
77	TiOx-Based RRAM Synapse With 64-Levels of Conductance and Symmetric Conductance Change by Adopting a Hybrid Pulse Scheme for Neuromorphic Computing. <i>IEEE Electron Device Letters</i> , 2016 , 37, 1559-1562	4.4	123
76	. <i>IEEE Electron Device Letters</i> , 2015 , 36, 681-683	4.4	115
75	Demonstration of Low Power 3-bit Multilevel Cell Characteristics in a TaOx-Based RRAM by Stack Engineering. <i>IEEE Electron Device Letters</i> , 2015 , 36, 32-34	4.4	86
74	Comprehensive scaling study of NbO2 insulator-metal-transition selector for cross point array application. <i>Applied Physics Letters</i> , 2016 , 108, 153502	3.4	61
73	Resistive Memory-Based Analog Synapse: The Pursuit for Linear and Symmetric Weight Update. <i>IEEE Nanotechnology Magazine</i> , 2018 , 12, 36-44	1.7	54
72	Optimized Programming Scheme Enabling Linear Potentiation in Filamentary HfO2 RRAM Synapse for Neuromorphic Systems. <i>IEEE Transactions on Electron Devices</i> , 2016 , 63, 5064-5067	2.9	53
71	Linking Conductive Filament Properties and Evolution to Synaptic Behavior of RRAM Devices for Neuromorphic Applications. <i>IEEE Electron Device Letters</i> , 2017 , 38, 1220-1223	4.4	49
70	Threshold switching behavior of Ag-Si based selector device and hydrogen doping effect on its characteristics. <i>AIP Advances</i> , 2015 , 5, 127221	1.5	43
69	Structurally engineered stackable and scalable 3D titanium-oxide switching devices for high-density nanoscale memory. <i>Advanced Materials</i> , 2015 , 27, 59-64	2.4	37
68	Steep Slope Field-Effect Transistors With Ag/TiO2-Based Threshold Switching Device. <i>IEEE Electron Device Letters</i> , 2016 , 37, 932-934	4.4	36
67	Bidirectional threshold switching in engineered multilayer (Cu2O/Ag:Cu2O/Cu2O) stack for cross-point selector application. <i>Applied Physics Letters</i> , 2015 , 107, 113504	3.4	34
66	Nanoscale (~10nm) 3D vertical ReRAM and NbO2 threshold selector with TiN electrode 2013 ,		28
65	Dual functionality of threshold and multilevel resistive switching characteristics in nanoscale HfO 2-based RRAM devices for artificial neuron and synapse elements. <i>Microelectronic Engineering</i> , 2017 , 182, 42-45	2.5	28
64	Control of Cu Conductive Filament in Complementary Atom Switch for Cross-Point Selector Device Application. <i>IEEE Electron Device Letters</i> , 2014 , 35, 60-62	4.4	27
63	Two-Terminal Structured Synaptic Device Using Ionic Electrochemical Reaction Mechanism for Neuromorphic System. <i>IEEE Electron Device Letters</i> , 2019 , 40, 546-549	4.4	26

62	Understanding and Optimization of Pulsed SET Operation in HfOx-Based RRAM Devices for Neuromorphic Computing Applications. <i>IEEE Electron Device Letters</i> , 2018 , 39, 672-675	4.4	26
61	Self-Limited CBRAM With Threshold Selector for 1S1R Crossbar Array Applications. <i>IEEE Electron Device Letters</i> , 2017 , 38, 1532-1535	4.4	24
60	Introduction of WO3 Layer in a Cu-Based Al2O3 Conductive Bridge RAM System for Robust Cycling and Large Memory Window. <i>IEEE Journal of the Electron Devices Society</i> , 2016 , 4, 163-166	2.3	23
59	Vertically Stacked ReRAM Composed of a Bidirectional Selector and CB-RAM for Cross-Point Array Applications. <i>IEEE Electron Device Letters</i> , 2013 , 34, 1512-1514	4.4	23
58	Controllable quantized conductance for multilevel data storage applications using conductive bridge random access memory. <i>Nanotechnology</i> , 2017 , 28, 115707	3.4	22
57	Hardware implementation of associative memory characteristics with analogue-type resistive-switching device. <i>Nanotechnology</i> , 2014 , 25, 495204	3.4	22
56	Retention modeling for ultra-thin density of Cu-based conductive bridge random access memory (CBRAM). <i>AIP Advances</i> , 2016 , 6, 025203	1.5	20
55	Engineering Oxygen Vacancy of Tunnel Barrier and Switching Layer for Both Selectivity and Reliability of Selector-Less ReRAM. <i>IEEE Electron Device Letters</i> , 2014 , 35, 1022-1024	4.4	20
54	Role of Local Chemical Potential of Cu on Data Retention Properties of Cu-Based Conductive-Bridge RAM. <i>IEEE Electron Device Letters</i> , 2016 , 37, 173-175	4.4	19
53	Impact of Selector Devices in Analog RRAM-Based Crossbar Arrays for Inference and Training of Neuromorphic System. <i>IEEE Transactions on Very Large Scale Integration (VLSI) Systems</i> , 2019 , 27, 2205-2212	2.6	18
52	Effects of Liner Thickness on the Reliability of AgTe/TiO2-Based Threshold Switching Devices. <i>IEEE Transactions on Electron Devices</i> , 2017 , 64, 4763-4767	2.9	18
51	Selector-less ReRAM with an excellent non-linearity and reliability by the band-gap engineered multi-layer titanium oxide and triangular shaped AC pulse 2013 ,		16
50	Highly Reliable Resistive Switching Without an Initial Forming Operation by Defect Engineering. <i>IEEE Electron Device Letters</i> , 2013 , 34, 1515-1517	4.4	16
49	Design Considerations of Selector Device in Cross-Point RRAM Array for Neuromorphic Computing 2018 ,		15
48	Integrated Crossbar Array With Resistive Synapses and Oscillation Neurons. <i>IEEE Electron Device Letters</i> , 2019 , 40, 1313-1316	4.4	15
47	Dependence of reactive metal layer on resistive switching in a bi-layer structure Ta/HfOx filament type resistive random access memory. <i>Applied Physics Letters</i> , 2014 , 104, 083507	3.4	13
46	Internal resistor of multi-functional tunnel barrier for selectivity and switching uniformity in resistive random access memory. <i>Nanoscale Research Letters</i> , 2014 , 9, 364	5	13
45	Tunnel barrier engineering of titanium oxide for high non-linearity of selector-less resistive random access memory. <i>Applied Physics Letters</i> , 2014 , 104, 052108	3.4	11

44	Multilayer-oxide-based bidirectional cell selector device for cross-point resistive memory applications. <i>Applied Physics Letters</i> , 2013 , 103, 202113	3-4	11
43	Improved Ferroelectric Switching in Sputtered HfZrOx Device Enabled by High Pressure Annealing. <i>IEEE Electron Device Letters</i> , 2020 , 41, 232-235	4-4	11
42	Monolithic integration of AgTe/TiO ₂ based threshold switching device with TiN liner for steep slope field-effect transistors 2016 ,		11
41	CommunicationImpact of Filament Instability in an Ag ₂ S-Based Conductive-Bridge RAM for Cross-Point Selector Applications. <i>ECS Journal of Solid State Science and Technology</i> , 2016 , 5, Q98-Q100	2	10
40	Accelerated Retention Test Method by Controlling Ion Migration Barrier of Resistive Random Access Memory. <i>IEEE Electron Device Letters</i> , 2015 , 36, 238-240	4-4	10
39	A nitrogen-treated memristive device for tunable electronic synapses. <i>Semiconductor Science and Technology</i> , 2014 , 29, 104006	1-8	10
38	Artificial Perspiration Membrane by Programmed Deformation of Thermoresponsive Hydrogels. <i>Advanced Materials</i> , 2020 , 32, e1905901	24	10
37	Microstructural engineering in interface-type synapse device for enhancing linear and symmetric conductance changes. <i>Nanotechnology</i> , 2019 , 30, 305202	3-4	9
36	Comparative Study of Cross-Point MRAM Array With Exponential and Threshold Selectors for Read Operation. <i>IEEE Electron Device Letters</i> , 2018 , 39, 680-683	4-4	9
35	Implementation of Convolutional Kernel Function Using 3-D TiOx Resistive Switching Devices for Image Processing. <i>IEEE Transactions on Electron Devices</i> , 2018 , 65, 4716-4718	2-9	9
34	Defect Engineering Using Bilayer Structure in Filament-Type RRAM. <i>IEEE Electron Device Letters</i> , 2013 , 34, 1250-1252	4-4	9
33	Effect of AC pulse overshoot on nonlinearity and reliability of selectorless resistive random access memory in AC pulse operation. <i>Solid-State Electronics</i> , 2015 , 104, 70-74	1-7	8
32	Recent Advancements in Emerging Neuromorphic Device Technologies. <i>Advanced Intelligent Systems</i> , 2020 , 2, 2000111	6	8
31	Two-Step Read Scheme in One-Selector and One-RRAM Crossbar-Based Neural Network for Improved Inference Robustness. <i>IEEE Transactions on Electron Devices</i> , 2018 , 65, 5549-5553	2-9	8
30	BEOL compatible (300°C) TiN/TiOx/Ta/TiN 3D nanoscale (~10nm) IMT selector 2013 ,		7
29	Optimized annealing conditions to enhance stability of polarization in sputtered HfZrOx layers for non-volatile memory applications. <i>Current Applied Physics</i> , 2020 , 20, 1441-1446	2-6	7
28	Improved reset breakdown strength in a HfOx-based resistive memory by introducing RuOx oxygen diffusion barrier. <i>AIP Advances</i> , 2016 , 6, 055114	1-5	7
27	Cu-ion-actuated three-terminal neuromorphic synaptic devices based on binary metal-oxide electrolyte and channel. <i>Applied Physics Letters</i> , 2021 , 119, 072103	3-4	7

26	CMOS compatible low-power volatile atomic switch for steep-slope FET devices. <i>Applied Physics Letters</i> , 2018 , 113, 033501	3.4	6
25	Selector devices for 3-D cross-point ReRAM 2014 ,		6
24	Exploiting defective RRAM array as synapses of HTM spatial pooler with boost-factor adjustment scheme for defect-tolerant neuromorphic systems. <i>Scientific Reports</i> , 2020 , 10, 11703	4.9	6
23	2016 ,		6
22	Multilevel conductance switching of a HfO ₂ RRAM array induced by controlled filament for neuromorphic applications 2016 ,		6
21	. <i>IEEE Electron Device Letters</i> , 2019 , 40, 1622-1625	4.4	5
20	Optimized Lightning-Rod Effect to Overcome Trade-Off Between Switching Uniformity and On/Off Ratio in ReRAM. <i>IEEE Electron Device Letters</i> , 2014 , 35, 214-216	4.4	5
19	Two- and three-terminal HfO ₂ -based multilevel resistive memories for neuromorphic analog synaptic elements. <i>Neuromorphic Computing and Engineering</i> ,		5
18	The band-gap energy dependence of metal oxides on non-linear characteristics in the HfO ₂ -based resistive random access memory. <i>Microelectronic Engineering</i> , 2015 , 147, 321-324	2.5	4
17	2014 ,		4
16	CommunicationComprehensive Assessment of a Back-to-Back Schottky Diode with Ultrathin TiO ₂ Layer for Cross-Point Selector Applications. <i>ECS Journal of Solid State Science and Technology</i> , 2016 , 5, Q188-Q190	2	4
15	Ion-Driven Electrochemical Random-Access Memory-Based Synaptic Devices for Neuromorphic Computing Systems: A Mini-Review.. <i>Micromachines</i> , 2022 , 13,	3.3	3
14	CommunicationEffect of a Self-Limited Reset Operation on the Reset Breakdown Characteristics of a Monolithically Integrated 1T1R RRAM. <i>ECS Journal of Solid State Science and Technology</i> , 2017 , 6, P440-P442	2	2
13	Recent Advancements in Emerging Neuromorphic Device Technologies. <i>Advanced Intelligent Systems</i> , 2020 , 2, 2070101	6	2
12	Effects of High-Pressure Hydrogen Annealing on the Formation of Conducting Filaments in Filament-Type Resistive Random-Access Memory. <i>Journal of Electronic Materials</i> , 2014 , 43, 3635-3639	1.9	2
11	Low-temperature spin-on-glass method involving high-pressure annealing for filling high-aspect-ratio structures. <i>Japanese Journal of Applied Physics</i> , 2014 , 53, 068007	1.4	2
10	Resistive-switching analogue memory device for neuromorphic application 2014 ,		2
9	Improvement in reliability characteristics (retention and endurance) of RRAM by using high-pressure hydrogen annealing 2014 ,		2

8	Ferroelectric Switching in Trilayer AlO/HfZrO/AlO Structure. <i>Micromachines</i> , 2020 , 11,	3.3	2
7	Device Design and Material Considerations of Ovonic Threshold Switch (OTS) for Cross-point MRAM Array 2019 ,		1
6	Design Space Exploration of Ovonic Threshold Switch (OTS) for Sub-Threshold Read Operation in Cross-Point Memory Arrays 2019 ,		1
5	Stepwise set operation for reliable switching uniformity and low operating current of ReRAMs. <i>Solid-State Electronics</i> , 2014 , 102, 42-45	1.7	1
4	Hybrid memory characteristics of NbOx threshold switching devices. <i>Applied Physics Letters</i> , 2021 , 119, 092102	3.4	1
3	Analog synaptic behavior of mobile ion source-limited electrochemical RAM using CuOx oxide electrode for deep learning accelerator. <i>Applied Physics Letters</i> , 2022 , 120, 122101	3.4	0
2	Area and Thickness Scaling of NbOx-Based Threshold Switches for Oscillation Neurons. <i>IEEE Journal of the Electron Devices Society</i> , 2022 , 10, 397-401	2.3	0
1	Editors' Choice Communication Hourglass-Shaped Metal-Filament Switching Device with Multi-Layer (AlOx/TiO2) Oxide Electrolytes. <i>ECS Journal of Solid State Science and Technology</i> , 2016 , 5, Q219-Q221	2	