

# Genshui Wang

## List of Publications by Year in Descending Order

**Source:** <https://exaly.com/author-pdf/4826592/genshui-wang-publications-by-year.pdf>

**Version:** 2024-04-09

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

181 papers	3,195 citations	26 h-index	47 g-index
195 ext. papers	3,677 ext. citations	3.5 avg, IF	5.01 L-index

#	Paper	IF	Citations
181	Significantly decreased depolarization hydrostatic pressure of 3D-printed PZT95/5 ceramics with periodically distributed pores. <i>Journal of the American Ceramic Society</i> , <b>2022</b> , 105, 412	3.8	0
180	Atomic reconfiguration among tri-state transition at ferroelectric/antiferroelectric phase boundaries in Pb(Zr,Ti)O <sub>2</sub> . <i>Nature Communications</i> , <b>2022</b> , 13, 1390	17.4	1
179	Discovery of electric devil staircase in perovskite antiferroelectric.. <i>Science Advances</i> , <b>2022</b> , 8, eabl9088	14.3	2
178	Ferroelectric Ceramics for Pyroelectric Detection Applications: A Review. <i>IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control</i> , <b>2021</b> , 68, 242-252	3.2	3
177	Hydrostatic-pressure-induced depolarization of (Pb <sub>1-1.5xLa</sub> )(Zr <sub>0.80</sub> Ti <sub>0.20</sub> )O <sub>3</sub> ferroelectric ceramics. <i>Journal of the American Ceramic Society</i> , <b>2021</b> , 104, 3269-3278	3.8	0
176	High-energy storage density in NaNbO <sub>3</sub> -modified (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -BiAlO <sub>3</sub> -based lead-free ceramics under low electric field. <i>Journal of the American Ceramic Society</i> , <b>2021</b> , 104, 2610-2620	3.8	3
175	Chemically Tunable Textured Interfacial Defects in PbZrO <sub>3</sub> -Based Antiferroelectric Perovskite Oxides. <i>Chemistry of Materials</i> , <b>2021</b> , 33, 6743-6751	9.6	1
174	Lead-free (Ag,K)NbO materials for high-performance explosive energy conversion. <i>Science Advances</i> , <b>2020</b> , 6, eaba0367	14.3	16
173	Grinding strain induced antiferroelectric-ferroelectric-antiferroelectric sandwich structure in bulk ceramics. <i>Scripta Materialia</i> , <b>2020</b> , 182, 27-31	5.6	1
172	Unveiling the ferroelectric nature of PbZrO <sub>3</sub> -based antiferroelectric materials. <i>Nature Communications</i> , <b>2020</b> , 11, 3809	17.4	28
171	Novel AgNbO <sub>3</sub> -based lead-free ceramics featuring excellent pyroelectric properties for infrared detecting and energy-harvesting applications via antiferroelectric/ferroelectric phase-boundary design. <i>Journal of Materials Chemistry C</i> , <b>2019</b> , 7, 4403-4414	7.1	18
170	Giant power output in lead-free ferroelectrics by shock-induced phase transition. <i>Physical Review Materials</i> , <b>2019</b> , 3,	3.2	15
169	Enhancing pyroelectric properties in (Pb <sub>1-1.5La</sub> )(Zr <sub>0.86</sub> Ti <sub>0.14</sub> )O <sub>3</sub> ceramics through composition modulated phase transition. <i>Ceramics International</i> , <b>2019</b> , 45, 7114-7119	5.1	8
168	Improved pyroelectric figures of merit of Mn-doped Zr-rich lead zirconate titanate bulk ceramics near room temperature for energy harvesting applications. <i>Journal of Alloys and Compounds</i> , <b>2019</b> , 779, 450-455	5.7	7
167	High performance Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -BiAlO <sub>3</sub> -K <sub>0.5</sub> Na <sub>0.5</sub> NbO <sub>3</sub> lead-free pyroelectric ceramics for thermal detectors. <i>Applied Physics Letters</i> , <b>2018</b> , 112, 142903	3.4	18
166	Enhanced pyroelectric properties in (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -BiAlO <sub>3</sub> -NaNbO <sub>3</sub> ternary system lead-free ceramics. <i>Journal of the American Ceramic Society</i> , <b>2018</b> , 101, 4044-4052	3.8	20
165	Dielectric and ferroelectric properties of lanthanum-modified lead zirconate stannate titanate (42/40/18) ceramics. <i>Journal of the American Ceramic Society</i> , <b>2018</b> , 101, 3979-3988	3.8	8

164	The depolarization performances of 0.97PbZrO <sub>3</sub> 0.03Ba(Mg <sup>1</sup> /3Nb <sup>2</sup> /3)O <sub>3</sub> ceramics under hydrostatic pressure. <i>Applied Physics Letters</i> , <b>2018</b> , 112, 062901	3.4	7
163	Tailored phase transition and electric properties of Pb <sub>0.99</sub> (Zr <sub>0.95</sub> Ti <sub>0.05</sub> ) <sub>0.98</sub> Nb <sub>0.02</sub> O <sub>3</sub> ferroelectric ceramics by ZnO modification. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , <b>2018</b> , 227, 48-52	3.1	1
162	Incommensurately Modulated Structures in Zr-rich PZT: Periodic Nanodomains, Reciprocal Configuration, and Nucleation. <i>Crystal Growth and Design</i> , <b>2018</b> , 18, 4395-4402	3.5	3
161	Antiferroelectrics for Energy Storage Applications: a Review. <i>Advanced Materials Technologies</i> , <b>2018</b> , 3, 1800111	6.8	184
160	La/Mn Codoped AgNbO <sub>3</sub> Lead-Free Antiferroelectric Ceramics with Large Energy Density and Power Density. <i>ACS Sustainable Chemistry and Engineering</i> , <b>2018</b> , 6, 16151-16159	8.3	66
159	Mechanical induced electrical failure of shock compressed PZT95/5 ferroelectric ceramics. <i>Current Applied Physics</i> , <b>2017</b> , 17, 448-453	2.6	6
158	Investigation of novel ferroelectric/gyromagnetic ferrite (Pb,Sr)TiO <sub>3</sub> /Y <sub>3</sub> Fe <sub>5</sub> O <sub>12</sub> layered thin films with potential applications in magnetically and electrically tuning devices. <i>Materials Letters</i> , <b>2017</b> , 195, 182-185	3.3	3
157	Electric field tunable thermal stability of energy storage properties of PLZST antiferroelectric ceramics. <i>Journal of the American Ceramic Society</i> , <b>2017</b> , 100, 2382-2386	3.8	22
156	Enhanced pyroelectric properties of Pb <sub>0.3</sub> Ca <sub>0.15</sub> Sr <sub>0.55</sub> TiO <sub>3</sub> ceramic with first-order dominated phase transition under low bias field. <i>Applied Physics Letters</i> , <b>2017</b> , 110, 102905	3.4	2
155	Electric transport and magnetic properties of La <sub>0.7</sub> Sr <sub>0.3</sub> MnO <sub>3</sub> thin films grown on PLZST ceramics. <i>Materials Letters</i> , <b>2017</b> , 199, 184-187	3.3	0
154	Enhanced shock performance by disperse porous structure: A case study in PZT95/5 ferroelectric ceramics. <i>Journal of the American Ceramic Society</i> , <b>2017</b> , 100, 5693-5699	3.8	6
153	Scaling behavior for (Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> based lead-free relaxor ferroelectric ceramics. <i>Journal of Applied Physics</i> , <b>2017</b> , 122, 064102	2.5	14
152	Enhanced ferroelectric properties and thermal stability of Mn-doped 0.96(Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> -0.04BiAlO <sub>3</sub> ceramics. <i>Journal of the American Ceramic Society</i> , <b>2017</b> , 100, 1030-1036	3.8	31
151	Linear composition-dependent phase transition behavior and energy storage performance of tetragonal PLZST antiferroelectric ceramics. <i>Journal of Alloys and Compounds</i> , <b>2017</b> , 691, 721-725	5.7	52
150	Temperature-dependent dielectric and energy-storage properties of Pb(Zr,Sn,Ti)O <sub>3</sub> antiferroelectric bulk ceramics. <i>AIP Advances</i> , <b>2016</b> , 6, 055203	1.5	16
149	Growth control of RF magnetron sputtered SrRuO <sub>3</sub> thin films through the thickness of LaNiO <sub>3</sub> seed layers. <i>Ceramics International</i> , <b>2016</b> , 42, 13925-13931	5.1	5
148	High charge-discharge performance of Pb <sub>0.98</sub> La <sub>0.02</sub> (Zr <sub>0.35</sub> Sn <sub>0.55</sub> Ti <sub>0.10</sub> ) <sub>0.995</sub> O <sub>3</sub> antiferroelectric ceramics. <i>Journal of Applied Physics</i> , <b>2016</b> , 120, 074107	2.5	81
147	An investigation on phase transition behaviors in MgO-doped Pb <sub>0.99</sub> (Zr <sub>0.95</sub> Ti <sub>0.05</sub> ) <sub>0.98</sub> Nb <sub>0.02</sub> O <sub>3</sub> ferroelectric ceramics by Raman and dielectric measurements. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , <b>2015</b> , 193, 170-174	3.1	7

146	Temperature-dependent stability of energy storage properties of Pb <sub>0.97</sub> La <sub>0.02</sub> (Zr <sub>0.58</sub> Sn <sub>0.335</sub> Ti <sub>0.085</sub> )O <sub>3</sub> antiferroelectric ceramics for pulse power capacitors. <i>Applied Physics Letters</i> , <b>2015</b> , 106, 262901	3.4	174
145	Enhanced dielectric tunability of Ba <sub>0.55</sub> Sr <sub>0.45</sub> TiO <sub>3</sub> /nAl <sub>2</sub> O <sub>3</sub> composite ceramic. <i>Ceramics International</i> , <b>2015</b> , 41, S551-S556	5.1	16
144	Phase characteristics of 0.92Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -0.08BiAlO <sub>3</sub> ceramics. <i>Applied Physics Letters</i> , <b>2015</b> , 106, 092903	3.4	8
143	Effect of interface configurations on the dynamic scaling behavior of Pb(Zr <sub>0.53</sub> Ti <sub>0.47</sub> )O <sub>3</sub> thin films. <i>Applied Physics Letters</i> , <b>2014</b> , 104, 092904	3.4	7
142	Field and Frequency Dependence of the Dynamic Hysteresis in Lead Zirconate Titanate Solid Solutions. <i>Journal of the American Ceramic Society</i> , <b>2014</b> , 97, 213-219	3.8	27
141	Dielectric and pyroelectric activities in Pb(Zr <sub>1-x</sub> Ti <sub>x</sub> )O <sub>3</sub> ceramics: The role of the phase transition effects. <i>Current Applied Physics</i> , <b>2014</b> , 14, 1411-1415	2.6	1
140	Electrical properties of lead-free KNN films on SRO/STO by RF magnetron sputtering. <i>Ceramics International</i> , <b>2014</b> , 40, 1195-1198	5.1	25
139	The effect of deposition power on the micro-structure and dielectric response of Pb <sub>0.4</sub> Sr <sub>0.6</sub> TiO <sub>3</sub> thin films. <i>Ceramics International</i> , <b>2014</b> , 40, 149-153	5.1	1
138	Temperature dependence of dynamic hysteresis behavior in Pb <sub>0.4</sub> Sr <sub>0.6</sub> TiO <sub>3</sub> ferroelectric films. <i>Solid State Communications</i> , <b>2014</b> , 192, 89-92	1.6	6
137	High temperature dielectric relaxation anomaly of Y <sup>3+</sup> and Mn <sup>2+</sup> doped barium strontium titanate ceramics. <i>Journal of Applied Physics</i> , <b>2014</b> , 116, 144103	2.5	4
136	Effect of polarization switching cycles on the dielectric response and Rayleigh constant in Pb <sub>0.4</sub> Sr <sub>0.6</sub> TiO <sub>3</sub> thin films. <i>Journal of Applied Physics</i> , <b>2014</b> , 115, 064102	2.5	6
135	Enhanced performances of sandwich structure Pb <sub>0.99</sub> (Zr <sub>0.95</sub> Ti <sub>0.05</sub> ) <sub>0.98</sub> Nb <sub>0.02</sub> O <sub>3</sub> ferroelectric ceramics for pulsed power application. <i>Materials Research Bulletin</i> , <b>2014</b> , 51, 167-170	5.1	7
134	Dielectric properties of La/Mn codoped Ba <sub>0.63</sub> Sr <sub>0.37</sub> TiO <sub>3</sub> thin films prepared by RF magnetron sputtering. <i>Ceramics International</i> , <b>2014</b> , 40, 12573-12577	5.1	17
133	Temperature-dependent ferroelectric dynamic hysteresis properties of modified PMN/BZT relaxor ceramics. <i>Physica Status Solidi - Rapid Research Letters</i> , <b>2013</b> , 7, 438-442	2.5	11
132	Low Temperature Deposition of High Performance Lead Strontium Titanate Thin Films by in situ RF Magnetron Sputtering. <i>Journal of the American Ceramic Society</i> , <b>2013</b> , 96, 1682-1684	3.8	19
131	Crystallographic orientation dependence of dielectric response in lead strontium titanate thin films. <i>Journal of Crystal Growth</i> , <b>2013</b> , 377, 143-146	1.6	7
130	High room-temperature pyroelectric response of MgO-modified Pb <sub>0.99</sub> (Zr <sub>0.95</sub> Ti <sub>0.05</sub> ) <sub>0.98</sub> Nb <sub>0.02</sub> O <sub>3</sub> ceramics. <i>Infrared Physics and Technology</i> , <b>2013</b> , 61, 325-329	2.7	5
129	Temperature and voltage stress dependent dielectric relaxation process of the doped Ba <sub>0.67</sub> Sr <sub>0.33</sub> TiO <sub>3</sub> ceramics. <i>Applied Physics Letters</i> , <b>2013</b> , 103, 112908	3.4	1

128	Characteristics of highly (001) oriented (K,Na)NbO <sub>3</sub> films grown on LaNiO <sub>3</sub> bottom electrodes by RF magnetron sputtering. <i>Ceramics International</i> , <b>2013</b> , 39, 1359-1363	5.1	17
127	Enhanced tunability performance of low temperature crystallized Pb <sub>0.4</sub> Sr <sub>0.6</sub> TiO <sub>3</sub> thin films derived from distinct microstructure. <i>Materials Letters</i> , <b>2013</b> , 107, 361-363	3.3	7
126	Effect of CuO Addition on the Microstructure and Electric Properties of Low-Temperature Sintered 0.25PMN0.40PT0.35PZ Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2013</b> , 96, 24-27	3.8	15
125	Evidence of macro-micro domain transition in poled PMN-BZT ceramics. <i>Ceramics International</i> , <b>2013</b> , 39, 9299-9303	5.1	15
124	Effect of residual stress on energy storage property in PbZrO <sub>3</sub> antiferroelectric thin films with different orientations. <i>Applied Physics Letters</i> , <b>2013</b> , 103, 162903	3.4	37
123	Low-temperature crystallization of high performance Pb <sub>0.4</sub> Sr <sub>0.6</sub> TiO <sub>3</sub> films compatible with the current silicon-based microelectronic technology. <i>Applied Physics Letters</i> , <b>2013</b> , 102, 212901	3.4	7
122	Identical scaling behavior of saturated dynamic hysteresis in rhombohedral lead zirconate titanate bulk ceramics. <i>Journal of Applied Physics</i> , <b>2013</b> , 114, 244101	2.5	7
121	Linear temperature scaling of ferroelectric hysteresis in Mn-doped Pb(Mn <sub>1/3</sub> Sb <sub>2/3</sub> )O <sub>3</sub> -Pb(Zr,Ti)O <sub>3</sub> ceramic with internal bias field. <i>Applied Physics Letters</i> , <b>2013</b> , 102, 142903	3.4	41
120	Pyroelectric response mechanism of barium strontium titanate ceramics in dielectric bolometer mode: The underlying essence of the enhancing effect of direct current bias field. <i>Applied Physics Letters</i> , <b>2013</b> , 102, 242911	3.4	4
119	Dielectric and enhanced pyroelectric properties of (Pb <sub>0.325</sub> Sr <sub>0.675</sub> )TiO <sub>3</sub> ceramics under direct current bias field. <i>Applied Physics Letters</i> , <b>2012</b> , 101, 262901	3.4	9
118	Phase diagram of (1-x)(0.89Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> 0.06BaTiO <sub>3</sub> 0.05K <sub>0.5</sub> Na <sub>0.5</sub> NbO <sub>3</sub> )xMnO <sub>2</sub> lead-free anti-ferroelectric ceramics. <i>Solid State Communications</i> , <b>2012</b> , 152, 1670-1672	1.6	9
117	Effects of sintering atmosphere on microstructure and electrical properties of BiScO <sub>3</sub> BbTiO <sub>3</sub> high-temperature piezoceramics. <i>Journal of Alloys and Compounds</i> , <b>2012</b> , 525, 149-153	5.7	5
116	Dielectric, ferroelectric and piezoelectric properties of 100-oriented Pb <sub>0.4</sub> Sr <sub>0.6</sub> TiO <sub>3</sub> thin film sputtered on LaNiO <sub>3</sub> electrode. <i>Journal of Crystal Growth</i> , <b>2012</b> , 347, 15-18	1.6	16
115	Formation Mechanism of Intragranular Pores in Pb(Zr <sub>0.95</sub> Ti <sub>0.05</sub> )O <sub>3</sub> Ferroelectric Ceramic. <i>Journal of the American Ceramic Society</i> , <b>2012</b> , 95, 223-226	3.8	7
114	Investigation of Phase Structure and Electrical Properties of Doped PMN-BZT Ceramics Prepared by Different Methods. <i>Journal of the American Ceramic Society</i> , <b>2012</b> , 95, 445-448	3.8	15
113	Abnormal electronic transition variations of lanthanum-modified lead zirconate stannate titanate ceramics near morphotropic phase boundary: A spectroscopic evidence. <i>Applied Physics Letters</i> , <b>2012</b> , 101, 011914	3.4	14
112	Effect of electrode materials on the scaling behavior of energy density in Pb(Zr <sub>0.96</sub> Ti <sub>0.03</sub> )Nb <sub>0.01</sub> O <sub>3</sub> antiferroelectric films. <i>Applied Physics Letters</i> , <b>2012</b> , 101, 112905	3.4	25
111	Phonon mode and phase transition behaviors of (1-x)PbSc <sub>1/2</sub> Ta <sub>1/2</sub> O <sub>3</sub> -xPbHfO <sub>3</sub> relaxor ferroelectric ceramics determined by temperature-dependent Raman spectra. <i>Applied Physics Letters</i> , <b>2011</b> , 99, 041902	3.4	10

110	Pyroelectric Responses in Pb(Sc <sub>1/2</sub> Ta <sub>1/2</sub> )O <sub>3</sub> Ceramics Measured from Hysteresis Loops at Various Temperatures. <i>Ferroelectrics</i> , <b>2011</b> , 413, 206-211	0.6	
109	Magnetic field modulated dielectric relaxation behavior of Pt/BiScO <sub>3</sub> -PbTiO <sub>3</sub> /La <sub>0.7</sub> Sr <sub>0.3</sub> MnO <sub>3</sub> heterostructure in metal-insulator transition region: An equivalent-circuit method. <i>Journal of Applied Physics</i> , <b>2011</b> , 110, 114118	2.5	3
108	Poling temperature tuned electric-field-induced ferroelectric to antiferroelectric phase transition in 0.89Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -0.06BaTiO <sub>3</sub> -0.05K <sub>0.5</sub> Na <sub>0.5</sub> NbO <sub>3</sub> ceramics. <i>Journal of Applied Physics</i> , <b>2011</b> , 110, 094109	2.5	15
107	Magnetocapacitance effects of Pb <sub>0.7</sub> Sr <sub>0.3</sub> TiO <sub>3</sub> /La <sub>0.7</sub> Sr <sub>0.3</sub> MnO <sub>3</sub> thin film on Si substrate. <i>Applied Physics Letters</i> , <b>2011</b> , 98, 052910	3.4	12
106	The Phase Transition Behavior of (1-x)Pb(Sc <sub>0.5</sub> Ta <sub>0.5</sub> )O <sub>3</sub> (x)PbHfO <sub>3</sub> Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 2530-2534	3.8	3
105	Microwave Properties of Bi <sub>1.5</sub> Zn <sub>1.0</sub> Nb <sub>1.5</sub> O <sub>7</sub> /Ba <sub>0.6</sub> Sr <sub>0.4</sub> TiO <sub>3</sub> Hetero Layered Films Directly Sputtered on Si up to 50 GHz. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 2262-2265	3.8	14
104	Effect of Sintering Atmosphere on the Microstructure and Electrical Properties of Donor-Doped Barium Strontium Calcium Titanate Pyroelectric Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 2003-2006	3.8	10
103	Optimization of PST Thin Films Grown by Sputtering and Complete Dielectric Performance Evaluation: An Alternative Material for Tunable Devices. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 4323-4328	3.8	13
102	Energy-Storage Properties of 0.89Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -0.06BaTiO <sub>3</sub> -0.05K <sub>0.5</sub> Na <sub>0.5</sub> NbO <sub>3</sub> Lead-Free Anti-ferroelectric Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 4382-4386	3.8	234
101	c/a Ratio-Dependent Energy-Storage Density in (0.9-x)Bi <sub>0.5</sub> Na <sub>0.5</sub> TiO <sub>3</sub> -xBaTiO <sub>3</sub> -0.1K <sub>0.5</sub> Na <sub>0.5</sub> NbO <sub>3</sub> Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 4162-4164	3.8	64
100	Frequency Dependence of Coercive Field in Soft Pb(Zr <sub>1-x</sub> Ti <sub>x</sub> )O <sub>3</sub> (0.20 ≤ x ≤ 0.60) Bulk Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2011</b> , 94, 4165-4168	3.8	17
99	Microgeometry effect on the properties of Pb <sub>0.99</sub> (Zr <sub>0.95</sub> Ti <sub>0.05</sub> ) <sub>0.98</sub> Nb <sub>0.02</sub> O <sub>3</sub> ferroelectric ceramics. <i>Materials Research Bulletin</i> , <b>2011</b> , 46, 1243-1246	5.1	10
98	Electrical properties of (Na,Ce) doped Bi <sub>5</sub> Ti <sub>3</sub> FeO <sub>15</sub> ceramics. <i>Physica Status Solidi (A) Applications and Materials Science</i> , <b>2011</b> , 208, 1047-1051	1.6	12
97	Dielectric and pyroelectric properties of poled Ba <sub>0.6</sub> Sr <sub>0.3</sub> Ca <sub>0.1</sub> TiO <sub>3</sub> ceramics. <i>Physica Status Solidi (A) Applications and Materials Science</i> , <b>2011</b> , 208, 1127-1131	1.6	6
96	Co-contributions of the magnetostriction and magnetoresistance to the giant room temperature magnetodielectric response in multiferroic composite thin films. <i>Solid State Communications</i> , <b>2011</b> , 151, 982-984	1.6	16
95	Dielectric and tunable properties of columnar Ba <sub>0.6</sub> Sr <sub>0.4</sub> TiO <sub>3</sub> -MgO composites prepared by spark plasma sintering. <i>Applied Physics Letters</i> , <b>2011</b> , 99, 202905	3.4	23
94	Mechanism of the Pyroelectric Response under Direct-Current Bias in La-Modified Lead Zirconate Titanate Stannate Ceramics. <i>Chinese Physics Letters</i> , <b>2011</b> , 28, 097701	1.8	1
93	Properties Evaluation of Piezoelectric Materials in Application of Cochlear Implant. <i>Ferroelectrics</i> , <b>2011</b> , 413, 272-278	0.6	2



92	Microstructure-Dielectric Properties Relationship in Ba <sub>0.6</sub> Sr <sub>0.4</sub> TiO <sub>3</sub> /Mg <sub>2</sub> SiO <sub>4</sub> /Al <sub>2</sub> O <sub>3</sub> Composite Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 161-166	3.8	18
91	Perfectly (001)- and (111)-Oriented (Ba,Sr)TiO <sub>3</sub> Thin Films Sputtered on Pt/TiO <sub>x</sub> /SiO <sub>2</sub> /Si Without Buffer Layers. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 350-352	3.8	13
90	Enhanced Ferroelectric Properties of Intragranular-Porous Pb(Zr <sub>0.95</sub> Ti <sub>0.05</sub> )O <sub>3</sub> Ceramic Fabricated with Carbon Nanotubes. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 642-645	3.8	16
89	Improved Dielectric Properties of Bi <sub>1.5</sub> Zn <sub>1.0</sub> Nb <sub>1.5</sub> O <sub>7</sub> /(111)-Oriented Ba <sub>0.6</sub> Sr <sub>0.4</sub> TiO <sub>3</sub> Bilayered Films for Tunable Microwave Applications. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 1215-1217	3.8	16
88	Growth and Electric Properties of MPB BiScO <sub>3</sub> /PbTiO <sub>3</sub> Thin Films on La <sub>0.7</sub> Sr <sub>0.3</sub> MnO <sub>3</sub> -Coated Silicon Substrates. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 1583	3.8	5
87	Effects of Ultrathin TiO <sub>x</sub> Seeding Layer on Crystalline Orientation and Electrical Properties of Sputtered (Ba,Sr)TiO <sub>3</sub> Thin Films. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 2136-2139	3.8	11
86	The Effect of Excess PbO on Dielectric and Pyroelectric Properties of Lead Scandium Tantalate Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 2735-2742	3.8	14
85	Unusual Curie Point Independence of Thickness and Interfacial Properties for Perfectly (111)-Oriented Ba <sub>0.6</sub> Sr <sub>0.4</sub> TiO <sub>3</sub> Thin Films. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 2526-2529	3.8	2
84	Structural, Dielectric, and Pyroelectric Properties of (111)PbSc <sub>0.5</sub> Ta <sub>0.5</sub> O <sub>3</sub> /PbHfO <sub>3</sub> Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 3023-3026	3.8	11
83	Microscopic Region Effect on the Dielectric Property of the Diffused Phase Transition Ferroelectrics: A Reasonable and Effective Diffuseness Characterizing Parameter. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 4011-4014	3.8	14
82	Charge-Discharge Properties of an Antiferroelectric Ceramics Capacitor Under Different Electric Fields. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 4015-4017	3.8	167
81	Pyroelectric Properties of Highly Ordered Pb(Sc <sub>0.5</sub> Ta <sub>0.5</sub> )O <sub>3</sub> Ceramics by a Two-Step Sintering Technique. <i>Journal of the American Ceramic Society</i> , <b>2010</b> , 93, 4030-4032	3.8	9
80	Microwave properties of epitaxial (111)-oriented Ba <sub>0.6</sub> Sr <sub>0.4</sub> TiO <sub>3</sub> thin films on Al <sub>2</sub> O <sub>3</sub> (0001) up to 40 GHz. <i>Applied Physics Letters</i> , <b>2010</b> , 97, 162909	3.4	35
79	Scaling Behavior of Ferroelectric Hysteresis Loop in 63PbTiO <sub>3</sub> /7BiScO <sub>3</sub> Bulk Ceramic. <i>Ferroelectrics</i> , <b>2010</b> , 403, 219-224	0.6	1
78	Investigation on the Phase Transition Behaviors in Pb <sub>0.97</sub> La <sub>0.02</sub> (Zr <sub>0.42</sub> Sn <sub>0.40</sub> Ti <sub>0.18</sub> )O <sub>3</sub> Ceramics. <i>Ferroelectrics</i> , <b>2010</b> , 402, 150-155	0.6	4
77	Effect of phase structure on the dynamic hysteresis scaling behavior in (111)BiScO <sub>3</sub> /PbTiO <sub>3</sub> bulk ceramics. <i>Journal of Alloys and Compounds</i> , <b>2010</b> , 500, 56-60	5.7	14
76	Quantitative dependence of the properties of Pb <sub>0.99</sub> (Zr <sub>0.95</sub> Ti <sub>0.05</sub> ) <sub>0.98</sub> Nb <sub>0.02</sub> O <sub>3</sub> ferroelectric ceramics on porosity. <i>Materials Research Bulletin</i> , <b>2010</b> , 45, 564-567	5.1	11
75	Effect of external fields on the switching current in PZT ferroelectric ceramics. <i>Solid State Communications</i> , <b>2010</b> , 150, 101-103	1.6	6

74	Polarization switching process of soft lead zirconate titanate bulk ceramics. <i>Solid State Communications</i> , <b>2010</b> , 150, 720-724	1.6	7
73	Dynamic ferroelectric hysteresis scaling behavior of bulk ceramics. <i>Solid State Communications</i> , <b>2010</b> , 150, 1045-1047	1.6	10
72	Depoling of porous $\text{Pb}_{0.99}(\text{Zr}_{0.95}\text{Ti}_{0.05})_{0.98}\text{Nb}_{0.02}\text{O}_3$ ferroelectric ceramics under shock wave load. <i>Current Applied Physics</i> , <b>2010</b> , 10, 1387-1390	2.6	10
71	Reversible pyroelectric response in $\text{Pb}_{0.955}\text{La}_{0.03}(\text{Zr}_{0.42}\text{Sn}_{0.40}\text{Ti}_{0.18})\text{O}_3$ ceramics near its phase transition. <i>Applied Physics Letters</i> , <b>2009</b> , 94, 252902	3.4	39
70	Effect of Donor, Acceptor, and Donor-Acceptor Codoping on the Electrical Properties of $\text{Ba}_{0.6}\text{Sr}_{0.4}\text{TiO}_3$ Thin Films for Tunable Device Applications. <i>Journal of the American Ceramic Society</i> , <b>2009</b> , 92, 2759-2761	3.8	17
69	Highly Temperature Stable Dielectric Properties of Nanograin Barium Strontium Titanate Thin Films Grown on Silicon Substrate. <i>Journal of the American Ceramic Society</i> , <b>2009</b> , 92, 2795-2797	3.8	3
68	Scaling behaviors of dynamic hysteresis in Zr-rich lead zirconate titanate bulk ceramics. <i>Solid State Communications</i> , <b>2009</b> , 149, 663-666	1.6	9
67	Orientation control of $\text{LaNiO}_3$ thin films by RF magnetron sputtering with different oxygen partial pressure. <i>Journal of Crystal Growth</i> , <b>2009</b> , 311, 4241-4246	1.6	18
66	Charge-discharge properties of lead zirconate stannate titanate ceramics. <i>Journal of Applied Physics</i> , <b>2009</b> , 106, 034105	2.5	115
65	PMN-PT thin films grown by sputtering on silicon substrate: influence of the annealing temperature on the physico-chemical and electrical properties of the films. <i>Research on Chemical Intermediates</i> , <b>2008</b> , 34, 201-215	2.8	
64	High-Temperature Domain Stability of Tetragonal-Structured $\text{BiScO}_3\text{-PbTiO}_3$ Ceramics. <i>Ferroelectrics</i> , <b>2008</b> , 363, 21-26	0.6	2
63	Annealing Temperature Effects on PMN-PT Thin Film. <i>Ferroelectrics</i> , <b>2008</b> , 362, 128-136	0.6	1
62	INTERFACIAL EFFECTS ON THE CRYSTALLIZATION TEMPERATURE OF PMN-PT FILMS DEPOSITED ON LNO OR Pt BOTTOM ELECTRODES. <i>Integrated Ferroelectrics</i> , <b>2008</b> , 98, 171-182	0.8	
61	Doped $\text{Pb}(\text{Zr},\text{Sn},\text{Ti})\text{O}_3$ Slim-Loop Ferroelectric Ceramics for High-Power Pulse Capacitors Application. <i>Ferroelectrics</i> , <b>2008</b> , 363, 56-63	0.6	50
60	The model of electric field dependent dielectric properties for porous ceramics. <i>Journal of Applied Physics</i> , <b>2008</b> , 103, 114103	2.5	15
59	Local Piezoelectric Hysteresis Loops for the Study of Electrical Properties of $0.7\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3\text{-}0.3\text{PbTiO}_3$ Thin Films: Bottom Electrode Dependence and Film Thickness Effect. <i>Ferroelectrics</i> , <b>2008</b> , 362, 21-29	0.6	7
58	Etching characteristics and absence of electrical properties damage of PZT thin films etched before crystallization. <i>Microelectronic Engineering</i> , <b>2008</b> , 85, 670-674	2.5	6
57	Investigation on FR(LT)BR(HT) phase transition and pyroelectric properties of porous Zr-rich lead zirconate titanate ceramics. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , <b>2007</b> , 140, 5-9	3.1	17



56	Indentation modulus and hardness of Pb(Zr, Ti)O <sub>3</sub> sol-gel films deposited on Pt and LaNiO <sub>3</sub> electrodes: An estimation of the CijD compliances. <i>Journal of the European Ceramic Society</i> , <b>2007</b> , 27, 223-230	6	19
55	Electric Field-Dependent Dielectric Properties and High Tunability of Porous Ba <sub>0.5</sub> Sr <sub>0.5</sub> TiO <sub>3</sub> Ceramics. <i>Journal of the American Ceramic Society</i> , <b>2007</b> , 90, 1327-1330	3.8	35
54	Orientation Control Growth of Lanthanum Nickelate Thin Films Using Chemical Solution Deposition. <i>Journal of the American Ceramic Society</i> , <b>2007</b> , 90, 3635-3637	3.8	21
53	Low temperature synthesis of Ba <sub>0.70</sub> Sr <sub>0.30</sub> TiO <sub>3</sub> powders by the molten-salt method. <i>Materials Chemistry and Physics</i> , <b>2007</b> , 106, 164-167	4.4	32
52	Formation and control of mechanism for the preparation of ultra-fine barium strontium titanate powders by the citrate precursor method. <i>Materials Research Bulletin</i> , <b>2007</b> , 42, 1602-1610	5.1	25
51	Effect of thermal strain on structure and polarization fatigue of CSD-derived PbZr <sub>0.53</sub> Ti <sub>0.47</sub> O <sub>3</sub> /LaNiO <sub>3</sub> hetero-structures. <i>Applied Physics A: Materials Science and Processing</i> , <b>2007</b> , 88, 657-660	2.6	10
50	Fabrication and characterization of fine-grained barium strontium titanate ceramics by the heterogeneous precipitation method. <i>Journal of Materials Science</i> , <b>2007</b> , 42, 6917-6922	4.3	2
49	NANOSCALE INVESTIGATIONS OF ELECTRICAL PROPERTIES IN RELAXOR Pb(Mg <sub>1/3</sub> Nb <sub>2/3</sub> )O <sub>3</sub> -PbTiO <sub>3</sub> THIN FILMS DEPOSITED ON PLATINUM AND LaNiO <sub>3</sub> ELECTRODES BY MEANS OF LOCAL PIEZOELECTRIC RESPONSE. <i>Integrated Ferroelectrics</i> , <b>2007</b> , 91, 80-96	0.8	20
48	Composition dependence of structural and optical properties for sol-gel derived (100)-oriented Ba <sub>1-x</sub> Sr <sub>x</sub> TiO <sub>3</sub> thin films. <i>Applied Physics Letters</i> , <b>2007</b> , 91, 061104	3.4	9
47	Electrostrictive and Piezoelectric Behavior of PMN-PT Thin Films. <i>Ferroelectrics</i> , <b>2007</b> , 351, 15-24	0.6	4
46	PREPARATION AND CHARACTERIZATIONS OF PbZr <sub>0.53</sub> Ti <sub>0.47</sub> O <sub>3</sub> THICK FILMS ON LaNiO <sub>3</sub> COATED Si BY MODIFIED METALLORGANIC DECOMPOSITION PROCESS. <i>Integrated Ferroelectrics</i> , <b>2006</b> , 80, 11-20	0.8	3
45	LOW-TEMPERATURE PREPARATION OF Pb(Zr <sub>x</sub> Ti <sub>1-x</sub> )O <sub>3</sub> THIN FILM. <i>Integrated Ferroelectrics</i> , <b>2006</b> , 81, 123-128	0.8	3
44	PREDICTED AND REALIZED IMPROVED PERFORMANCES OF PZT FILM/SILICON BASED STRUCTURES FOR INTEGRATED PYROSENSORICS. <i>Integrated Ferroelectrics</i> , <b>2006</b> , 80, 3-9	0.8	2
43	Fabrication and Electrical Properties of Lead Zirconate Titanate Thick Films on Si Substrate by Using Lanthanum Nickelate Buffer Layer. <i>Journal of the American Ceramic Society</i> , <b>2006</b> , 89, 3417-3420	3.8	10
42	Pyroelectric figure of merit in alternating hemicyanine/NC Langmuir-Blodgett films incorporating barium ions. <i>Colloids and Surfaces A: Physicochemical and Engineering Aspects</i> , <b>2006</b> , 284-285, 74-77	5.1	1
41	Combined annealing temperature and thickness effects on properties of PbZr <sub>0.53</sub> Ti <sub>0.47</sub> O <sub>3</sub> films on LaNiO <sub>3</sub> /Si substrate by sol-gel process. <i>Journal of Crystal Growth</i> , <b>2006</b> , 293, 370-375	1.6	16
40	Mechanical properties measured by nano-indentation of Pb(Zr, Ti)O <sub>3</sub> sol-gel films deposited on Pt and LaNiO <sub>3</sub> electrodes. <i>Surface and Coatings Technology</i> , <b>2006</b> , 201, 3155-3162	4.4	17
39	The third-order optical nonlinearity of Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> ferroelectric thin film on quartz. <i>Thin Solid Films</i> , <b>2006</b> , 496, 333-335	2.2	25

38	Preparation of highly (100)-oriented LaNiO <sub>3</sub> nanocrystalline films by metalorganic chemical liquid deposition. <i>Journal of Crystal Growth</i> , <b>2005</b> , 277, 450-456	1.6	44
37	The effect of LaNiO <sub>3</sub> bottom electrode thickness on ferroelectric and dielectric properties of (100) oriented PbZr <sub>0.53</sub> Ti <sub>0.47</sub> O <sub>3</sub> films. <i>Journal of Crystal Growth</i> , <b>2005</b> , 284, 184-189	1.6	18
36	Effect of excess Pb on crystallinity and ferroelectric properties of PZT(40/60) films on LaNiO <sub>3</sub> coated Si substrates by MOD technique. <i>Applied Surface Science</i> , <b>2005</b> , 240, 275-279	6.7	19
35	Spectroscopic ellipsometry investigations of PLT ferroelectric thin films with various La concentrations in the mid-infrared spectral region. <i>Applied Physics A: Materials Science and Processing</i> , <b>2005</b> , 80, 841-846	2.6	3
34	PYROELECTRIC CHARACTERIZATION OF HYSTERESIS PHENOMENA ASYMMETRY IN PZT FILM ON SILICON STRUCTURES. <i>Integrated Ferroelectrics</i> , <b>2005</b> , 73, 27-35	0.8	3
33	Fabrication of ferroelectric PbZr <sub>x</sub> Ti <sub>1-x</sub> O <sub>3</sub> thick films and their optical waveguide properties. <i>Journal of Vacuum Science and Technology A: Vacuum, Surfaces and Films</i> , <b>2004</b> , 22, 422-424	2.9	1
32	The optical properties of Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> thin films with different thickness prepared by chemical solution deposition. <i>Materials Research Bulletin</i> , <b>2004</b> , 39, 1223-1229	5.1	8
31	Optical characterization of ferroelectric Bi (mathsf_{3.25}}La (mathsf_{0.75}}Ti(mathsf_{3}})O (mathsf_{12}}) thin films. <i>European Physical Journal B</i> , <b>2004</b> , 38, 431-436	1.2	8
30	Infrared optical properties of PbZr <sub>0.4</sub> Ti <sub>0.6</sub> O <sub>3</sub> /La <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> heterostructures on platinized silicon substrate. <i>Applied Physics A: Materials Science and Processing</i> , <b>2004</b> , 78, 119-123	2.6	2
29	Effects of thickness on the infrared optical properties of Ba <sub>0.9</sub> Sr <sub>0.1</sub> TiO <sub>3</sub> ferroelectric thin films. <i>Applied Physics A: Materials Science and Processing</i> , <b>2004</b> , 78, 757-760	2.6	14
28	Effect of substitution of vanadium on the structure and electrical properties of Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> thin films. <i>Applied Physics A: Materials Science and Processing</i> , <b>2004</b> , 78, 1089-1091	2.6	8
27	The grain size effect of the Pb(Zr <sub>0.45</sub> Ti <sub>0.55</sub> )O <sub>3</sub> thin films deposited on LaNiO <sub>3</sub> -coated silicon by modified sol-gel process. <i>Journal of Crystal Growth</i> , <b>2004</b> , 260, 109-114	1.6	46
26	Preparation and characterization of multi-coating PZT thick films by sol-gel process. <i>Journal of Crystal Growth</i> , <b>2004</b> , 264, 307-311	1.6	14
25	Infrared spectroscopic ellipsometry of (Pb, La)(Zr, Ti)O <sub>3</sub> thin films on platinized silicon. <i>Physics Letters, Section A: General, Atomic and Solid State Physics</i> , <b>2004</b> , 320, 478-486	2.3	11
24	Spectroscopic-ellipsometry characterization of the interface layer of PbZr <sub>0.40</sub> Ti <sub>0.60</sub> O <sub>3</sub> /LaNiO <sub>3</sub> /Pt multilayer thin films. <i>Journal of Vacuum Science and Technology A: Vacuum, Surfaces and Films</i> , <b>2004</b> , 22, 1152-1157	2.9	4
23	Electrical and optical properties of Bi <sub>2</sub> Ti <sub>2</sub> O <sub>7</sub> thin films prepared by metalorganic decomposition method. <i>Applied Physics Letters</i> , <b>2004</b> , 85, 1214-1216	3.4	21
22	Ferroelectric Properties of PbZr <sub>0.40</sub> Ti <sub>0.60</sub> O <sub>3</sub> /La <sub>x</sub> Sr <sub>1-x</sub> CoO <sub>3</sub> Heterostructures Prepared by Chemical Solution Routes. <i>Integrated Ferroelectrics</i> , <b>2004</b> , 64, 277-288	0.8	1
21	Phase transition in ferroelectric hemicyanine Langmuir-Blodgett multilayers <b>2004</b> , 5564, 133		

20	Investigations of the Optical Properties of Ba <sub>0.9</sub> Sr <sub>0.1</sub> TiO <sub>3</sub> Ferroelectric Thin Films by Spectroscopic Ellipsometry. <i>Japanese Journal of Applied Physics</i> , <b>2003</b> , 42, 1400-1404	1.4	8
19	Thickness Dependence of Infrared Optical Properties of LaNiO <sub>3</sub> Thin Films Prepared on Platinized Silicon Substrates. <i>Japanese Journal of Applied Physics</i> , <b>2003</b> , 42, 7045-7049	1.4	6
18	Infrared Optical Characterization of PLT Thin Films for Applications in Uncooled Infrared Detectors. <i>Journal of Infrared, Millimeter and Terahertz Waves</i> , <b>2003</b> , 24, 1939-1954		1
17	Ferroelectricity of weak-polar organic molecules in alternate Langmuir-Blodgett multilayer films. <i>Science Bulletin</i> , <b>2003</b> , 48, 2176-2179		1
16	Structural and optical properties of Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> ferroelectric thin films prepared by chemical solution methods. <i>Applied Physics A: Materials Science and Processing</i> , <b>2003</b> , 76, 83-86	2.6	11
15	Structure-related infrared optical properties of BaTiO <sub>3</sub> thin films grown on Pt/Ti/SiO <sub>2</sub> /Si substrates. <i>Journal of Physics and Chemistry of Solids</i> , <b>2003</b> , 64, 2445-2450	3.9	22
14	Infrared optical properties of Bi <sub>2</sub> Ti <sub>2</sub> O <sub>7</sub> thin films by spectroscopic ellipsometry. <i>Thin Solid Films</i> , <b>2003</b> , 440, 190-194	2.2	5
13	Dielectric functions of ferroelectric Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> thin films on Si(100) substrates. <i>Applied Physics Letters</i> , <b>2003</b> , 83, 3686-3688	3.4	30
12	Optical properties of Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> thin films using spectroscopic ellipsometry. <i>Journal of Applied Physics</i> , <b>2003</b> , 93, 3811-3815	2.5	26
11	Investigations on the infrared optical properties of BaTiO <sub>3</sub> ferroelectric thin films by spectroscopic ellipsometry. <i>Semiconductor Science and Technology</i> , <b>2003</b> , 18, 449-453	1.8	16
10	Structure and Optical Properties of Ba <sub>0.9</sub> Sr <sub>0.1</sub> TiO <sub>3</sub> Ferroelectric Thin Films Prepared by Chemical Solution Routes. <i>Physica Status Solidi A</i> , <b>2002</b> , 194, 56-63		4
9	Structural and electrical properties of polycrystalline PbZr <sub>0.5</sub> Ti <sub>0.5</sub> O <sub>3</sub> films deposited on La <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> coated silicon by sol-gel process. <i>Applied Physics A: Materials Science and Processing</i> , <b>2002</b> , 74, 707-710	2.6	4
8	Highly (111)-oriented PbTiO <sub>3</sub> films prepared by rf planar magnetron sputtering and their optical properties. <i>Surface and Coatings Technology</i> , <b>2002</b> , 160, 173-176	4.4	12
7	Infrared optical properties of Bi <sub>3.25</sub> La <sub>0.75</sub> Ti <sub>3</sub> O <sub>12</sub> ferroelectric thin films using spectroscopic ellipsometry. <i>Journal Physics D: Applied Physics</i> , <b>2002</b> , 35, 3221-3224	3	4
6	Enhanced fatigue property of PZT thin films using LaNiO <sub>3</sub> thin layer as bottom electrode. <i>Applied Physics A: Materials Science and Processing</i> , <b>2001</b> , 73, 323-325	2.6	29
5	Effect of hydrolysis on properties of PbZr <sub>0.5</sub> Ti <sub>0.5</sub> O <sub>3</sub> ferroelectric thin films derived from a modified sol-gel process. <i>Journal of Crystal Growth</i> , <b>2001</b> , 233, 269-274	1.6	4
4	Study of Properties of Urea and L-Alanine Doped Triglycine Sulfate (UrLATGS) Crystals. <i>Journal of Infrared, Millimeter and Terahertz Waves</i> , <b>2001</b> , 22, 329-334		2
3	PbZr <sub>0.5</sub> Ti <sub>0.5</sub> O <sub>3</sub> /La <sub>0.5</sub> Sr <sub>0.5</sub> CoO <sub>3</sub> heterostructures prepared by chemical solution routes on silicon with no fatigue polarization. <i>Applied Physics Letters</i> , <b>2001</b> , 79, 3476-3478	3.4	45

2	Properties of highly (100) oriented Ba <sub>0.9</sub> Sr <sub>0.1</sub> TiO <sub>3</sub> /LaNiO <sub>3</sub> heterostructures prepared by chemical solution routes. <i>Applied Physics Letters</i> , <b>2001</b> , 78, 4172-4174	3-4	26
1	Low-temperature preparation of highly (001)-oriented PZT thin films on Pt/Ti/SiO <sub>2</sub> /Si using LaNiO <sub>3</sub> as a buffer layer <b>2000</b> , 4086, 667		1