

Yuan-Fong Chau

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/4908964/yuan-fong-chau-publications-by-year.pdf>

Version: 2024-04-26

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

117
papers

2,412
citations

35
h-index

42
g-index

134
ext. papers

3,040
ext. citations

2.5
avg, IF

5.56
L-index

#	Paper	IF	Citations
117	The Use of Gigantochloa Bamboo-Derived Biochar for the Removal of Methylene Blue from Aqueous Solution. <i>Adsorption Science and Technology</i> , 2022 , 2022, 1-12	3.6	0
116	Mid infrared sensing structure based on a metal-insulator-metal waveguides with a triangular-shaped resonator. <i>Optics Communications</i> , 2022 , 128282	2	0
115	Theoretical Study of CO Adsorption Interactions with Cr-Doped Tungsten Oxide/Graphene Composites for Gas Sensor Application.. <i>ACS Omega</i> , 2022 , 7, 528-539	3.9	1
114	Biosensing on a Plasmonic Dual-Band Perfect Absorber Using Intersection Nanostructure.. <i>ACS Omega</i> , 2022 , 7, 1139-1149	3.9	4
113	Breaking the Symmetry of a Metal-Insulator-Metal-Based Resonator for Sensing Applications.. <i>Nanoscale Research Letters</i> , 2022 , 17, 48	5	1
112	Enhanced photoluminescence and shortened lifetime of DCJTB by photoinduced metal deposition on a ferroelectric lithography substrate.. <i>Scientific Reports</i> , 2022 , 12, 6173	4.9	0
111	A multichannel color filter with the functions of optical sensor and switch. <i>Scientific Reports</i> , 2021 , 11, 22910	4.9	0
110	Machine learning approaches to predict adsorption capacity of <i>Azolla pinnata</i> in the removal of methylene blue. <i>Journal of the Taiwan Institute of Chemical Engineers</i> , 2021 , 132, 104134-104134	5.3	11
109	Multiple-Mode Bowtie Cavities for Refractive Index and Glucose Sensors Working in Visible and Near-infrared Wavelength Ranges. <i>Plasmonics</i> , 2021 , 16, 1633-1644	2.4	2
108	Plasmonic refractive index sensor based on the combination of rectangular and circular resonators including baffles. <i>Chinese Journal of Physics</i> , 2021 , 71, 286-299	3.5	9
107	Multiple Fano resonance modes in an ultra-compact plasmonic waveguide-cavity system for sensing applications. <i>Results in Physics</i> , 2021 , 27, 104527	3.7	4
106	Improved Refractive Index-Sensing Performance of Multimode Fano-Resonance-Based Metal-Insulator-Metal Nanostructures. <i>Nanomaterials</i> , 2021 , 11,	5.4	6
105	A Theoretical Insight of Cr Dopant in Tungsten Oxide for Gas Sensor Application. <i>Materials Today Communications</i> , 2021 , 28, 102508	2.5	2
104	Significantly enhanced coupling effect and gap plasmon resonance in a MIM-cavity based sensing structure. <i>Scientific Reports</i> , 2021 , 11, 18515	4.9	8
103	Localized surface plasmon resonance enhanced by the light-scattering property of silver nanoparticles for improved luminescence of polymer light-emitting diodes. <i>Journal of Industrial and Engineering Chemistry</i> , 2021 , 103, 283-291	6.3	1
102	Highly sensitive metal-insulator-metal plasmonic refractive index sensor with a centrally coupled nanoring containing defects. <i>Journal Physics D: Applied Physics</i> , 2021 , 54, 115301	3	17
101	Enhanced photoluminescence of DCJTB with ordered Ag-SiO ₂ core-shell nanostructures via nanosphere lithography. <i>Results in Physics</i> , 2020 , 17, 103168	3.7	11

100	Perfect Dual-Band Absorber Based on Plasmonic Effect with the Cross-Hair/Nanorod Combination. <i>Nanomaterials</i> , 2020 , 10,	5-4	42
99	Reusable TiN Substrate for Surface Plasmon Resonance Heterodyne Phase Interrogation Sensor. <i>Nanomaterials</i> , 2020 , 10,	5-4	9
98	Review of Experimental Setups for Plasmonic Photocatalytic Reactions. <i>Catalysts</i> , 2020 , 10, 46	4	15
97	Ultra-broad bandgap metal-insulator-metal waveguide filter with symmetrical stubs and defects. <i>Results in Physics</i> , 2020 , 17, 103116	3-7	21
96	Mid-infrared sensing properties of a plasmonic metal-insulator-metal waveguide with a single stub including defects. <i>Journal Physics D: Applied Physics</i> , 2020 , 53, 115401	3	22
95	Enhancing plasmonic effect in periodic nanometal square prisms with fences and cavities for refractive index and temperature sensing applications. <i>Journal of Nanoparticle Research</i> , 2020 , 22, 1	2-3	12
94	Highly Sensitive and Tunable Plasmonic Sensor Based on a Nanoring Resonator with Silver Nanorods. <i>Nanomaterials</i> , 2020 , 10,	5-4	39
93	Ultrawide Bandgap and High Sensitivity of a Plasmonic Metal-Insulator-Metal Waveguide Filter with Cavity and Baffles. <i>Nanomaterials</i> , 2020 , 10,	5-4	19
92	Plasmonic perfect absorber based on metal nanorod arrays connected with veins. <i>Results in Physics</i> , 2019 , 15, 102567	3-7	39
91	Plasmonic effects in the enclosed and opened metallodielectric bowtie nanostructures. <i>Optics Communications</i> , 2019 , 450, 180-189	2	3
90	Strong and tunable plasmonic field coupling and enhancement generating from the protruded metal nanorods and dielectric cores. <i>Results in Physics</i> , 2019 , 13, 102290	3-7	22
89	Ultra-High Refractive Index Sensing Structure Based on a Metal-Insulator-Metal Waveguide-Coupled T-Shape Cavity with Metal Nanorod Defects. <i>Nanomaterials</i> , 2019 , 9,	5-4	50
88	Tunable plasmonic effects arising from metal-dielectric nanorods. <i>Applied Optics</i> , 2019 , 58, 2530-2539	1-7	6
87	Magnetic Field-Enhancing Photocatalytic Reaction in Micro Optofluidic Chip Reactor. <i>Nanoscale Research Letters</i> , 2019 , 14, 323	5	12
86	Fabrication and Characterization of a Metallic-Dielectric Nanorod Array by Nanosphere Lithography for Plasmonic Sensing Application. <i>Nanomaterials</i> , 2019 , 9,	5-4	47
85	Plasmonic effects in composite metal nanostructures for sensing applications. <i>Journal of Nanoparticle Research</i> , 2018 , 20, 1	2-3	39
84	Depolying Tunable Metal-Shell/Dielectric Core Nanorod Arrays as the Virtually Perfect Absorber in the Near-Infrared Regime. <i>ACS Omega</i> , 2018 , 3, 7508-7516	3-9	55
83	Raman Spectrometry of Scattering of Nano-Gold Ceria Films. <i>Advanced Science Letters</i> , 2018 , 24, 8940-8943		1

82	A Comparative Study of Visible Raman Scattering of Ceria Prepared by Sol-gel and Hydrothermal Techniques with Gold Nanoparticles. <i>IOP Conference Series: Materials Science and Engineering</i> , 2018 , 409, 012012	0.4	0
81	Resonant optical transmission through the sub-wavelength air-hole arrays in a gold thin film for sensing applications. <i>IOP Conference Series: Materials Science and Engineering</i> , 2018 , 409, 012011	0.4	
80	Crystal Structure, Surface Topography, Surface Morphology and Optical Properties of DC Magnetron Sputtered VO ₂ Thin Films using VO ₂ Target. <i>IOP Conference Series: Materials Science and Engineering</i> , 2018 , 409, 012025	0.4	1
79	Design of crossing metallic metasurface arrays based on high sensitivity of gap enhancement and transmittance shift for plasmonic sensing applications. <i>Journal Physics D: Applied Physics</i> , 2017 , 50, 045105	0.5	31
78	Investigation of plasmonic effects on the metal nanoparticle arrays for biosensor applications. <i>IOP Conference Series: Materials Science and Engineering</i> , 2017 , 191, 012016	0.4	1
77	Plasmonic effects arising from a grooved surface of a gold nanorod. <i>Journal Physics D: Applied Physics</i> , 2017 , 50, 125302	3	8
76	Near infrared surface-enhanced Raman scattering based on star-shaped gold/silver nanoparticles and hyperbolic metamaterial. <i>Scientific Reports</i> , 2017 , 7, 5446	4.9	65
75	Light energy transformation over a few nanometers. <i>Journal Physics D: Applied Physics</i> , 2017 , 50, 3756013		7
74	Simultaneous realization of high sensing sensitivity and tunability in plasmonic nanostructures arrays. <i>Scientific Reports</i> , 2017 , 7, 16817	4.9	53
73	Intriguing Standing Wave Numbers and Plasmonic Effects on the Solid-Metal/Metal-Shell Nanorod Surface. <i>Plasmonics</i> , 2017 , 12, 277-285	2.4	0
72	Manipulating near field enhancement and optical spectrum in a pair-array of the cavity resonance based plasmonic nanoantennas. <i>Journal Physics D: Applied Physics</i> , 2016 , 49, 475102	3	25
71	Rapid fabrication of three-dimensional gold dendritic nanoforests for visible light-enhanced methanol oxidation. <i>Electrochimica Acta</i> , 2016 , 192, 15-21	6.7	41
70	Metal nano-particles sizing by thermal annealing for the enhancement of surface plasmon effects in thin-film solar cells application. <i>Optics Communications</i> , 2016 , 370, 85-90	2	33
69	Plasmonic spectrum on 1D and 2D periodic arrays of rod-shape metal nanoparticle pairs with different core patterns for biosensor and solar cell applications. <i>Journal of Optics (United Kingdom)</i> , 2016 , 18, 115003	1.7	42
68	Tailoring surface plasmon resonance and dipole cavity plasmon modes of scattering cross section spectra on the single solid-gold/gold-shell nanorod. <i>Journal of Applied Physics</i> , 2016 , 120, 093110	2.5	39
67	Tunable Optical Performances on a Periodic Array of Plasmonic Bowtie Nanoantennas with Hollow Cavities. <i>Nanoscale Research Letters</i> , 2016 , 11, 411	5	37
66	Tunable silver-shell dielectric core nano-beads array for thin-film solar cell application. <i>Journal of Nanoparticle Research</i> , 2016 , 18, 1	2.3	22
65	Comparative study of low-frequency noise in 0.18 μm and 0.35 μm gate-length nMOSFETs with gate area of 1.1 μm^2 . <i>Microelectronics Reliability</i> , 2016 , 60, 10-15	1.2	2

64	A simple structure of all circular-air-holes photonic crystal fiber for achieving high birefringence and low confinement loss. <i>Journal of Applied Physics</i> , 2015 , 118, 243102	2.5	12
63	Numerical investigation of surface plasmon resonance effects on photocatalytic activities using silver nanobeads photodeposited onto a titanium dioxide layer. <i>Optics Communications</i> , 2014 , 331, 223-228	2.2	5
62	Deposition of Ta2O5 upon silver nanorods as an ultra-thin light absorber. <i>Thin Solid Films</i> , 2014 , 567, 38-46	2.2	7
61	Gap enhancement and transmittance spectra of a periodic bowtie nanoantenna array buried in a silica substrate. <i>Optics Communications</i> , 2014 , 324, 227-233	2	14
60	Buried Effects of Surface Plasmon Resonance Modes for Periodic Metal-Dielectric Nanostructures Consisting of Coupled Spherical Metal Nanoparticles with Cylindrical Pore Filled with a Dielectric. <i>Plasmonics</i> , 2014 , 9, 1-9	2.4	20
59	Effective Coupling of Incident Light Through an Air Region into an S-Shape Plasmonic Ag Nanowire Waveguide with Relatively Long Propagation Length. <i>Plasmonics</i> , 2014 , 9, 573-579	2.4	14
58	Structurally and materially sensitive hybrid surface plasmon modes in periodic silver-shell nanopearl and its dimer arrays. <i>Journal of Nanoparticle Research</i> , 2013 , 15, 1	2.3	40
57	Numerical Investigation of a Castle-like Contour Plasmonic Nanoantenna with Operating Wavelengths Ranging in Ultraviolet-Visible, Visible Light, and Infrared Light. <i>Plasmonics</i> , 2013 , 8, 755-761	2.4	11
56	Analysis of transmittance properties of surface plasmon modes on periodic solid/outline bowtie nanoantenna arrays. <i>Physics of Plasmas</i> , 2013 , 20, 064503	2.1	38
55	Photonic Crystals with Large Complete Bandgap Composed of an Approximately Ordered Array of Laurel-Crown-Like Structures Fabricated by Employing Anodic Aluminum Oxide Template. <i>Japanese Journal of Applied Physics</i> , 2013 , 52, 010206	1.4	
54	Z-Axis Displacement Sensor Based on Total-Internal Reflection and Surface Plasmon Resonance in Heterodyne Interferometry. <i>Advanced Materials Research</i> , 2013 , 746, 564-569	0.5	
53	THEORETICAL ANALYSIS OF SUB-WAVELENGTH LIGHT PROPAGATION THROUGH THE DOUBLE-CHAIN SILVER NANORINGS. <i>Progress in Electromagnetics Research</i> , 2013 , 133, 331-346	3.8	4
52	Numerical Analysis on Birefringence of Photonic Crystal Fiber by Tuning Patterns and Infiltrating Materials of Innermost Air Holes. <i>Japanese Journal of Applied Physics</i> , 2013 , 52, 062502	1.4	2
51	A COMPACT 90° BENT EQUAL OUTPUT PORTS OF PHOTONIC CRYSTAL BEAM SPLITTER WITH COMPLETE BAND GAP BASED ON DEFECT RESONANCE INTERFACE. <i>Progress in Electromagnetics Research M</i> , 2012 , 27, 231-240	0.6	2
50	Fabrication of three dimensional split ring resonators by stress-driven assembly method. <i>Optics Express</i> , 2012 , 20, 9415-20	3.3	45
49	Long-ranging propagation based on resonant coupling effects using a series connection of ten nanoshells in a plasmon waveguide. <i>Applied Optics</i> , 2012 , 51, 640-3	1.7	6
48	Design of plasmonic toroidal metamaterials at optical frequencies. <i>Optics Express</i> , 2012 , 20, 1760-8	3.3	137
47	Tunable plasmonic resonance arising from broken-symmetric silver nanobeads with dielectric cores. <i>Journal of Optics (United Kingdom)</i> , 2012 , 14, 114010	1.7	37

46	A Study of Controlling Color Mixing of Red, Green, and Blue LEDs Based on Photometry Theory. <i>Sensor Letters</i> , 2012 , 10, 1056-1062	0.9	3
45	Evolution of the complete photonic bandgap of two-dimensional photonic crystal. <i>Optics Express</i> , 2011 , 19, 4862-7	3.3	25
44	LOCALIZED RESONANCE OF COMPOSITE CORE-SHELL NANOSPHERES, NANOBARS AND NANOSPHERICAL CHAINS. <i>Progress in Electromagnetics Research B</i> , 2011 , 28, 183-199	0.7	35
43	A comparative study of solid-silver and silver-shell nanodimers on surface plasmon resonances. <i>Journal of Nanoparticle Research</i> , 2011 , 13, 637-644	2.3	36
42	Manipulation of subwavelength optical fields and resonant field enhancements of a silver-shell nanocylinder pair and chain waveguides with different core-shell patterns. <i>Journal of Nanoparticle Research</i> , 2011 , 13, 3939-3949	2.3	2
41	Highly enhanced surface plasmon resonance in a coupled silver nanodumbbell. <i>Applied Physics A: Materials Science and Processing</i> , 2011 , 104, 801-805	2.6	5
40	Dispersion properties, birefringence and confinement loss of rotational elliptic air-hole photonic crystal fiber. <i>Applied Physics A: Materials Science and Processing</i> , 2011 , 104, 857-861	2.6	5
39	Plasmonics Effects of Nanometal Embedded in a Dielectric Substrate. <i>Plasmonics</i> , 2011 , 6, 581-589	2.4	38
38	Design of high birefringence and low confinement loss photonic crystal fibers with five rings hexagonal and octagonal symmetry air-holes in fiber cladding. <i>Journal of Applied Physics</i> , 2011 , 109, 093103	1.5	35
37	Numerical Investigations on Birefringent Holey Fibers by Modified Elliptical Air Holes in Fiber Cladding. <i>Japanese Journal of Applied Physics</i> , 2011 , 50, 112502	1.4	
36	Complete bandgap arising from the effects of hollow, veins, and intersecting veins in a square lattice of square dielectric rods photonic crystal. <i>Applied Physics Letters</i> , 2011 , 98, 263115	3.4	13
35	Numerical investigation of birefringence and confinement loss formed by rectangular/elliptical/circular air holes photonic crystal fibers. <i>Journal of Modern Optics</i> , 2011 , 58, 1673-1677	1.1	6
34	Numerical Investigations on Birefringent Holey Fibers by Modified Elliptical Air Holes in Fiber Cladding. <i>Japanese Journal of Applied Physics</i> , 2011 , 50, 112502	1.4	
33	A COMPARATIVE STUDY OF HIGH BIREFRINGENCE AND LOW CONFINEMENT LOSS PHOTONIC CRYSTAL FIBER EMPLOYING ELLIPTICAL AIR HOLES IN FIBER CLADDING WITH TETRAGONAL LATTICE. <i>Progress in Electromagnetics Research B</i> , 2010 , 22, 39-52	0.7	31
32	Ultrahigh Birefringence with Ultralow Confinement Loss of Photonic Crystal Fibers 2010 ,		1
31	A New Type of Optical Antenna: Plasmonics Nanoshell Bowtie Antenna with Dielectric Hole. <i>Journal of Electromagnetic Waves and Applications</i> , 2010 , 24, 1621-1632	1.3	35
30	Surface plasmon resonance in a hexagonal nanostructure formed by seven core shell nanocylinders. <i>Applied Optics</i> , 2010 , 49, 920-6	0.2	37
29	Controlling surface plasmon of several pair arrays of silver-shell nanocylinders. <i>Applied Optics</i> , 2010 , 49, 1163-9	0.2	24

28	Plasmon field enhancement in silver core-protruded silicon shell nanocylinder illuminated with light at 633 nm. <i>Applied Optics</i> , 2010 , 49, 6295-301	0.2	14
27	Enhanced surface plasmon resonance based on the silver nanoshells connected by the nanobars. <i>Optics Express</i> , 2010 , 18, 3510-8	3.3	37
26	Electromagnetic energy vortex associated with sub-wavelength plasmonic Taiji marks. <i>Optics Express</i> , 2010 , 18, 19665-71	3.3	35
25	Surface Plasmon Resonances Effects on Different Patterns of Solid-silver and Silver-shell Nanocylindrical Pairs. <i>Journal of Electromagnetic Waves and Applications</i> , 2010 , 24, 1005-1014	1.3	38
24	Surface Plasmon Effects Excited by the Dielectric Hole in a Silver-Shell Nanospherical Pair. <i>Plasmonics</i> , 2009 , 4, 253-259	2.4	38
23	Intersecting veins effects of a two-dimensional photonic crystal with a large two-dimensional complete bandgap. <i>Optics Communications</i> , 2009 , 282, 4296-4298	2	9
22	Three-dimensional analysis of surface plasmon resonance modes on a gold nanorod. <i>Applied Optics</i> , 2009 , 48, 617-22	0.2	43
21	Surface plasmon effects excitation from three-pair arrays of silver-shell nanocylinders. <i>Physics of Plasmas</i> , 2009 , 16, 022303	2.1	37
20	Near-field optical properties and surface plasmon effects generated by a dielectric hole in a silver-shell nanocylinder pair. <i>Applied Optics</i> , 2008 , 47, 5557-61	0.2	55
19	Highly Birefringent Index-Guiding Photonic Crystal Fiber with Squeezed Differently Sized Air-Holes in Cladding. <i>Japanese Journal of Applied Physics</i> , 2008 , 47, 3755-3759	1.4	39
18	Effect of internal period on the optical dispersion of indefinite-medium materials. <i>Physical Review B</i> , 2008 , 77,	3.3	26
17	Analysis of High Birefringence of Four Types of Photonic Crystal Fiber by Combining Circular and Elliptical Air Holes in Fiber Cladding 2008 , 2008, 1-6		5
16	Three-Dimensional Analysis of Scattering Field Interactions and Surface Plasmon Resonance in Coupled Silver Nanospheres. <i>Plasmonics</i> , 2008 , 3, 157-164	2.4	40
15	The plasmon and distribution effects between incident light and active layer in PtOx-type super-resolution near-field structure. <i>Optics Communications</i> , 2008 , 281, 1293-1299	2	1
14	High birefringence and low loss circular air-holes photonic crystal fiber using complex unit cells in cladding. <i>Optics Communications</i> , 2008 , 281, 4334-4338	2	53
13	Three-dimensional analysis of silver nano-particles doping effects on super resolution near-field structure. <i>Optics Communications</i> , 2007 , 269, 389-394	2	36
12	The optical properties between an incident wave and the active layer of a bubble-pit AgOx-type super-resolution near-field structure. <i>Applied Physics A: Materials Science and Processing</i> , 2007 , 89, 381-385	2.6	3
11	Near-Field Optics Imaging in Silica Waveguide Using Near-Field Scanning Optical Microscope. <i>Japanese Journal of Applied Physics</i> , 2007 , 46, 238-242	1.4	2

10	High birefringence photonic crystal fiber with a complex unit cell of asymmetric elliptical air hole cladding. <i>Applied Optics</i> , 2007 , 46, 5276-81	1.7	58
9	Significantly Enhanced Birefringence of Photonic Crystal Fiber Using Rotational Binary Unit Cell in Fiber Cladding. <i>Japanese Journal of Applied Physics</i> , 2007 , 46, L1048-L1051	1.4	36
8	50/50 beam splitter using a one-dimensional metal photonic crystal with parabolalike dispersion. <i>Applied Physics Letters</i> , 2007 , 90, 251909	3.4	35
7	Two-Dimensional and Three-Dimensional Analysis of Taper Structures for Coupling into and out of Photonic Crystal Slab Waveguides. <i>Japanese Journal of Applied Physics</i> , 2006 , 45, 7746-7752	1.4	2
6	Efficient mode coupling technique between photonic crystal heterostructure waveguide and silica waveguides. <i>Optics Communications</i> , 2005 , 253, 308-314	2	6
5	Imaging Properties of Three Dimensional Aperture Near-Field Scanning Optical Microscopy and Optimized Near-Field Fiber Probe Designs. <i>Japanese Journal of Applied Physics</i> , 2004 , 43, 8115-8125	1.4	13
4	Significantly Enhanced Coupling Efficiency in 2D Photonic Crystal Waveguides by Using Cabin-Side-Like Tapered Structures at Two Terminals. <i>Japanese Journal of Applied Physics</i> , 2004 , 43, L1064-L1067	1.4	3
3	Near-field optics simulation of a solid immersion lens combining with a conical probe and a highly efficient solid immersion lens-probe system. <i>Journal of Applied Physics</i> , 2004 , 95, 3378-3384	2.5	6
2	Coupling technique for efficient interfacing between silica waveguides and planar photonic crystal circuits. <i>Applied Optics</i> , 2004 , 43, 6656-63	1.7	38
1	Radome slope compensation using multiple-model Kalman filters. <i>Journal of Guidance, Control, and Dynamics</i> , 1995 , 18, 637-640	2.1	29