

Jinho Bae

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/4932224/publications.pdf>

Version: 2024-02-01

116
papers

1,718
citations

279798

23
h-index

377865

34
g-index

120
all docs

120
docs citations

120
times ranked

1423
citing authors

#	ARTICLE	IF	CITATIONS
1	All-printed humidity sensor based on graphene/methyl-red composite with high sensitivity. Carbon, 2016, 105, 23-32.	10.3	125
2	Bio-waste sunflower husks powder based recycled triboelectric nanogenerator for energy harvesting. Energy Reports, 2021, 7, 724-731.	5.1	61
3	Ink-jet printed stretchable strain sensor based on graphene/ZnO composite on micro-random ridged PDMS substrate. Composites Part A: Applied Science and Manufacturing, 2018, 107, 519-528.	7.6	58
4	All-Printed Differential Temperature Sensor for the Compensation of Bending Effects. Langmuir, 2016, 32, 11432-11439.	3.5	46
5	Ultra-robust tribo- and piezo-electric nanogenerator based on metal organic frameworks (MOF-5) with high environmental stability. Nano Energy, 2022, 96, 107128.	16.0	46
6	All range highly linear and sensitive humidity sensor based on 2D material TiSi2 for real-time monitoring. Sensors and Actuators B: Chemical, 2021, 345, 130371.	7.8	43
7	All-printed and highly stable organic resistive switching device based on graphene quantum dots and polyvinylpyrrolidone composite. Organic Electronics, 2015, 25, 225-231.	2.6	42
8	A flat-panel-shaped hybrid piezo/triboelectric nanogenerator for ambient energy harvesting. Nanotechnology, 2017, 28, 175402.	2.6	42
9	Disposable all-printed electronic biosensor for instantaneous detection and classification of pathogens. Scientific Reports, 2018, 8, 5920.	3.3	42
10	Biowaste Peanut Shell Powder-Based Triboelectric Nanogenerator for Biomechanical Energy Scavenging and Sustainably Powering Electronic Supplies. ACS Applied Electronic Materials, 2020, 2, 3953-3963.	4.3	41
11	Spectral shape tunable band-rejection filter using a long-period fiber grating with divided coil heaters. IEEE Photonics Technology Letters, 2003, 15, 407-409.	2.5	38
12	Printable Highly Stable and Superfast Humidity Sensor Based on Two Dimensional Molybdenum Diselenide. Scientific Reports, 2020, 10, 5509.	3.3	36
13	Natural seagrass tribopositive material based spray coatable triboelectric nanogenerator. Nano Energy, 2021, 89, 106458.	16.0	36
14	All printed full range humidity sensor based on Fe2O3. Sensors and Actuators A: Physical, 2020, 311, 112072.	4.1	32
15	Wide range and stable ink-jet printed humidity sensor based on graphene and zinc oxide nanocomposite. Journal of Materials Science: Materials in Electronics, 2018, 29, 5806-5813.	2.2	31
16	Bio-compatible organic humidity sensor based on natural inner egg shell membrane with multilayer crosslinked fiber structure. Scientific Reports, 2019, 9, 5824.	3.3	30
17	Schottky diode based resistive switching device based on ZnO/PEDOT:PSS heterojunction to reduce sneak current problem. Journal of Materials Science: Materials in Electronics, 2019, 30, 4607-4617.	2.2	29
18	Two dimensional Zirconium diselenide based humidity sensor for flexible electronics. Sensors and Actuators B: Chemical, 2022, 358, 131507.	7.8	29

#	ARTICLE	IF	CITATIONS
19	Organic non-volatile memory cell based on resistive elements through electro-hydrodynamic technique. <i>Organic Electronics</i> , 2015, 17, 121-128.	2.6	28
20	Microstrip Patch Sensor for Salinity Determination. <i>Sensors</i> , 2017, 17, 2941.	3.8	28
21	Humidity sensor based on Gallium Nitride for real time monitoring applications. <i>Scientific Reports</i> , 2021, 11, 11088.	3.3	27
22	PVA/TEOS crosslinked membranes incorporating zinc oxide nanoparticles and sodium alginate to improve reverse osmosis performance for desalination. <i>Journal of Applied Polymer Science</i> , 2019, 136, 47559.	2.6	26
23	Ultra-low power non-volatile resistive crossbar memory based on pull up resistors. <i>Organic Electronics</i> , 2017, 41, 73-78.	2.6	25
24	Inkjet-printed antenna on thin PET substrate for dual band Wi-Fi communications. <i>Microsystem Technologies</i> , 2017, 23, 3701-3709.	2.0	25
25	Bipolar resistive switching device based on N,N'-bis(3-methylphenyl)-N,N'-diphenylbenzidine and poly(3,4-ethylenedioxythiophene):poly(styrene sulfonate)/poly(vinyl alcohol) bilayer stacked structure. <i>Applied Physics A: Materials Science and Processing</i> , 2018, 124, 1.	2.3	23
26	Dynamic EDFA gain-flattening filter using two LPFGs with divided coil heaters. <i>IEEE Photonics Technology Letters</i> , 2005, 17, 1226-1228.	2.5	21
27	Capacitive coupled non-zero λ and type-II memristive properties of the NiFe ₂ O ₄ @TiO ₂ nanocomposite. <i>Materials Science in Semiconductor Processing</i> , 2021, 125, 105646.	4.0	21
28	Design of versatile printed organic resistor based on resistivity (ρ) control. <i>Applied Physics A: Materials Science and Processing</i> , 2015, 119, 1499-1506.	2.3	20
29	Resistive switching device based on water and zinc oxide heterojunction for soft memory applications. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2019, 246, 1-6.	3.5	20
30	Inner egg shell membrane based bio-compatible capacitive and piezoelectric function dominant self-powered pressure sensor array for smart electronic applications. <i>RSC Advances</i> , 2020, 10, 29214-29227.	3.6	20
31	Triboelectric nanogenerator based on lignocellulosic waste fruit shell tribopositive material: Comparative analysis. <i>Materials Today Sustainability</i> , 2022, 18, 100146.	4.1	20
32	Non-volatile resistive switching based on zirconium dioxide: poly (4-vinylphenol) nano-composite. <i>Applied Physics A: Materials Science and Processing</i> , 2019, 125, 1.	2.3	19
33	Novel Recycled Triboelectric Nanogenerator Based on Polymer-Coated Trash Soda Can for Clean Energy Harvesting. <i>Advanced Sustainable Systems</i> , 2021, 5, 2100161.	5.3	19
34	Flexible frequency selective passive circuits based on memristor and capacitor. <i>Organic Electronics</i> , 2017, 51, 119-127.	2.6	18
35	Inkjet printed self-healable strain sensor based on graphene and magnetic iron oxide nano-composite on engineered polyurethane substrate. <i>Scientific Reports</i> , 2020, 10, 18234.	3.3	18
36	Natural Hierarchically Structured Highly Porous Tomato Peel Based Triboelectric and Piezoelectric Nanogenerator for Efficient Energy Harvesting. <i>Advanced Sustainable Systems</i> , 2021, 5, 2100066.	5.3	18

#	ARTICLE	IF	CITATIONS
37	Printed non-volatile resistive switches based on zinc stannate (ZnSnO ₃). <i>Current Applied Physics</i> , 2016, 16, 757-762.	2.4	17
38	Solution-processed flexible non-volatile resistive switching device based on poly[(9,9-di-n-octylfluorenyl-2,7-diyl)-alt-(benzo[2,1,3]thiadiazol-4,8-diyl)]: polyvinylpyrrolidone composite and its conduction mechanism. <i>Applied Physics A: Materials Science and Processing</i> , 2019, 125, 1.	2.3	17
39	Particle triboelectric nanogenerator (P-TENG). <i>Nano Energy</i> , 2022, 100, 107475.	16.0	17
40	Flexible and passive photo sensor based on perylene/graphene composite. <i>Sensors and Actuators B: Chemical</i> , 2015, 220, 634-640.	7.8	16
41	Organic diode with high rectification ratio made of electrohydrodynamic printed organic layers. <i>Electronic Materials Letters</i> , 2016, 12, 270-275.	2.2	16
42	Inkjet printed transparent and bendable patch antenna based on polydimethylsiloxane and indium tin oxide nanoparticles. <i>Microwave and Optical Technology Letters</i> , 2016, 58, 2884-2887.	1.4	16
43	Highly bendable asymmetric resistive switching memory based on zinc oxide and magnetic iron oxide heterojunction. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 1105-1115.	2.2	16
44	Soft ionic liquid based resistive memory characteristics in a two terminal discrete polydimethylsiloxane cylindrical microchannel. <i>Journal of Materials Chemistry C</i> , 2020, 8, 13368-13374.	5.5	16
45	Stretchable photo sensor using perylene/graphene composite on ridged polydimethylsiloxane substrate. <i>Optics Express</i> , 2015, 23, 30583.	3.4	15
46	Flexible resistive switching device based on poly(3,4-ethylenedioxythiophene):poly(styrene sulfonate) (PEDOT:PSS)/poly(4-vinylphenol) (PVP) composite and methyl red heterojunction. <i>Applied Physics A: Materials Science and Processing</i> , 2017, 123, 1.	2.3	15
47	Resistive switching device with highly asymmetric current-voltage characteristics: a solution to backward sneak current in passive crossbar arrays. <i>Nanotechnology</i> , 2018, 29, 455201.	2.6	15
48	Soft and flexible: core-shell ionic liquid resistive memory for electronic synapses. <i>Microsystems and Nanoengineering</i> , 2021, 7, 78.	7.0	15
49	Highly Flexible and Asymmetric Hexagonal-Shaped Crystalline Structured Germanium Dioxide-Based Multistate Resistive Switching Memory Device for Data Storage and Neuromorphic Computing. <i>Advanced Electronic Materials</i> , 2022, 8, .	5.1	15
50	All printed antenna based on silver nanoparticles for 1.8 GHz applications. <i>Applied Physics A: Materials Science and Processing</i> , 2016, 122, 1.	2.3	14
51	All printed organic humidity sensor based on egg albumin. <i>Sensing and Bio-Sensing Research</i> , 2020, 28, 100337.	4.2	14
52	Ink-jet printed transparent and flexible electrodes based on silver nanoparticles. <i>Journal of Materials Science: Materials in Electronics</i> , 2018, 29, 49-55.	2.2	13
53	Asymmetric GaN/ZnO Engineered Resistive Memory Device for Electronic Synapses. <i>ACS Applied Electronic Materials</i> , 2022, 4, 297-307.	4.3	13
54	All printed wide range humidity sensor array combining MoSe ₂ and PVOH in series. <i>Journal of Materials Science: Materials in Electronics</i> , 2020, 31, 7683-7697.	2.2	12

#	ARTICLE	IF	CITATIONS
55	Bioinspired Soft Multistate Resistive Memory Device Based on Silk Fibroin Gel for Neuromorphic Computing. <i>Advanced Engineering Materials</i> , 2022, 24, .	3.5	12
56	Synthesis of Flat-Top Bandpass Filters Using Two-Band Rejection Long-Period Fiber Gratings. <i>IEEE Photonics Technology Letters</i> , 2007, 19, 1466-1468.	2.5	11
57	Flexible Resistive Switching Memory with a Schottky Diode Function Based on a Zinc Oxide/Methylene Blue Heterojunction. <i>Journal of Electronic Materials</i> , 2020, 49, 4764-4772.	2.2	11
58	Wide range and highly linear signal processed systematic humidity sensor array using Methylene Blue and Graphene composite. <i>Scientific Reports</i> , 2021, 11, 16665.	3.3	11
59	Two Methods for Synthesizing the Long Period Fiber Gratings with the Inverted Erbium Gain Spectrum. <i>Japanese Journal of Applied Physics</i> , 1999, 38, L819-L822.	1.5	10
60	Analysis of the Fiber Bragg Gratings using the Lattice Filter Model. <i>Japanese Journal of Applied Physics</i> , 2000, 39, 1752-1756.	1.5	10
61	Resistive switching memory utilizing water and titanium dioxide thin film Schottky diode. <i>Journal of Materials Science: Materials in Electronics</i> , 2019, 30, 18744-18752.	2.2	10
62	Ionic liquid multistate resistive switching characteristics in two terminal soft and flexible discrete channels for neuromorphic computing. <i>Microsystems and Nanoengineering</i> , 2022, 8, .	7.0	10
63	Numerical optimization approach for designing bandpass filters using fiber Bragg gratings. <i>Optical Engineering</i> , 2003, 42, 23.	1.0	9
64	Analysis of Concatenated Long Period Fiber Gratings Having Phase-Shifted and Cascaded Effects. <i>Japanese Journal of Applied Physics</i> , 2003, 42, 5098-5101.	1.5	9
65	Analysis for long period fiber gratings using thermal kernel function. <i>Optics Express</i> , 2004, 12, 797.	3.4	9
66	Synthesis of Long-Period Fiber Gratings With the Inverted Erbium Gain Spectrum Using the Multiport Lattice Filter Model. <i>Journal of Lightwave Technology</i> , 2004, 22, 1976-1986.	4.6	9
67	Numerically extrapolated discrete layer-peeling algorithm for synthesis of nonuniform fiber Bragg gratings. <i>Optics Express</i> , 2011, 19, 8254.	3.4	8
68	An inkjet-printed microstrip patch sensor for liquid identification. <i>Sensors and Actuators A: Physical</i> , 2017, 268, 141-147.	4.1	8
69	The Schur algorithm applied to the design of optical multi-mirror structures. <i>Numerical Linear Algebra With Applications</i> , 2005, 12, 283-292.	1.6	7
70	Multistate Resistive Switching with Self-Rectifying Behavior and Synaptic Characteristics in a Solution-processed ZnO/PTAA Bilayer Memristor. <i>Journal of the Electrochemical Society</i> , 2022, 169, 063517.	2.9	7
71	Multiport Lattice Filter Model for Long-Period Fiber Gratings. <i>Japanese Journal of Applied Physics</i> , 2000, 39, 6576-6577.	1.5	6
72	Circulant Matrix Factorization Based on Schur Algorithm for Designing Optical Multimirror Filters. <i>Japanese Journal of Applied Physics</i> , 2006, 45, 5163-5168.	1.5	6

#	ARTICLE	IF	CITATIONS
73	Synthesis method based on genetic algorithm for designing EDFA gain flattening LPFGs having phase-shifted effect. <i>Optical Fiber Technology</i> , 2009, 15, 320-323.	2.7	5
74	Enhancing Mechanical Energy Transfer of Piezoelectric Supercapacitors. <i>Advanced Materials Technologies</i> , 2022, 7, 2100550.	5.8	5
75	Expired Pharmaceutical Drugs as Tribopositive Material for Triboelectric Nanogenerator. <i>Advanced Sustainable Systems</i> , 2021, 5, 2100205.	5.3	4
76	Equalization of the non-flat erbium gain spectrum using the multiport lattice filter model. , 0, , .		3
77	Flexible dual-band antenna for communication and radar applications. , 2016, , .		3
78	A flexible differential temperature sensor for wearable electronics applications. , 2019, , .		3
79	Resistive switching device with highly-asymmetric current-voltage characteristics: its error analysis and new design parameter. <i>Semiconductor Science and Technology</i> , 2019, 34, 025007.	2.0	3
80	<title>Analysis of the fiber Bragg gratings using the lattice filter model</title>. , 1998, , .		2
81	Equalization of Erbium Gain Spectrum Using the Multiport Lattice Filter. <i>Fiber and Integrated Optics</i> , 2002, 21, 31-42.	2.5	2
82	Synthesis of Tunable Long-Period Fiber Gratings with Inverted Erbium-Doped Fiber Amplifier Spectrum Using Thermal Change Parameters. <i>Japanese Journal of Applied Physics</i> , 2005, 44, L156-L158.	1.5	2
83	Synthesis method based on optimization techniques for designing piecewise-uniform long-period fiber gratings controlled by thermal changes. <i>Journal of the Optical Society of America B: Optical Physics</i> , 2006, 23, 1241.	2.1	2
84	The block Schur algorithm for designing optical multi-layered structures. <i>Optics Communications</i> , 2007, 272, 40-43.	2.1	2
85	DYNAMIC MODELING AND STRUCTURAL ANALYSIS OF MANTA-TYPE UUV. <i>International Journal of Modern Physics B</i> , 2011, 25, 4319-4322.	2.0	2
86	The Schur Algorithm Applied to the One-Dimensional Continuous Inverse Scattering Problem. <i>IEEE Transactions on Signal Processing</i> , 2013, 61, 3311-3320.	5.3	2
87	Liquid Capacitor Based on Hafnium Oxide. <i>Key Engineering Materials</i> , 0, 801, 211-216.	0.4	2
88	Target Classification Algorithm Using Complex-valued Support Vector Machine. <i>Journal of the Institute of Electronics and Information Engineers</i> , 2013, 50, 182-188.	0.0	2
89	Target Detection Algorithm Based on Seismic Sensor for Adaptation of Background Noise. <i>Journal of the Institute of Electronics and Information Engineers</i> , 2013, 50, 258-266.	0.0	2
90	EEG Signal Classification Algorithm based on DWT and SVM for Driving Robot Control. <i>Journal of the Institute of Electronics and Information Engineers</i> , 2015, 52, 117-125.	0.0	2

#	ARTICLE	IF	CITATIONS
91	Expired Pharmaceutical Drugs as Tribopositive Material for Triboelectric Nanogenerator (Adv.) Tj ETQq1 1 0.784314rgBT /Overlock 10T	5.8	2
92	Multiport lattice filter model for long-period fiber gratings. , 2000, 3944, 780.		1
93	<title>Parameter identification for the cascaded fiber optic lattice structure using the Schur algorithm</title>. , 2001, , .		1
94	A New Layer-Peeling Algorithm for Lossy Media without Using Phase Information. Japanese Journal of Applied Physics, 2002, 41, L770-L772.	1.5	1
95	SEMI-EMPIRICAL KERNEL FUNCTION FOR THE ANALYSIS OF FIBER BRAGG GRATINGS UNDER TEMPERATURE DISTRIBUTIONS. International Journal of Modern Physics B, 2011, 25, 4208-4211.	2.0	1
96	Synthesis of Optical IIR Allpass Filters Using Layer Peeling Algorithm Based on Eigenvalue Problem. IEEE Photonics Technology Letters, 2013, 25, 626-628.	2.5	1
97	Implementation of a Rotational Ultrasound Biomicroscopy System Equipped with a High-Frequency Angled Needle Transducer " Ex Vivo Ultrasound Imaging of Porcine Ocular Posterior Tissues. Sensors, 2014, 14, 17807-17816.	3.8	1
98	Flexible and stackable non-volatile resistive memory for high integration. Proceedings of SPIE, 2015, , .	0.8	1
99	Inkjet printed organic-inorganic bilayer photoconductive sensor. , 2018, , .		1
100	All-printed organic and oxide hetero-structure device with photoconductivity. , 2018, , .		1
101	All-printed Stretchable Photo-Conductive Device Fabricated on Engineered PDMS. , 2018, , .		1
102	Classification of Transient Signals in Ocean Background Noise Using Bayesian Classifier. Journal of Ocean Engineering and Technology, 2012, 26, 57-63.	1.2	1
103	Schur Algorithm for Sub-bottom Profiling. Journal of the Institute of Electronics and Information Engineers, 2013, 50, 156-163.	0.0	1
104	Sub-bottom Profiling Algorithm using Parametric Array. Journal of Ocean Engineering and Technology, 2014, 28, 55-63.	1.2	1
105	Target Path Detection Algorithm Using Activation Time Lag of PDR Sensors Based on USN. The Journal of the Institute of Internet Broadcasting and Communication, 2015, 15, 179-186.	0.0	1
106	Extracting 3-D parameters of an object from its 2-D images using the simulated annealing. , 2000, , .		0
107	A Low-Cost Orbit Determination Method for Mobile Communication Satellites. Transactions of the Japan Society for Aeronautical and Space Sciences, 2004, 46, 271-274.	0.7	0
108	Analysis of Long Period Fiber Grating using Thermally Tunable Multiport Lattice Model. , 2006, , .		0

#	ARTICLE	IF	CITATIONS
109	Semi-Empirical Model for the Thermally tunable LPFG. , 2007, , .		0
110	Semi-empirical multi-port lattice model for long-period fiber grating analysis under arbitrary temperature distributions. Optics Express, 2008, 16, 598.	3.4	0
111	A novel maneuvering target tracking algorithm based on moving slide window. , 2010, , .		0
112	New Combined Matrix Model for the Analysis of Merged Optical Fiber Gratings with both Long- and Short-Period Fiber Gratings. Japanese Journal of Applied Physics, 2010, 49, 070207.	1.5	0
113	Implementation of an ultrasound biomicroscopy system by rotational scanning of a high-frequency angled needle transducer. , 2011, , .		0
114	Memristor-capacitor passive filters to tune both cut-off frequency and bandwidth. Proceedings of SPIE, 2017, , .	0.8	0
115	Analysis of Features and Discriminability of Transient Signals for a Shallow Water Ambient Noise Environment. Journal of the Institute of Electronics and Information Engineers, 2014, 51, 209-220.	0.0	0
116	Enhancing Mechanical Energy Transfer of Piezoelectric Supercapacitors (Adv. Mater. Technol. 4/2022). Advanced Materials Technologies, 2022, 7, .	5.8	0