

Zhonghao Jiang

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/4997896/publications.pdf>

Version: 2024-02-01

79
papers

2,469
citations

186209

28
h-index

214721

47
g-index

80
all docs

80
docs citations

80
times ranked

2325
citing authors

#	ARTICLE	IF	CITATIONS
1	Thermodynamic analysis on wetting states and wetting state transitions of rough surfaces. <i>Advances in Colloid and Interface Science</i> , 2020, 278, 102136.	7.0	31
2	Effect of Zn addition on the microstructures and mechanical behaviors of As-cast Mg-2.5Y-1Ce-0.5Mn alloy. <i>Materials Research Express</i> , 2020, 7, 016564.	0.8	0
3	Nanoindentation creep deformation behaviour of high nitrogen nickel-free austenitic stainless steel. <i>Materials Science and Technology</i> , 2019, 35, 1592-1599.	0.8	6
4	A universal method to fabricate Cu films with superhydrophobic and anti-corrosion properties. <i>Materials Science and Technology</i> , 2019, 35, 695-701.	0.8	6
5	Nanoindentation creep behavior and its relation to activation volume and strain rate sensitivity of nanocrystalline Cu. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2019, 751, 35-41.	2.6	30
6	Strain rate dependence of tensile strength and ductility of nano and ultrafine grained coppers. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2018, 712, 341-349.	2.6	16
7	Strain Rate Dependence of Tensile Properties of Extruded Mg-9Y-3Zn-1Mn Alloy. <i>Advanced Engineering Materials</i> , 2018, 20, 1800123.	1.6	3
8	Plastic deformation and fracture behaviour of high-nitrogen nickel-free austenitic stainless steel. <i>Materials Science and Technology</i> , 2017, 33, 1635-1644.	0.8	9
9	Fabrication of Superhydrophobic Calcium Phosphate Coating on Mg-Zn-Ca alloy and Its Corrosion Resistance. <i>Journal of Materials Engineering and Performance</i> , 2017, 26, 6117-6129.	1.2	19
10	A novel open architecture built by ultra-fine single-crystal $\text{Co}_2(\text{CO}_3)_2(\text{OH})_2$ nanowires and reduced graphene oxide for asymmetric supercapacitors. <i>Journal of Materials Chemistry A</i> , 2016, 4, 17171-17179.	5.2	74
11	A unique porous architecture built by ultrathin wrinkled $\text{NiCo}_2\text{O}_4/\text{rGO}/\text{NiCo}_2\text{O}_4$ sandwich nanosheets for pseudocapacitance and Li ion storage. <i>Journal of Materials Chemistry A</i> , 2016, 4, 10304-10313.	5.2	72
12	Plastic flow behavior and its relationship to tensile mechanical properties of high nitrogen nickel-free austenitic stainless steel. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2016, 662, 432-442.	2.6	25
13	Carbon-Encapsulated Co_3O_4 Nanoparticles as Anode Materials with Super Lithium Storage Performance. <i>Scientific Reports</i> , 2015, 5, 16629.	1.6	73
14	Ultrathin Mesoporous NiCo_2O_4 Nanosheet Networks as High-Performance Anodes for Lithium Storage. <i>ChemPlusChem</i> , 2015, 80, 1725-1731.	1.3	31
15	Effects of loading strain rate and stacking fault energy on nanoindentation creep behaviors of nanocrystalline Cu, Ni-20 wt.%Fe and Ni. <i>Journal of Alloys and Compounds</i> , 2015, 647, 670-680.	2.8	55
16	The Synthesis and Electrochemical Behavior of High-Nitrogen Nickel-Free Austenitic Stainless Steel. <i>Journal of Materials Engineering and Performance</i> , 2014, 23, 3957-3962.	1.2	16
17	Impact dynamics of water droplets on Cu films with three-level hierarchical structures. <i>Journal of Materials Science</i> , 2014, 49, 3379-3390.	1.7	14
18	Cu surfaces with controlled structures: From intrinsically hydrophilic to apparently superhydrophobic. <i>Applied Surface Science</i> , 2014, 290, 320-326.	3.1	28

#	ARTICLE	IF	CITATIONS
19	Effect of strain rate on tensile properties of electric brush-plated nanocrystalline copper. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2014, 618, 621-628.	2.6	22
20	Microstructures and mechanical properties of extruded Mg \hat{e} 2Sn \hat{e} xYb (x=0, 0.1, 0.5 \hat{A} at.%) sheets. <i>Journal of Magnesium and Alloys</i> , 2014, 2, 257-264.	5.5	10
21	Influences of Y and Y-Rich Mischmetal Additions on Microstructure and Compressive Properties of As-Cast Al-Mg-Mn Alloy. <i>Journal of Materials Engineering and Performance</i> , 2013, 22, 1201-1207.	1.2	4
22	Stable ductility of an electrodeposited nanocrystalline Ni \hat{e} 20wt.%Fe alloy in tensile plastic deformation. <i>Journal of Alloys and Compounds</i> , 2013, 553, 99-105.	2.8	9
23	Friction and Wear Behavior of Nanocrystalline Nickel in Air and Vacuum. <i>Tribology Letters</i> , 2013, 49, 481-490.	1.2	14
24	Dislocation-mediated creep process in nanocrystalline Cu. <i>Chinese Physics B</i> , 2013, 22, 037303.	0.7	7
25	Study on energy loss of high-energy protons in nano crystalline Ni. <i>Radiation Effects and Defects in Solids</i> , 2013, 168, 933-939.	0.4	0
26	Preparation of Nanocrystalline Cu Films by Brush-Plating. <i>Integrated Ferroelectrics</i> , 2012, 137, 52-60.	0.3	2
27	High-speed creep process mediated by rapid dislocation absorption in nanocrystalline Cu. <i>Journal of Applied Physics</i> , 2012, 111, 063506.	1.1	16
28	Microstructure and Mechanical Properties of an Extruded Mg-2Dy-0.5Zn Alloy. <i>Journal of Materials Science and Technology</i> , 2012, 28, 543-551.	5.6	23
29	Self-assembly growth and electron work function of copper phthalocyanine films on indium tin oxide glass. <i>Applied Surface Science</i> , 2012, 258, 3373-3377.	3.1	8
30	On the correlation between surface morphology and electron work function of indium tin oxide. <i>Journal of Applied Physics</i> , 2012, 111, 123714.	1.1	15
31	Changes in surface morphology and work function caused by corrosion in aluminum alloys. <i>Journal of Physics and Chemistry of Solids</i> , 2012, 73, 781-787.	1.9	16
32	Double-peak ageing behavior of Mg \hat{e} 2Dy \hat{e} 0.5Zn alloy. <i>Journal of Alloys and Compounds</i> , 2011, 509, 8268-8275.	2.8	31
33	Preparation of nano-silver iodide powders and their efficiency as ice-nucleating agent in weather modification. <i>Advanced Powder Technology</i> , 2011, 22, 613-616.	2.0	12
34	Synthesis of \hat{I}^2 -phase Ag $1\hat{a}$ xCu $1\hat{a}$ (x=0 \hat{a} 0.5) solid solutions nanocrystals. <i>Materials Research Bulletin</i> , 2011, 46, 910-913.	2.7	5
35	Superhydrophobicity of bionic alumina surfaces fabricated by hard anodizing. <i>Journal of Bionic Engineering</i> , 2011, 8, 369-374.	2.7	32
36	An elevated temperature Mg \hat{e} Dy \hat{e} Zn alloy with long period stacking ordered phase by extrusion. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2011, 528, 3609-3614.	2.6	54

#	ARTICLE	IF	CITATIONS
37	Preparation of nano-Cr ₂ xAlxO ₃ (x=0~1) solid solution powders by using citrate-dispersant method. Materials Science and Engineering B: Solid-State Materials for Advanced Technology, 2010, 172, 33-36.	1.7	2
38	The origin of the ultrahigh strength and good ductility in nanotwinned copper. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2010, 527, 4270-4274.	2.6	23
39	Microstructures and mechanical properties of Mg ₂ Y ₁ Mn ₁ Nd alloys fabricated by extrusion. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2010, 527, 4383-4388.	2.6	12
40	Fabrication of super-hydrophobic nano-sized copper films by electroless plating. Thin Solid Films, 2010, 518, 3731-3734.	0.8	13
41	Super-hydrophobic property of nano-sized cupric oxide films. Surface and Coatings Technology, 2010, 204, 3200-3204.	2.2	53
42	Wetting of Cu substrates with micrometer and nanometer grains by molten Sn _{3.5} Ag _{0.7} Cu alloy. Surface and Interface Analysis, 2010, 42, 1681-1684.	0.8	5
43	Dual-phase nanocrystalline Ni ₂ Co alloy with high strength and enhanced ductility. Journal of Materials Research, 2010, 25, 401-405.	1.2	5
44	ENHANCED TENSILE DUCTILITY IN AN ELECTRODEPOSITED Cu WITH NANO-SIZED GROWTH TWINS. International Journal of Modern Physics B, 2010, 24, 2537-2542.	1.0	3
45	Tensile-relaxation behavior of electrodeposited nanocrystalline Ni. Journal of Applied Physics, 2010, 108, 054319.	1.1	11
46	Compressive creep behavior of an electric brush-plated nanocrystalline Cu at room temperature. Journal of Applied Physics, 2009, 106, .	1.1	16
47	The grain refinement mechanism of electrodeposited copper. Journal of Materials Research, 2009, 24, 3226-3236.	1.2	6
48	Microstructure and tensile deformation of nanocrystalline Cu produced by pulse electrodeposition. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2009, 517, 316-320.	2.6	19
49	Microstructure and properties of thin wall by laser cladding forming. Journal of Materials Processing Technology, 2009, 209, 4970-4976.	3.1	35
50	A novel electrodeposited nanostructured Ni coating with grain size gradient distribution. Surface and Coatings Technology, 2008, 203, 142-147.	2.2	22
51	Electroless Ni-P deposition on magnesium alloy from a sulfate bath. Journal Wuhan University of Technology, Materials Science Edition, 2008, 23, 60-64.	0.4	4
52	Bulk Nanostructured Cu with High Strength and Good Ductility. Advanced Engineering Materials, 2008, 10, 41-45.	1.6	13
53	Formation of a Multiphase Gradient Structure in a Zr ₂ Cu ₂ Ni ₂ Al ₂ O Alloy. Advanced Engineering Materials, 2008, 10, 384-388.	1.6	12
54	The Optimal Grain Sized Nanocrystalline Ni with High Strength and Good Ductility Fabricated by a Direct Current Electrodeposition. Advanced Engineering Materials, 2008, 10, 539-546.	1.6	31

#	ARTICLE	IF	CITATIONS
55	High strength and high ductility of electrodeposited nanocrystalline Ni with a broad grain size distribution. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2008, 487, 410-416.	2.6	69
56	Strain rate dependence of tensile ductility in an electrodeposited Cu with ultrafine grain size. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2008, 479, 136-141.	2.6	28
57	Enhanced tensile ductility in an electrodeposited nanocrystalline copper. <i>Journal of Materials Research</i> , 2008, 23, 2238-2244.	1.2	20
58	Mechanical behavior of an electrodeposited nanostructured Cu with a mixture of nanocrystalline grains and nanoscale growth twins in submicrometer grains. <i>Journal of Applied Physics</i> , 2008, 104, 084305.	1.1	18
59	Strong work-hardening effect in a multiphase ZrCuAlNiO alloy. <i>Applied Physics Letters</i> , 2008, 92, .	1.5	23
60	Deformation mechanism transition caused by strain rate in a pulse electric brush-plated nanocrystalline Cu. <i>Journal of Applied Physics</i> , 2008, 104, .	1.1	33
61	Ductileâ€“brittleâ€“ductile transition in an electrodeposited 13 nanometer grain sized Niâ€“8.6wt.% Co alloy. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2007, 459, 75-81.	2.6	36
62	High corrosion-resistance nanocrystalline Ni coating on AZ91D magnesium alloy. <i>Surface and Coatings Technology</i> , 2006, 200, 5413-5418.	2.2	187
63	Enhanced tensile ductility in an electrodeposited nanocrystalline Ni. <i>Scripta Materialia</i> , 2006, 54, 579-584.	2.6	113
64	Strain rate sensitivity of a nanocrystalline Cu synthesized by electric brush plating. <i>Applied Physics Letters</i> , 2006, 88, 143115.	1.5	83
65	Strain rate sensitivity of face-centered-cubic nanocrystalline materials based on dislocation deformation. <i>Journal of Applied Physics</i> , 2006, 99, 076103.	1.1	61
66	AN INVESTIGATION OF SMOOTH NANOSIZED COPPER FILMS ON GLASS SUBSTRATE BY IMPROVED ELECTROLESS PLATING. <i>Surface Review and Letters</i> , 2006, 13, 471-478.	0.5	4
67	High corrosion-resistant Niâ€“P/Ni/Niâ€“P multilayer coatings on steel. <i>Surface and Coatings Technology</i> , 2005, 197, 61-67.	2.2	97
68	An analytical model for elastic stress field distribution in fibre composite with partially debonded interface. <i>Composites Science and Technology</i> , 2005, 65, 1176-1194.	3.8	17
69	Electroless Niâ€“P plating on AZ91D magnesium alloy from a sulfate solution. <i>Journal of Alloys and Compounds</i> , 2005, 391, 104-109.	2.8	127
70	A black phosphate coating for C1008 steel. <i>Surface and Coatings Technology</i> , 2004, 176, 215-221.	2.2	102
71	A new analytical model for three-dimensional elastic stress field distribution in short fibre composite. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2004, 366, 381-396.	2.6	31
72	Elasticâ€“plastic stress transfer in short fibre-reinforced metalâ€“matrix composites. <i>Composites Science and Technology</i> , 2004, 64, 1661-1670.	3.8	17

#	ARTICLE	IF	CITATIONS
73	An analytical study of the influence of thermal residual stresses on the elastic and yield behaviors of short fiber-reinforced metal matrix composites. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 1998, 248, 256-275.	2.6	56
74	Effects of microstructural variables on the deformation behaviour of dual-phase steel. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 1995, 190, 55-64.	2.6	150
75	A dislocation density approximation for the flow stress-grain size relation of polycrystals. <i>Acta Metallurgica Et Materialia</i> , 1995, 43, 3349-3360.	1.9	41
76	The relationship between ductility and material parameters for dual-phase steel. <i>Journal of Materials Science</i> , 1993, 28, 1814-1818.	1.7	38
77	A new relationship between the flow stress and the microstructural parameters for dual phase steel. <i>Acta Metallurgica Et Materialia</i> , 1992, 40, 1587-1597.	1.9	31
78	Influence of predeformation on microstructure and mechanical properties of 1020 dual phase steel. <i>Materials Science and Technology</i> , 1991, 7, 527-532.	0.8	13
79	Enhanced tensile ductility in an electrodeposited nanocrystalline Ni. , 0, , .		1