

Peter Hanselaer

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/5296235/peter-hanselaer-publications-by-year.pdf>

Version: 2024-04-20

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

116
papers

2,016
citations

24
h-index

41
g-index

131
ext. papers

2,322
ext. citations

2.7
avg, IF

4.99
L-index

#	Paper	IF	Citations
116	Multi-Channel LED Luminaires: An Object-Oriented Approach for Retail Lighting Based on the SOR Framework. <i>Sustainability</i> , 2022 , 14, 5994	3.6	
115	A Comparison of Partition Scaling and Magnitude Estimation for Brightness Scaling. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2021 , 17, 265-279	3.5	1
114	Derivation of Brightness Scales Using Partition Scaling. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2021 , 17, 125-139	3.5	1
113	CAM18sl brightness prediction for unrelated saturated stimuli including age effects. <i>Optics Express</i> , 2021 , 29, 29257-29274	3.3	1
112	Effect of adapting field size on chromatic adaptation. <i>Optics Express</i> , 2020 , 28, 17266-17285	3.3	7
111	Freeform Fresnel lenses with a low number of discontinuities for tailored illumination applications. <i>Optics Express</i> , 2020 , 28, 24489-24500	3.3	4
110	BRDF characterization of Al-coated thermoplastic polymer surfaces 2020 , 17, 1195-1205		2
109	Relationship between pupillary size, brightness, and photoreceptor responses for unrelated self-luminous stimuli at low photopic light levels. <i>Color Research and Application</i> , 2020 , 45, 977-991	1.3	1
108	Impact of Illumination Correlated Color Temperature, Background Lightness, and Painting Color Content on Color Appearance and Appreciation of Paintings. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2020 , 16, 25-44	3.5	22
107	Development of an image-based gloss measurement instrument 2019 , 16, 913-921		3
106	Efficient Design Method of Segmented Lenses for Lighting Applications with Prescribed Intensity and Low Peak Luminance. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2019 , 15, 281-292	3.5	2
105	Assessing the application of an image color appearance model to basic self-luminous scenes. <i>Color Research and Application</i> , 2019 , 44, 848-858	1.3	1
104	Safety perception of stairs with integrated lighting. <i>Building and Environment</i> , 2019 , 166, 106389	6.5	4
103	Improving the opto-thermal performance of transmissive laser-based white light sources through beam shaping. <i>Optics Express</i> , 2019 , 27, A235-A244	3.3	6
102	Luminance spreading freeform lens arrays with accurate intensity control. <i>Optics Express</i> , 2019 , 27, 32994-33004	3.3	4
101	Impact of the starting point chromaticity on memory color matching accuracy. <i>Optics Express</i> , 2019 , 27, 35308-35324	3.3	6
100	Ray mapping method for off-axis and non-paraxial freeform illumination lens design. <i>Optics Letters</i> , 2019 , 44, 771-774	3	29

99	PILOT STUDY ON COLOR MATCHING ACCURACY USING DIFFERENT PRIMARIES 2019 ,		2
98	Exploring the applicability of the CAM18sl brightness prediction. <i>Optics Express</i> , 2019 , 27, 14423-14436	3.3	4
97	Holistic opto-thermal simulation framework for high-brightness light sources based on fluorescent conversion. <i>Optics Express</i> , 2019 , 27, A1324-A1337	3.3	1
96	Pupillary light reflex, receptive field mechanism and correction for retinal position for the assessment of visual discomfort. <i>Lighting Research and Technology</i> , 2019 , 51, 291-303	2	4
95	Towards a New Colour Appearance Model for Self-luminous Stimuli. <i>Journal of Science and Technology in Lighting</i> , 2018 , 41, 153-164	0.1	1
94	A psychophysical model for visual discomfort based on receptive fields. <i>Lighting Research and Technology</i> , 2018 , 50, 205-217	2	12
93	Color appearance model for self-luminous stimuli. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , 2018 , 35, 2000-2009	1.8	12
92	THE INFLUENCE OF ADAPTING FIELD SIZE ON DEGREE OF CHROMATIC ADAPTATION 2018 ,		4
91	Receptive Field Mechanism and Pupillary Light Reflex for the Assessment of Visual Discomfort 2018 , 75-80		
90	Brightness Model for Neutral Self-Luminous Stimuli and Backgrounds. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2018 , 14, 231-244	3.5	7
89	Application specific extension of the MCRI: Memory colors and preferred colors of reddish meat products. <i>Color Research and Application</i> , 2018 , 43, 899-906	1.3	
88	Defining the Actual Luminous Surface in the Unified Glare Rating. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2017 , 13, 201-210	3.5	10
87	Analysis of painted artworks color appearance under various lighting settings 2017 ,		6
86	Study of chromatic adaptation using memory color matches, Part I: neutral illuminants. <i>Optics Express</i> , 2017 , 25, 7732-7748	3.3	33
85	Study of chromatic adaptation using memory color matches, Part II: colored illuminants. <i>Optics Express</i> , 2017 , 25, 8350-8365	3.3	31
84	Radiance based method for accurate determination of volume scattering parameters using GPU-accelerated Monte Carlo. <i>Optics Express</i> , 2017 , 25, 22575-22586	3.3	5
83	Selecting the optimal synthesis parameters of InP/CdxZnSe quantum dots for a hybrid remote phosphor white LED for general lighting applications. <i>Optics Express</i> , 2017 , 25, A1009-A1022	3.3	10
82	Flexible design method for freeform lenses with an arbitrary lens contour. <i>Optics Letters</i> , 2017 , 42, 5238-5241	3.3	18

81	Memory and preferred colours and the colour rendition of white light sources. <i>Lighting Research and Technology</i> , 2016 , 48, 393-411	2	25
80	Determination of volume scattering parameters that reproduce the luminance characteristics of diffusers. <i>Optics Express</i> , 2016 , 24, 11727-38	3.3	5
79	Analysis of energy savings of three daylight control systems in a school building by means of monitoring. <i>Energy and Buildings</i> , 2016 , 127, 969-979	7	34
78	Repeatability and reproducibility of specular gloss meters in theory and practice 2016 , 13, 941-951		5
77	Design of an inexpensive integrating sphere student laboratory setup for the optical characterization of light sources. <i>European Journal of Physics</i> , 2016 , 37, 015302	0.8	3
76	Optical Modelling of Luminescent Cascade Systems with the Adding-Doubling Method. <i>Springer Proceedings in Physics</i> , 2016 , 67-80	0.2	
75	Modelling Incomplete Chromatic Adaptation and Colour Contrast Using Memory Colour. <i>Color and Imaging Conference</i> , 2016 , 2016, 82-87	0.8	2
74	An Efficient Optothermal Simulation Framework for Optimization of High-Luminance White Light Sources. <i>IEEE Photonics Journal</i> , 2016 , 8, 1-15	1.8	9
73	Spot phosphor concept applied to a remote phosphor light-emitting diode light engine. <i>Optical Engineering</i> , 2016 , 55, 115103	1.1	1
72	Spot phosphor concept applied to the remote phosphor configuration of a white phosphor-converted LED 2016 ,		1
71	Opto-thermal study of cooling strategies for high-luminance white-light solid-state sources 2016 ,		1
70	Practical limitations of near-field goniophotometer measurements imposed by a dynamic range mismatch. <i>Optics Express</i> , 2015 , 23, 2240-51	3.3	5
69	Rayfiles including spectral and colorimetric information. <i>Optics Express</i> , 2015 , 23, A361-70	3.3	6
68	Experimental driven modelling of the color appearance of unrelated self-luminous stimuli: CAM15u. <i>Optics Express</i> , 2015 , 23, 12045-64	3.3	25
67	Chromaticity of unique white in illumination mode. <i>Optics Express</i> , 2015 , 23, 12488-95	3.3	24
66	Brightness prediction of different sized unrelated self-luminous stimuli. <i>Optics Express</i> , 2015 , 23, 13455-66	3.3	8
65	Calculation of the Unified Glare Rating based on luminance maps for uniform and non-uniform light sources. <i>Building and Environment</i> , 2015 , 84, 60-67	6.5	20
64	Determination of the optimal amount of scattering in a wavelength conversion plate for white LEDs. <i>Optics Express</i> , 2015 , 23, A1629-41	3.3	5

63	Impact of cross-regional differences on color rendition evaluation of white light sources. <i>Optics Express</i> , 2015 , 23, 30216-26	3.3	12
62	Experimental validation of adding-doubling modeling of solar cells including luminescent down-shifting layers. <i>Journal of Renewable and Sustainable Energy</i> , 2015 , 7, 043130	2.5	5
61	Near-field and far-field goniophotometry of narrow-beam LED arrays. <i>Lighting Research and Technology</i> , 2015 , 47, 470-482	2	5
60	Impact of the Geometrical and Optical Parameters on the Performance of a Cylindrical Remote Phosphor LED. <i>IEEE Photonics Journal</i> , 2015 , 7, 1-14	1.8	6
59	The use of the adding-doubling method for the optical optimization of planar luminescent down shifting layers for solar cells. <i>Optics Express</i> , 2014 , 22 Suppl 3, A765-78	3.3	7
58	Absolute determination of photoluminescence quantum efficiency using an integrating sphere setup. <i>Review of Scientific Instruments</i> , 2014 , 85, 123115	1.7	71
57	Experimental determination of the absorption and scattering properties of YAG:Ce phosphor 2014 ,		3
56	Estimation of the effective phase function of bulk diffusing materials with the inverse adding-doubling method. <i>Applied Optics</i> , 2014 , 53, 2117-25	1.7	20
55	Predicting the brightness of unrelated self-luminous stimuli. <i>Optics Express</i> , 2014 , 22, 16298-309	3.3	12
54	Cross-cultural variation of memory colors of familiar objects. <i>Optics Express</i> , 2014 , 22, 32308-28	3.3	24
53	A hybrid tool for spectral ray tracing simulations of luminescent cascade systems. <i>Optics Express</i> , 2014 , 22, 24582-93	3.3	5
52	Chromaticity of unique white in object mode. <i>Optics Express</i> , 2014 , 22, 25830-41	3.3	41
51	Power and photon budget of a remote phosphor LED module. <i>Optics Express</i> , 2014 , 22 Suppl 4, A1079-92,3	3.3	18
50	Toward the soft metrology of surface gloss: A review. <i>Color Research and Application</i> , 2014 , 39, 559-570	1.3	29
49	42.3: Invited Paper: Progress in the Soft Metrology of Appearance: the Contribution of Digital Image Representations. <i>Digest of Technical Papers SID International Symposium</i> , 2014 , 45, 603-606	0.5	1
48	Taking the spectral overlap between excitation and emission spectra of fluorescent materials into account with Monte Carlo simulations 2014 ,		3
47	Determination of the bulk scattering parameters of diffusing materials. <i>Applied Optics</i> , 2013 , 52, 4083-90,7	1.7	16
46	Optical determination of the junction temperature of OLEDs. <i>Organic Electronics</i> , 2013 , 14, 2770-2776	3.5	10

45	Determination and Optimization of the Luminescence External Quantum Efficiency of Silver-Clusters Zeolite Composites. <i>Journal of Physical Chemistry C</i> , 2013 , 117, 6998-7004	3.8	55
44	A batch LED reactor for the photocatalytic degradation of phenol. <i>Chemical Engineering and Processing: Process Intensification</i> , 2013 , 71, 43-50	3.7	64
43	Quality Assessment of Virtual Prototypes of Surgical Luminaires using Near-field Ray-data. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2013 , 9, 189-200	3.5	2
42	Simulating the spatial luminance distribution of planar light sources by sampling of ray files. <i>Optics Express</i> , 2013 , 21, 24099-111	3.3	9
41	Brightness perception of unrelated self-luminous colors. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , 2013 , 30, 1248-55	1.8	22
40	Color sensitivity of the multi-exposure HDR imaging process. <i>Advanced Optical Technologies</i> , 2013 , 2,	0.9	1
39	Bayesian deconvolution method applied to experimental bidirectional transmittance distribution functions. <i>Measurement Science and Technology</i> , 2013 , 24, 035202	2	5
38	Impact of the accurateness of bidirectional reflectance distribution function data on the intensity and luminance distributions of a light-emitting diode mixing chamber as obtained by simulations. <i>Optical Engineering</i> , 2013 , 52, 095101	1.1	6
37	A memory colour quality metric for white light sources. <i>Energy and Buildings</i> , 2012 , 49, 216-225	7	64
36	Linear LED tubes versus fluorescent lamps: An evaluation. <i>Energy and Buildings</i> , 2012 , 49, 429-436	7	39
35	Failure analysis of electrical-thermal-optical characteristics of LEDs based on AlGaInP and InGaN/GaN. <i>Semiconductors</i> , 2012 , 46, 1310-1315	0.7	8
34	Optimization of colour quality of LED lighting with reference to memory colours. <i>Lighting Research and Technology</i> , 2012 , 44, 7-15	2	21
33	Overall gloss evaluation in the presence of multiple cues to surface glossiness. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , 2012 , 29, 1105-14	1.8	16
32	Extended adding-doubling method for fluorescent applications. <i>Optics Express</i> , 2012 , 20, 17856-72	3.3	18
31	Luminance-based specular gloss characterization. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , 2011 , 28, 1322-30	1.8	19
30	Optimal colour quality of LED clusters based on memory colours. <i>Optics Express</i> , 2011 , 19, 6903-12	3.3	18
29	Correlation between color quality metric predictions and visual appreciation of light sources. <i>Optics Express</i> , 2011 , 19, 8151-66	3.3	88
28	Colour appearance rating of familiar real objects. <i>Color Research and Application</i> , 2011 , 36, 192-200	1.3	70

27	Fluorescence errors in integrating sphere measurements of remote phosphor type LED light sources 2011 ,		2
26	Efficiency Evaluation of Phosphor-white High-power Light-emitting Diodes. <i>Journal of Light and Visual Environment</i> , 2011 , 35, 199-206		2
25	Stray light performance of a combined monochromator spectrograph UV irradiance measuring instrument. <i>Measurement Science and Technology</i> , 2010 , 21, 085304	2	3
24	Feasibility study of a brute-force ray tracing approach to obtain luminance maps of luminaires modeled with ray files 2010 ,		3
23	Modeling high power light-emitting diode spectra and their variation with junction temperature. <i>Journal of Applied Physics</i> , 2010 , 108, 043104	2.5	56
22	Memory colours and colour quality evaluation of conventional and solid-state lamps. <i>Optics Express</i> , 2010 , 18, 26229-44	3.3	85
21	Geometry of illumination, luminance contrast, and gloss perception. <i>Journal of the Optical Society of America A: Optics and Image Science, and Vision</i> , 2010 , 27, 2046-54	1.8	29
20	Modelling the spatial colour distribution of phosphor-white high power light-emitting diodes 2010 ,		3
19	Criteria for energy efficient lighting in buildings. <i>Energy and Buildings</i> , 2010 , 42, 341-347	7	70
18	A new integrating sphere design for spectral radiant flux determination of light-emitting diodes. <i>Measurement Science and Technology</i> , 2009 , 20, 095111	2	18
17	High power light-emitting diode junction temperature determination from current-voltage characteristics. <i>Journal of Applied Physics</i> , 2008 , 104, 093104	2.5	87
16	Design of an instrument for measuring the spectral bidirectional scatter distribution function. <i>Applied Optics</i> , 2008 , 47, 5454-67	0.2	53
15	Thermal characterization of single-die and multi-die high power light-emitting diodes 2008 ,		3
14	A Narrow Beam Reflector for a Two-Dimensional Array of Power Light Emitting Diodes. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 2008 , 4, 243-254	3.5	1
13	Power density targets for efficient lighting of interior task areas. <i>Lighting Research and Technology</i> , 2007 , 39, 171-184	2	17
12	An investigation of the chemical stability of a monomer/polymer gel dosimeter. <i>Physics in Medicine and Biology</i> , 2000 , 45, 859-78	3.8	156
11	On the temperature dependence of the Mott-Schottky characteristics of high-barrier Ti β -Si metal-insulator-semiconductor diodes. <i>Journal of Applied Physics</i> , 1987 , 61, 2277-2281	2.5	0
10	Large barrier tunnel metal-insulator-semiconductor structures. <i>Semiconductor Science and Technology</i> , 1987 , 2, 94-101	1.8	4

9	The influence of a HF and an annealing treatment on the barrier height of p- and n-type Si MIS structures. <i>Applied Physics A: Solids and Surfaces</i> , 1986 , 39, 129-133		55
8	The influence of silicide formation on the barrier height of Ti/Si MIS Schottky barriers. <i>Semiconductor Science and Technology</i> , 1986 , 1, 376-382	1.8	6
7	Current-voltage characteristic of Ti-pSi metal-oxide-semiconductor diodes. <i>Journal of Applied Physics</i> , 1984 , 56, 2309-2314	2.5	93
6	An experimental study of Ti-pSi MIS type Schottky barriers. <i>Journal Physics D: Applied Physics</i> , 1982 , 15, L7-L10	3	7
5	Investigation on photoelectrochemical cells based upon silicon/methanol interfaces. Part 2: p-type Si. <i>Solar Energy Materials and Solar Cells</i> , 1982 , 7, 33-42		4
4	Visualization of Lighting Quality and Object Appearance When Using Multichannel Light Sources. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 1-14	3.5	1
3	Impact of Color-Matching Primaries on Observer Matching: Part I [Accuracy]. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 1-23	3.5	4
2	Impact of Color Matching Primaries on Observer Matching: Part II [Observer Variability]. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 1-18	3.5	1
1	Road Marking Contrast Threshold Revisited. <i>LEUKOS - Journal of Illuminating Engineering Society of North America</i> , 1-20	3.5	1