

Dae-Eun Kim

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/5312997/dae-eun-kim-publications-by-year.pdf>

Version: 2024-04-28

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

163
papers

3,982
citations

33
h-index

55
g-index

166
ext. papers

4,522
ext. citations

5
avg, IF

5.83
L-index

#	Paper	IF	Citations
163	Features of the Conductive Carbon Coatings Formation on Titanium Electrodes Using C60 Ion Beams. <i>Springer Proceedings in Physics</i> , 2022 , 385-394	0.2	
162	Numerical and experimental study of tribological properties of glass/polymer-based micro ball bearings. <i>Wear</i> , 2022 , 488-489, 204173	3.5	
161	Tribological properties of the hierarchically structured graphene oxide composite coatings reinforced with polyvinyl alcohol. <i>Wear</i> , 2022 , 490-491, 204212	3.5	
160	Tribochemical reaction and wear mechanism of MoDTC based friction modifier. <i>Tribology International</i> , 2022 , 165, 107302	4.9	1
159	One-step method to enhance biotribological properties and biocompatibility of DLC coating by ion beam irradiation. <i>Friction</i> , 2022 , 10, 1114-1126	5.6	1
158	Formation Mechanism of High-Entropy Spinel Thin Film and its Mechanical and Magnetic Properties: Linking High-Entropy Alloy to High-Entropy Ceramic. <i>Applied Surface Science</i> , 2021 , 151719	6.7	4
157	Formation of Functional Conductive Carbon Coating on Si by C60 Ion Beam 2021 , 131		3
156	Formation of discrete periodic nanolayered coatings through tailoring of nanointerfaces-Toward zero macroscale wear. <i>Science Advances</i> , 2021 , 7, eabk1224	14.3	1
155	Ultrafast green microwave-assisted synthesis of high-entropy oxide nanoparticles for Li-ion battery applications. <i>Materials Chemistry and Physics</i> , 2021 , 262, 124265	4.4	17
154	Friction and wear behaviors of bare and diamond-like carbon/chromium bi-layer coated SKH51 steel at low temperatures. <i>Surface and Coatings Technology</i> , 2021 , 412, 127018	4.4	4
153	Molecular dynamics simulation and experimental investigation of tribological behavior of nanodiamonds in aqueous suspensions. <i>Tribology International</i> , 2021 , 156, 106838	4.9	5
152	Effects of molybdenum-based substrate coatings on tribological performance of graphene films. <i>Carbon</i> , 2021 , 176, 488-499	10.4	2
151	Understanding of the lubrication mechanism of reduced graphene oxide coating via dual in-situ monitoring of the chemical and topographic structural evolution. <i>Carbon</i> , 2021 , 173, 941-952	10.4	5
150	Effect of V-Groove Surface Pattern on the Tribological Properties of Epoxy. <i>Tribology Transactions</i> , 2021 , 64, 302-312	1.8	0
149	Formation of wear-resistant graphite/diamond-like carbon nanocomposite coatings on Ti using accelerated C60-ions. <i>Surface and Coatings Technology</i> , 2021 , 424, 127670	4.4	1
148	Superior surface protection governed by optimized interface characteristics in WC/DLC multilayer coating. <i>Surface and Coatings Technology</i> , 2020 , 385, 125446	4.4	6
147	Molecular dynamics investigation on the nano-mechanical behaviour of C fullerene and its crystallized structure. <i>Nanoscale</i> , 2020 , 12, 9849-9858	7.7	5

146	Mechanism of Heat-Induced Fusion of Silver Nanowires. <i>Scientific Reports</i> , 2020 , 10, 9271	4.9	9
145	Effect of friction on the contact stress of a coated polymer gear. <i>Friction</i> , 2020 , 8, 1169-1177	5.6	7
144	In vitro study of a novel multi-substituted hydroxyapatite nanopowder synthesized by an ultra-fast, efficient and green microwave-assisted method. <i>Materials Science and Engineering C</i> , 2020 , 117, 111310	8.3	7
143	RF magnetron sputtering mediated NiTi/Ag coating on Ti-alloy substrate with enhanced biocompatibility and durability. <i>Materials Science and Engineering C</i> , 2019 , 99, 304-314	8.3	12
142	Superior lubrication of dense/porous-coupled nanoscale C/WS ₂ multilayer coating on ductile substrate. <i>Applied Surface Science</i> , 2019 , 476, 724-732	6.7	14
141	Tribological Self-healing Coating based on Hydrogel. <i>Mechanisms and Machine Science</i> , 2019 , 3771-3774	0.3	
140	Characterization of the friction and wear effects of graphene nanoparticles in oil on the ring/cylinder liner of internal combustion engine. <i>Industrial Lubrication and Tribology</i> , 2019 , 71, 642-652	1.3	5
139	Assessment of nano-scale tribological and mechanical properties of flexible transparent polymers based on atomic force microscopy. <i>CIRP Annals - Manufacturing Technology</i> , 2019 , 68, 599-602	4.9	1
138	Enhancement of tribological properties of DLC by incorporation of amorphous titanium using magnetron sputtering process. <i>Ceramics International</i> , 2019 , 45, 11971-11981	5.1	13
137	Increased elasticity and damping capacity of diamond-like carbon coatings by immobilized C fullerene clusters. <i>Nanoscale</i> , 2019 , 11, 2863-2870	7.7	8
136	Lubrication of Carbon-based Coatings. <i>Mechanisms and Machine Science</i> , 2019 , 3775-3778	0.3	
135	Hard, Flexible, and Transparent Nanolayered SiN /BN Periodical Coatings. <i>ACS Applied Materials & Interfaces</i> , 2019 , 11, 9685-9690	9.5	4
134	Ion-beam irradiation of DLC-based nanocomposite: Creation of a highly biocompatible surface. <i>Applied Surface Science</i> , 2019 , 469, 896-903	6.7	13
133	Highly durable and biocompatible periodical Si/DLC nanocomposite coatings. <i>Nanoscale</i> , 2018 , 10, 4852-4860	7.7	16
132	Selective release of less defective graphene during sliding of an incompletely reduced graphene oxide coating on steel. <i>Carbon</i> , 2018 , 134, 411-422	10.4	18
131	Fabrication of polytetrafluoroethylene/carbon nanotube composite coatings for friction and wear reduction. <i>Polymer Composites</i> , 2018 , 39, E710-E722	3	10
130	Development of polyimide films reinforced with boron nitride and boron nitride nanosheets for transparent flexible device applications. <i>Nano Research</i> , 2018 , 11, 2366-2378	10	31
129	Highly transparent micro-patterned protective coatings on polyethylene terephthalate for flexible solar cell applications. <i>Solar Energy</i> , 2018 , 171, 629-637	6.8	12

128	Significant improvement in cell adhesion and wear resistance of biomedical β -type titanium alloy through ultrasonic nanocrystal surface modification. <i>Journal of Alloys and Compounds</i> , 2018 , 762, 941-949	5.7	36
127	A Study on Frictional Characteristics of PDMS Under Various Conditions. <i>Journal of the Korean Society for Precision Engineering</i> , 2018 , 35, 803-807	0.3	6
126	Simultaneous grain refinement and nanoscale spinodal decomposition of β phase in Ti-Nb-Ta-Zr alloy induced by ultrasonic mechanical impacts. <i>Journal of Alloys and Compounds</i> , 2018 , 738, 540-549	5.7	27
125	Tribological characteristics of micro-ball bearing with V-shaped grooves coated with ultra-thin protective layers. <i>Tribology International</i> , 2018 , 119, 481-490	4.9	7
124	Elevated temperature wear behavior of thermally sprayed WC-Co/nanodiamond composite coatings. <i>Surface and Coatings Technology</i> , 2017 , 315, 283-293	4.4	28
123	Nanostructured β -type titanium alloy fabricated by ultrasonic nanocrystal surface modification. <i>Ultrasonics Sonochemistry</i> , 2017 , 39, 698-706	8.9	35
122	Development of flexible polymer sheet with high surface durability using discretely embedded micro-balls. <i>CIRP Annals - Manufacturing Technology</i> , 2017 , 66, 527-530	4.9	4
121	Tribology of multilayer coatings for wear reduction: A review. <i>Friction</i> , 2017 , 5, 248-262	5.6	86
120	Smart wearable heaters with high durability, flexibility, water-repellent and shape memory characteristics. <i>Composites Science and Technology</i> , 2017 , 152, 173-180	8.6	23
119	A highly flexible transparent conductive electrode based on nanomaterials. <i>NPG Asia Materials</i> , 2017 , 9, e438-e438	10.3	57
118	Microstructure evolution and enhanced vacuum tribological performance of Ni-doped WS ₂ composite coating. <i>Surface and Coatings Technology</i> , 2017 , 325, 81-88	4.4	13
117	Durability and Self-healing Effects of Hydrogel Coatings with respect to Contact Condition. <i>Scientific Reports</i> , 2017 , 7, 6896	4.9	17
116	Synthesis and Multi Scale Tribological Behavior of WC-Co/Nanodiamond Nanocomposites. <i>Scientific Reports</i> , 2017 , 7, 7060	4.9	7
115	Functional Multi-Nanolayer Coatings of Amorphous Carbon/Tungsten Carbide with Exceptional Mechanical Durability and Corrosion Resistance. <i>ACS Applied Materials & Interfaces</i> , 2017 , 9, 30149-30160	9.5	20
114	Design and Construction of a Micro-Tribotester for Precise In-Situ Wear Measurements. <i>Micromachines</i> , 2017 , 8, 103	3.3	16
113	Effects of vibration frequency and amplitude on friction reduction and wear characteristics of silicon. <i>Tribology International</i> , 2016 , 94, 198-206	4.9	15
112	Self-healing Characteristics of Collagen Coatings with Respect to Surface Abrasion. <i>Scientific Reports</i> , 2016 , 6, 20563	4.9	21
111	Ultra-thin carbon-based nanocomposite coatings for superior wear resistance under lubrication with nano-diamond additives. <i>RSC Advances</i> , 2016 , 6, 56918-56929	3.7	14

110	Highly wear-resistant and biocompatible carbon nanocomposite coatings for dental implants. <i>Biomaterials</i> , 2016 , 102, 130-6	15.6	28
109	Nano-lubrication: A review. <i>International Journal of Precision Engineering and Manufacturing</i> , 2016 , 17, 829-841	1.7	28
108	Fundamental investigation of micro-scale wear characteristics of ultra-fine gold wires under low contact force and long sliding distance. <i>Wear</i> , 2016 , 348-349, 1-9	3.5	1
107	Surface damage behavior of polyurethane O-rings in automated material handling system for glass panels. <i>International Journal of Precision Engineering and Manufacturing</i> , 2016 , 17, 43-50	1.7	4
106	Tribological properties, corrosion resistance and biocompatibility of magnetron sputtered titanium-amorphous carbon coatings. <i>Applied Surface Science</i> , 2016 , 371, 262-274	6.7	38
105	Mechanical and high temperature wear properties of extruded Al composite reinforced with Al ₁₃ Fe ₄ CMA nanoparticles. <i>Materials and Design</i> , 2016 , 90, 532-544	8.1	30
104	Investigation of mechanical behavior of single- and multi-layer graphene by using molecular dynamics simulation. <i>International Journal of Precision Engineering and Manufacturing</i> , 2016 , 17, 1693-1701	1.7	14
103	Wear Reduction of Borosilicate Glass Microballs Using Vapor-Phase Lubrication With n-Pentanol. <i>Tribology Transactions</i> , 2016 , 59, 507-512	1.8	1
102	Frictional behavior between silicon and steel coated with graphene oxide in dry sliding and water lubrication conditions. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2016 , 3, 91-97	3.8	33
101	Investigation of micro-abrasion characteristics of thin metallic coatings by in-situ SEM scratch test. <i>International Journal of Precision Engineering and Manufacturing</i> , 2016 , 17, 1139-1147	1.7	10
100	Tribological Properties of Graphene Oxide Nanosheet Coating Fabricated by Using Electrodynamic Spraying Process. <i>Tribology Letters</i> , 2015 , 57, 1	2.8	23
99	Development of highly durable and low friction micro-structured PDMS coating based on bio-inspired surface design. <i>CIRP Annals - Manufacturing Technology</i> , 2015 , 64, 519-522	4.9	20
98	Toward Zero Micro/Macro-Scale Wear Using Periodic Nano-Layered Coatings. <i>ACS Applied Materials & Interfaces</i> , 2015 , 7, 18136-44	9.5	32
97	Tribological properties of twin wire arc spray coated aluminum cylinder liner. <i>Materials and Design</i> , 2015 , 84, 231-237	8.1	19
96	Frictional Characteristics of Sub-100- μm Borosilicate Glass Balls for Actuator Applications. <i>Journal of Microelectromechanical Systems</i> , 2015 , 24, 2161-2169	2.5	4
95	Highly efficient perovskite solar cells based on mechanically durable molybdenum cathode. <i>Nano Energy</i> , 2015 , 17, 131-139	17.1	35
94	Friction and Deformation Behaviors of ~60- μm Stainless Steel Micro-balls for Application in Small Precision Devices. <i>Tribology Letters</i> , 2015 , 59, 1	2.8	3
93	Water Lubrication of Stainless Steel using Reduced Graphene Oxide Coating. <i>Scientific Reports</i> , 2015 , 5, 17034	4.9	64

92	Mechanically Recoverable and Highly Efficient Perovskite Solar Cells: Investigation of Intrinsic Flexibility of Organic/Inorganic Perovskite. <i>Advanced Energy Materials</i> , 2015 , 5, 1501406	21.8	106
91	Assessment of surface damage characteristics of polymeric optical sheets of LCD backlight unit. <i>Polymer Testing</i> , 2015 , 48, 140-150	4.5	
90	A review of recent applications of atmospheric pressure plasma jets for materials processing 2015 , 12, 225-235		163
89	Evaluation of the mechanical and tribological properties of a TFT-LCD panel. <i>Tribology International</i> , 2014 , 73, 95-100	4.9	9
88	Tribology of graphene: A review. <i>International Journal of Precision Engineering and Manufacturing</i> , 2014 , 15, 577-585	1.7	141
87	Self-healing phenomenon and dynamic hardness of C60-based nanocomposite coatings. <i>Nano Letters</i> , 2014 , 14, 2536-40	11.5	16
86	Effect of Ag content on the microstructure, tribological and corrosion properties of amorphous carbon coatings on 316L SS. <i>Surface and Coatings Technology</i> , 2014 , 240, 128-136	4.4	40
85	Structural and tribological characteristics of poly(vinylidene fluoride)/functionalized graphene oxide nanocomposite thin films. <i>Composites Science and Technology</i> , 2014 , 90, 187-192	8.6	46
84	Multi-functional ceramic hybrid coatings on biodegradable AZ31 Mg implants: electrochemical, tribological and quantum chemical aspects for orthopaedic applications. <i>RSC Advances</i> , 2014 , 4, 24272	3.7	42
83	Design of endoscopic micro-robotic end effectors: safety and performance evaluation based on physical intestinal tissue damage characteristics. <i>Biomedical Microdevices</i> , 2014 , 16, 397-413	3.7	7
82	Tribological properties of carbon nanotube/polyethylene oxide composite coatings. <i>Composites Science and Technology</i> , 2014 , 101, 102-109	8.6	16
81	Vapor phase lubrication using high molecular weight lubricant for friction reduction of metals. <i>International Journal of Precision Engineering and Manufacturing</i> , 2014 , 15, 867-873	1.7	11
80	Ultra-thin nano-patterned wear-protective diamond-like carbon coatings deposited on glass using a C60 ion beam. <i>Carbon</i> , 2014 , 80, 534-543	10.4	25
79	Non-volatile organic memory with sub-millimetre bending radius. <i>Nature Communications</i> , 2014 , 5, 3583	17.4	182
78	Tribological properties of nanostructured DLC coatings deposited by C60 ion beam. <i>Tribology International</i> , 2013 , 60, 127-135	4.9	42
77	Minimum lubrication technique using silicone oil for friction reduction of stainless steel. <i>International Journal of Precision Engineering and Manufacturing</i> , 2013 , 14, 875-880	1.7	22
76	Improvement of the tribological properties of Al6061/Ti6 alloy under dry sliding conditions. <i>Tribology International</i> , 2013 , 64, 24-32	4.9	29
75	Wear minimization through utilization of atomic-scale functional surface structure. <i>Applied Physics Letters</i> , 2013 , 103, 151904	3.4	4

74	Fundamental Investigation of the Wear Progression of Silicon Atomic Force Microscope Probes. <i>Tribology Letters</i> , 2013 , 52, 315-325	2.8	16
73	An investigation of the tribological and nano-scratch behaviors of FeNiCr alloy sintered by direct metal laser sintering. <i>Materials & Design</i> , 2013 , 47, 386-394		19
72	Effects of Proximity on Hardness and Elastic Modulus Measurements of SiO ₂ and Cu by Nanoindentation. <i>Tribology Letters</i> , 2013 , 49, 85-94	2.8	16
71	Frictional behavior of Ag nanodot-pattern fabricated by thermal dewetting. <i>Surface and Coatings Technology</i> , 2013 , 215, 234-240	4.4	9
70	Tribological behavior of dual-layer electroless-plated Ag/carbon nanotube coatings. <i>Thin Solid Films</i> , 2013 , 534, 410-416	2.2	15
69	Frictional behavior of atmospheric plasma jet deposited carbon/nano ZnO composite coatings. <i>Composites Science and Technology</i> , 2013 , 77, 60-66	8.6	14
68	Durability and degradation mechanism of graphene coatings deposited on Cu substrates under dry contact sliding. <i>Carbon</i> , 2013 , 54, 472-481	10.4	112
67	Dendritic cell-based immunotherapy for colon cancer using an HLA-A*0201-restricted cytotoxic T-lymphocyte epitope from tumor-associated antigen 90K. <i>Cellular and Molecular Immunology</i> , 2013 , 10, 275-82	15.4	11
66	Sliding and rolling frictional behavior of a single ZnO nanowire during manipulation with an AFM. <i>Nanoscale</i> , 2013 , 5, 6081-7	7.7	33
65	Docetaxel-loaded thermoresponsive conjugated linoleic acid-incorporated poloxamer hydrogel for the suppression of peritoneal metastasis of gastric cancer. <i>Biomaterials</i> , 2013 , 34, 1433-41	15.6	46
64	Effectiveness of high-frequency ultrasonic peening treatment on the tribological characteristics of Cu-based sintered materials on steel substrate. <i>Materials & Design</i> , 2013 , 45, 118-124		24
63	Tribological Characteristics of Silver Electroless-Plating Process According to Thicknesses Variation. <i>Transactions of the Korean Society of Mechanical Engineers, A</i> , 2013 , 37, 219-225	1	
62	Effect of surface roughness of top cover layer on the efficiency of dye-sensitized solar cell. <i>Solar Energy</i> , 2012 , 86, 2049-2055	6.8	26
61	MD simulation of the frictional behavior of CNTs with respect to orientation. <i>Tribology International</i> , 2012 , 50, 51-56	4.9	8
60	Friction and Wear Characteristics of C/Si Bi-layer Coatings Deposited on Silicon Substrate by DC Magnetron Sputtering. <i>Tribology Letters</i> , 2012 , 48, 123-131	2.8	24
59	Measurement of the elastic modulus of polymeric films using an AFM with a steel micro-spherical probe tip. <i>Polymer Testing</i> , 2012 , 31, 926-930	4.5	22
58	Effects of ultrasonic nanocrystalline surface modification on the tribological properties of AZ91D magnesium alloy. <i>Tribology International</i> , 2012 , 54, 106-113	4.9	108
57	Effectiveness of bubble structure in contact damage reduction of Au film. <i>Tribology International</i> , 2012 , 55, 40-45	4.9	6

56	Fretting wear and friction reduction of CP titanium and Ti6Al4V alloy by ultrasonic nanocrystalline surface modification. <i>Surface and Coatings Technology</i> , 2012 , 207, 135-142	4.4	157
55	Accelerated wear test of FKM elastomer for life prediction of seals. <i>Polymer Testing</i> , 2012 , 31, 993-1000	4.5	29
54	Molecular dynamics simulation of atomic-scale frictional behavior of corrugated nano-structured surfaces. <i>Nanoscale</i> , 2012 , 4, 3937-44	7.7	17
53	Characterization of durability of coatings for cell phone cover by wear, erosion, and pull-off tests. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 1633-1639	1.7	3
52	Nano-scale wear: A review. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 1709-1718	1.7	57
51	Effect of elevated annealing temperature on the microstructure and nano-hardness of ZnO films deposited by the sol-gel process. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 2005-2009	1.7	7
50	A phase II study of concurrent chemoradiotherapy with weekly docetaxel and cisplatin in advanced oesophageal cancer. <i>Cancer Chemotherapy and Pharmacology</i> , 2012 , 70, 683-90	3.5	24
49	Development of rotary tool for removal of intravascular blood clots. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 413-419	1.7	1
48	Development of a CrN/Cu nanocomposite coating on titanium-modified stainless steel for antibacterial activity against <i>Pseudomonas aeruginosa</i> . <i>Biofouling</i> , 2012 , 28, 779-87	3.3	8
47	Design Approach and Structural Analysis for Development of a Micro-Wear Tester. <i>Transactions of the Society of Information Storage Systems</i> , 2012 , 8, 6-10		
46	Tribological properties of polymer/silica composite coatings for microsystems applications. <i>Tribology International</i> , 2011 , 44, 1926-1931	4.9	22
45	Friction and wear characteristics of multi-layer graphene films investigated by atomic force microscopy. <i>Surface and Coatings Technology</i> , 2011 , 205, 4864-4869	4.4	140
44	Prognostic significance of a systemic inflammatory response in patients receiving first-line palliative chemotherapy for recurred or metastatic gastric cancer. <i>BMC Cancer</i> , 2011 , 11, 489	4.8	61
43	A novel approach to wear reduction of micro-components by synthesis of carbon nanotube-silver composite coating. <i>CIRP Annals - Manufacturing Technology</i> , 2011 , 60, 599-602	4.9	28
42	Characteristics of Progressive Damage of ZnO Nanowires during Contact Sliding under Relatively Low Loads. <i>Journal of Nanomaterials</i> , 2011 , 2011, 1-7	3.2	
41	An optimal micropatterned end-effector for enhancing frictional force on large intestinal surface. <i>ACS Applied Materials & Interfaces</i> , 2010 , 2, 1308-16	9.5	12
40	Assessment of adhesion between thin film and silicon based on a scratch test. <i>Journal of Mechanical Science and Technology</i> , 2010 , 24, 97-101	1.6	17
39	Adhesion characteristics of the snail foot under various surface conditions. <i>International Journal of Precision Engineering and Manufacturing</i> , 2010 , 11, 623-628	1.7	6

38	Key Parameter of Peel-off Test for Reliability Assessment of Toner Film. <i>Transactions of the Korean Society of Mechanical Engineers, A</i> , 2010 , 34, 1567-1573	1	
37	Effects of Self-Assembled Monolayer and PFPE Lubricant on Wear Characteristics of Flat Silicon Tips. <i>Tribology Letters</i> , 2009 , 34, 61-73	2.8	11
36	Investigation of penetration force of living cell using an atomic force microscope. <i>Journal of Mechanical Science and Technology</i> , 2009 , 23, 1932-1938	1.6	21
35	Nano-scale friction: A review. <i>International Journal of Precision Engineering and Manufacturing</i> , 2009 , 10, 141-151	1.7	62
34	Effect of annealing temperature on the tribological behavior of ZnO films prepared by sol-gel method. <i>Thin Solid Films</i> , 2009 , 517, 1690-1700	2.2	32
33	Comparison of Indentation and Scribing Behaviors of Crystalline and Initially Deformed Silicon Tips by Molecular Dynamics Simulation. <i>IEEE Transactions on Magnetics</i> , 2009 , 45, 2328-2331	2	3
32	Experimental Investigation of Friction and Wear Characteristics of O-Ring. <i>Transactions of the Korean Society of Mechanical Engineers, A</i> , 2009 , 33, 1125-1131	1	3
31	Wetting characteristics of ZnO smooth film and nanowire structure with and without OTS coating. <i>Applied Surface Science</i> , 2008 , 254, 7370-7376	6.7	26
30	Tribological characteristics of ZnO nanowires investigated by atomic force microscope. <i>Applied Physics A: Materials Science and Processing</i> , 2008 , 92, 267-274	2.6	12
29	Wear characteristics of microscopic bushings for MEMS applications investigated by an AFM. <i>Journal of Micromechanics and Microengineering</i> , 2007 , 17, 1877-1887	2	12
28	Nano-tribological characteristics of PZT thin film investigated by atomic force microscopy. <i>Surface and Coatings Technology</i> , 2007 , 201, 7983-7991	4.4	19
27	Study on nanoscale abrasive interaction between nanoprobe and self-assembled molecular surface for probe-based nanolithography process. <i>Ultramicroscopy</i> , 2007 , 107, 1-7	3.1	12
26	Wear rate of vertically grown ZnO nanowires sliding against steel micro-sphere. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2007 , 460-461, 370-376	5.3	7
25	Wear characteristics of diamond-coated atomic force microscope probe. <i>Ultramicroscopy</i> , 2007 , 108, 1-10	3.1	37
24	Micro/nanomechanical properties of aluminum-doped zinc oxide films prepared by radio frequency magnetron sputtering. <i>Surface and Coatings Technology</i> , 2006 , 201, 2547-2552	4.4	32
23	Experimental investigation of frictional and viscoelastic properties of intestine for microendoscope application. <i>Tribology Letters</i> , 2006 , 22, 143-149	2.8	75
22	Direct force measurement of the interaction between liposome and the C2A domain of synaptotagmin I using atomic force microscopy. <i>Biotechnology Letters</i> , 2006 , 28, 505-9	3	3
21	Development of flying type head/slider for optical recording technology. <i>Tribology International</i> , 2005 , 38, 578-587	4.9	

20	Nano-scale patterning by mechano-chemical scanning probe lithography. <i>Applied Surface Science</i> , 2005 , 239, 209-221	6.7	26
19	Tribological characteristics of probe tip and PZT media for AFM-based recording technology. <i>IEEE Transactions on Magnetics</i> , 2005 , 41, 849-854	2	25
18	Molecular dynamics simulation study of the nano-wear characteristics of alkanethiol self-assembled monolayers. <i>Applied Physics A: Materials Science and Processing</i> , 2005 , 81, 109-114	2.6	36
17	Characteristics of fracture during the approach process and wear mechanism of a silicon AFM tip. <i>Ultramicroscopy</i> , 2005 , 102, 161-71	3.1	113
16	Nano-mechanical and tribological characteristics of ultra-thin amorphous carbon film investigated by afm. <i>Journal of Mechanical Science and Technology</i> , 2004 , 18, 1772-1781		3
15	Surface Damage Characteristics of Self-Assembled Monolayers of Alkanethiols on Metal Surfaces. <i>Tribology Letters</i> , 2004 , 17, 835-844	2.8	26
14	Particle monitoring method using acoustic emission signal for analysis of slider/disk/particle interaction. <i>Tribology International</i> , 2004 , 37, 849-857	4.9	14
13	Prediction of asperity contact condition using FFT-based analysis for micro-grooved surface design in tribological applications. <i>Journal Physics D: Applied Physics</i> , 2003 , 36, 939-945	3	4
12	Fundamental Investigation of Micro Wear Rate Using an Atomic Force Microscope. <i>Tribology Letters</i> , 2003 , 15, 135-144	2.8	79
11	Micro/nano-tribological characteristics of self-assembled monolayer and its application in nano-structure fabrication. <i>Wear</i> , 2003 , 255, 808-818	3.5	56
10	Effect of substrate and protective coating on the tribological characteristics of optical recording media. <i>Wear</i> , 2003 , 255, 1306-1313	3.5	8
9	Effect of surface topography on the frictional behavior at the micro/nano-scale. <i>Wear</i> , 2003 , 254, 1019-1031	3.5	41
8	Tribological design methods for minimum surface damage of HDD slider. <i>Tribology International</i> , 2003 , 36, 467-473	4.9	13
7	Investigation of the tribological behavior of octadecyltrichlorosilane deposited on silicon. <i>Wear</i> , 2001 , 251, 1169-1176	3.5	65
6	Application of single asperity abrasion process for surface micro-machining. <i>Wear</i> , 2001 , 251, 1133-1143	3.5	17
5	Strategies for improvement of tribological characteristics at the head/disk interface. <i>IEEE Transactions on Magnetics</i> , 2001 , 37, 912-917	2	5
4	Experimental investigation of AE and friction signals related to the durability of head/disk interface. <i>Tribology International</i> , 1999 , 32, 399-405	4.9	8
3	Effect of slider load on the wear debris contamination tendency of head/slider. <i>IEEE Transactions on Magnetics</i> , 1999 , 35, 2355-2357	2	8

- 2 Assessment of surface damage mechanisms of head/disk interface using CSS and drag tests. *IEEE Transactions on Magnetics*, **1998**, 34, 1714-1716 2 8
- 1 Experimental Investigation of the Influence of Machining Condition on the Contact Sliding Behavior of Metals. *Journal of Manufacturing Science and Engineering, Transactions of the ASME*, **1998**, 120, 395-400³³ 7