

Murat Kilic

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/533001/publications.pdf>

Version: 2024-02-01

14
papers

292
citations

1162367

8
h-index

1058022

14
g-index

14
all docs

14
docs citations

14
times ranked

262
citing authors

#	ARTICLE	IF	CITATIONS
1	Effect of machining on surface roughness of wood. Building and Environment, 2006, 41, 1074-1078.	3.0	94
2	The effects of ply organization and loading direction on bending strength and modulus of elasticity in laminated veneer lumber (LVL) obtained from beech (<i>Fagus orientalis</i> L.) and lombardy poplar (<i>Populus nigra</i> L.). Construction and Building Materials, 2007, 21, 1720-1725.	3.2	61
3	Nail and screw withdrawal strength of laminated veneer lumber made up hardwood and softwood layers. Construction and Building Materials, 2007, 21, 894-900.	3.2	32
4	The effect of the cutting direction, number of blades and grain size of the abrasives on surface roughness of Taurus cedar (<i>Cedrus Libani</i> A. Rich.) woods. Building and Environment, 2008, 43, 696-701.	3.0	26
5	The shear strength of Calabrian pine (<i>Pinus brutia</i> Ten.) bonded with polyurethane and polyvinyl acetate adhesives. Journal of Applied Polymer Science, 2006, 99, 3050-3061.	1.3	19
6	The effect of surface roughness on tensile strength of the medium density fiberboard (MDF) overlaid with polyvinyl chloride (PVC). Materials & Design, 2009, 30, 4580-4583.	5.1	18
7	Shear strength of calabrian pine (<i>Pinus brutia</i> Ten.) bonded with polyurethane and polyvinyl acetate adhesives. Journal of Applied Polymer Science, 2006, 100, 4856-4867.	1.3	8
8	Compression, cleavage, and shear resistance of composite construction materials produced from softwoods and hardwoods. Journal of Applied Polymer Science, 2006, 102, 3673-3678.	1.3	8
9	Influence of steaming on surface roughness of beech and sapele flooring material. Journal of Materials Processing Technology, 2008, 199, 448-451.	3.1	7
10	The effects of steaming of beech (<i>Fagus orientalis</i> L.) and sapele (<i>Entandrophragma</i>) Tj ETQq0 0 0 rgBT /Overlock 10 Tf 50 38 2009, 113, 3492-3497.	1.3	6
11	Properties of composite laminated material produced with layers of beech and paperboard made from waste paper. Journal of Applied Polymer Science, 2006, 101, 1943-1952.	1.3	4
12	Some important physical properties of laminated veneer lumber (Lvl) made from oriental beech and Lombardy poplar. AIP Conference Proceedings, 2012, , .	0.3	3
13	Determination of the Surface Roughness Values of Turkish Red Pine (<i>Pinus brutia</i> (Ten.)) Woods. BioResources, 2016, 12, .	0.5	3
14	Effect on Shear Strength of Machining Methods in <i>Pinus nigra</i> Arnold Bonded with Polyurethane and Polyvinyl Acetate Adhesives. BioResources, 2016, 11, .	0.5	3