

# Shrabanee Sen

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/5447019/publications.pdf>

Version: 2024-02-01

40  
papers

1,475  
citations

304368

22  
h-index

315357

38  
g-index

40  
all docs

40  
docs citations

40  
times ranked

1476  
citing authors

#	ARTICLE	IF	CITATIONS
1	Structural and electrical properties of Ca <sup>2+</sup> -modified PZT electroceramics. <i>Physica B: Condensed Matter</i> , 2007, 387, 56-62.	1.3	191
2	The influence of hydrogen bonding on the dielectric constant and the piezoelectric energy harvesting performance of hydrated metal salt mediated PVDF films. <i>Physical Chemistry Chemical Physics</i> , 2015, 17, 17429-17436.	1.3	139
3	Self-Poled Transparent and Flexible UV Light-Emitting Cerium Complex-PVDF Composite: A High-Performance Nanogenerator. <i>ACS Applied Materials &amp; Interfaces</i> , 2015, 7, 1298-1307.	4.0	129
4	Yb <sup>3+</sup> assisted self-polarized PVDF based ferroelectretic nanogenerator: A facile strategy of highly efficient mechanical energy harvester fabrication. <i>Nano Energy</i> , 2016, 30, 621-629.	8.2	124
5	Impedance spectroscopy study of strontium modified lead zirconate titanate ceramics. <i>Journal of Applied Physics</i> , 2006, 99, 124114.	1.1	98
6	Enhancement in energy storage and piezoelectric performance of three phase (PZT/MWCNT/PVDF) composite. <i>Materials Chemistry and Physics</i> , 2020, 244, 122639.	2.0	70
7	Improved breakdown strength and electrical energy storage performance of $\text{Ti}^{3+}$ -poly(vinylidene fluoride)/TiO <sub>2</sub> nanocomposite film. <i>Journal of Applied Physics</i> , 2017, 121, 074303.	1.3	56
8	Impedance analysis of 0.65Pb(Mg <sup>1/3</sup> Nb <sup>2/3</sup> )O <sub>3</sub> -0.35PbTiO <sub>3</sub> ceramic. <i>Journal of Alloys and Compounds</i> , 2008, 453, 395-400.	2.8	47
9	Polyglycolated zinc ferrite incorporated poly(vinylidene fluoride)(PVDF) composites with enhanced piezoelectric response. <i>Journal of Alloys and Compounds</i> , 2017, 722, 829-838.	2.8	43
10	Role of suppressed oxygen vacancies in the BiFeO <sub>3</sub> nanofiller to improve the polar phase and multifunctional performance of poly(vinylidene fluoride). <i>Physical Chemistry Chemical Physics</i> , 2019, 21, 5974-5988.	1.3	43
11	Polyvinylpyrrolidone modified barium zirconate titanate /polyvinylidene fluoride nanocomposites as self-powered sensor. <i>Ceramics International</i> , 2018, 44, 11196-11203.	2.3	36
12	Improved dielectric constant and breakdown strength of $\text{Ti}^{3+}$ -phase dominant super toughened polyvinylidene fluoride/TiO <sub>2</sub> nanocomposite film: an excellent material for energy storage applications and piezoelectric throughput. <i>Nanotechnology</i> , 2017, 28, 015503.	1.3	35
13	Nano-ZnO decorated ZnSnO <sub>3</sub> as efficient fillers in PVDF matrixes: toward simultaneous enhancement of energy storage density and efficiency and improved energy harvesting activity. <i>Nanoscale</i> , 2020, 12, 20908-20921.	2.8	34
14	The preparation of $\text{Ti}^{3+}$ -crystalline non-electrically poled photoluminescent ZnO-PVDF nanocomposite film for wearable nanogenerators. <i>Nanotechnology</i> , 2016, 27, 445403.	1.3	33
15	Synthesis and characterization of SmFeO <sub>3</sub> and its effect on the electrical and energy storage properties of PVDF. <i>Materials Research Bulletin</i> , 2020, 130, 110941.	2.7	32
16	Hydroxylated BiFeO <sub>3</sub> as efficient fillers in poly(vinylidene fluoride) for flexible dielectric, ferroelectric, energy storage and mechanical energy harvesting application. <i>Dalton Transactions</i> , 2021, 50, 1824-1837.	1.6	31
17	Enhanced dielectric, ferroelectric, energy storage and mechanical energy harvesting performance of ZnO-PVDF composites induced by MWCNTs as an additive third phase. <i>Soft Matter</i> , 2021, 17, 8483-8495.	1.2	31
18	Conducting polyaniline decorated in-situ poled Ferrite nanorod-PVDF based nanocomposite as piezoelectric energy harvester. <i>Journal of Alloys and Compounds</i> , 2020, 815, 152312.	2.8	29

#	ARTICLE	IF	CITATIONS
19	Enhanced dielectric and energy storage performance of surface treated gallium ferrite/polyvinylidene fluoride nanocomposites. RSC Advances, 2016, 6, 105137-105145.	1.7	26
20	Flexible, hybrid nanogenerator based on Zinc Ferrite nanorods incorporated poly(vinylidene fluoride) nanocomposites. Materials Research Bulletin, 2019, 118, 110515.	2.7	26
21	Tailored piezoelectric performance of self-polarized PVDF/ZnO composites by optimization of aspect ratio of ZnO nanorods. Polymer Composites, 2020, 41, 3351-3363.	2.3	26
22	Effect of doping Ca ions on structural and electrical properties of Ba(Zr <sub>0.05</sub> Ti <sub>0.95</sub> )O <sub>3</sub> electroceramics. Journal of Materials Science: Materials in Electronics, 2004, 15, 671-675.	1.1	24
23	Frequency dependent energy storage and dielectric performance of Ba <sup>2+</sup> /Zr Co-doped BiFeO <sub>3</sub> loaded PVDF based mechanical energy harvesters: effect of corona poling. Soft Matter, 2020, 16, 8492-8505.	1.2	23
24	Space charge induced augmented dielectric permittivity and improved energy harvesting ability of nano-Ag decorated ZnSnO <sub>3</sub> filled PVDF based flexible nanogenerator. Composites Science and Technology, 2021, 213, 108916.	3.8	23
25	Flexible piezoelectric energy harvesters using different architectures of ferrite based nanocomposites. CrystEngComm, 2019, 21, 3478-3488.	1.3	20
26	Improved dielectric and touch sensing performance of surface modified zinc ferrite (ZF)/Polyvinylidene fluoride (PVDF) composite. Sensors and Actuators A: Physical, 2017, 267, 301-309.	2.0	18
27	Significantly suppressed leakage current and reduced band gap of BiFeO <sub>3</sub> through Ba <sup>2+</sup> /Zr Co-Substitution: Structural, optical, electrical and magnetic study. Materials Chemistry and Physics, 2020, 254, 123362.	2.0	15
28	Effect of surface modification of ceramic particles by SDS on the electrical properties of PZT-PVDF and BT-PVDF composites: interface effect. Journal of Materials Science: Materials in Electronics, 2015, 26, 2969-2976.	1.1	14
29	Structural, dielectric and electrical properties of Ca modified BaSn <sub>0.15</sub> Ti <sub>0.85</sub> O <sub>3</sub> Ceramics. Journal of Materials Science, 2005, 40, 5457-5462.	1.7	12
30	Electrical behaviour of PMN-PT/PVDF nanocomposite. Journal Physics D: Applied Physics, 2008, 41, 165305.	1.3	8
31	Surface Modified Zinc Ferrite (ZF) / Polyvinylidene fluoride (PVDF) Nanocomposite: A Novel Material for Application as a Flexible Energy Harvester. Materials Today: Proceedings, 2018, 5, 10047-10053.	0.9	8
32	Novel technique for synthesis and characterization of nanosized Ba <sub>1-x</sub> Sr <sub>x</sub> Sn <sub>0.15</sub> Ti <sub>0.85</sub> O <sub>3</sub> ceramics. Physica Status Solidi A, 2004, 201, 937-943.	1.7	7
33	Influence of nanoparticle size on nucleation of electroactive phase and energy storage behaviour of zinc ferrite/ poly(vinylidene fluoride) nanocomposite. Journal of Materials Science: Materials in Electronics, 2019, 30, 5137-5148.	1.1	6
34	Influence of Various Physiochemical Parameters of AFeO <sub>3</sub> (A = Bi, Er, Ga, La, Sm, Y) Fillers on the Dielectric, Ferroelectric, Energy Storage, and Mechanical Energy Harvesting Performance of PVDF. Macromolecular Materials and Engineering, 2022, 307, .	1.7	6
35	Investigation of density of states and electrical properties of Ba <sub>0.5</sub> Co <sub>0.5</sub> Bi <sub>2</sub> Nb <sub>2</sub> O <sub>9</sub> nanoceramics prepared by chemical route. Journal of Materials Science: Materials in Electronics, 2017, 28, 4676-4683.	1.1	3
36	Enhancement of Electroactive $\hat{1}^2$ -phase and Superior Dielectric Properties in Cerium Based Poly(vinylidene fluoride) Composite Films. Materials Today: Proceedings, 2018, 5, 10084-10090.	0.9	3

#	ARTICLE	IF	CITATIONS
37	Enhanced dielectric, ferroelectrics and piezoelectric behavior of tape casted BCT-BZT piezoelectric wafer. Journal of Materials Science: Materials in Electronics, 2018, 29, 14046-14054.	1.1	3
38	Low-Temperature Synthesis of 0.65 PbMg <sub>1/3</sub> Nb <sub>2/3</sub> O <sub>3</sub> ?0.35PbTiO <sub>3</sub> Ceramics. Journal of the American Ceramic Society, 2007, 90, 2634-2638.	1.9	2
39	The preparation of $\hat{I}^3$ -poly(vinylidene fluoride)/ZnS nanocomposite for energy storage application. Materials Today: Proceedings, 2018, 5, 10091-10096.	0.9	1
40	Synthesis and Characterization of Nanosized Ba <sub>1-x</sub> Mg <sub>x</sub> Sn <sub>0.15</sub> Ti <sub>0.85</sub> O <sub>3</sub> Ceramics. Ferroelectrics, 2005, 324, 21-29.	0.3	0