

Masatoshi Shioya

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/5475353/publications.pdf>

Version: 2024-02-01

46
papers

694
citations

516215

16
h-index

580395

25
g-index

47
all docs

47
docs citations

47
times ranked

800
citing authors

#	ARTICLE	IF	CITATIONS
1	Mechanism for anisotropic thermal expansion of polyamide fibers. <i>Sensors and Actuators B: Chemical</i> , 2021, 344, 130262.	4.0	11
2	Viscoelastic Characteristics in Fragmentation Tests of Carbon Fiber and Glass Fiber Reinforced Polypropylene Composites. <i>Journal of the Japan Society for Composite Materials</i> , 2020, 46, 204-211.	0.1	0
3	Fatigue Mechanism Analysed Based on the Changes in Microstructure and Axial Compression Strength of a Poly(<i>p</i> -phenylene-2,6-benzobisoxazole) Fiber. <i>Journal of Fiber Science and Technology</i> , 2019, 75, 186-192.	0.2	0
4	Maximum available tensile strength of carbon fibers. <i>Advanced Materials Letters</i> , 2018, 9, 885-888.	0.3	0
5	Determination of intrinsic strength of carbon fibers. <i>Carbon</i> , 2016, 100, 208-213.	5.4	12
6	Analysis on Fracture Behavior of High Strength Fibers Using Micromechanical Tests. <i>Seikei-Kakou</i> , 2016, 28, 352-356.	0.0	0
7	Correlations between the abrasive wear, fatigue, and tensile properties of filler-dispersed polyamide 6. <i>Wear</i> , 2015, 338-339, 297-306.	1.5	22
8	Influence of viscoelasticity on friction coefficient of abrasive wear for filler-dispersed polyamide 6. <i>Wear</i> , 2015, 324-325, 17-26.	1.5	8
9	Extraordinarily large swelling energy of iodine-treated poly(vinyl alcohol) demonstrated by jump of a film. <i>Journal of Polymer Science, Part B: Polymer Physics</i> , 2014, 52, 1357-1365.	2.4	2
10	Improving the gas barrier properties of Fe ₃ O ₄ /graphite nanoplatelet reinforced nanocomposites by a low magnetic field induced alignment. <i>Composites Science and Technology</i> , 2014, 99, 124-130.	3.8	71
11	Reduction in tensile strength of polyacrylonitrile-based carbon fibers in liquids and its application to defect analysis. <i>Carbon</i> , 2013, 65, 63-70.	5.4	21
12	Structure change of carbon fibers during axial compression. <i>Carbon</i> , 2013, 57, 416-424.	5.4	23
13	Structure changes during tensile deformation and mechanical properties of a twisted carbon nanotube yarn. <i>Carbon</i> , 2013, 60, 193-201.	5.4	22
14	Utilization of Triacetylcellulose Waste for the Production of Carbonaceous Adsorbents. <i>Journal of Polymers and the Environment</i> , 2012, 20, 626-630.	2.4	3
15	Relationship between axial compression strength and longitudinal microvoid size for PAN-based carbon fibers. <i>Carbon</i> , 2012, 50, 2860-2869.	5.4	23
16	Analysis on Abrasive Wear Rate of VGCF/Polyamide 6 Composite Fibers. <i>Tribology Online</i> , 2011, 6, 207-218.	0.2	10
17	Wear Resistance and Tensile Properties of Filler-added Polyamide 6 Fibers. <i>Journal of Fiber Science and Technology</i> , 2011, 67, 109-118.	0.0	6
18	A method to determine wear rates of fibers and its application to polymeric fibers added with inorganic fillers. <i>Wear</i> , 2010, 268, 1148-1156.	1.5	10

#	ARTICLE	IF	CITATIONS
19	Carbonaceous adsorbents produced from coffee lees. <i>Journal of Materials Science</i> , 2009, 44, 1137-1139.	1.7	7
20	Small-Angle X-ray Scattering Study on the Tensile Fracture Process of Poly(ethylene terephthalate) Fiber. <i>Macromolecules</i> , 2008, 41, 4758-4765.	2.2	29
21	A comparative study of fracture behavior between carbon black/poly(ethylene terephthalate) and multiwalled carbon nanotube/poly(ethylene terephthalate) composite films. <i>Journal of Applied Polymer Science</i> , 2007, 106, 152-160.	1.3	29
22	Synchrotron radiation small-angle X-ray scattering study on fracture process of carbon nanotube/poly(ethylene terephthalate) composite films. <i>Composites Science and Technology</i> , 2007, 67, 3209-3218.	3.8	25
23	Carbonization behavior of L-tryptophan and gluten. <i>Journal of Materials Science</i> , 2007, 42, 2076-2080.	1.7	4
24	Control of diameter, morphology, and structure of PVDF nanofiber fabricated by electrospray deposition. <i>Journal of Polymer Science, Part B: Polymer Physics</i> , 2006, 44, 779-786.	2.4	108
25	Small-angle X-ray scattering of long-period structures forming bundles. <i>Polymer</i> , 2006, 47, 3616-3628.	1.8	9
26	Wear Resistance and Mechanical Properties of Polymeric Fibers Filled with Inorganic Fillers. <i>Materials Research Society Symposia Proceedings</i> , 2006, 977, 1.	0.1	4
27	Chemically Retted Kenaf Fibers. <i>Journal of Fiber Science and Technology</i> , 2005, 61, 115-117.	0.0	12
28	Mechanical properties of woven laminates and felt composites using carbon fibers. Part 1: in-plane properties. <i>Composites Science and Technology</i> , 2004, 64, 2221-2229.	3.8	44
29	Mechanical properties of woven laminates and felt composites using carbon fibers. Part 2: interlaminar properties. <i>Composites Science and Technology</i> , 2004, 64, 2231-2238.	3.8	21
30	Analysis of Defects in Poly(ethylene terephthalate) Fibers. <i>Journal of Fiber Science and Technology</i> , 2004, 60, 346-351.	0.0	7
31	Swelling behavior of high-speed spun poly (ethylene terephthalate) fibers. <i>Journal of Macromolecular Science - Physics</i> , 2002, 41, 397-406.	0.4	2
32	Activation energy of structural development for phenol formaldehyde resin-based carbon fibers. <i>Carbon</i> , 2001, 39, 1869-1878.	5.4	9
33	Variation of Longitudinal Modulus with Twist for Yarns Composed of High Modulus Fibers. <i>Textile Reseach Journal</i> , 2001, 71, 928-936.	1.1	6
34	CHARACTERIZATION OF MICROVOIDS IN WILD SILK FIBERS USING STANNIC ACID TREATMENT. <i>Journal of Macromolecular Science - Physics</i> , 2001, 40, 1069-1078.	0.4	5
35	Characterization of microvoids in mulberry and tussah silk fibers using stannic acid treatment. <i>Journal of Applied Polymer Science</i> , 1999, 73, 363-367.	1.3	26
36	Influences of Fundamental Characteristics of Weft Yarns and Decatizing Treatment on Mechanical Properties of Silk Necktie Fabrics. <i>Journal of the Textile Machinery Society of Japan English Edition</i> , 1999, 45, 1-5.	0.1	0

#	ARTICLE	IF	CITATIONS
37	Changes in fiber structure of Japanese oak silk fibers by the treatment with methacrylamide. Journal of Macromolecular Science - Physics, 1997, 36, 503-511.	0.4	1
38	Mechanical properties of tussah silk fibers treated with methacrylamide. Journal of Applied Polymer Science, 1997, 65, 2051-2057.	1.3	18
39	Influence of swelling of noncrystalline regions in silk fibers on modification with methacrylamide. Journal of Applied Polymer Science, 1996, 59, 51-56.	1.3	20
40	Mechanical properties of silk fibers treated with methacrylamide. Journal of Applied Polymer Science, 1996, 61, 1359-1364.	1.3	17
41	Estimation of fibre and interfacial shear strength by using a single-fibre composite. Composites Science and Technology, 1995, 55, 33-39.	3.8	33
42	Analysis of Swelling Behavior of Silk Fibers by Small-Angle X-Ray Scattering.. Journal of Fiber Science and Technology, 1994, 50, 199-207.	0.0	4
43	Analysis of Structure and Swelling Behavior of Silk Fibers Treated with a Mixture of Glyoxal and Urethane Resins.. Journal of Fiber Science and Technology, 1994, 50, 505-509.	0.0	1
44	Temperature-Time Superposition of Resistivity of Carbon Fibers during Heat-treatment by Direct Currenting. Tanso, 1994, 1994, 119-123.	0.1	2
45	Morphological study on carbon fibers and films derived from polyoxadiazole.. Journal of Fiber Science and Technology, 1992, 48, 379-383.	0.0	4
46	CONSIDERATION ON THE EFFECT OF RESIN PROPERTIES ON TENSILE STRENGTH OF CARBON FIBER-RESIN COMPOSITE STRANDS. Journal of Fiber Science and Technology, 1984, 40, T13-T19.	0.0	2