

Hyun-Taek Lee

List of Publications by Year in Descending Order

Source: <https://exaly.com/author-pdf/5605019/hyun-taek-lee-publications-by-year.pdf>

Version: 2024-04-24

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

91
papers

4,698
citations

38
h-index

67
g-index

95
ext. papers

5,548
ext. citations

6
avg, IF

5.95
L-index

#	Paper	IF	Citations
91	Superhydrophobicity and corrosion resistance of AISI 4140 mold made through nanosecond laser texturing. <i>International Journal of Advanced Manufacturing Technology</i> , 2022 , 119, 5119	3.2	0
90	A Multiscale Adhesion Model for Deposition Prediction in Laser Enhanced Nanoparticle Deposition Process. <i>Acta Materialia</i> , 2021 , 208, 116740	8.4	0
89	Precise glass microstructuring with laser induced backside wet etching using error-compensating scan path. <i>Journal of Materials Processing Technology</i> , 2021 , 291, 117046	5.3	3
88	Shape memory alloy-driven undulatory locomotion of a soft biomimetic ray robot. <i>Bioinspiration and Biomimetics</i> , 2021 , 16,	2.6	1
87	Shape memory textile composites with multi-mode actuations for soft morphing skins. <i>Composites Part B: Engineering</i> , 2020 , 198, 108170	10	22
86	Direct printing of performance tunable strain sensor via nanoparticle laser patterning process. <i>Virtual and Physical Prototyping</i> , 2020 , 15, 265-277	10.1	6
85	Microtentacle Actuators Based on Shape Memory Alloy Smart Soft Composite. <i>Advanced Functional Materials</i> , 2020 , 30, 2002510	15.6	12
84	Crack-free fabrication of Prussian blue-based blending film for the dramatic enhancement of dual electrochromic device. <i>Ceramics International</i> , 2020 , 46, 21008-21013	5.1	5
83	Shape Memory Alloy-Based Microscale Bending Actuator Fabricated by a Focused Ion Beam Chemical Vapor Deposition (FIB-CVD) Gap-Filling Process. <i>International Journal of Precision Engineering and Manufacturing</i> , 2020 , 21, 491-498	1.7	5
82	Shape Memory Alloy-Based Soft Finger with Changeable Bending Length Using Targeted Variable Stiffness. <i>Soft Robotics</i> , 2020 , 7, 283-291	9.2	21
81	Directly Printed Low-Cost Nanoparticle Sensor for Vibration Measurement during Milling Process. <i>Materials</i> , 2020 , 13,	3.5	2
80	50 nm Scale Alignment Method for Hybrid Manufacturing Processes for Full 3D Structuring. <i>International Journal of Precision Engineering and Manufacturing</i> , 2020 , 21, 2407-2417	1.7	
79	Microtentacle Actuators: Microtentacle Actuators Based on Shape Memory Alloy Smart Soft Composite (Adv. Funct. Mater. 34/2020). <i>Advanced Functional Materials</i> , 2020 , 30, 2070231	15.6	0
78	Hybrid composite actuator with shape retention capability for morphing flap of unmanned aerial vehicle (UAV). <i>Composite Structures</i> , 2020 , 243, 112227	5.3	7
77	Stretchable Biaxial and Shear Strain Sensors Using Diffractive Structural Colors. <i>ACS Nano</i> , 2020 , 14, 53926539927	26.3	99
76	Low-voltage modulated inorganic smart windows using solid polymer electrolyte. <i>Solar Energy Materials and Solar Cells</i> , 2019 , 200, 109966	6.4	5
75	Highly Sensitive Solvent-free Silver Nanoparticle Strain Sensors with Tunable Sensitivity Created Using an Aerodynamically Focused Nanoparticle Printer. <i>ACS Applied Materials & Interfaces</i> , 2019 , 11, 26421-26432	9.5	15

74	Simulation of electrical conductivity for nanoparticles and nanotubes composite sensor according to geometrical properties of nanomaterials. <i>Composites Part B: Engineering</i> , 2019 , 174, 107003	10	7
73	Colour-tunable 50% strain sensor using surface-nanopatterning of soft materials via nanoimprinting with focused ion beam milling process. <i>CIRP Annals - Manufacturing Technology</i> , 2019 , 68, 595-598	4.9	10
72	Laser Controlled 65 Micrometer Long Microrobot Made of Ni-Ti Shape Memory Alloy. <i>Advanced Materials Technologies</i> , 2019 , 4, 1900583	6.8	10
71	Direct printing of highly sensitive, stretchable, and durable strain sensor based on silver nanoparticles/multi-walled carbon nanotubes composites. <i>Composites Part B: Engineering</i> , 2019 , 161, 395-401	10	68
70	Simulation of dynamic growth rate of focused ion beam-induced deposition using Hausdorff distance. <i>Sensors and Actuators A: Physical</i> , 2019 , 286, 169-177	3.9	1
69	Soft Tendril-Inspired Grippers: Shape Morphing of Programmable Polymer-Paper Bilayer Composites. <i>ACS Applied Materials & Interfaces</i> , 2018 , 10, 10419-10427	9.5	80
68	Shape Memory Alloy (SMA)-Based Microscale Actuators with 60% Deformation Rate and 1.6 kHz Actuation Speed. <i>Small</i> , 2018 , 14, e1801023	11	31
67	Microstructural Control of the Electrochromic and Ion Storage Layers on the Performance of an Electrochromic Device Fabricated by the Kinetic Spray Technique. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2018 , 5, 231-238	3.8	6
66	Resistive pressure sensor based on cylindrical micro structures in periodically ordered electrospun elastic fibers. <i>Smart Materials and Structures</i> , 2018 , 27, 11LT01	3.4	10
65	Blooming Knit Flowers: Loop-Linked Soft Morphing Structures for Soft Robotics. <i>Advanced Materials</i> , 2017 , 29, 1606580	24	46
64	An Overview of Shape Memory Alloy-Coupled Actuators and Robots. <i>Soft Robotics</i> , 2017 , 4, 3-15	9.2	111
63	Site-specific characterization of beetle horn shell with micromechanical bending test in focused ion beam system. <i>Acta Biomaterialia</i> , 2017 , 57, 395-403	10.8	4
62	Curved shape memory alloy-based soft actuators and application to soft gripper. <i>Composite Structures</i> , 2017 , 176, 398-406	5.3	61
61	Advanced scanning paths for focused ion beam milling. <i>Vacuum</i> , 2017 , 143, 40-49	3.7	10
60	Design and Fabrication of Soft Morphing Ray Propulsor: Undulator and Oscillator. <i>Soft Robotics</i> , 2017 , 4, 49-60	9.2	40
59	Direct printing of anisotropic wetting patterns using aerodynamically focused nanoparticle (AFN) printing. <i>Applied Surface Science</i> , 2017 , 396, 1450-1457	6.7	13
58	Shape Memory Alloy-Based Soft Gripper with Variable Stiffness for Compliant and Effective Grasping. <i>Soft Robotics</i> , 2017 , 4, 379-389	9.2	137
57	Effect of laser-excited ceramic nanoparticles on hardness and porosity of dry-sprayed coating. <i>CIRP Annals - Manufacturing Technology</i> , 2017 , 66, 519-522	4.9	4

56	From 3D to 4D printing Design, material and fabrication for multi-functional multi-materials. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2017 , 4, 291-299	3.8	40
55	Direct Printing of Strain Sensors via Nanoparticle Printer for the Applications to Composite Structural Health Monitoring. <i>Procedia CIRP</i> , 2017 , 66, 238-242	1.8	24
54	Pulse width modulation as energy-saving strategy of shape memory alloy based smart soft composite actuator. <i>International Journal of Precision Engineering and Manufacturing</i> , 2017 , 18, 895-901	1.7	10
53	CAD/CAM for scalable nanomanufacturing: A network-based system for hybrid 3D printing. <i>Microsystems and Nanoengineering</i> , 2017 , 3, 17072	7.7	4
52	Soft morphing hand driven by SMA tendon wire. <i>Composites Part B: Engineering</i> , 2016 , 105, 138-148	10	60
51	Design and evaluation of micro-cutting tools for local planarization. <i>International Journal of Precision Engineering and Manufacturing</i> , 2016 , 17, 1267-1273	1.7	8
50	A review on fabrication processes for electrochromic devices. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2016 , 3, 397-421	3.8	49
49	Deployable Soft Composite Structures. <i>Scientific Reports</i> , 2016 , 6, 20869	4.9	51
48	Soft composite hinge actuator and application to compliant robotic gripper. <i>Composites Part B: Engineering</i> , 2016 , 98, 397-405	10	53
47	Room-Temperature Fabrication of a Flexible Thermoelectric Generator Using a Dry-Spray Deposition System. <i>Journal of Electronic Materials</i> , 2016 , 45, 2286-2290	1.9	6
46	Shape memory alloy/glass fiber woven composite for soft morphing winglets of unmanned aerial vehicles. <i>Composite Structures</i> , 2016 , 140, 202-212	5.3	41
45	Woven type smart soft composite for soft morphing car spoiler. <i>Composites Part B: Engineering</i> , 2016 , 86, 285-298	10	38
44	Comparison of mold designs for SMA-based twisting soft actuator. <i>Sensors and Actuators A: Physical</i> , 2016 , 237, 96-106	3.9	18
43	Flexible ceramic-elastomer composite piezoelectric energy harvester fabricated by additive manufacturing. <i>Journal of Composite Materials</i> , 2016 , 50, 1573-1579	2.7	12
42	35 Hz shape memory alloy actuator with bending-twisting mode. <i>Scientific Reports</i> , 2016 , 6, 21118	4.9	60
41	Novel fabrication of an electrochromic antimony-doped tin oxide film using a nanoparticle deposition system. <i>Applied Surface Science</i> , 2016 , 377, 370-375	6.7	18
40	Design and analysis of a smart soft composite structure for various modes of actuation. <i>Composites Part B: Engineering</i> , 2016 , 95, 155-165	10	20
39	From design for manufacturing (DFM) to manufacturing for design (MFD) via hybrid manufacturing and smart factory: A review and perspective of paradigm shift. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2016 , 3, 209-222	3.8	51

38	Low-cost fabrication of WO ₃ films using a room temperature and low-vacuum air-spray based deposition system for inorganic electrochromic device applications. <i>Thin Solid Films</i> , 2015 , 589, 412-418	2.2	31
37	Nanoscale 3D printing process using aerodynamically focused nanoparticle (AFN) printing, micro-machining, and focused ion beam (FIB). <i>CIRP Annals - Manufacturing Technology</i> , 2015 , 64, 523-526	4.9	17
36	SMA-based smart soft composite structure capable of multiple modes of actuation. <i>Composites Part B: Engineering</i> , 2015 , 82, 152-158	10	44
35	A smart soft actuator using a single shape memory alloy for twisting actuation. <i>Smart Materials and Structures</i> , 2015 , 24, 125033	3.4	32
34	A review of electrically-assisted manufacturing. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2015 , 2, 365-376	3.8	83
33	Design and development of bio-mimetic soft robotic hand with shape memory alloy		4
32	Smart soft composite actuator with shape retention capability using embedded fusible alloy structures. <i>Composites Part B: Engineering</i> , 2015 , 78, 507-514	10	53
31	Shape memory alloy (SMA)-based head and neck immobilizer for radiotherapy. <i>Journal of Computational Design and Engineering</i> , 2015 , 2, 176-182	4.6	8
30	Fabrication of wrist-like SMA-based actuator by double smart soft composite casting. <i>Smart Materials and Structures</i> , 2015 , 24, 125003	3.4	39
29	Cellulose nanofiber assisted deposition of titanium dioxide on fluorine-doped tin oxide glass. <i>RSC Advances</i> , 2014 , 4, 987-991	3.7	4
28	Bio-inspired deposition of silver nano-particles (AgNPs) on silicon substrate. <i>Materials Letters</i> , 2014 , 116, 175-177	3.3	1
27	Locomotion of inchworm-inspired robot made of smart soft composite (SSC). <i>Bioinspiration and Biomimetics</i> , 2014 , 9, 046006	2.6	118
26	A comparison of energy consumption in bulk forming, subtractive, and additive processes: Review and case study. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2014 , 1, 261-279	3.8	201
25	Aerodynamically focused nanoparticle (AFN) printing: novel direct printing technique of solvent-free and inorganic nanoparticles. <i>ACS Applied Materials & Interfaces</i> , 2014 , 6, 16466-71	9.5	24
24	Cross-shaped twisting structure using SMA-based smart soft composite. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2014 , 1, 153-156	3.8	40
23	Empirical power-consumption model for material removal in three-axis milling. <i>Journal of Cleaner Production</i> , 2014 , 78, 54-62	10.3	72
22	Fabrication of transparent superhydrophobic surface on thermoplastic polymer using laser beam machining and compression molding for mass production. <i>CIRP Annals - Manufacturing Technology</i> , 2014 , 63, 525-528	4.9	42
21	Effect of backstitch tool path on micro-drilling of printed circuit board. <i>Precision Engineering</i> , 2014 , 38, 691-696	2.9	13

20	Hybrid manufacturing in micro/nano scale: A Review. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2014 , 1, 75-92	3.8	119
19	An evaluation of green manufacturing technologies based on research databases. <i>International Journal of Precision Engineering and Manufacturing - Green Technology</i> , 2014 , 1, 5-9	3.8	44
18	Alignment Algorithm for Nano-scale Three-dimensional Printing System. <i>Journal of the Korean Society for Precision Engineering</i> , 2014 , 31, 1101-1106	0.3	2
17	Control of machining parameters for energy and cost savings in micro-scale drilling of PCBs. <i>Journal of Cleaner Production</i> , 2013 , 54, 41-48	10.3	58
16	Woven type smart soft composite beam with in-plane shape retention. <i>Smart Materials and Structures</i> , 2013 , 22, 125007	3.4	14
15	A turtle-like swimming robot using a smart soft composite (SSC) structure. <i>Smart Materials and Structures</i> , 2013 , 22, 014007	3.4	78
14	Effect of stand-off distance for cold gas spraying of fine ceramic particles (. <i>Surface and Coatings Technology</i> , 2012 , 206, 2125-2132	4.4	49
13	Review: Developments in micro/nanoscale fabrication by focused ion beams. <i>Vacuum</i> , 2012 , 86, 1014-1035	3.7	125
12	An overview on the cellulose based conducting composites. <i>Composites Part B: Engineering</i> , 2012 , 43, 2822-2826	10	54
11	A flexible and highly sensitive strain-gauge sensor using reversible interlocking of nanofibres. <i>Nature Materials</i> , 2012 , 11, 795-801	27	1227
10	Smart soft composite: An integrated 3D soft morphing structure using bend-twist coupling of anisotropic materials. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 631-634	1.7	86
9	Nano-particle deposition system (NPDS): Low energy solvent-free dry spray process for direct patterning of metals and ceramics at room temperature. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 1107-1112	1.7	34
8	Review of biomimetic underwater robots using smart actuators. <i>International Journal of Precision Engineering and Manufacturing</i> , 2012 , 13, 1281-1292	1.7	227
7	Laser-assisted nano particle deposition system and its application for dye sensitized solar cell fabrication. <i>CIRP Annals - Manufacturing Technology</i> , 2012 , 61, 575-578	4.9	17
6	Room temperature deposition of TiO ₂ using nano particle deposition system (NPDS): Application to dye-sensitized solar cell (DSSC). <i>International Journal of Precision Engineering and Manufacturing</i> , 2011 , 12, 749-752	1.7	21
5	Geometric optimization of micro drills using Taguchi methods and response surface methodology. <i>International Journal of Precision Engineering and Manufacturing</i> , 2011 , 12, 871-875	1.7	56
4	Deposition of TiO ₂ layers for dye-sensitized solar cells using nano-particle deposition system. <i>Current Applied Physics</i> , 2011 , 11, S122-S126	2.6	8
3	Deposition mechanism of dry sprayed ceramic particles at room temperature using a nano-particle deposition system. <i>Acta Materialia</i> , 2011 , 59, 2693-2703	8.4	110

- | | | | |
|---|---|-----|-----|
| 2 | Fabrication and reliable implementation of an ionic polymer-metal composite (IPMC) biaxial bending actuator. <i>Smart Materials and Structures</i> , 2011 , 20, 105026 | 3.4 | 16 |
| 1 | Review of manufacturing processes for soft biomimetic robots. <i>International Journal of Precision Engineering and Manufacturing</i> , 2009 , 10, 171-181 | 1.7 | 182 |