

# Tae Kuk Ko

## List of Publications by Citations

**Source:** <https://exaly.com/author-pdf/5720004/tae-kuk-ko-publications-by-citations.pdf>

**Version:** 2024-04-28

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

111  
papers

861  
citations

14  
h-index

25  
g-index

111  
ext. papers

978  
ext. citations

1.8  
avg, IF

3.58  
L-index

#	Paper	IF	Citations
111	Bipolar resistive switching behavior in Ti/MnO <sub>2</sub> /Pt structure for nonvolatile memory devices. <i>Applied Physics Letters</i> , <b>2009</b> , 95, 042105	3.4	122
110	Study on a Series Resistive SFCL to Improve Power System Transient Stability: Modeling, Simulation, and Experimental Verification. <i>IEEE Transactions on Industrial Electronics</i> , <b>2009</b> , 56, 2412-2419	8.9	73
109	Analysis of a Joint Method Between Superconducting YBCO Coated Conductors. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 3266-3269	1.8	49
108	Study on Optimal Location of a Resistive SFCL Applied to an Electric Power Grid. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2009</b> , 19, 2048-2052	1.8	41
107	Conceptual Design of Superconducting Linear Synchronous Motor for 600-km/h Wheel-Type Railway. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-4	1.8	33
106	Development of 220 V/300 A Class Non-Inductive Winding Type Fault Current Limiter Using 2G HTS Wire. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 1863-1866	1.8	27
105	Recovery Characteristics of Resistive SFCL Wound With YBCO Coated Conductor in a Power System. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 1859-1862	1.8	26
104	Characteristics of Contactless Power Transfer for HTS Coil Based on Electromagnetic Resonance Coupling. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 5400604-5400604	1.8	23
103	A Study on the Design of the Stabilizer of Coated Conductor for Applying to SFCL. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 1855-1858	1.8	23
102	Determination of Maximum Permissible Temperature Rise Considering Repetitive Over-Current Characteristics of YBCO Coated Conductors. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2008</b> , 18, 660-663	1.8	20
101	Analytical and Experimental Studies on the Hybrid Fault Current Limiter Employing Asymmetric Non-Inductive Coil and Fast Switch. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2009</b> , 19, 1896-1899	1.8	19
100	Analysis of the Operational Characteristics of a Resistive SFCL by Using the YBCO Coated Conductor. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 1851-1854	1.8	18
99	Experimental Analysis on Initial Current Decay Characteristics of Persistent-Mode HTS Coil by External Alternating Magnetic Field. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	17
98	Design, fabrication, and test of high-T <sub>c</sub> superconducting DC reactor for inductive superconducting fault current limiter. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2004</b> , 14, 827-830	1.8	17
97	Electrical Breakdown Characteristics of Superconducting Magnet System in Sub-Cooled Liquid Nitrogen. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 1509-1512	1.8	14
96	Theoretical and Experimental Analysis of AC Loss Characteristic of Bifilar Pancake Coil With Coated Conductor. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2008</b> , 18, 1232-1235	1.8	13
95	The short-circuit characteristics of a DC reactor type superconducting fault current limiter with fault detection and signal control of the power converter. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2005</b> , 15, 2102-2105	1.8	13

94	Development of 6.6 kV-200 A DC reactor type superconducting fault current limiter. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2004</b> , 14, 867-870	1.8	13
93	Dielectric Tests of Superconducting Coils for Development of High Voltage Superconducting Machines. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 1493-1496	1.8	11
92	Test of DC reactor type fault current limiter using SMES magnet for optimal design. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2002</b> , 12, 850-853	1.8	11
91	PID Control of an Electromagnet-Based Rotary HTS Flux Pump for Maintaining Constant Field in HTS Synchronous Motors. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2018</b> , 28, 1-5	1.8	11
90	Design and characteristic analysis of a rod type high-T <sub>c</sub> superconducting fault current limiter through electromagnetic analysis. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2001</b> , 11, 2102-2105	1.8	10
89	A Study on the Non-Inductive Coils for Hybrid Fault Current Limiter Using Experiment and Numerical Analysis. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 1151-1154	1.8	9
88	Resistive switching characteristics of TiN/MnO <sub>2</sub> /Pt memory devices. <i>Physica Status Solidi - Rapid Research Letters</i> , <b>2010</b> , 4, 233-235	2.5	9
87	Characteristic Analysis of HTSC Persistent Current Switch for Maglev Application. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 2099-2102	1.8	8
86	Fabrication and Charging Test of HTS Field Windings Using HTS Contactless Rotary Excitation Device. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2019</b> , 29, 1-7	1.8	7
85	Corrections to Evaluations on AC Electrical Characteristics of No-Insulation Coil for Power Devices [Jun 13 4700604]. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2013</b> , 23, 9700201-9700201	1.8	7
84	Conceptual Design for HTS Coil in Superconducting Electromagnet for Maglev. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 1560-1563	1.8	7
83	Experimental Study on the Electrical Breakdown Characteristics of Sub-Cooled Liquid Nitrogen for Designing a High Voltage Superconducting Machine. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 1662-1666	1.8	7
82	Quench Analysis of a Superconducting Magnet for RISP 28 GHz ECR Ion Source. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	6
81	Operational Characteristics of a Small-Scale Novel Hybrid Resistive-Type SFCL With Controlled Power Electronics. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-5	1.8	6
80	Experimental Analysis of Charging Characteristics of HTS Field Coils With HTS Contactless Rotary Excitation Device Considering Various HTS Loads. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2018</b> , 28, 1-5	1.8	6
79	Experimental Analysis on AC Loss and Fault Current Test of HTS Coils Co-Wound With Various Inserted Materials. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2016</b> , 1-1	1.8	6
78	Dielectric Characteristics of Solid Insulation Materials With Respect to Surface Roughness. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	6
77	Quench Detection Method for HTS Coils Using Electromagnetically Coupled Coils. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	6

76	Characteristic Comparison for the Various Winding Methods of HTS Magnets. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 4902907-4902907	1.8	6
75	Design and cooling characteristic results of cryogenic system for 6.6 kV/200 A inductive fault current limiter. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2004</b> , 14, 883-886	1.8	6
74	Evaluation of Electrical and Thermal Properties of Stacked YBCO Coated Conductors for Current Lead Application. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	5
73	Characteristic Analysis of a 1-kW-Class HTS Motor Considering Armature Current Information. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2018</b> , 28, 1-5	1.8	5
72	A Study on the Superconducting Synchronous Generator With the Fixed-Type Field Coil. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2013</b> , 23, 5200305-5200305	1.8	5
71	Theoretical Analysis and Design Consideration of Advanced Linear Type Magnetic Flux Pump. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 1097-1100	1.8	5
70	Estimation of Current Decay Performance of HTS Electromagnet for Maglev. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 907-910	1.8	5
69	Experimental Analysis of Bifilar Pancake Type Fault Current Limiting Coil Using Stabilizer-Free Coated Conductor. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2009</b> , 19, 1797-1800	1.8	5
68	Design and manufacturing of the large scale high-T/sub c/ superconducting DC magnet for the 2.3 MVA SFCL. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2005</b> , 15, 1965-1969	1.8	5
67	Electrical degradation of a high-T/sub c/ superconductor by continuous current transport. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2003</b> , 13, 2949-2952	1.8	5
66	Characteristics of critical current of high-T/sub c/ superconducting magnets wound with various tensions. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2003</b> , 13, 2080-2083	1.8	5
65	Charging Characteristics of Rotary HTS Flux Pump With Several Superconducting Wires. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2019</b> , 29, 1-5	1.8	4
64	Analysis of a High-Tc Superconducting Power Converting System. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	4
63	Design, Fabrication, and Operating Test of the Prototype HTS Electromagnet for EMS-Based Maglev. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 3600504-3600504	1.8	4
62	Evaluations on AC Electrical Characteristics of No-Insulation Coil for Power Devices. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2013</b> , 23, 4700604-4700604	1.8	4
61	A Research on Design Method and Theoretical Analysis of Electromagnetic Suspension System Considering Magnetic Interface Between Coils. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 1523-1527	1.8	4
60	Experimental Analysis of Flux Pump for Compensating Current Decay in the Persistent Current Mode Using HTS Magnet. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 1693-1696	1.8	4
59	A Research About Bending Strain Effect on Splice Characteristics in $\text{YBa}_2\text{Cu}_3\text{O}_{7-x}$ Coated Conductors Under Various Pressures in Splicing. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 3001-3004	1.8	4

58	Design and test of modified bridge type superconducting fault current limiter with reverse magnetized core. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2003</b> , 13, 2016-2019	1.8	4
57	Test and Analysis of Electromagnetic and Mechanical Properties of HTS Coil During Quench State. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2016</b> , 26, 1-4	1.8	4
56	Operational Characteristics of HTS Coils With Flux Diverters in Semipersistent Mode Under Alternating Magnetic Field. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2016</b> , 26, 1-5	1.8	4
55	A Novel Fault Diagnosis Method for High-Temperature Superconducting Field Coil of Superconducting Rotating Machine. <i>Applied Sciences (Switzerland)</i> , <b>2020</b> , 10, 223	2.6	3
54	Over-Current Characteristics Influenced by Ag Stabilizer Thickness in a GdBCO Coated Conductor (CC). <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 3029-3032	1.8	3
53	Longitudinal and Transverse Quench Propagation in Pancake Coils Using Coated Conductors With Additional Copper Tape in Liquid Helium. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 2160-2163	1.8	3
52	Design and Test of a Superconducting Power Supply With YBCO Coated Conductor Load. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2008</b> , 18, 1415-1418	1.8	3
51	A New Quench Protection System Using Dual-Capacitor Switching for Fast Energy Extraction From HTS Magnets. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2019</b> , 29, 1-5	1.8	2
50	. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2019</b> , 29, 1-5	1.8	2
49	Degradation Characteristics of Superconducting Wires With Respect to Electrical Breakdown Tests. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	2
48	Measurement of Magnetic Field Properties of a 3.0 T/m Air-Core HTS Quadrupole Magnet and Optimal Shape Design to Increase the Critical Current Reduced by the Incident Magnetic Field. <i>Electronics (Switzerland)</i> , <b>2020</b> , 9, 450	2.6	2
47	Degradation of Critical Current in an HTS Tape With Combined Bending and Torsion Considering Curvature of Elliptical Shape. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2018</b> , 28, 1-5	1.8	2
46	Evaluation on Electrical and Thermal Characteristics of Multi-Stacked HTS Coated Conductor With Various Stabilizers. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-4	1.8	2
45	A Study on the Loss in a Superconducting Magnet by the Control Current in a Hybrid Electro-Magnetic Suspension System. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 3600105-3600105	1.8	2
44	A Study on Recovery Characteristics of Joined Tapes From the View of Thermal and Electrical Variation for Superconducting Magnets. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 4703505-4703505	1.8	2
43	Experimental Study of the New Type of HTS Elements for Current Leads to be Applied to the Nuclear Fusion Devices. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 4801204-4801204	1.8	2
42	Numerical Analysis and Electrical Insulation Design of a Single-Phase 154 kV Class Non-Inductively Wound Solenoid Type Superconducting Fault Current Limiter. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 5602104-5602104	1.8	2
41	Transition Criteria for Critical Current Measurement of High Temperature Superconductor in AC Circumstance. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 6400204-6400204	1.8	2

40	A Novel and Smart Design of Superconducting Fault Current Controller: Implementation and Verification for Various Fault Condition. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2013</b> , 23, 5602904-5602904	1.8	2
39	Experimental Analysis of Unequal Voltage Distribution on a Single YBCO Coated Conductor Affected by Inhomogeneous Critical Currents in Liquid Nitrogen and Sub-Cooled Liquid Nitrogen. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 2992-2996	1.8	2
38	Experimental Study on the Lightning Impulse Dielectric Characteristics of Sub-Cooled Liquid Nitrogen for a High Voltage Superconducting Fault Current Limiter. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 1336-1339	1.8	2
37	Parameter Determination of a Condition for Simultaneous Quench in Series-Connected YBCO Coated Conductors. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 1207-1210	1.8	2
36	Characteristic analysis of a heater-triggered switching system for the charging of Bi-2223 double-pancake load. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2003</b> , 13, 2227-2230	1.8	2
35	DC critical current estimate of the short HTS cable consisted of Bi-2223 tapes. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2004</b> , 14, 670-673	1.8	2
34	A study on the efficiency of low-Tc superconducting power supply considering the series-parallel connections of superconducting circuits. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2002</b> , 12, 804-807	1.8	2
33	A variation of impedance of a high-Tc superconducting fault current limiter with an open core. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2002</b> , 12, 846-849	1.8	2
32	Analysis of the Notch Effect on Flux Diverters for High-Temperature Superconducting Magnets. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2016</b> , 26, 1-4	1.8	2
31	A Study on the YBCO-Coated Conductor Current Lead With Asymmetric Structure Tape Considering Temperature Distribution. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2017</b> , 27, 1-5	1.8	1
30	A Numerical and Experimental Analysis of the Temperature Dependence of the n-Index for 2G HTS Tape Surrounding the 77 K Temperature Range. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	1
29	Analysis of the Current Charge and Discharge Characteristics of a Small-Scale Turn-to-Turn Soldered HTS Coil. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	1
28	Charging Characteristics of Series Connected Insulation and No-Insulation HTS Coils by Rotary HTS Flux Pump. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2020</b> , 30, 1-5	1.8	1
27	Optimal Design and Performance Evaluation of Dual-Capacitor Switching (DCS) Quench Protection System for Superconducting Magnet. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2020</b> , 30, 1-5	1.8	1
26	Analytic Study of the Active Quench Detection Method for High-Temperature Superconducting Magnet Using Resonance Circuit. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2018</b> , 28, 1-4	1.8	1
25	Experimental Analysis of Thermally and Magnetically Triggered Switch for High-Tc Superconducting Power Converting System. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2016</b> , 26, 1-4	1.8	1
24	The Effect of Bobbin Material on the Thermal Stability of a Conduction-Cooled HTS Racetrack Coil. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-5	1.8	1
23	Design and Experimental Evaluation on kA-Class HTS Binary Superconducting Current Lead Using a Liquid Nitrogen Bath Under Short-Term Current Test. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-5	1.8	1

22	Design and Test of a High-Tc Superconducting Power Conversion System With the GdBCO Magnet. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-5	1.8	1
21	The Effect of Operating Temperature on Transport AC Loss According to an YBCO Superconducting Tape Array Geometry. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2011</b> , 21, 3329-3333	1.8	1
20	Proposal and Fundamental Analysis of Cylindrical Type Magnetic Flux Pump for High Field Magnet. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2010</b> , 20, 1685-1688	1.8	1
19	Characteristics of Simultaneous Quenches in Series-Connected YBaCuO Coated Conductors. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2009</b> , 19, 1814-1817	1.8	1
18	Current-Lead Design for Cryocooled HTS Fault Current Limiters. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 2244-2247	1.8	1
17	Characteristics Analysis of a High-Tc Persistent Current System With Double Pancake Magnet Using Coated Conductor. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2007</b> , 17, 3282-3285	1.8	1
16	Design, fabrication and testing of a high-Tc superconducting power supply with the Bi-2223 load. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2002</b> , 12, 837-841	1.8	1
15	Analysis of the operational characteristics of a high-Tc superconducting power supply with the Bi-2223 pancake load. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2001</b> , 11, 4071-4077	1.8	1
14	Thermal and Electrical Characteristics of Hollow Former with Fault Current Limiting Function for Superconducting Power Cable. <i>IEEE Transactions on Power Delivery</i> , <b>2021</b> , 1-1	4.3	1
13	Numerical Analysis and Design of Damper Layer for MW-Class HTS Synchronous Wind Turbine Generator. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-5	1.8	0
12	Electromagnetic Design of a 15 MW-Class HTS Flux Switching Synchronous Generator considering Mechanical Stress of the Rotor Core. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2014</b> , 24, 1-5	1.8	0
11	Fabrication and Experimental Analysis of 6.6 kV/100 A Class Single-Phase Superconducting Fault Current Controller With Superconducting DC Reactor Coil. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-5	1.8	0
10	A Study on the Shape of Iron-Core for a Hybrid Electro-Magnetic Suspension System. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2012</b> , 22, 3600204-3600204	1.8	0
9	Effect of Crossover Turns in Double-Pancake Winding on Magnetic Field Homogeneity of HTS NMR Magnet. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2019</b> , 29, 1-5	1.8	
8	Design and Test of HTS Power Converting System With Multiple Magnets Considering Various Sequential Controls of Heater-Triggered Switches. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2016</b> , 26, 1-4	1.8	
7	A Study on an Algorithm for Finding Magnetic Center of an Asymmetric HTS Magnet With 3-Axis Mapper. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2013</b> , 23, 4900204-4900204	1.8	
6	HTS Wire Consumption Reduction in a Coil With an Actively Controllable Magnetic Core for a Fault Current Controller. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2013</b> , 23, 5604004-5604004	1.8	
5	Proof-of-Concept of a Millisecond-Scale Electromagnetic Levitator Using High-Temperature Superconducting Coils. <i>IEEE Transactions on Applied Superconductivity</i> , <b>2015</b> , 25, 1-4	1.8	

- 4 Experimental Test and Numerical Analysis to Estimate Permissible Transport Current Considering Protection of High-Tc Superconducting Tapes in Adiabatic Condition. *IEEE Transactions on Applied Superconductivity*, **2011**, 21, 1665-1669 1.8
- 3 Determination of heater triggering parameters of superconducting power supply with series-connected double-pancake load. *IEEE Transactions on Applied Superconductivity*, **2004**, 14, 650-653<sup>1.8</sup>
- 2 The short circuit analysis of integrated three phase superconducting fault current limiter with two phase superconducting circuits. *IEEE Transactions on Applied Superconductivity*, **2002**, 12, 854-858 1.8
- 1 Discharge Voltage Effects on High- $T_C$  Superconducting Tapes With Respect to Tensile Stress. *IEEE Transactions on Applied Superconductivity*, **2016**, 1-1 1.8