

Joelle Aubin

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/588885/publications.pdf>

Version: 2024-02-01

45
papers

2,139
citations

257450

24
h-index

233421

45
g-index

46
all docs

46
docs citations

46
times ranked

1899
citing authors

#	ARTICLE	IF	CITATIONS
1	Determination of mass transfer coefficients in high-pressure CO ₂ -H ₂ O flows in microcapillaries using a colorimetric method. <i>Chemical Engineering Science</i> , 2022, 248, 117161.	3.8	6
2	Design, performance characterization and applications of continuous oscillatory baffled reactors. <i>Chemical Engineering and Processing: Process Intensification</i> , 2022, 180, 108718.	3.6	8
3	Gas-liquid flow characterization and mass transfer study in a microreactor for oligomerization catalyst testing. <i>Chemical Engineering and Processing: Process Intensification</i> , 2021, 166, 108476.	3.6	1
4	Gas-liquid-liquid reactions: Contacting mechanisms and effective process technologies. <i>Catalysis Today</i> , 2020, 346, 46-57.	4.4	6
5	Predicting power consumption in continuous oscillatory baffled reactors. <i>Chemical Engineering Science</i> , 2020, 212, 115310.	3.8	13
6	Determination of mass transfer coefficients in high-pressure two-phase flows in capillaries using Raman spectroscopy. <i>Chemical Engineering Science</i> , 2020, 228, 115960.	3.8	12
7	Mixing performance in continuous oscillatory baffled reactors. <i>Chemical Engineering Science</i> , 2020, 219, 115600.	3.8	13
8	Simulation of micromixing in a T-mixer under laminar flow conditions. <i>Chemical Engineering Science</i> , 2020, 222, 115706.	3.8	24
9	Advances in Mixing Research: 16th European Conference on Mixing. <i>Chemical Engineering and Technology</i> , 2019, 42, 1544-1544.	1.5	2
10	Valorization of waste cooking oil based biodiesel for biolubricant production in a vertical pulsed column: Energy efficient process approach. <i>Energy</i> , 2019, 189, 116266.	8.8	22
11	Estimation of characteristic coagulation time based on Brownian coagulation theory and stability ratio modeling using electrokinetic measurements. <i>Chemical Engineering Journal</i> , 2019, 369, 818-827.	12.7	4
12	Hydrodynamics of CO ₂ -ethanol flow in a microchannel under elevated pressure. <i>Chemical Engineering Science</i> , 2018, 178, 297-311.	3.8	13
13	Hydrodynamics in a stirred tank in the transitional flow regime. <i>Chemical Engineering Research and Design</i> , 2018, 132, 865-880.	5.6	8
14	Optimization of methyl ester production from waste cooking oil in a batch tri-orifice oscillatory baffled reactor. <i>Fuel Processing Technology</i> , 2017, 167, 641-647.	7.2	44
15	Towards the design of an intensified coagulator. <i>Chemical Engineering and Processing: Process Intensification</i> , 2017, 121, 1-14.	3.6	2
16	Aggregation and breakup of acrylic latex particles inside millimetric scale reactors. <i>Chemical Engineering and Processing: Process Intensification</i> , 2017, 113, 65-73.	3.6	11
17	Hydrodynamics and mixing in continuous oscillatory flow reactors—Part I: Effect of baffle geometry. <i>Chemical Engineering and Processing: Process Intensification</i> , 2016, 108, 78-92.	3.6	29
18	Fast and inexpensive method for the fabrication of transparent pressure-resistant microfluidic chips. <i>Microfluidics and Nanofluidics</i> , 2016, 20, 1.	2.2	22

#	ARTICLE	IF	CITATIONS
19	Hydrodynamics and mixing in continuous oscillatory flow reactors—Part II: Characterisation methods. <i>Chemical Engineering and Processing: Process Intensification</i> , 2016, 102, 102-116.	3.6	24
20	Reactor Comparison for the Esterification of Fatty Acids from Waste Cooking Oil. <i>Chemical Engineering and Technology</i> , 2015, 38, 2161-2169.	1.5	13
21	On the combined effects of surface tension force calculation and interface advection on spurious currents within Volume of Fluid and Level Set frameworks. <i>Journal of Computational Physics</i> , 2015, 297, 611-636.	3.8	87
22	Intensification of waste cooking oil transformation by transesterification and esterification reactions in oscillatory baffled and microstructured reactors for biodiesel production. <i>Green Processing and Synthesis</i> , 2014, 3, 419-429.	3.4	18
23	Key role of temperature monitoring in interpretation of microwave effect on transesterification and esterification reactions for biodiesel production. <i>Bioresource Technology</i> , 2014, 161, 270-279.	9.6	57
24	Mixing and recirculation characteristics of gas—liquid Taylor flow in microreactors. <i>Chemical Engineering Research and Design</i> , 2013, 91, 2225-2234.	5.6	25
25	Intensified processes for FAME production from waste cooking oil: A technological review. <i>Chemical Engineering Journal</i> , 2013, 233, 201-223.	12.7	73
26	Hydrodynamics and Mass Transfer in Gas—Liquid Flows in Microreactors. <i>Chemical Engineering and Technology</i> , 2012, 35, 1346-1358.	1.5	147
27	Characteristics of liquid slugs in gas—liquid Taylor flow in microchannels. <i>Chemical Engineering Science</i> , 2012, 68, 640-649.	3.8	104
28	Hydrodynamics of gas—liquid Taylor flow in rectangular microchannels. <i>Microfluidics and Nanofluidics</i> , 2012, 12, 355-369.	2.2	86
29	Measuring the scale of segregation in mixing data. <i>Canadian Journal of Chemical Engineering</i> , 2011, 89, 1122-1138.	1.7	21
30	Current methods for characterising mixing and flow in microchannels. <i>Chemical Engineering Science</i> , 2010, 65, 2065-2093.	3.8	167
31	Effect of microchannel aspect ratio on residence time distributions and the axial dispersion coefficient. <i>Chemical Engineering and Processing: Process Intensification</i> , 2009, 48, 554-559.	3.6	55
32	A new definition of mixing and segregation: Three dimensions of a key process variable. <i>Chemical Engineering Research and Design</i> , 2009, 87, 633-647.	5.6	95
33	Impact of sampling method and scale on the measurement of mixing and the coefficient of variance. <i>AIChE Journal</i> , 2008, 54, 3068-3083.	3.6	25
34	Design of multiple impeller stirred tanks for the mixing of highly viscous fluids using CFD. <i>Chemical Engineering Science</i> , 2006, 61, 2913-2920.	3.8	45
35	Alternate Operating Methods for Improving the Performance of Continuous Stirred Tank Reactors. <i>Chemical Engineering Research and Design</i> , 2006, 84, 569-582.	5.6	33
36	Design of micromixers using CFD modelling. <i>Chemical Engineering Science</i> , 2005, 60, 2503-2516.	3.8	165

#	ARTICLE	IF	CITATIONS
37	Modeling turbulent flow in stirred tanks with CFD: the influence of the modeling approach, turbulence model and numerical scheme. <i>Experimental Thermal and Fluid Science</i> , 2004, 28, 431-445.	2.7	209
38	European Federation of Chemical Engineering Working Party on Mixing. <i>Chemical Engineering Research and Design</i> , 2004, 82, 1575-1579.	5.6	4
39	Gas-Liquid Mass Transfer. <i>Chemical Engineering Research and Design</i> , 2004, 82, 1589-1596.	5.6	33
40	Gas-Liquid Mass Transfer. <i>Chemical Engineering Research and Design</i> , 2004, 82, 1161-1168.	5.6	20
41	PIV measurements of flow in an aerated tank stirred by a down- and an up-pumping axial flow impeller. <i>Experimental Thermal and Fluid Science</i> , 2004, 28, 447-456.	2.7	91
42	Characterization of the Mixing Quality in Micromixers. <i>Chemical Engineering and Technology</i> , 2003, 26, 1262-1270.	1.5	114
43	Gas-Liquid Flow Generated by a Pitched-Blade Turbine: Particle Image Velocimetry Measurements and Computational Fluid Dynamics Simulations. <i>Industrial & Engineering Chemistry Research</i> , 2003, 42, 5318-5332.	3.7	53
44	Effect of Axial Agitator Configuration (Up-Pumping, Down-Pumping, Reverse Rotation) on Flow Patterns Generated in Stirred Vessels. <i>Chemical Engineering Research and Design</i> , 2001, 79, 845-856.	5.6	103
45	Blending of Newtonian and Shear-Thinning Fluids in a Tank Stirred with a Helical Screw Agitator. <i>Chemical Engineering Research and Design</i> , 2000, 78, 1105-1114.	5.6	31