## Tarun K Bhattacharyya

## List of Publications by Citations

 $\textbf{Source:} \ https://exaly.com/author-pdf/6080245/tarun-k-bhattacharyya-publications-by-citations.pdf$ 

Version: 2024-04-10

This document has been generated based on the publications and citations recorded by exaly.com. For the latest version of this publication list, visit the link given above.

The third column is the impact factor (IF) of the journal, and the fourth column is the number of citations of the article.

15 109 723 21 h-index g-index citations papers 2.6 139 4.93 947 L-index avg, IF ext. citations ext. papers

#	Paper	IF	Citations
109	Position Mutated Hierarchical Particle Swarm Optimization and its Application in Synthesis of Unequally Spaced Antenna Arrays. <i>IEEE Transactions on Antennas and Propagation</i> , <b>2012</b> , 60, 3174-3181	4.9	47
108	Characterization of diamond-like nanocomposite thin films grown by plasma enhanced chemical vapor deposition. <i>Journal of Applied Physics</i> , <b>2010</b> , 107, 124320	2.5	46
107	Microelectromechanical resonators for radio frequency communication applications. <i>Microsystem Technologies</i> , <b>2011</b> , 17, 1557-1580	1.7	40
106	MoS2-based nanosensors in biomedical and environmental monitoring applications. <i>Electrochimica Acta</i> , <b>2020</b> , 349, 136370	6.7	31
105	The evolution of graphene-based electronic devices. <i>International Journal of Smart and Nano Materials</i> , <b>2010</b> , 1, 201-223	3.6	29
104	Glassy carbon microneedles-new transdermal drug delivery device derived from a scalable C-MEMS process. <i>Microsystems and Nanoengineering</i> , <b>2018</b> , 4, 38	7.7	23
103	Influence of flow rate on different properties of diamond-like nanocomposite thin films grown by PECVD. <i>AIP Advances</i> , <b>2012</b> , 2, 022132	1.5	22
102	Deoxyribonucleic Acid Functionalized Carbon Nanotube Network as Humidity Sensors. <i>IEEE Sensors Journal</i> , <b>2013</b> , 13, 1806-1816	4	19
101	Lignocellulose based Bio-waste Materials derived Activated Porous Carbon as Superior Electrode Materials for High-Performance Supercapacitor. <i>Journal of Energy Storage</i> , <b>2021</b> , 34, 102229	7.8	19
100	Synthesis of ZnO nanosphere for picomolar level detection of bovine serum albumin. <i>IEEE Transactions on Nanobioscience</i> , <b>2015</b> , 14, 129-37	3.4	18
99	Opportunities in Device Scaling for 3-nm Node and Beyond: FinFET Versus GAA-FET Versus UFET. <i>IEEE Transactions on Electron Devices</i> , <b>2020</b> , 67, 2633-2638	2.9	18
98	A Compact Yagi-Uda Type Pattern Diversity Antenna Driven by CPW-Fed Pseudomonopole. <i>IEEE Transactions on Antennas and Propagation</i> , <b>2016</b> , 64, 25-32	4.9	18
97	Design, fabrication and characterization of high performance SOI MEMS piezoresistive accelerometers. <i>Microsystem Technologies</i> , <b>2015</b> , 21, 55-63	1.7	16
96	A high o/p resistance, wide swing and perfect current matching charge pump having switching circuit for PLL. <i>Microelectronics Journal</i> , <b>2013</b> , 44, 649-657	1.8	15
95	\$hbox{MnO}_{2}\$ Nanowire Embedded Hydrogen Peroxide Monopropellant MEMS Thruster. Journal of Microelectromechanical Systems, <b>2013</b> , 22, 406-417	2.5	15
94	Development of SU-8 hollow microneedles on a silicon substrate with microfluidic interconnects for transdermal drug delivery. <i>Journal of Micromechanics and Microengineering</i> , <b>2018</b> , 28, 105017	2	13
93	Design, modeling and FEM-based simulations of a 1-DoF MEMS bulk micromachined piezoresistive accelerometer. <i>Microsystem Technologies</i> , <b>2015</b> , 21, 2241-2258	1.7	13

## (2021-2018)

92	Design and Scalable Fabrication of Hollow SU-8 Microneedles for Transdermal Drug Delivery. <i>IEEE Sensors Journal</i> , <b>2018</b> , 18, 5635-5644	4	12
91	ZnO/ \$gamma\$ -Fe2O3 Heterostructure Toward High-Performance Acetone Sensing. <i>IEEE Sensors Journal</i> , <b>2019</b> , 19, 8576-8582	4	10
90	Ultra-Low Level Detection of L-Histidine Using Solution-Processed ZnO Nanorod on Flexible Substrate. <i>IEEE Transactions on Nanobioscience</i> , <b>2015</b> , 14, 634-40	3.4	10
89	Feasibility Studies on Nafion Membrane Actuated Micropump Integrated With Hollow Microneedles for Insulin Delivery Device. <i>Journal of Microelectromechanical Systems</i> , <b>2019</b> , 28, 987-996	2.5	9
88	Hierarchical ZnO Nanorods With Tailored Surface Defects for Enhanced Acetone Sensing. <i>IEEE Sensors Journal</i> , <b>2019</b> , 19, 3601-3608	4	9
87	Functionalized Gold Nanoparticles Decorated Reduced Graphene Oxide Sheets for Efficient Detection of Mercury. <i>IEEE Sensors Journal</i> , <b>2020</b> , 20, 5712-5719	4	9
86	. IEEE Sensors Journal, <b>2015</b> , 15, 2947-2950	4	8
85	Theoretical analysis and simulation of SU-8 microneedles for effective skin penetration and drug delivery <b>2015</b> ,		8
84	A Nonlinear Transient Analysis of Regenerative Frequency Dividers. <i>IEEE Transactions on Circuits and Systems I: Regular Papers</i> , <b>2007</b> , 54, 2646-2660	3.9	8
83	Synthesis of Bovine Serum Albumin Conjugated With ZnO Nanosphere for High-Speed Humidity Sensing Application. <i>IEEE Sensors Journal</i> , <b>2016</b> , 16, 1510-1517	4	8
82	Consideration of UFET Architecture for the 5 nm Node and Beyond Logic Transistor. <i>IEEE Journal of the Electron Devices Society</i> , <b>2018</b> , 6, 1129-1135	2.3	8
81	A 1.30.4-GHz 3.1-mW VCO Using Electro-Thermo- Mechanically Tunable Self-Assembled MEMS Inductor on HR Substrate. <i>IEEE Transactions on Microwave Theory and Techniques</i> , <b>2015</b> , 63, 459-469	4.1	7
80	Microelectromechanical system cantilever-based frequency doublers. <i>Journal of Intelligent Material Systems and Structures</i> , <b>2013</b> , 24, 240-246	2.3	7
79	Analysis of the Pull-In Phenomenon in Microelectromechanical Varactors 2012,		7
78	Design of a Low Power, High Speed Complementary Input Folded Regulated Cascode OTA for a Parallel Pipeline ADC <b>2011</b> ,		7
77	PSO-based output matching network for concurrent dual-band LNA <b>2010</b> ,		7
76	A fast automatic frequency and amplitude control LC-VCO circuit with noise filtering technique for a fractional-N PLL frequency synthesizer. <i>Microelectronics Journal</i> , <b>2016</b> , 52, 134-146	1.8	7
75	Flexible Room Temperature Ammonia Gas Sensor Based on Low-Temperature Tuning of Functional Groups in Grapheme. <i>IEEE Transactions on Electron Devices</i> , <b>2021</b> , 68, 3181-3188	2.9	7

74	Electroplated nickel based micro-machined disk resonators for high frequency applications. <i>Microsystem Technologies</i> , <b>2013</b> , 19, 525-535	1.7	6
73	. IEEE Transactions on Electron Devices, <b>2014</b> , 61, 400-407	2.9	6
72	Fully Concurrent Dual-Band LNA Operating in 900 MHz/2.4 GHz Bands for Multi-standard Wireless Receiver with Sub-2dB Noise Figure <b>2010</b> ,		6
71	7.95mW 2.4GHz Fully-Integrated CMOS Integer N Frequency Synthesizer <b>2007</b> ,		6
70	Causes of PLL spurs and their modeling. Analog Integrated Circuits and Signal Processing, 2019, 100, 639	9- <b>6</b> . <u>5</u> 2	5
69	A PFD and Charge Pump switching circuit to optimize the output phase noise of the PLL in 0.13-Jim CMOS <b>2015</b> ,		5
68	Efficient design technique for pulse swallow based fractional-N frequency divider 2015,		5
67	Parasitic aware impedance matching techniques for RF amplifiers. <i>Analog Integrated Circuits and Signal Processing</i> , <b>2012</b> , 70, 91-102	1.2	5
66	An experimental analysis of electrostatically vibrated array of polysilicon cantilevers. <i>Microsystem Technologies</i> , <b>2010</b> , 16, 2131-2145	1.7	5
65	Resistive Analysis of Scattering-Dependent Electrical Transport in Single-Wall Carbon-Nanotube Networks. <i>IEEE Transactions on Electron Devices</i> , <b>2020</b> , 67, 5676-5684	2.9	5
64	A fast and efficient constant loop bandwidth with proposed PFD and pulse swallow divider circuit in Ifractional-N PLL frequency synthesizer. <i>Microelectronics Journal</i> , <b>2017</b> , 61, 21-34	1.8	4
63	Selective Detection of Hg(II) Over Cd(II) and Pb(II) Ions by DNA Functionalized CNT. <i>IEEE Sensors Journal</i> , <b>2014</b> , 1-1	4	4
62	Electro-thermal analysis of an embedded boron diffused microheater for thruster applications. <i>Microsystem Technologies</i> , <b>2014</b> , 20, 23-33	1.7	4
61	Low power 120 KSPS 12bit SAR ADC with a novel switch control method for internal CDAC <b>2011</b> ,		4
60	A concurrent low-area dual band 0.9/2.4 GHz LNA in 0.13 pm RF CMOS technology for multi-band wireless receiver <b>2010</b> ,		4
59	A gain boosted fully concurrent dual-band interstage matched LNA operating in 900 MHz/2.4 GHz with sub-2dB Noise Figure <b>2010</b> ,		4
58	Spur reduction architecture for multiphase fractional PLLs. <i>IET Circuits, Devices and Systems</i> , <b>2019</b> , 13, 1169-1180	1.1	4
57	Emergence of two-dimensional nanomaterials-based breath sensors for non-invasive detection of diseases. <i>Sensors and Actuators A: Physical</i> , <b>2022</b> , 338, 113507	3.9	4

## (2011-2018)

56	Charge pump with reduced current mismatch for reference spur minimization in PLLs. <i>Analog Integrated Circuits and Signal Processing</i> , <b>2018</b> , 95, 209-221	1.2	3
55	Conjugation of Bovine Serum Albumin With ZnO Nanosphere-A Novel Approach for Ultra-Low Level Mercury Ion Detection. <i>IEEE Transactions on Nanobioscience</i> , <b>2016</b> , 15, 748-755	3.4	3
54	Reduction of Hole Injection Barrier Height at TCO/P Interface Using a-SiO:H Interlayer. <i>IEEE Journal of Photovoltaics</i> , <b>2018</b> , 8, 8-15	3.7	3
53	Mutated IWO Optimized 4-D Array for Femtocell Cognitive Radio. <i>IEEE Antennas and Wireless Propagation Letters</i> , <b>2017</b> , 16, 2614-2617	3.8	3
52	Design of PID controller for ultra-sensitive Nano-g resolution MEMS tunneling accelerometer <b>2014</b> ,		3
51	Spur suppression in frequency synthesizer using switched capacitor array 2012,		3
50	Optimized Stage Ratio of Tapered CMOS Inverters for Minimum Power and Mismatch Jitter Product <b>2010</b> ,		3
49	Pseudo Concurrent Quad-Band LNA Operating in 900 MHz/1.8 GHz and 900 MHz/2.4 GHz Bands for Multi-standard Wireless Receiver <b>2011</b> ,		3
48	Synthesis of thinned uniformly-excited time- modulated linear arrays using an improved invasive weed optimization algorithm <b>2012</b> ,		3
47	A technique to improve the linearization of frequencyWoltage characteristic of LC-VCO. <i>Analog Integrated Circuits and Signal Processing</i> , <b>2010</b> , 62, 253-257	1.2	3
46	ReviewMoSe2 Nanostructures and Related Electrodes for Advanced Supercapacitor Developments. <i>Journal of the Electrochemical Society</i> , <b>2022</b> , 169, 013503	3.9	3
45	Parasitic loss mitigation and photocurrent enhancement in amorphous silicon solar cells by using phosphorous-doped fluorinated pc-SiO:H back reflector. <i>Journal of Materials Science: Materials in Electronics</i> , <b>2018</b> , 29, 11104-11116	2.1	2
44	A Model of Spurs for Delta-Sigma Fractional PLLs <b>2019</b> ,		2
43	Structural comparison of SU-8 microtubes fabricated by direct laser writing and UV lithography <b>2017</b> ,		2
42	Prediction of reference spur in frequency synthesisers. IET Circuits, Devices and Systems, 2015, 9, 131-13	<b>39</b> 1.1	2
41	Spur reducing architecture of frequency synthesiser using switched capacitors. <i>IET Circuits, Devices and Systems</i> , <b>2014</b> , 8, 237-245	1.1	2
40	A High Speed, Low Jitter and Fast Acquisition CMOS Phase Frequency Detector for Charge Pump PLL. <i>Lecture Notes in Computer Science</i> , <b>2012</b> , 166-171	0.9	2
39	Low Offset, Low Noise, Variable Gain Interfacing Circuit with a Novel Scheme for Sensor Sensitivity and Offset Compensation for MEMS Based, Wheatstone Bridge Type, Resistive Smart Sensor <b>2011</b> ,		2

38	Design of a CMOS Bandgap Reference with Low Temperature Coefficient and High Power Supply Rejection Performance. <i>International Journal of VLSI Design &amp; Communication Systems</i> , <b>2011</b> , 2, 139-150	0.3	2
37	Comparative analysis of a variety of high-Q capacitively transduced bulk-mode microelectromechanical resonator geometries. <i>Microsystem Technologies</i> , <b>2011</b> , 17, 1361-1371	1.7	2
36	Pseudo Concurrent Quad-Band LNA Operating in 900 MHz/1.8 GHz and 900 MHz/2.4 GHz Bands for Multi-standard Wireless Receiver <b>2010</b> ,		2
35	Micromechanical radial-contour mode disk resonator for a CMOS-MEMS oscillator 2010,		2
34	Highly sensitive tunneling accelerometer for low actuation voltage operation 2010,		2
33	MEMS Piezoresistive Accelerometers. Springer Tracts in Mechanical Engineering, 2014, 19-34	0.3	2
32	A Miniaturized and Reconfigurable On-chip Slot Antenna for RFID Applications 2019,		2
31	Tuning Surface Defects of Mesoporous ZnO Nanorods for High Speed Humidity Sensing Application <b>2018</b> ,		2
30	A novel pulse swallow based frequency divider circuit for a phase-locked loops. <i>Analog Integrated Circuits and Signal Processing</i> , <b>2017</b> , 92, 55-69	1.2	1
29	Spurs in subsampling fractional PLLs. Analog Integrated Circuits and Signal Processing, 2019, 100, 621-632	<b>2</b> 1.2	1
28	Electrothermal Characteristics of Electroplated Ni-Based Tunable MEMS Inductor on High-Resistivity Substrate With Displacement Actuator. <i>IEEE Magnetics Letters</i> , <b>2015</b> , 6, 1-4	1.6	1
27	A 7.1-GHz 0.7-mW Programmable Counter With Fast EOC Generation in 65-nm CMOS. <i>IEEE Transactions on Circuits and Systems II: Express Briefs</i> , <b>2020</b> , 67, 2397-2401	3.5	1
26	Implementation of a digital Imodulator and programmable prescaler divider circuit for a fractional-N PLL <b>2016</b> ,		1
25	Fabrication of BSA-MoS2 Bio-Composite Electronic Devices for Low-Power and Fast-Response Chemical Sensor. <i>IEEE Sensors Journal</i> , <b>2018</b> , 1-1	4	1
24	Phase noise analysis of proposed PFD and CP switching circuit and its advantages over various PFD/CP switching circuits in phase-locked loops. <i>The Integration VLSI Journal</i> , <b>2018</b> , 63, 115-129	1.4	1
23	Implementation of dynamic element matching DAC and its use for noise cancellation in [] fractional-N PLL <b>2014</b> ,		1
22	A 55-mW 300MS/s 8-bit CMOS Parallel Pipeline ADC <b>2012</b> ,		1
21	A comparative study between a micromechanical cantilever resonator and MEMS-based passives for band-pass filtering application <b>2011</b> ,		1

20	A CMOS bandgap reference with high PSRR and improved temperature stability for system-on-chip applications <b>2011</b> ,		1
19	Design of low power parallel pipeline ADC in 180nm standard CMOS process <b>2011</b> ,		1
18	A monopropellant hydrazine MEMS thruster for attitude control of nanosatellites 2010,		1
17	Use of TSK type fuzzy system based fitness function approximation for efficient optimization of low-profile wideband diversity PIFA by PSO <b>2009</b> ,		1
16	Broad band behavioral modeling of on-chip RF inductors and transformers. <i>Microwave and Optical Technology Letters</i> , <b>2007</b> , 49, 2212-2216	1.2	1
15	Reduced graphene oxide nanosheets for selective picomolar detection of Bovine serum albumin. <i>IEEE Transactions on Nanobioscience</i> , <b>2021</b> , PP,	3.4	1
14	Microwave synthesized manganese vanadium oxide: High performing electrode material for energy storage. <i>Materials Today: Proceedings</i> , <b>2021</b> , 50, 74-74	1.4	1
13	A constant loop bandwidth in delta sigma fractional-N PLL frequency synthesizer with phase noise cancellation. <i>The Integration VLSI Journal</i> , <b>2019</b> , 65, 175-188	1.4	1
12	A Package-Cognizant CMOS On-chip Antenna for 2.4-GHz Free-space and Implantable Applications. <i>IEEE Transactions on Antennas and Propagation</i> , <b>2021</b> , 1-1	4.9	1
11	Mixed-Phase nc-SiOX:H Interlayer to Improve Light Trapping and Shunt Quenching in a-Si:H Solar Cell. <i>IEEE Journal of Photovoltaics</i> , <b>2019</b> , 9, 18-25	3.7	O
10	Pseudo Electron Injection in Amine-Modified MoSEBased Sensor for Humidity Monitoring. <i>IEEE Transactions on Electron Devices</i> , <b>2021</b> , 68, 5173-5178	2.9	О
9	Correction on <b>E</b> ffect of Temperature Variation and Packaging on SOI MEMS Inductor With DRIE Trench on Low-Resistivity Substratel[Feb 14 400-407]. <i>IEEE Transactions on Electron Devices</i> , <b>2015</b> , 62, 236-236	2.9	
8	Spur reduction in frequency synthesizer with an array of switched capacitors. <i>International Journal of Circuit Theory and Applications</i> , <b>2015</b> , 43, 1815-1831	2	
7	A Wide Tunable Hysteresis CML Delay Cell for High Frequency. <i>IEEE Microwave and Wireless Components Letters</i> , <b>2020</b> , 30, 641-644	2.6	
6	Low-Field Transport in Bovine Serum Albumin Conjugated ZnO Nanoparticle Networks. <i>IEEE Electron Device Letters</i> , <b>2016</b> , 37, 100-102	4.4	
5	A top-down design methodology of MEMS varactor for RF applications based on a substrate-induced capacitive model. <i>Microsystem Technologies</i> , <b>2011</b> , 17, 1589-1598	1.7	
4	Design and Analysis of a CMOS Moore Fractal MOM Capacitor With an Application to an RF Active Image Reject Filter. <i>IEEE Transactions on Electron Devices</i> , <b>2021</b> , 1-7	2.9	
3	Power and area-efficient static current mode logic frequency divider in 180-nm complementary metal-oxide-semiconductor technology. <i>International Journal of Circuit Theory and Applications</i> , <b>2021</b> , 49, 2396	2	

Semi analytical model for electrical transport in single wall carbon nanotube thin film transistors. Solid-State Electronics, **2021**, 180, 107988

1.7

Synthesis of BSA-Conjugated ZnO Nanoparticle for Pb2+ Sensing Applications. *IETE Journal of Research*,1-5

0.9