

# Xingyang He

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/6194537/publications.pdf>

Version: 2024-02-01

71  
papers

2,794  
citations

185998  
28  
h-index

182168  
51  
g-index

71  
all docs

71  
docs citations

71  
times ranked

905  
citing authors

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 1  | Effect of organic alkali on hydration of GGBS-FA blended cementitious material activated by sodium carbonate. <i>Ceramics International</i> , 2022, 48, 1611-1621.  | 2.3 | 8         |
| 2  | One-step synthesis of nanoscale anhydrous calcium sulfate whiskers: direct conversion of calcium carbonate by mixed acid with microemulsion method. <i>Journal of Nanoparticle Research</i> , 2022, 24, 1.                    | 0.8 | 6         |
| 3  | One-pot synthesis of polydopamine/Ag microspheres through microemulsion environment and its methylene blue removal application. <i>Journal of Polymer Research</i> , 2022, 29, 1.   | 1.2 | 6         |
| 4  | Research on mechanical-activated nanoscale bentonite and surface aging behavior of its modified asphalt. <i>Construction and Building Materials</i> , 2022, 321, 126356.  | 3.2 | 11        |
| 5  | Mechanical performance, hydration characteristics and microstructures of high volume blast furnace ferronickel slag cement mortar by wet grinding activation. <i>Construction and Building Materials</i> , 2022, 320, 126148. | 3.2 | 16        |
| 6  | Enhancement of compressive strength of high-volume fly ash cement paste by wet grinded cement: Towards low carbon cementitious materials. <i>Construction and Building Materials</i> , 2022, 323, 126458.                     | 3.2 | 18        |
| 7  | Improvement in flexural strength of Portland cement by lamellar structured montmorillonite. <i>Construction and Building Materials</i> , 2022, 329, 127208.   | 3.2 | 6         |
| 8  | Nano C-S-H seeds prepared from ground granulated blast-furnace slag-carbide slag and its application in Portland cement. <i>Construction and Building Materials</i> , 2022, 329, 127204.                                      | 3.2 | 13        |
| 9  | Research on the properties of wet-ground waste limestone powder as foam stabilizer in foamed concrete. <i>Construction and Building Materials</i> , 2022, 329, 127203.  | 3.2 | 17        |
| 10 | Sustainable clinker-free solid waste binder produced from wet-ground granulated blast-furnace slag, phosphogypsum and carbide slag. <i>Construction and Building Materials</i> , 2022, 330, 127218.                           | 3.2 | 67        |
| 11 | Light-weight carbon fiber/silver-coated hollow glass spheres/epoxy composites as highly effective electromagnetic interference shielding material. <i>Journal of Reinforced Plastics and Composites</i> , 2022, 41, 497-508.  | 1.6 | 3         |
| 12 | Compressive strength and permeability of steam-cured mortar incorporating high volume fly ash with different activation degrees by wet milling. <i>Journal of Building Engineering</i> , 2022, 56, 104767.                    | 1.6 | 0         |
| 13 | Hydration and Compressive Strength of Activated Blast-Furnace Slag“Steel Slag with Na <sub>2</sub> CO <sub>3</sub> . <i>Materials</i> , 2022, 15, 4375.   | 1.3 | 4         |
| 14 | Improving the mechanical property and water resistance of ½-hemihydrate phosphogypsum by incorporating ground blast-furnace slag and steel slag. <i>Construction and Building Materials</i> , 2022, 344, 128265.              | 3.2 | 11        |
| 15 | The thermal performances of cement-based materials with different types of microencapsulated phase change materials. <i>Construction and Building Materials</i> , 2022, 345, 128388.  | 3.2 | 9         |
| 16 | Effect of steam curing on compressive strength and microstructure of high volume ultrafine fly ash cement mortar. <i>Construction and Building Materials</i> , 2021, 266, 120894.   | 3.2 | 77        |
| 17 | Effect of wet grinded lithium slag on compressive strength and hydration of sulphoaluminate cement system. <i>Construction and Building Materials</i> , 2021, 267, 120465.  | 3.2 | 66        |
| 18 | Nano particles prepared from hardened cement paste by wet grinding and its utilization as an accelerator in Portland cement. <i>Journal of Cleaner Production</i> , 2021, 283, 124632.  | 4.6 | 29        |

| #  | ARTICLE  | IF  | CITATIONS |
|----|--|-----|-----------|
| 19 | Laboratory Evaluation for Utilization of Phosphogypsum through Carbide Slag Highly-Effective Activating Anhydrous Phosphogypsum. Journal Wuhan University of Technology, Materials Science Edition, 2021, 36, 392-399. | 0.4 | 6         |
| 20 | Improving durability of heat-cured high volume fly ash cement mortar by wet-grinding activation. Construction and Building Materials, 2021, 289, 123157.   | 3.2 | 33        |
| 21 | Effect of wet-grinding steel slag on the properties of Portland cement: An activated method and rheology analysis. Construction and Building Materials, 2021, 286, 122823.   | 3.2 | 61        |
| 22 | An accelerator prepared from waste concrete recycled powder and its effect on hydration of cement-based materials. Construction and Building Materials, 2021, 296, 123767.   | 3.2 | 51        |
| 23 | A comparative study on concrete slurry waste: performance optimization from the wet-milling process. Materials and Structures/Materiaux Et Constructions, 2021, 54, 1.   | 1.3 | 7         |
| 24 | The influence of wet ground fly ash on the performance of foamed concrete. Construction and Building Materials, 2021, 304, 124676.   | 3.2 | 25        |
| 25 | Potential usage of porous autoclaved aerated concrete waste as eco-friendly internal curing agent for shrinkage compensation. Journal of Cleaner Production, 2021, 320, 128894.  | 4.6 | 15        |
| 26 | Mechanical and microstructure development of portland cement modified with micro-encapsulated phase change materials. Construction and Building Materials, 2021, 304, 124652.  | 3.2 | 9         |
| 27 | Green reaction-type nucleation seed accelerator prepared from coal fly ash ground in water environment. Construction and Building Materials, 2021, 306, 124840.  | 3.2 | 14        |
| 28 | Heat-cured cement-based composites with wet-grinded fly ash and carbide slag slurry: Hydration, compressive strength and carbonation. Construction and Building Materials, 2021, 307, 124916.                          | 3.2 | 12        |
| 29 | Preparation of nano cement particles by wet-grinding and its effect on hydration of cementitious system. Construction and Building Materials, 2021, 307, 125051.   | 3.2 | 9         |
| 30 | Eco-friendly UHPC prepared from high volume wet-grinded ultrafine GGBS slurry. Construction and Building Materials, 2021, 308, 125057.   | 3.2 | 60        |
| 31 | Preparation of nano-kaolin by wet-grinding process and its application as accelerator in Portland cement. Journal of Building Engineering, 2021, 44, 103401.   | 1.6 | 1         |
| 32 | New treatment technology: The use of wet-milling concrete slurry waste to substitute cement. Journal of Cleaner Production, 2020, 242, 118347.   | 4.6 | 67        |
| 33 | Shrinkage properties and microstructure of high volume ultrafine phosphorous slag blended cement mortars with superabsorbent polymer. Journal of Building Engineering, 2020, 29, 101121.                               | 1.6 | 17        |
| 34 | Preparation for micro-lithium slag via wet grinding and its application as accelerator in Portland cement. Journal of Cleaner Production, 2020, 250, 119528.   | 4.6 | 107       |
| 35 | Feasibility of incorporating autoclaved aerated concrete waste for cement replacement in sustainable building materials. Journal of Cleaner Production, 2020, 250, 119455.   | 4.6 | 112       |
| 36 | Utilization of Carbide Slag by Wet Grinding as an Accelerator in Calcium Sulfoaluminate Cement. Materials, 2020, 13, 4526.   | 1.3 | 16        |

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 37 | Wet-milling disposal of autoclaved aerated concrete demolition waste " A comparison with classical supplementary cementitious materials. <i>Advanced Powder Technology</i> , 2020, 31, 3736-3746.                                       | 2.0 | 20        |
| 38 | Nano-carbide slag seed as a new type accelerator for Portland cement. <i>Materials Letters</i> , 2020, 278, 128464.   | 1.3 | 16        |
| 39 | Nano-treatment of Autoclaved Aerated Concrete Waste and Its Usage in Cleaner Building Materials. <i>Journal Wuhan University of Technology, Materials Science Edition</i> , 2020, 35, 786-793.  | 0.4 | 8         |
| 40 | Ultra-fine slag activated by sodium carbonate at ambient temperature. <i>Construction and Building Materials</i> , 2020, 264, 120695.   | 3.2 | 19        |
| 41 | Utilization of carbide slag-granulated blast furnace slag system by wet grinding as low carbon cementitious materials. <i>Construction and Building Materials</i> , 2020, 249, 118763.  | 3.2 | 70        |
| 42 | Effects of wet-grinded superfine waste glass on the fresh properties and reaction characteristic of cement pastes. <i>Construction and Building Materials</i> , 2020, 247, 118593.  | 3.2 | 22        |
| 43 | Preparation of ultrafine fly ash by wet grinding and its utilization for immobilizing chloride ions in cement paste. <i>Waste Management</i> , 2020, 113, 456-468.  | 3.7 | 21        |
| 44 | Microemulsion synthesis of anhydrous calcium sulfate nanowhiskers with calcium acetate solution and its surface structure stable and crystal phase evolution after modification. <i>Journal of Nanoparticle Research</i> , 2020, 22, 1. | 0.8 | 5         |
| 45 | Mechanical Properties and Microscopic Mechanism of Coral Sand-Cement Mortar. <i>Advances in Materials Science and Engineering</i> , 2020, 2020, 1-11.   | 1.0 | 4         |
| 46 | Fluid Permeability of Ground Steel Slag-Blended Composites Evaluated by Pore Structure. <i>Advances in Materials Science and Engineering</i> , 2020, 2020, 1-14.  | 1.0 | 0         |
| 47 | Evaluation Method of Relative Humidity Changes in Below-Grade Concrete Structure Space Depending on Different Waterproofing Material and Installation Method. <i>Materials</i> , 2020, 13, 742.   | 1.3 | 0         |
| 48 | Compressive strength and hydration process of ground granulated blast furnace slag-waste gypsum system managed by wet grinding. <i>Construction and Building Materials</i> , 2019, 228, 116777.   | 3.2 | 47        |
| 49 | Micro-environment regulation synthesis of calcium sulfate nanoparticles and its water removal application. <i>Materials Research Express</i> , 2019, 6, 1050b8.   | 0.8 | 4         |
| 50 | Eco-friendly treatment of low-calcium coal fly ash for high pozzolanic reactivity: A step towards waste utilization in sustainable building material. <i>Journal of Cleaner Production</i> , 2019, 238, 117962.                         | 4.6 | 170       |
| 51 | Segmented fractal pore structure covering nano- and micro-ranges in cementing composites produced with GGBS. <i>Construction and Building Materials</i> , 2019, 225, 1170-1182.   | 3.2 | 57        |
| 52 | Compressive strength and hydration process of wet-grinded granulated blast-furnace slag activated by sodium sulfate and sodium carbonate. <i>Cement and Concrete Composites</i> , 2019, 97, 387-398.                                    | 4.6 | 125       |
| 53 | Microemulsion Synthesis of Nanosized Calcium Sulfate Hemihydrate and Its Morphology Control by Different Surfactants. <i>ACS Omega</i> , 2019, 4, 9552-9556.  | 1.6 | 14        |
| 54 | Compressive strength and hydration of high-volume wet-grinded coal fly ash cementitious materials. <i>Construction and Building Materials</i> , 2019, 206, 248-260.   | 3.2 | 62        |

| #  | ARTICLE   | IF  | CITATIONS |
|----|---|-----|-----------|
| 55 | Effect of organic alkali on compressive strength and hydration of wet-grinded granulated blast-furnace slag containing Portland cement. <i>Construction and Building Materials</i> , 2019, 206, 10-18.                      | 3.2 | 21        |
| 56 | Efficiency of wet-grinding on the mechano-chemical activation of granulated blast furnace slag (GBFS). <i>Construction and Building Materials</i> , 2019, 199, 185-193.   | 3.2 | 45        |
| 57 | Effects of nano-SiO <sub>2</sub> on early strength and microstructure of steam-cured high volume fly ash cement system. <i>Construction and Building Materials</i> , 2019, 194, 350-359.                                    | 3.2 | 173       |
| 58 | Pore structure of affected zone around saturated and large superabsorbent polymers in cement paste. <i>Cement and Concrete Composites</i> , 2019, 97, 54-67.  | 4.6 | 91        |
| 59 | Self-hydration characteristics of ground granulated blast-furnace slag (GGBFS) by wet-grinding treatment. <i>Construction and Building Materials</i> , 2018, 167, 96-105.   | 3.2 | 59        |
| 60 | Effect of hydroxypropyl-methyl cellulose ether on rheology of cement paste plasticized by polycarboxylate superplasticizer. <i>Construction and Building Materials</i> , 2018, 160, 341-350.                                | 3.2 | 105       |
| 61 | Pore structure evaluation of cementing composites blended with coal by-products: Calcined coal gangue and coal fly ash. <i>Fuel Processing Technology</i> , 2018, 181, 75-90.   | 3.7 | 120       |
| 62 | Effect of Steel Slag and Granulated Blast-furnace Slag on the Mechanical Strength and Pore Structure of Cement Composites. <i>Journal Wuhan University of Technology, Materials Science Edition</i> , 2018, 33, 1186-1192.  | 0.4 | 5         |
| 63 | Effect of triisopropanolamine on compressive strength and hydration of steaming-cured cement-fly ash paste. <i>Construction and Building Materials</i> , 2018, 192, 836-845.  | 3.2 | 46        |
| 64 | The effect of ultrahigh volume ultrafine blast furnace slag on the properties of cement pastes. <i>Construction and Building Materials</i> , 2018, 189, 438-447.  | 3.2 | 37        |
| 65 | Utilization of lithium slag by wet-grinding process to improve the early strength of sulphoaluminate cement paste. <i>Journal of Cleaner Production</i> , 2018, 205, 536-551.   | 4.6 | 182       |
| 66 | Physico-chemical Characteristics of Wet-milled Ultrafine-granulated Phosphorus Slag as a Supplementary Cementitious Material. <i>Journal Wuhan University of Technology, Materials Science Edition</i> , 2018, 33, 625-633. | 0.4 | 34        |
| 67 | Synthesis of $\frac{1}{2}$ -hemihydrate gypsum from cleaner phosphogypsum. <i>Journal of Cleaner Production</i> , 2018, 195, 396-405.   | 4.6 | 89        |
| 68 | Effect of sodium gluconate on dispersion of polycarboxylate superplasticizer with different grafting density in side chain. <i>Journal of Industrial and Engineering Chemistry</i> , 2017, 55, 91-100.                      | 2.9 | 120       |
| 69 | Effect of silica fume on the thaumasite form of sulfate attack on cement-based materials. <i>Journal Wuhan University of Technology, Materials Science Edition</i> , 2017, 32, 1108-1114.                                   | 0.4 | 6         |
| 70 | Use of different barium salts to inhibit the thaumasite form of sulfate attack in cement-based materials. <i>Journal Wuhan University of Technology, Materials Science Edition</i> , 2016, 31, 361-366.                     | 0.4 | 5         |
| 71 | Influence of annealing on the structure of silica glass. <i>Journal Wuhan University of Technology, Materials Science Edition</i> , 2013, 28, 902-906.  | 0.4 | 3         |