

Wolfgang Gindl-Altmutter

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/6331296/publications.pdf>

Version: 2024-02-01

172
papers

8,593
citations

53794

45
h-index

51608

86
g-index

177
all docs

177
docs citations

177
times ranked

7510
citing authors

#	ARTICLE	IF	CITATIONS
1	Review: current international research into cellulose nanofibres and nanocomposites. Journal of Materials Science, 2010, 45, 1-33.	3.7	2,042
2	All-cellulose nanocomposite. Polymer, 2005, 46, 10221-10225.	3.8	286
3	A comparison of different methods to calculate the surface free energy of wood using contact angle measurements. Colloids and Surfaces A: Physicochemical and Engineering Aspects, 2001, 181, 279-287.	4.7	238
4	Surface chemical functionalization of cellulose nanocrystals by 3-aminopropyltriethoxysilane. International Journal of Biological Macromolecules, 2018, 106, 1288-1296.	7.5	214
5	Sugar beet cellulose nanofibril-reinforced composites. Cellulose, 2007, 14, 419-425.	4.9	210
6	Mechanical properties of spruce wood cell walls by nanoindentation. Applied Physics A: Materials Science and Processing, 2004, 79, 2069-2073.	2.3	205
7	Mechanical properties of adhesives for bonding wood – A review. International Journal of Adhesion and Adhesives, 2013, 45, 32-41.	2.9	188
8	The influence of temperature on latewood lignin content in treeline Norway spruce compared with maximum density and ring width. Trees - Structure and Function, 2000, 14, 409-414.	1.9	160
9	Technological performance of formaldehyde-free adhesive alternatives for particleboard industry. International Journal of Adhesion and Adhesives, 2019, 94, 99-131.	2.9	159
10	Tensile properties of cellulose acetate butyrate composites reinforced with bacterial cellulose. Composites Science and Technology, 2004, 64, 2407-2413.	7.8	145
11	The significance of the elastic modulus of wood cell walls obtained from nanoindentation measurements. Composites Part A: Applied Science and Manufacturing, 2004, 35, 1345-1349.	7.6	134
12	Cell-wall hardness and Young's modulus of melamine-modified spruce wood by nano-indentation. Composites Part A: Applied Science and Manufacturing, 2002, 33, 1141-1145.	7.6	114
13	Impregnation of softwood cell walls with melamine-formaldehyde resin. Bioresource Technology, 2003, 87, 325-330.	9.6	106
14	Mechanical Properties of Regenerated Cellulose Fibres for Composites. Macromolecular Symposia, 2006, 244, 119-125.	0.7	106
15	Adhesive penetration of wood cell walls investigated by scanning thermal microscopy (SThM). Holzforschung, 2008, 62, 91-98.	1.9	92
16	Mechanical characterisation of wood-adhesive interphase cell walls by nanoindentation. Holzforschung, 2006, 60, 429-433.	1.9	91
17	Cellulose nanofibrils as filler for adhesives: effect on specific fracture energy of solid wood-adhesive bonds. Cellulose, 2011, 18, 1227-1237.	4.9	91
18	The Relationship between near Infrared Spectra of Radial Wood Surfaces and Wood Mechanical Properties. Journal of Near Infrared Spectroscopy, 2001, 9, 255-261.	1.5	87

#	ARTICLE	IF	CITATIONS
19	Actual versus apparent within cell wall variability of nanoindentation results from wood cell walls related to cellulose microfibril angle. <i>Journal of Materials Science</i> , 2009, 44, 4399-4406.	3.7	83
20	The interphase in phenol-formaldehyde and polymeric methylene di-phenyl-di-isocyanate glue lines in wood. <i>International Journal of Adhesion and Adhesives</i> , 2004, 24, 279-286.	2.9	79
21	Improving the mechanical resistance of waterborne wood coatings by adding cellulose nanofibres. <i>Reactive and Functional Polymers</i> , 2014, 85, 214-220.	4.1	77
22	Using UV-Microscopy to Study Diffusion of Melamine-Urea-Formaldehyde Resin in Cell Walls of Spruce Wood. <i>Holzforschung</i> , 2002, 56, 103-107.	1.9	76
23	Lignification of spruce tracheid secondary cell walls related to longitudinal hardness and modulus of elasticity using nano-indentation. <i>Canadian Journal of Botany</i> , 2002, 80, 1029-1033.	1.1	74
24	Particle Board and Oriented Strand Board Prepared with Nanocellulose-Reinforced Adhesive. <i>Journal of Nanomaterials</i> , 2012, 2012, 1-8.	2.7	72
25	Anisotropy of the modulus of elasticity in regenerated cellulose fibres related to molecular orientation. <i>Polymer</i> , 2008, 49, 792-799.	3.8	70
26	Drawing of self-reinforced cellulose films. <i>Journal of Applied Polymer Science</i> , 2007, 103, 2703-2708.	2.6	66
27	Effect of addition of microfibrillated cellulose to urea-formaldehyde on selected adhesive characteristics and distribution in particle board. <i>Cellulose</i> , 2016, 23, 571-580.	4.9	65
28	Application of surface chemical functionalized cellulose nanocrystals to improve the performance of UF adhesives used in wood based composites - MDF type. <i>Carbohydrate Polymers</i> , 2019, 206, 11-20.	10.2	65
29	Effects of thermal modification on the adhesion between spruce wood (<i>Picea abies</i> Karst.) and a thermoplastic polymer. <i>European Journal of Wood and Wood Products</i> , 2006, 64, 373-376.	2.9	64
30	Elastic properties of adhesive polymers. II. Polymer films and bond lines by means of nanoindentation. <i>Journal of Applied Polymer Science</i> , 2006, 102, 1234-1239.	2.6	62
31	The strength and stiffness of oriented wood and cellulose-fibre materials: A review. <i>Progress in Materials Science</i> , 2022, 125, 100916.	32.8	61
32	All-cellulose composites prepared from flax and lyocell fibres compared to epoxy matrix composites. <i>Composites Science and Technology</i> , 2012, 72, 1304-1309.	7.8	60
33	Direct measurement of strain distribution along a wood bond line. Part 2: Effects of adhesive penetration on strain distribution. <i>Holzforschung</i> , 2005, 59, 307-310.	1.9	58
34	Elastic properties of adhesive polymers. I. Polymer films by means of electronic speckle pattern interferometry. <i>Journal of Applied Polymer Science</i> , 2007, 103, 3936-3939.	2.6	58
35	Changes in the Molecular Orientation and Tensile Properties of Uniaxially Drawn Cellulose Films. <i>Biomacromolecules</i> , 2006, 7, 3146-3150.	5.4	57
36	Artificial weathering of wood surfaces modified by melamine formaldehyde resins. <i>European Journal of Wood and Wood Products</i> , 2006, 64, 198-203.	2.9	57

#	ARTICLE	IF	CITATIONS
37	Survey of selected adhesive bonding properties of nine European softwood and hardwood species. <i>European Journal of Wood and Wood Products</i> , 2016, 74, 809-819.	2.9	57
38	Axial compression strength of Norway spruce related to structural variability and lignin content. <i>Composites Part A: Applied Science and Manufacturing</i> , 2002, 33, 1623-1628.	7.6	55
39	Comparing Mechanical Properties of Normal and Compression Wood in Norway Spruce: The Role of Lignin in Compression Parallel to the Grain. <i>Holzforschung</i> , 2002, 56, 395-401.	1.9	54
40	Structure and properties of a pulp fibre-reinforced composite with regenerated cellulose matrix. <i>Applied Physics A: Materials Science and Processing</i> , 2006, 83, 19-22.	2.3	54
41	Lignocellulose Nanofiber-Reinforced Polystyrene Produced from Composite Microspheres Obtained in Suspension Polymerization Shows Superior Mechanical Performance. <i>ACS Applied Materials & Interfaces</i> , 2016, 8, 13520-13525.	8.0	54
42	Structural changes during tensile testing of an all-cellulose composite by in situ synchrotron X-ray diffraction. <i>Composites Science and Technology</i> , 2006, 66, 2639-2647.	7.8	52
43	Direct measurement of strain distribution along a wood bond line. Part 1: Shear strain concentration in a lap joint specimen by means of electronic speckle pattern interferometry. <i>Holzforschung</i> , 2005, 59, 300-306.	1.9	50
44	Identification of stiffness tensor components of wood cell walls by means of nanoindentation. <i>Composites Part A: Applied Science and Manufacturing</i> , 2011, 42, 2101-2109.	7.6	48
45	Dry, hydrophobic microfibrillated cellulose powder obtained in a simple procedure using alkyl ketene dimer. <i>Cellulose</i> , 2016, 23, 1189-1197.	4.9	47
46	Reinforcement of polycaprolactone with microfibrillated lignocellulose. <i>Industrial Crops and Products</i> , 2016, 93, 302-308.	5.2	46
47	A General Aqueous Silanization Protocol to Introduce Vinyl, Mercapto or Azido Functionalities onto Cellulose Fibers and Nanocelluloses. <i>Molecules</i> , 2018, 23, 1427.	3.8	46
48	Comparison of UV and confocal Raman microscopy to measure the melamine-formaldehyde resin content within cell walls of impregnated spruce wood. <i>Holzforschung</i> , 2005, 59, 210-213.	1.9	44
49	Nanoindentation mapping of a wood-adhesive bond. <i>Applied Physics A: Materials Science and Processing</i> , 2007, 88, 371-375.	2.3	44
50	Compatibility between Cellulose and Hydrophobic Polymer Provided by Microfibrillated Lignocellulose. <i>ChemSusChem</i> , 2015, 8, 87-91.	6.8	44
51	Comparing dry bond strength of spruce and beech wood glued with different adhesives by means of scarf- and lap joint testing method. <i>European Journal of Wood and Wood Products</i> , 2006, 64, 269-271.	2.9	43
52	Biomechanics of a branch stem junction in softwood. <i>Trees - Structure and Function</i> , 2006, 20, 643-648.	1.9	42
53	Wet esterification of never-dried cellulose: a simple process to surface-acetylated cellulose nanofibers. <i>Green Chemistry</i> , 2020, 22, 5605-5609.	9.0	41
54	Superhydrophobic coatings on wood made of plant oil and natural wax. <i>Progress in Organic Coatings</i> , 2020, 148, 105891.	3.9	38

#	ARTICLE	IF	CITATIONS
55	Using a water-soluble melamine-formaldehyde resin to improve the hardness of Norway spruce wood. <i>Journal of Applied Polymer Science</i> , 2004, 93, 1900-1907.	2.6	36
56	Changes in microfibril angle in cyclically deformed dry coir fibers studied by in-situ synchrotron X-ray diffraction. <i>Journal of Materials Science</i> , 2008, 43, 350-356.	3.7	35
57	Cellulose in Never-Dried Gel Oriented by an AC Electric Field. <i>Biomacromolecules</i> , 2009, 10, 1315-1318.	5.4	35
58	Nanoindentation of regenerated cellulose fibres. <i>Cellulose</i> , 2006, 13, 1-7.	4.9	33
59	Variability in surface polarity of wood by means of AFM adhesion force mapping. <i>Colloids and Surfaces A: Physicochemical and Engineering Aspects</i> , 2014, 457, 82-87.	4.7	33
60	Mechanism of stress transfer in a single wood fibre-LDPE composite by means of electronic laser speckle interferometry. <i>Composites Part A: Applied Science and Manufacturing</i> , 2006, 37, 1406-1412.	7.6	32
61	Strain hardening in regenerated cellulose fibres. <i>Composites Science and Technology</i> , 2006, 66, 2049-2053.	7.8	32
62	Reduced polarity and improved dispersion of microfibrillated cellulose in poly(lactic-acid) provided by residual lignin and hemicellulose. <i>Journal of Materials Science</i> , 2017, 52, 60-72.	3.7	32
63	Lignin-based multiwall carbon nanotubes. <i>Composites Part A: Applied Science and Manufacturing</i> , 2019, 121, 175-179.	7.6	32
64	Nano meets the sheet: adhesive-free application of nanocellulosic suspensions in paper conservation. <i>Heritage Science</i> , 2017, 5, .	2.3	31
65	Comparison of four technical lignins as a resource for electrically conductive carbon particles. <i>BioResources</i> , 2019, 14, 1091-1109.	1.0	31
66	Characteristics of Spruce [<i>Picea abies</i> (L.) Karst] Latewood Formed under Abnormally Low Temperatures. <i>Holzforschung</i> , 2000, 54, 9-11.	1.9	30
67	Micromechanical properties of the interphase in pMDI and UF bond lines. <i>Wood Science and Technology</i> , 2012, 46, 611-620.	3.2	30
68	Overview of White-Rot Research: Where We are Today. <i>ACS Symposium Series</i> , 2003, , 73-96.	0.5	28
69	Measurement of strain distribution in timber finger joints. <i>Wood Science and Technology</i> , 2006, 40, 631-636.	3.2	28
70	Effects of altitude on tracheid differentiation and lignification of Norway spruce. <i>Canadian Journal of Botany</i> , 2001, 79, 815-821.	1.1	28
71	Tensile shear strength of UF- and MUF-bonded veneer related to data of adhesives and cell walls measured by nanoindentation. <i>Holzforschung</i> , 2010, 64, .	1.9	27
72	Morphology and rheology of cellulose nanofibrils derived from mixtures of pulp fibres and papermaking fines. <i>Cellulose</i> , 2016, 23, 2439-2448.	4.9	27

#	ARTICLE	IF	CITATIONS
73	Comparison of two optical methods for contactless, full field and highly sensitive in-plane deformation measurements using the example of plywood. <i>Wood Science and Technology</i> , 2011, 45, 755-765.	3.2	26
74	On the drying behavior of natural oils used for solid wood finishing. <i>Progress in Organic Coatings</i> , 2020, 148, 105831.	3.9	26
75	Evaluating fundamental position-dependent differences in wood cell wall adhesion using nanoindentation. <i>International Journal of Adhesion and Adhesives</i> , 2013, 40, 129-134.	2.9	25
76	Suitability of Different Variants of Polyethylene Glycol Impregnation for the Dimensional Stabilization of Oak Wood. <i>Polymers</i> , 2018, 10, 81.	4.5	25
77	Preparation of High Strength Plywood from Partially Delignified Densified Wood. <i>Polymers</i> , 2020, 12, 1796.	4.5	25
78	EFFECTS OF CELL ANATOMY ON THE PLASTIC AND ELASTIC BEHAVIOUR OF DIFFERENT WOOD SPECIES LOADED PERPENDICULAR TO GRAIN. <i>IAWA Journal</i> , 2003, 24, 117-128.	2.7	24
79	Comparison of molecular orientation and mechanical properties of lyocell fibre tow and staple fibres. <i>Cellulose</i> , 2009, 16, 765-772.	4.9	24
80	Facile preparation of superhydrophobic wood surfaces via spraying of aqueous alkyl ketene dimer dispersions. <i>RSC Advances</i> , 2019, 9, 24357-24367.	3.6	24
81	Transparent layer-by-layer coatings based on biopolymers and CeO ₂ to protect wood from UV light. <i>Progress in Organic Coatings</i> , 2020, 138, 105409.	3.9	24
82	Observation of the influence of temperature on the mechanical properties of wood adhesives by nanoindentation. <i>Holzforschung</i> , 2008, 62, 714-717.	1.9	23
83	Orientation of cellulose crystallites in regenerated cellulose fibres under tensile and bending loads. <i>Cellulose</i> , 2006, 13, 621-627.	4.9	22
84	Effect of plasma treatment on cell-wall adhesion of urea-formaldehyde resin revealed by nanoindentation. <i>Holzforschung</i> , 2014, 68, 707-712.	1.9	22
85	Electrically conductive kraft lignin-based carbon filler for polymers. <i>Carbon</i> , 2015, 89, 161-168.	10.3	22
86	Nanocellulosic fillers for waterborne wood coatings: reinforcement effect on free-standing coating films. <i>Wood Science and Technology</i> , 2017, 51, 601-613.	3.2	22
87	SEM and UV-microscopic investigation of glue lines in Parallam Â® PSL. <i>European Journal of Wood and Wood Products</i> , 2001, 59, 211-214.	2.9	21
88	A two-step modification treatment of solid wood by bulk modification and surface treatment. <i>Wood Science and Technology</i> , 2005, 39, 502-511.	3.2	21
89	Tensile Testing of Single Regenerated Cellulose Fibres. <i>Macromolecular Symposia</i> , 2006, 244, 83-88.	0.7	21
90	EFFECTS OF MACRO- AND MICRO-STRUCTURAL VARIABILITY ON THE SHEAR BEHAVIOR OF SOFTWOOD. <i>IAWA Journal</i> , 2004, 25, 231-243.	2.7	20

#	ARTICLE	IF	CITATIONS
91	Converse Piezoelectric Effect in Cellulose I Revealed by Wide-Angle X-ray Diffraction. <i>Biomacromolecules</i> , 2010, 11, 1281-1285.	5.4	20
92	Studying thermal conductivity of wood at cell wall level by scanning thermal microscopy (SThM). <i>Holzforschung</i> , 2013, 67, 155-159.	1.9	20
93	Microfibrillated Lignocellulose Enables the Suspension-Polymerisation of Unsaturated Polyester Resin for Novel Composite Applications. <i>Polymers</i> , 2016, 8, 255.	4.5	20
94	CELL-WALL LIGNIN CONTENT RELATED TO TRACHEID DIMENSIONS IN DROUGHT-SENSITIVE AUSTRIAN PINE (PINUS NIGRA). <i>IAWA Journal</i> , 2001, 22, 113-120.	2.7	19
95	Comparison of the TL-Shear Strength of Normal and Compression Wood of European Larch. <i>Holzforschung</i> , 2003, 57, 421-426.	1.9	19
96	Knots in trees: strain distribution in a naturally optimised structure. <i>Wood Science and Technology</i> , 2010, 44, 389-398.	3.2	19
97	Shear strength of the lyocell fiber/polymer matrix interface evaluated with the microbond technique. <i>Journal of Composite Materials</i> , 2012, 46, 359-367.	2.4	19
98	Reinforcement effect of pulp fines and microfibrillated cellulose in highly densified binderless paperboards. <i>Journal of Cleaner Production</i> , 2021, 281, 125258.	9.3	19
99	Reorientation of crystalline and noncrystalline regions in regenerated cellulose fibers and films tested in uniaxial tension. <i>Journal of Polymer Science, Part B: Polymer Physics</i> , 2008, 46, 297-304.	2.1	18
100	Electrically Conducting Carbon Microparticles by Direct Carbonization of Spent Wood Pulping Liquor. <i>ACS Sustainable Chemistry and Engineering</i> , 2018, 6, 3385-3391.	6.7	18
101	Alkali-extracted tree bark for efficient bio-based thermal insulation. <i>Construction and Building Materials</i> , 2021, 271, 121577.	7.2	18
102	Feasibility of particle board production using bone glue. <i>European Journal of Wood and Wood Products</i> , 2009, 67, 243-245.	2.9	17
103	Elastic properties of adhesive polymers. III. Adhesive polymer films under dry and wet conditions characterized by means of nanoindentation. <i>Journal of Applied Polymer Science</i> , 2010, 118, 1331-1334.	2.6	17
104	Microfibrillated cellulose and cellulose nanopaper from Miscanthus biogas production residue. <i>Cellulose</i> , 2014, 21, 1601-1610.	4.9	16
105	Light microscopic detection of UF adhesive in industrial particle board. <i>Wood Science and Technology</i> , 2015, 49, 517-526.	3.2	16
106	Fabrication of homogeneous and enhanced soybean protein isolate-based composite films via incorporating TEMPO oxidized nanofibrillated cellulose stabilized nano-ZnO hybrid. <i>Cellulose</i> , 2017, 24, 4807-4819.	4.9	16
107	Wood pulp fiber reinforced melamine-formaldehyde composites. <i>Journal of Materials Science</i> , 2004, 39, 3245-3247.	3.7	15
108	Evaluation of Experimental Parameters in the Microbond Test with Regard to Lyocell Fibers. <i>Journal of Reinforced Plastics and Composites</i> , 2010, 29, 2356-2367.	3.1	15

#	ARTICLE	IF	CITATIONS
109	Comparison of fracture energy testing by means of double cantilever beam-(DCB)-specimens and lap joint testing method for the characterization of adhesively bonded wood. <i>European Journal of Wood and Wood Products</i> , 2012, 70, 3-10.	2.9	15
110	Simple Green Route to Performance Improvement of Fully Bio-Based Linseed Oil Coating Using Nanofibrillated Cellulose. <i>Polymers</i> , 2017, 9, 425.	4.5	15
111	Chemical versus physical grafting of photoluminescent amino-functional carbon dots onto transparent nematic nanocellulose gels and aerogels. <i>Cellulose</i> , 2019, 26, 7781-7796.	4.9	15
112	The Effect of Varying Latewood Proportion on the Radial Distribution of Lignin Content in a Pine Stem. <i>Holzforschung</i> , 2001, 55, 455-458.	1.9	14
113	Determination of adhesive energy at the wood cell-wall/UF interface by nanoindentation (NI). <i>Holzforschung</i> , 2012, 66, 781-787.	1.9	14
114	Carbon Microparticles from Organosolv Lignin as Filler for Conducting Poly(Lactic Acid). <i>Polymers</i> , 2016, 8, 205.	4.5	14
115	Effects of Fiber Angle on the Tensile Properties of Partially Delignified and Densified Wood. <i>Materials</i> , 2020, 13, 5405.	2.9	14
116	Sponge-like polypyrrole nanofibrillated cellulose aerogels: synthesis and application. <i>Journal of Materials Chemistry C</i> , 2021, 9, 12615-12623.	5.5	14
117	Climatic Significance of Light Rings in Timberline Spruce, <i>Picea abies</i> , Austrian Alps. <i>Arctic, Antarctic, and Alpine Research</i> , 1999, 31, 242.	1.1	14
118	The effect of lignin on the moisture-dependent behavior of spruce wood in axial compression. <i>Journal of Materials Science Letters</i> , 2001, 20, 2161-2162.	0.5	13
119	Wood modification with tricine. <i>Holzforschung</i> , 2015, 69, 985-991.	1.9	13
120	Shear strain distribution in PRF and PUR bonded 3-ply wood sheets by means of electronic laser speckle interferometry. <i>Wood Science and Technology</i> , 2006, 40, 351-357.	3.2	12
121	Detection of UF resin on wood particles and in particleboards: potential of selected methods for practice-oriented offline detection. <i>European Journal of Wood and Wood Products</i> , 2012, 70, 829-837.	2.9	12
122	Synergy of multi-scale toughening and protective mechanisms at hierarchical branch-stem interfaces. <i>Scientific Reports</i> , 2015, 5, 14522.	3.3	12
123	Nanopaper Properties and Adhesive Performance of Microfibrillated Cellulose from Different (Ligno-)Cellulosic Raw Materials. <i>Polymers</i> , 2017, 9, 326.	4.5	12
124	How softwood tree branches are attached to stems: hierarchical extension of Shigo's stem-branch model. <i>Trees - Structure and Function</i> , 2018, 32, 1113-1121.	1.9	12
125	Highly effective impregnation and modification of spruce wood with epoxy-functional siloxane using supercritical carbon dioxide solvent. <i>Wood Science and Technology</i> , 2018, 52, 1607-1620.	3.2	12
126	Reinforcing effect of poly(furfuryl alcohol) in cellulose-based porous materials. <i>Cellulose</i> , 2019, 26, 4431-4444.	4.9	12

#	ARTICLE	IF	CITATIONS
127	Effect of grain angle on shear strength of glued end grain to flat grain joints of defect-free softwood timber. <i>Wood Science and Technology</i> , 2007, 41, 501-509.	3.2	11
128	Urea-formaldehyde microspheres as a potential additive to wood adhesive. <i>Journal of Wood Science</i> , 2018, 64, 390-397.	1.9	11
129	Adhesive strength and micromechanics of wood bonded at low temperature. <i>International Journal of Adhesion and Adhesives</i> , 2020, 103, 102697.	2.9	11
130	Adhesive bond strength of end grain joints in softwood with varying density. <i>Holzforschung</i> , 2008, 62, 237-242.	1.9	10
131	High-Modulus Oriented Cellulose Nanopaper. <i>ACS Symposium Series</i> , 2012, , 3-16.	0.5	10
132	Cell-layer dependent adhesion differences in wood bonds. <i>Composites Part A: Applied Science and Manufacturing</i> , 2018, 114, 21-29.	7.6	10
133	Wetting Behavior of Alder (<i>Alnus cordata</i> (Loisel) Duby) Wood Surface: Effect of Thermo-Treatment and Alkyl Ketene Dimer (AKD). <i>Forests</i> , 2019, 10, 770.	2.1	10
134	Differences in adhesion between IC-PUR and MUF wood adhesives to (ligno)cellulosic surfaces revealed by nanoindentation. <i>International Journal of Adhesion and Adhesives</i> , 2020, 98, 102507.	2.9	10
135	Structure and electrical resistivity of individual carbonised natural and man-made cellulose fibres. <i>Journal of Materials Science</i> , 2020, 55, 10271-10280.	3.7	10
136	Comparing the suitability of domestic spruce, beech, and poplar wood for high-strength densified wood. <i>European Journal of Wood and Wood Products</i> , 2022, 80, 859-876.	2.9	10
137	UV-microscopic analysis of acetylated spruce and birch cell walls. <i>Holzforschung</i> , 2004, 58, 483-488.	1.9	9
138	Fine Cellulosic Materials Produced from Chemical Pulp: the Combined Effect of Morphology and Rate of Addition on Paper Properties. <i>Nanomaterials</i> , 2019, 9, 321.	4.1	9
139	Comparison of the in-plane shear strength of OSB and plywood using five point bending and EN 789 steel plate test methods. <i>European Journal of Wood and Wood Products</i> , 2005, 63, 160-164.	2.9	8
140	Tensile strength of softwood butt end joints. Part 1: Effect of grain angle on adhesive bond strength. <i>Wood Material Science and Engineering</i> , 2007, 2, 83-89.	2.3	8
141	Effects of Long-term Storage on the Mechanical Characteristics of Wood Plastic Composites Produced from Thermally Modified Wood Fibers. <i>Journal of Thermoplastic Composite Materials</i> , 2010, 23, 845-853.	4.2	8
142	Reliability of wood adhesive bonds in a 50 year old glider construction. <i>European Journal of Wood and Wood Products</i> , 2012, 70, 381-384.	2.9	8
143	Adhesive distribution related to mechanical performance of high density wood fibre board. <i>International Journal of Adhesion and Adhesives</i> , 2017, 78, 23-27.	2.9	8
144	Nanocellulose from fractionated sulfite wood pulp. <i>Cellulose</i> , 2020, 27, 9325-9336.	4.9	8

#	ARTICLE	IF	CITATIONS
145	Pore Development during the Carbonization Process of Lignin Microparticles Investigated by Small Angle X-ray Scattering. <i>Molecules</i> , 2021, 26, 2087.	3.8	8
146	Thermal conductivity of untreated and chemically treated poplar bark and wood. <i>Holzforschung</i> , 2021, 75, 1125-1135.	1.9	8
147	Cure Kinetics and Inverse Analysis of Epoxy-Amine Based Adhesive Used for Fastening Systems. <i>Materials</i> , 2021, 14, 3853.	2.9	8
148	Nanocellulose-modified Wood Adhesives. <i>Materials and Energy</i> , 2014, , 253-264.	0.1	7
149	Comparative adhesion analysis at glue joints in European beech and Norway spruce wood by means of nanoindentation. <i>International Journal of Adhesion and Adhesives</i> , 2014, 50, 45-49.	2.9	7
150	Effects of UV-irradiation on tricine impregnated wood. <i>European Journal of Wood and Wood Products</i> , 2014, 72, 617-622.	2.9	7
151	Radial crystalline texture in a lyocell fibre revealed by synchrotron nanofocus wide-angle X-ray scattering. <i>Cellulose</i> , 2014, 21, 845-851.	4.9	7
152	Residual wood polymers facilitate compounding of microfibrillated cellulose with poly(lactic acid) for 3D printer filaments. <i>Philosophical Transactions Series A, Mathematical, Physical, and Engineering Sciences</i> , 2018, 376, 20170046.	3.4	7
153	Electrically-Conductive Sub-Micron Carbon Particles from Lignin: Elucidation of Nanostructure and Use as Filler in Cellulose Nanopapers. <i>Nanomaterials</i> , 2018, 8, 1055.	4.1	7
154	Preparation and Characterization of Bacterial Cellulose-Carbon Dot Hybrid Nanopaper for Potential Sensing Applications. <i>Applied Sciences (Switzerland)</i> , 2019, 9, 107.	2.5	7
155	Comparative Adhesive Bonding of Wood Chemically Modified with Either Acetic Anhydride or Butylene Oxide. <i>Forests</i> , 2021, 12, 546.	2.1	6
156	The Optical Appearance of Wood Related to Nanoscale Surface Roughness. <i>BioResources</i> , 2013, 8, .	1.0	6
157	Mechanical characterisation of adhesives in particle boards by means of nanoindentation. <i>European Journal of Wood and Wood Products</i> , 2010, 68, 421-426.	2.9	5
158	The significance of lap-shear testing of wood adhesive bonds by means of Volkersen's shear lag model. <i>European Journal of Wood and Wood Products</i> , 2012, 70, 903-905.	2.9	5
159	Increase of error in lignin measurement using ultraviolet microscopy due to multiple scanning. <i>Journal of Wood Science</i> , 1999, 45, 179-180.	1.9	4
160	Efficient Wood Hydrophobization Exploiting Natural Roughness Using Minimum Amounts of Surfactant-Free Plant Oil Emulsions. <i>ACS Omega</i> , 2021, 6, 22202-22212.	3.5	4
161	Efficient recovery of superhydrophobic wax surfaces on solid wood. <i>European Journal of Wood and Wood Products</i> , 2022, 80, 345-353.	2.9	4
162	Low temperature and moisture dependent curing behavior of selected wood adhesives. <i>International Journal of Adhesion and Adhesives</i> , 2022, 117, 103178.	2.9	4

#	ARTICLE	IF	CITATIONS
163	Oil-absorbing porous cellulosic material from sized wood pulp fines. <i>Holzforschung</i> , 2018, 73, 83-92.	1.9	3
164	Facile Preparation of Mechanically Robust and Functional Silica/Cellulose Nanofiber Gels Reinforced with Soluble Polysaccharides. <i>Nanomaterials</i> , 2022, 12, 895.	4.1	3
165	Properties of Woven Natural Fiber-Reinforced Biocomposites. <i>Journal of Renewable Materials</i> , 2016, 4, 215-224.	2.2	2
166	Effects of fibrillar cellulosic additives on particleboard production and properties. <i>Wood Material Science and Engineering</i> , 2022, 17, 106-112.	2.3	2
167	In-Situ X-ray Diffraction as a Tool to Probe Mechanical Phenomena Down to the Nano-Scale. <i>Advanced Engineering Materials</i> , 2006, 8, 1084-1088.	3.5	1
168	Reinforcement of Poly (Lactic Acid) with Spray-dried Lignocellulosic Material. <i>BioResources</i> , 2016, 12, .	1.0	1
169	Micromechanics of Cellulose Fibres and Their Composites. , 2017, , 299-321.		1
170	Wood Adhesive Bondlines by Nanoindentation. , 2007, , 493-494.		1
171	Thermosetting natural fiber based composites. , 2021, , 187-214.		0
172	Fully bio-based composite foams made of wheat gluten and disintegrated spruce tree bark. <i>Results in Materials</i> , 2022, 15, 100299.	1.8	0