Kin Seng Chiang

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/6332763/publications.pdf

Version: 2024-02-01

322 papers

7,842 citations

45 h-index 71 g-index

325 all docs 325 docs citations

325 times ranked

3934 citing authors

| # | Article | IF | CITATIONS |
|----|---|--------------|-----------|
| 1 | Low-power all-optical switch based on a graphene-buried polymer waveguide Mach-Zehnder interferometer. Optics Express, 2022, 30, 6786. | 3.4 | 20 |
| 2 | All-optical mode switching with a graphene-buried polymer waveguide directional coupler. Optics Letters, 2022, 47, 2414. | 3.3 | 8 |
| 3 | Robust Mode Matching between Structurally Dissimilar Optical Fiber Waveguides. ACS Photonics, 2021, 8, 857-863. | 6.6 | 31 |
| 4 | Electro-optic reconfigurable two-mode (de)multiplexer on thin-film lithium niobate. Optics Letters, 2021, 46, 1001. | 3.3 | 23 |
| 5 | Ultralow-loss fusion splicing between negative curvature hollow-core fibers and conventional SMFs with a reverse-tapering method. Optics Express, 2021, 29, 22470. | 3.4 | 34 |
| 6 | Lab on optical fiber: surface nano-functionalization for real-time monitoring of VOC adsorption/desorption in metal-organic frameworks. Nanophotonics, 2021, 10, 2705-2716. | 6.0 | 13 |
| 7 | Symmetric Two-Mode Waveguide Directional Coupler on Thin-Film Lithium Niobate for Electro-Optic Mode Switching. , 2021, , . | | O |
| 8 | Leaky-mode long-period grating on a lithium-niobate-on-insulator waveguide. Optica, 2021, 8, 1624. | 9.3 | 16 |
| 9 | Graphene-Buried Polymer Waveguide Mach-Zehnder Interferometer for Low-Power All-Optical Switching. , 2021, , . | | O |
| 10 | Reversely tapered multicore fibers for simplified all-fiber fan-in and fan-out devices. , 2021, , . | | 0 |
| 11 | Polymer waveguide Mach-Zehnder interferometer coated with dipolar polycarbonate for on-chip nitroaromatics detection. Sensors and Actuators B: Chemical, 2020, 305, 127406. | 7.8 | 15 |
| 12 | Equivalent Circuit of Quantum-Dot LED and Acquisition of Carrier Lifetime in Active Layer. IEEE Electron Device Letters, 2020, 41, 87-90. | 3.9 | 6 |
| 13 | Phenolic-compounds sensor based on immobilization of tyrosinase in polyacrylamide gel on long-period fiber grating. Optics and Laser Technology, 2020, 131, 106464. | 4.6 | 14 |
| 14 | Nanoscale light–matter interactions in metal–organic frameworks cladding optical fibers. Nanoscale, 2020, 12, 9991-10000. | 5 . 6 | 25 |
| 15 | Reconfigurable Three-Mode Converter Based On Cascaded Electro-Optic Long-Period Gratings. IEEE Journal of Selected Topics in Quantum Electronics, 2020, 26, 1-6. | 2.9 | 19 |
| 16 | Trade-Offs Between Illumination and Modulation Performances of Quantum-Dot LED. IEEE Photonics Technology Letters, 2020, 32, 726-729. | 2.5 | 3 |
| 17 | Electro-optic mode-selective switch based on cascaded three-dimensional lithium-niobate waveguide directional couplers. Optics Express, 2020, 28, 35506. | 3.4 | 15 |
| 18 | Graphene electrodes for electric poling of electro-optic polymer films. Optics Letters, 2020, 45, 2383. | 3.3 | 10 |

| # | Article | IF | CITATIONS |
|----|--|-----|-----------|
| 19 | Polarization-insensitive ultra-broadband mode filter based on a 3D graphene structure buried in an optical waveguide. Optica, 2020, 7, 744. | 9.3 | 22 |
| 20 | Graphene-Coated Surface-Plasmon-Resonance Waveguide Biosensor. , 2020, , . | | 0 |
| 21 | Three-Mode Switch Based on Electro-Optic Long-Period Gratings Integrated along a Lithium-Niobate Waveguide. , 2020, , . | | 0 |
| 22 | Optical modulation in hybrid antiresonant hollow-core fiber infiltrated with vanadium dioxide phase change nanocrystals. Optics Letters, 2020, 45, 4240. | 3.3 | 5 |
| 23 | Electrically generated optical waveguide in a lithium-niobate thin film. Optics Express, 2020, 28, 29895. | 3.4 | 3 |
| 24 | Electro-Optic Mode-Selective Switch Based on Cascaded Lithium-Niobate Waveguide Directional Couplers., 2020,,. | | 0 |
| 25 | Polarization-Insensitive Mode Filtering With L-Shaped Graphene Structure Embedded in Polymer Waveguide. , 2020, , . | | 0 |
| 26 | Mode (De)multiplexer Without Mode Conversion Based on Three-Core Waveguide Directional Coupler. , 2020, , . | | 0 |
| 27 | High-Order-Mode-Pass Mode (De)Multiplexer With a Hybrid-Core Vertical Directional Coupler. Journal of Lightwave Technology, 2019, 37, 3932-3938. | 4.6 | 9 |
| 28 | Optofluidic laser explosive sensor with ultralow detection limit and large dynamic range using donor-acceptor-donor organic dye. Sensors and Actuators B: Chemical, 2019, 298, 126830. | 7.8 | 14 |
| 29 | Comparison of different optical models of graphene for the analysis of graphene-attached microfibers and D-shaped fibers. Optics Communications, 2019, 452, 347-354. | 2.1 | 4 |
| 30 | Ultra-Broadband Mode Filter Based on Phase-Shifted Long-Period Grating. IEEE Photonics Technology Letters, 2019, 31, 1052-1055. | 2.5 | 23 |
| 31 | Effects of Injection Current on the Modulation Bandwidths of Quantum-Dot Light-Emitting Diodes. IEEE Transactions on Electron Devices, 2019, 66, 4805-4810. | 3.0 | 10 |
| 32 | A photochromic dye doped polymeric Mach–Zehnder interferometer for UV light detection. Journal of Materials Chemistry C, 2019, 7, 6257-6265. | 5.5 | 21 |
| 33 | Externally pumped low-loss graphene-based fiber Mach-Zehnder all-optical switches with mW switching powers. Optics Express, 2019, 27, 4216. | 3.4 | 26 |
| 34 | Polarization-insensitive mode-independent thermo-optic switch based on symmetric waveguide directional coupler. Optics Express, 2019, 27, 35385. | 3.4 | 19 |
| 35 | Buried graphene electrode heater for a polymer waveguide thermo-optic device. Optics Letters, 2019, 44, 1480. | 3.3 | 36 |
| 36 | All-optical loss modulation with graphene-buried polymer waveguides. Optics Letters, 2019, 44, 3685. | 3.3 | 9 |

3

| # | Article | IF | Citations |
|----|--|--------------|-----------|
| 37 | Mode-Selective Switch Based on Thermo-Optic Asymmetric Directional Coupler. IEEE Photonics Technology Letters, 2018, 30, 618-621. | 2.5 | 30 |
| 38 | Nano-functionalized long-period fiber grating probe for disease-specific protein detection. Journal of Materials Chemistry B, 2018, 6, 386-392. | 5. 8 | 18 |
| 39 | Ultra-efficient and stable electro-optic dendrimers containing supramolecular homodimers of semifluorinated dipolar aromatics. Materials Chemistry Frontiers, 2018, 2, 901-909. | 5.9 | 49 |
| 40 | Thermo-Optically Controlled Vertical Waveguide Directional Couplers for Mode-Selective Switching. IEEE Photonics Journal, 2018, 10, 1-14. | 2.0 | 20 |
| 41 | A Lithium-Niobate Waveguide Directional Coupler for Switchable Mode Multiplexing. IEEE Photonics Technology Letters, 2018, 30, 1764-1767. | 2.5 | 13 |
| 42 | Optimization of Illumination Performance of Trichromatic White Light-Emitting Diode and Characterization of Its Modulation Bandwidth for Communication Applications. IEEE Photonics Journal, 2018, 10, 1-11. | 2.0 | 8 |
| 43 | Mode Multiplexer With Cascaded Vertical Asymmetric Waveguide Directional Couplers. Journal of Lightwave Technology, 2018, 36, 2903-2911. | 4.6 | 46 |
| 44 | Three-dimensional long-period waveguide gratings for mode-division-multiplexing applications. Optics Express, 2018, 26, 15289. | 3 . 4 | 23 |
| 45 | Reconfigurable broadband mode (de)multiplexer based on an integrated thermally induced long-period grating and asymmetric Y-junction. Optics Letters, 2018, 43, 2082. | 3.3 | 36 |
| 46 | Graphene electrodes for lithium-niobate electro-optic devices. Optics Letters, 2018, 43, 1718. | 3.3 | 29 |
| 47 | Fast and low-power thermo-optic switch based on organic–inorganic hybrid strip-loaded waveguides. Optics Letters, 2018, 43, 5102. | 3.3 | 17 |
| 48 | Volatile organic gas recognition with an in-line fiber Mach-Zehnder interferometer coated with ZIF-8. , 2018, , . | | 0 |
| 49 | Symmetric lithium-niobate waveguide fabricated by bonding for mode-division-multiplexing applications. , 2018, , . | | 0 |
| 50 | Broadband filtering of the fundamental mode of a few-mode waveguide with a phase-shifted long-period grating. , 2018 , , . | | 1 |
| 51 | Broadband Mode Router Based on Three-Dimensional Mach-Zehnder Interferometer and Waveguide Branches. , 2018, , . | | 4 |
| 52 | Analysis of mode-selective coupling between few-mode fibers and waveguides with lateral misalignment. , $2018, , .$ | | 0 |
| 53 | Polymer optical waveguide devices for mode-division-multiplexing applications. Proceedings of SPIE, 2017, , . | 0.8 | 1 |
| 54 | Tuning the strength of intramolecular charge-transfer of triene-based nonlinear optical dyes for electro-optics and optofluidic lasers. Journal of Materials Chemistry C, 2017, 5, 7472-7478. | 5 . 5 | 38 |

| # | Article | IF | CITATIONS |
|----|---|-----|-----------|
| 55 | Horizontal Directional Coupler Formed With Waveguides of Different Heights for Mode-Division Multiplexing. IEEE Photonics Journal, 2017, 9, 1-9. | 2.0 | 22 |
| 56 | Wide-Range pH Sensor Based on a Smart- Hydrogel-Coated Long-Period Fiber Grating. IEEE Journal of Selected Topics in Quantum Electronics, 2017, 23, 284-288. | 2.9 | 56 |
| 57 | Light-emitting diode conditioned with YAG:Ce $<$ sup $>$ 3+ $<$ /sup $>$ phosphors and CdSe/ZnS quantum dots for high color-rendering-index white-light generation. , 2017, , . | | 0 |
| 58 | Graphene-Based Ammonia-Gas Sensor Using In-Fiber Mach-Zehnder Interferometer. IEEE Photonics Technology Letters, 2017, 29, 2035-2038. | 2.5 | 47 |
| 59 | Graphene-coated in-fiber Mach-Zehnder interferometer for ammonia gas sensing. , 2017, , . | | 0 |
| 60 | Thermo-optic switchable mode multiplexer based on cascaded vertical waveguide directional couplers., 2017,,. | | 2 |
| 61 | Broadband mode switch based on a three-dimensional waveguide Mach–Zehnder interferometer. Optics Letters, 2017, 42, 4877. | 3.3 | 37 |
| 62 | Ultra-broadband mode converters based on length-apodized long-period waveguide gratings. Optics Express, 2017, 25, 14341. | 3.4 | 38 |
| 63 | Ultra-broadband mode multiplexers based on three-dimensional asymmetric waveguide branches. Optics Letters, 2017, 42, 407. | 3.3 | 56 |
| 64 | Ultra-broadband mode filters based on graphene-embedded waveguides. Optics Letters, 2017, 42, 3868. | 3.3 | 45 |
| 65 | Ultra-broadband mode conversion with length-apodized long-period grating on polymer waveguide. , 2017, , . | | 0 |
| 66 | Mode-selective coupling between few-mode fibers and buried channel waveguides. Optics Express, 2016, 24, 30108. | 3.4 | 18 |
| 67 | Modulation instabilities in equilateral three-core optical fibers. Journal of the Optical Society of America B: Optical Physics, 2016, 33, 2357. | 2.1 | 11 |
| 68 | Surface-Plasmon-Resonance Refractive-Index Sensor With Cu-Coated Polymer Waveguide. IEEE Photonics Technology Letters, 2016, 28, 1835-1838. | 2.5 | 38 |
| 69 | Electro-optic mode switch based on lithium-niobate Mach–Zehnder interferometer. Applied Optics, 2016, 55, 4418. | 2.1 | 38 |
| 70 | Experimental verification of optical models of graphene with multimode slab waveguides. Optics Letters, 2016, 41, 2129. | 3.3 | 66 |
| 71 | Mode converters based on cascaded long-period waveguide gratings. Optics Letters, 2016, 41, 3130. | 3.3 | 60 |
| 72 | Mode-Selective Characteristics of an Optical Fiber With a High-Index Core and a Photonic Bandgap Cladding. IEEE Journal of Selected Topics in Quantum Electronics, 2016, 22, 251-257. | 2.9 | 5 |

| # | Article | IF | CITATIONS |
|----|---|-----|-----------|
| 73 | Mode Conversion with Vertical Polymer-Waveguide Directional Coupler. , 2016, , . | | 2 |
| 74 | Broadband photonic lantern mode multiplexers based on multilayer polymer waveguides. , 2015, , . | | 0 |
| 75 | Temperature-Insensitive Mode Converters With CO ₂ -Laser Written Long-Period Fiber Gratings. IEEE Photonics Technology Letters, 2015, 27, 1006-1009. | 2.5 | 101 |
| 76 | Mode converter with sidewall-corrugated polymer waveguide grating. , 2015, , . | | 2 |
| 77 | Lithium-Niobate Mach-Zehnder Interferometer With Enhanced Index Contrast by SiO ₂ Film. IEEE Photonics Technology Letters, 2015, 27, 1224-1227. | 2.5 | 10 |
| 78 | Breathers and †black†fogue waves of coupled nonlinear Schrö dinger equations with dispersion and nonlinearity of opposite signs. Communications in Nonlinear Science and Numerical Simulation, 2015, 28, 28-38. | 3.3 | 30 |
| 79 | Compact Three-Dimensional Polymer Waveguide Mode Multiplexer. Journal of Lightwave Technology, 2015, 33, 4580-4588. | 4.6 | 67 |
| 80 | Mode switch based on electro-optic long-period waveguide grating in lithium niobate. Optics Letters, 2015, 40, 237. | 3.3 | 46 |
| 81 | Compact three-core fibers with ultra-low differential group delays for broadband mode-division multiplexing. Optics Express, 2015, 23, 20867. | 3.4 | 12 |
| 82 | Mode multiplexer based on integrated horizontal and vertical polymer waveguide couplers. Optics Letters, 2015, 40, 3125. | 3.3 | 50 |
| 83 | Polarization Switching in a Mode-Locked Fiber Laser Based on Reduced Graphene Oxide. IEEE Photonics Technology Letters, 2015, 27, 2535-2538. | 2.5 | 6 |
| 84 | Widely Wavelength-Tunable Mode Converter Based on Polymer Waveguide Grating. IEEE Photonics Technology Letters, 2015, 27, 1985-1988. | 2.5 | 39 |
| 85 | Application of the Hilbert Transform Method for the Retrieval of the Phase Characteristics of Plasmonic Metal Bragg Gratings. Plasmonics, 2015, 10, 107-115. | 3.4 | 0 |
| 86 | Sidewall-Grating-Assisted Polymer-Waveguide Directional Coupler for Forward Coupling of Fundamental Modes., 2015,,. | | 6 |
| 87 | Mode Rotator with Two Cascaded Waveguide Gratings. , 2015, , . | | 0 |
| 88 | Graphene enhanced evanescent field in microfiber multimode interferometer for highly sensitive gas sensing. Optics Express, 2014, 22, 28154. | 3.4 | 71 |
| 89 | Graphene Bragg gratings on microfiber. Optics Express, 2014, 22, 23829. | 3.4 | 18 |
| 90 | UV exposure on a single-mode fiber within a multimode interference structure. Optics Letters, 2014, 39, 6521. | 3.3 | 3 |

| # | Article | IF | CITATIONS |
|-----|--|-----|-----------|
| 91 | Temperature-Insensitive Real-Time Inclinometer Based on an Etched Fiber Bragg Grating. IEEE Photonics Technology Letters, 2014, 26, 1049-1052. | 2.5 | 17 |
| 92 | Graphene-based D-shaped fiber multicore mode interferometer for chemical gas sensing. Optics Letters, 2014, 39, 6030. | 3.3 | 44 |
| 93 | Mode-Locked Fiber Laser With Transverse-Mode Selection Based on a Two-Mode FBG. IEEE Photonics Technology Letters, 2014, 26, 1766-1769. | 2.5 | 57 |
| 94 | Propagation of Solitary Pulses in Optical Fibers with Both Self-Steepening and Quintic Nonlinear Effects. Communications in Theoretical Physics, 2014, 61, 735-741. | 2.5 | 4 |
| 95 | A real-time inclinometer based on an etched fiber Bragg grating connected to hollow-core fiber. , 2014, , . | | 0 |
| 96 | Switching of ultrashort pulses in nonlinear high-birefringence two-core optical fibers. Optics Communications, 2014, 318, 11-16. | 2.1 | 6 |
| 97 | Graphene-coated microfiber Bragg grating for high-sensitivity gas sensing. Optics Letters, 2014, 39, 1235. | 3.3 | 170 |
| 98 | Four-Wave Mixing in a Microfiber Attached Onto a Graphene Film. IEEE Photonics Technology Letters, 2014, 26, 249-252. | 2.5 | 66 |
| 99 | Modulation instability with arbitrarily high perturbation frequencies in metamaterials with nonlinear dispersion and saturable nonlinearity. Journal of the Optical Society of America B: Optical Physics, 2014, 31, 1484. | 2.1 | 26 |
| 100 | Effects of average index variation in apodized long-period fiber gratings. Photonic Sensors, 2013, 3, 102-111. | 5.0 | 4 |
| 101 | Effect of irradiation symmetry of CO ₂ laser on mode coupling in long-period gratings inscribed in photonic crystal fiber. Proceedings of SPIE, 2013, , . | 0.8 | 1 |
| 102 | Remote high temperature sensing with a reflective bandpass long-period fiber grating and a fiber ring laser. Measurement Science and Technology, 2013, 24, 094023. | 2.6 | 4 |
| 103 | Two-core photonic crystal fiber with zero intermodal dispersion. Optics Communications, 2013, 293, 49-53. | 2.1 | 2 |
| 104 | Micro-Fiber-Based FBG Sensor for Simultaneous Measurement of Vibration and Temperature. IEEE Photonics Technology Letters, 2013, 25, 1751-1753. | 2.5 | 45 |
| 105 | Phase Retrieval From Transmission Spectrum for Long-Period Fiber Gratings. Journal of Lightwave Technology, 2013, 31, 2223-2229. | 4.6 | 4 |
| 106 | Propylene Carbonate Based Compact Fiber Mach–Zehnder Interferometric Electric Field Sensor. Journal of Lightwave Technology, 2013, 31, 1566-1572. | 4.6 | 14 |
| 107 | Micro-fiber inclinometer based on deformation of FBG. Proceedings of SPIE, 2013, , . | 0.8 | 0 |
| 108 | All-fiber vibration sensor based on a Fabry–Perot interferometer and a microstructure beam. Journal of the Optical Society of America B: Optical Physics, 2013, 30, 1211. | 2.1 | 42 |

| # | Article | IF | CITATIONS |
|-----|---|-----|-----------|
| 109 | Long-period gratings inscribed in photonic crystal fiber by symmetric CO_2 laser irradiation. Optics Express, 2013, 21, 13208. | 3.4 | 26 |
| 110 | Industry Compatible Embossing Process for the Fabrication of Waveguide-Embedded Optical Printed Circuit Boards. Journal of Lightwave Technology, 2013, 31, 4045-4050. | 4.6 | 14 |
| 111 | Modulation instabilities in birefringent two-core optical fibres. Journal of Physics B: Atomic, Molecular and Optical Physics, 2012, 45, 165404. | 1.5 | 22 |
| 112 | Pressure-assisted low-loss fusion splicing between photonic crystal fiber and single-mode fiber. Optics Express, 2012, 20, 24465. | 3.4 | 25 |
| 113 | CO_2 laser induced refractive index changes in optical polymers. Optics Express, 2012, 20, 576. | 3.4 | 7 |
| 114 | Long-Period Fiber Grating Within D-Shaped Fiber Using Magnetic Fluid for Magnetic-Field Detection. IEEE Photonics Journal, 2012, 4, 2095-2104. | 2.0 | 58 |
| 115 | Remote sensing based on reflective bandpass long-period fiber grating and fiber ring laser. , 2012, , . | | 1 |
| 116 | Electro-optic long-period waveguide grating devices. , 2012, , . | | 0 |
| 117 | All Single-Mode Fiber Mach–Zehnder Interferometer Based on Two Peanut-Shape Structures. Journal of Lightwave Technology, 2012, 30, 805-810. | 4.6 | 110 |
| 118 | Formulae for the Design of Polarization-Insensitive Multimode Interference Couplers. IEEE Photonics Technology Letters, 2011, 23, 1277-1279. | 2.5 | 12 |
| 119 | Bottom-Heating Approach for the Realization of Thermooptic Polymer Waveguide Devices. IEEE Photonics Technology Letters, 2011, 23, 155-157. | 2.5 | 2 |
| 120 | Modulation instabilities in two-core optical fibers. Journal of the Optical Society of America B: Optical Physics, 2011, 28, 1693. | 2.1 | 70 |
| 121 | Wavelength switching of picosecond pulses generated from a self-seeded Fabry–Perot laser diode with a tilted fiber Bragg grating formed in a graded-index multimode fiber. Applied Optics, 2011, 50, 829. | 2.1 | 3 |
| 122 | Tunable negative-tap photonic microwave filter based on a cladding-mode coupler and an optically injected laser of large detuning. Optics Express, 2011, 19, 12045. | 3.4 | 16 |
| 123 | Torsion sensing with a fiber ring laser incorporating a pair of rotary long-period fiber gratings. Optics Communications, 2011, 284, 5299-5302. | 2.1 | 61 |
| 124 | Nonlinear Switching of Ultrashort Pulses in Multicore Fibers. IEEE Journal of Quantum Electronics, 2011, 47, 1499-1505. | 1.9 | 21 |
| 125 | Optical sensing based on light coupling between two parallel long-period fiber gratings. Photonic Sensors, 2011, 1, 204-209. | 5.0 | 1 |
| 126 | Propagation of ultrashort pulses in a nonlinear two-core photonic crystal fiber. Applied Physics B: Lasers and Optics, 2010, 98, 815-820. | 2.2 | 23 |

| # | Article | IF | CITATIONS |
|-----|---|-----|-----------|
| 127 | Fabry–Perot optical fiber tip sensor for high temperature measurement. Optics Communications, 2010, 283, 3683-3685. | 2.1 | 108 |
| 128 | Development of optical polymer waveguide devices., 2010,,. | | 6 |
| 129 | All-Fiber Tunable Microwave Photonic Filter Based on a Cladding-Mode Coupler. IEEE Photonics Technology Letters, 2010, 22, 1241-1243. | 2.5 | 5 |
| 130 | Planar long-period grating filter based on long-range surface plasmon mode of buried metal stripe waveguide. Optics Express, 2010, 18, 8963. | 3.4 | 9 |
| 131 | Pulse propagation in a decoupled two-core fiber. Optics Express, 2010, 18, 21261. | 3.4 | 11 |
| 132 | Thermally tunable lithium-niobate long-period waveguide grating filter fabricated by reactive ion etching. Optics Letters, 2010, 35, 484. | 3.3 | 22 |
| 133 | Microwave photonic filter based on circulating a cladding mode in a fiber ring resonator. Optics Letters, 2010, 35, 769. | 3.3 | 21 |
| 134 | Analysis of Lithium Niobate Electrooptic Long-Period Waveguide Gratings. Journal of Lightwave Technology, 2010, 28, 1477-1484. | 4.6 | 11 |
| 135 | CO <inf>2</inf> -laser writing of long-period gratings in tensioned boron-doped fibers., 2009,,. | | 0 |
| 136 | Propagation of ultrashort pulses in a nonlinear long-period fiber grating. Applied Physics B: Lasers and Optics, 2009, 94, 599-607. | 2.2 | 5 |
| 137 | Fabrication of segmented cladding fiber by bicomponent spinning. Polymer Engineering and Science, 2009, 49, 1865-1870. | 3.1 | 16 |
| 138 | UV-written long-period waveguide grating coupler for broadband add/drop multiplexing. Optics Communications, 2009, 282, 378-381. | 2.1 | 10 |
| 139 | Effects of group-delay difference on ultrashort pulse propagation in an active nonlinear LPFG. Optics Communications, 2009, 282, 4796-4799. | 2.1 | 0 |
| 140 | Optical coupling between a long-period fiber grating and a parallel tilted fiber Bragg grating. Optics Letters, 2009, 34, 1726. | 3.3 | 28 |
| 141 | Characterization of Long-Period Fiber Gratings Written by CO\$_{2}\$ Laser in Twisted Single-Mode Fibers. Journal of Lightwave Technology, 2009, 27, 4863-4869. | 4.6 | 42 |
| 142 | CO_2 laser writing of long-period fiber grating in photonic crystal fiber under tension. Optics Express, 2009, 17, 4533. | 3.4 | 28 |
| 143 | Refractive-index sensor based on long-range surface plasmon mode excitation with longperiod waveguide grating. Optics Express, 2009, 17, 7933. | 3.4 | 39 |
| 144 | All-fiber bandwidth-tunable band-rejection filter based on a composite grating induced by CO_2 laser pulses. Optics Express, 2009, 17, 16750. | 3.4 | 7 |

| # | Article | IF | Citations |
|-----|---|-----|-----------|
| 145 | Active chromatic control on the group velocity of light at arbitrary wavelength in benzocyclobutene polymer. Optics Express, 2009, 17, 18292. | 3.4 | 2 |
| 146 | Development of long-period fiber grating coupling devices. Applied Optics, 2009, 48, F61. | 2.1 | 13 |
| 147 | Design and Fabrication of Polymer Cross Fiber for Large-Core Single-Mode Operation. Journal of Lightwave Technology, 2009, 27, 101-107. | 4.6 | 14 |
| 148 | Glass Structure Changes in CO\$_{2}\$-Laser Writing of Long-Period Fiber Gratings in Boron-Doped Single-Mode Fibers. Journal of Lightwave Technology, 2009, 27, 857-863. | 4.6 | 81 |
| 149 | Highly Sensitive Temperature-Independent Strain Sensor Based on a Long-Period Fiber Grating With a CO\$_{2}\$-Laser Engraved Rotary Structure. IEEE Photonics Technology Letters, 2009, 21, 543-545. | 2.5 | 25 |
| 150 | Writing of Apodized Phase-Shifted Long-Period Fiber Gratings With a Computer-Controlled CO\$_{2}\$ Laser. IEEE Photonics Technology Letters, 2009, 21, 657-659. | 2.5 | 27 |
| 151 | CO\$_{2}\$ Laser-Written Long-Period Fiber Gratings in a Germanium–Boron Codoped Fiber: Effects of Applying Tension During the Writing Process. IEEE Photonics Technology Letters, 2009, 21, 1456-1458. | 2.5 | 9 |
| 152 | Wavelength-Switchable Picosecond Laser Pulses Generated from a Self-Seeded Fabry-Perot Laser Diode and a Tilted Multimode Fiber Bragg Grating. , 2009, , . | | 0 |
| 153 | Large-core single-mode channel waveguide based on geometrically shaped leaky cladding. Applied Physics B: Lasers and Optics, 2008, 90, 507-512. | 2.2 | 12 |
| 154 | Light guidance in a photonic bandgap slab waveguide consisting of two different Bragg reflectors. Optics Communications, 2008, 281, 5797-5803. | 2.1 | 13 |
| 155 | Growth of c-axis orientation ZnO films on polymer substrates by radio-frequency magnetron sputtering. Optical Materials, 2008, 30, 1244-1250. | 3.6 | 13 |
| 156 | Writing of Long-Period Gratings in Conventional and Photonic-Crystal Polarization-Maintaining Fibers by CO\$_{2}\$-Laser Pulses. IEEE Photonics Technology Letters, 2008, 20, 132-134. | 2.5 | 43 |
| 157 | Broadband Multiport Dynamic Optical Power Distributor Based on Thermooptic Polymer Waveguide Vertical Couplers. IEEE Photonics Technology Letters, 2008, 20, 273-275. | 2.5 | 5 |
| 158 | Lithium–Niobate Channel Waveguide for the Realization of Long-Period Gratings. IEEE Photonics Technology Letters, 2008, 20, 1258-1260. | 2.5 | 12 |
| 159 | CO_2 laser writing of long-period fiber gratings in optical fibers under tension. Optics Letters, 2008, 33, 1933. | 3.3 | 48 |
| 160 | Refractive-Index Profiling of Buried Planar Waveguides by an Inverse Wentzel–Kramer–Brillouin Method. Journal of Lightwave Technology, 2008, 26, 1367-1373. | 4.6 | 9 |
| 161 | Analysis of Erbium-Doped Ultralarge-Core Segmented-Cladding Fibers for Optical Amplification. Journal of Lightwave Technology, 2008, 26, 3098-3103. | 4.6 | 5 |
| 162 | Analysis of Six-Port Optical Fiber Couplers Based on Three Parallel Long-Period Fiber Gratings. Journal of Lightwave Technology, 2008, 26, 3277-3286. | 4.6 | 7 |

| # | Article | IF | Citations |
|-----|--|-----|-----------|
| 163 | Laser-micromachined Fabry-Perot optical fiber tip sensor for high-resolution temperature-independent measurement of refractive index. Optics Express, 2008, 16, 2252. | 3.4 | 318 |
| 164 | Electro-optic long-period waveguide gratings in lithium niobate. Optics Express, 2008, 16, 20409. | 3.4 | 26 |
| 165 | CO <inf>2</inf> -Laser Writing of Polymer Long-Period Waveguide Gratings. , 2008, , . | | 2 |
| 166 | Technique of applying the prism-coupler method for accurate measurement of the effective indices of channel waveguides. Optical Engineering, 2008, 47, 034601. | 1.0 | 19 |
| 167 | Dynamics in the writing of long-period gratings in boron-doped fibers by CO <inf>2</inf> -laser pulses. , 2008, , . | | 0 |
| 168 | High-sensitivity temperature-independent strain sensor based on a long-period fiber grating with a CO 2 -laser engraved rotary structure. , 2008, , . | | 1 |
| 169 | Development of Long-Period Fiber Grating Coupling Devices. , 2008, , . | | 0 |
| 170 | Mach-Zehnder Electro-Optic Modulator Based on Epitaxial Ba _{0.7} Sr _{0.3} TiO ₃ Thin Films. Ferroelectrics, 2007, 357, 109-114. | 0.6 | 2 |
| 171 | Disappearance of modes in planar Bragg waveguides. Optics Letters, 2007, 32, 2369. | 3.3 | 5 |
| 172 | Symmetric 3 \times 3 optical coupler using three parallel long-period fiber gratings. Optics Express, 2007, 15, 6494. | 3.4 | 14 |
| 173 | Light coupling between two parallel CO_2-laser written long-period fiber gratings. Optics Express, 2007, 15, 17645. | 3.4 | 47 |
| 174 | Characterization of Ultrathin Dielectric Films With the Prism-Coupler Method. Journal of Lightwave Technology, 2007, 25, 1206-1212. | 4.6 | 10 |
| 175 | Characterization of Single-Mode Fiber With Fiber Bragg Gratings for the Design of Long-Period Gratings. Journal of Lightwave Technology, 2007, 25, 2129-2134. | 4.6 | 5 |
| 176 | Characterization of Cladding Modes for the Design of Long-Period Fiber Gratings., 2007,,. | | 0 |
| 177 | Effects of intrapulse stimulated Raman scattering on short pulse propagation in a nonlinear two-core fiber. Applied Physics B: Lasers and Optics, 2007, 87, 45-52. | 2.2 | 4 |
| 178 | CO/sub 2/-laser-induced long-period gratings in graded-index multimode fibers for sensor applications. IEEE Photonics Technology Letters, 2006, 18, 190-192. | 2.5 | 21 |
| 179 | Broad-band optical coupler based on evanescent-field coupling between three parallel long-period fiber gratings. IEEE Photonics Technology Letters, 2006, 18, 229-231. | 2.5 | 11 |
| 180 | Band-rejection filter with widely tunable center wavelength and contrast using metal long-period grating on polymer waveguide. IEEE Photonics Technology Letters, 2006, 18, 1109-1111. | 2.5 | 32 |

| # | Article | IF | Citations |
|-----|---|-----|-----------|
| 181 | Fiber-Bragg-grating cavity sensor interrogated with a self-seeded fabry-Perot laser diode. IEEE Photonics Technology Letters, 2006, 18, 2153-2155. | 2.5 | 13 |
| 182 | Condition for the realization of a temperature-insensitive long-period waveguide grating. Optics Letters, 2006, 31, 2716. | 3.3 | 18 |
| 183 | Widely tunable long-period waveguide grating couplers. Optics Express, 2006, 14, 12644. | 3.4 | 44 |
| 184 | Widely tunable optical bandpass filter by use of polymer long-period waveguide gratings. Applied Optics, 2006, 45, 2755. | 2.1 | 33 |
| 185 | Design and fabrication of a broadband polymer vertically coupled optical switch. Journal of Lightwave Technology, 2006, 24, 904-911. | 4.6 | 23 |
| 186 | Transfer-matrix method for the analysis of two parallel dissimilar nonuniform long-period fiber gratings. Journal of Lightwave Technology, 2006, 24, 1008-1018. | 4.6 | 13 |
| 187 | Design of long-period waveguide grating filter by control of waveguide cladding profile. Journal of Lightwave Technology, 2006, 24, 3540-3546. | 4.6 | 10 |
| 188 | Analysis of long-period waveguide grating arrays. Journal of Lightwave Technology, 2006, 24, 3856-3863. | 4.6 | 13 |
| 189 | Optical rib waveguide based on epitaxial Ba0.7Sr0.3TiO3 thin film grown on MgO. Thin Solid Films, 2006, 510, 329-333. | 1.8 | 16 |
| 190 | Leaky optical waveguide for high power applications. Applied Physics B: Lasers and Optics, 2006, 85, 11-16. | 2.2 | 15 |
| 191 | Polarization-insensitive polymer waveguide Bragg gratings. Microwave and Optical Technology Letters, 2006, 48, 334-338. | 1.4 | 9 |
| 192 | CO/sub 2/-laser fabricated long-period grating sensors in graded-index multimode fibers. , 2006, , . | | 0 |
| 193 | Radial Effective Index Method for the Analysis of Microstructured Fibers. , 2006, , 83-90. | | 1 |
| 194 | Fiber-bragg-grating force sensor based on a wavelength switching actively mode-locked fiber laser. , 2005, , . | | 1 |
| 195 | Interrogation of fiber Bragg grating sensors using dual-wavelength pulses generated from a self-seeded Fabry-Perot laser diode. , 2005, , . | | 0 |
| 196 | Properties of PCF-based long period gratings. , 2005, , . | | 3 |
| 197 | Generation of multiwavelength picosecond pulses using a self-seeded Fabry-Perot laser diode and a spectrum-split fiber Bragg grating. , 2005, , . | | 0 |
| 198 | Analysis of apodized phase-shifted long-period fiber gratings. Optics Communications, 2005, 244, 233-243. | 2.1 | 42 |

| # | Article | IF | Citations |
|-----|---|-----|-----------|
| 199 | Design and fabrication of a three-dimensional polymer optical waveguide polarization splitter. Optics Communications, 2005, 250, 297-301. | 2.1 | 13 |
| 200 | Interrogation of fiber Bragg grating displacement/bending sensors using dual-wavelength pulses generated from a self-seeded Fabry-Perot laser diode. Optical Engineering, 2005, 44, 114401. | 1.0 | 2 |
| 201 | Refractive-index profiling of single-mode graded-index optical planar waveguides by the inverse Wentzel-Kramers-Brillouin method with improved accuracy. Optical Engineering, 2005, 44, 054601. | 1.0 | 5 |
| 202 | THEORY OF PULSE PROPAGATION IN OPTICAL DIRECTIONAL COUPLERS. Journal of Nonlinear Optical Physics and Materials, 2005, 14, 133-147. | 1.8 | 9 |
| 203 | Pulsed Laser Deposition of Ba0.6Sr0.4TiO3 Thin Films and Their Optical Properties. Integrated Ferroelectrics, 2005, 69, 443-451. | 0.7 | 2 |
| 204 | UV-written buried waveguide devices in epoxy-coated benzocyclobutene., 2005,,. | | 1 |
| 205 | Temperature sensitivity of a long-period waveguide grating in a channel waveguide. Applied Physics Letters, 2005, 86, 241115. | 3.3 | 36 |
| 206 | Generation of picosecond pulses at five close wavelengths by use of a self-seeded Fabry–Perot laser diode and a spectrum-split fiber Bragg grating. Applied Optics, 2005, 44, 2895. | 2.1 | 5 |
| 207 | Fiber-Bragg-grating force sensor based on a wavelength-switching actively mode-locked erbium-doped fiber laser. Applied Optics, 2005, 44, 4822. | 2.1 | 12 |
| 208 | Microbend-induced mode coupling in a graded-index multimode fiber. Applied Optics, 2005, 44, 7394. | 2.1 | 44 |
| 209 | Analysis and design of long-period waveguide-grating couplers. Journal of Lightwave Technology, 2005, 23, 4363-4373. | 4.6 | 22 |
| 210 | Long-period gratings in polymer ridge waveguides. Optics Express, 2005, 13, 1150. | 3.4 | 25 |
| 211 | Fiber-Bragg-grating force sensor based on a wavelength-switched self-seeded Fabry-Pe/spl acute/rot laser diode. IEEE Photonics Technology Letters, 2005, 17, 450-452. | 2.5 | 18 |
| 212 | UV-written long-period gratings on polymer waveguides. IEEE Photonics Technology Letters, 2005, 17, 594-596. | 2.5 | 45 |
| 213 | Polarization dependence in polymer waveguide directional couplers. IEEE Photonics Technology Letters, 2005, 17, 1465-1467. | 2.5 | 6 |
| 214 | Tailoring the transmission characteristics of polymer long-period waveguide gratings by UV irradiation. IEEE Photonics Technology Letters, 2005, 17, 2340-2342. | 2.5 | 12 |
| 215 | Fiber Bragg-grating incorporated microbend sensor for simultaneous mechanical parameter and temperature measurement. IEEE Photonics Technology Letters, 2005, 17, 2697-2699. | 2.5 | 7 |
| 216 | Soliton interaction in a two-core optical fiber. Optics Communications, 2004, 229, 431-439. | 2.1 | 60 |

| # | Article | IF | CITATIONS |
|-----|---|-----|-----------|
| 217 | Long-Period Waveguide Gratings. Japanese Journal of Applied Physics, 2004, 43, 5690-5696. | 1.5 | 15 |
| 218 | Multiplexing of Temperature-Compensated Fiber-Bragg-Grating Magnetostrictive Sensors With a Dual-Wavelength Pulse Laser. IEEE Photonics Technology Letters, 2004, 16, 572-574. | 2.5 | 16 |
| 219 | Generation of Dual-Wavelength Picosecond Pulses From a Self-Seeded Fabry–PÉrot Laser Diode and a Polarization-Maintaining Fiber Bragg Grating. IEEE Photonics Technology Letters, 2004, 16, 1742-1744. | 2.5 | 23 |
| 220 | Birefringence characteristics of benzocyclobutene rib optical waveguides. Electronics Letters, 2004, 40, 372. | 1.0 | 14 |
| 221 | Scaling property and multi-resonance of PCF-based long period gratings. Optics Express, 2004, 12, 6252. | 3.4 | 18 |
| 222 | Analysis of Two Parallel Long-Period Fiber Gratings. Journal of Lightwave Technology, 2004, 22, 1358-1366. | 4.6 | 55 |
| 223 | Propagation of short pulses in an active nonlinear two-core optical fiber. IEEE Journal of Quantum Electronics, 2004, 40, 1597-1602. | 1.9 | 18 |
| 224 | Temperature compensation for a fiber-Bragg-grating-based magnetostrictive sensor. Microwave and Optical Technology Letters, 2003, 36, 211-213. | 1.4 | 13 |
| 225 | Evaluation of intermodal dispersion in a two-core fiber with non-identical cores. Optics Communications, 2003, 219, 171-176. | 2.1 | 14 |
| 226 | Birefringence in benzocyclobutene strip optical waveguides. IEEE Photonics Technology Letters, 2003, 15, 700-702. | 2.5 | 32 |
| 227 | Widely tunable long-period gratings fabricated in polymer-clad ion-exchanged glass waveguides. IEEE Photonics Technology Letters, 2003, 15, 1094-1096. | 2.5 | 81 |
| 228 | Generation of dual-wavelength picosecond pulses with close wavelength separation from a self-seeded Fabry-Perot laser diode. IEEE Photonics Technology Letters, 2003, 15, 1452-1454. | 2.5 | 16 |
| 229 | Analysis of corrugated long-period gratings in slab waveguides and their polarization dependence. Journal of Lightwave Technology, 2003, 21, 3399-3405. | 4.6 | 67 |
| 230 | Holey optical fiber with circularly distributed holes analyzed by the radial effective-index method. Optics Letters, 2003, 28, 2449. | 3.3 | 24 |
| 231 | Temperature-compensated fiber-Bragg-grating-based magnetostrictive sensor for dc and ac currents. Optical Engineering, 2003, 42, 1906. | 1.0 | 47 |
| 232 | Triangular-shaped bulk-optic glass sensor for simultaneous measurement of three ac currents. Optical Engineering, 2003, 42, 421. | 1.0 | 0 |
| 233 | Magneto-optical electric-current sensor with enhanced sensitivity. Measurement Science and Technology, 2002, 13, N61-N63. | 2.6 | 17 |
| 234 | Large mode area single-mode fiber: a modified segmented cladding fiber. , 2002, , . | | 0 |

| # | Article | IF | Citations |
|-----|---|-----|-----------|
| 235 | Long-period gratings in planar optical waveguides. Applied Optics, 2002, 41, 6351. | 2.1 | 94 |
| 236 | A wide-angle X-junction in polymer using truncated-structural branches (TSB). Journal of Lightwave Technology, 2002, 20, 86-91. | 4.6 | 13 |
| 237 | Study of polarization-dependent coupling in optical waveguide directional couplers by the effective-index method with built-in perturbation correction. Journal of Lightwave Technology, 2002, 20, 1018-1026. | 4.6 | 25 |
| 238 | Temperature compensation of long-period fiber grating for refractive-index sensing with bending effect. IEEE Photonics Technology Letters, 2002, 14, 361-362. | 2.5 | 86 |
| 239 | Soliton states in a nonlinear directional coupler with intermodal dispersion. Physics Letters, Section A: General, Atomic and Solid State Physics, 2002, 301, 27-34. | 2.1 | 15 |
| 240 | Thermal effects on the transmission spectra of long-period fiber gratings. Optics Communications, 2002, 208, 321-327. | 2.1 | 96 |
| 241 | Recent Advances in the Analysis of Long-Period Fibre Gratings. , 2002, , . | | 0 |
| 242 | Polarimetric four-wave mixing in a single-mode fiber. IEEE Photonics Technology Letters, 2001, 13, 803-805. | 2.5 | 2 |
| 243 | Gain flattening of an erbium-doped fiber amplifier using a high-birefringence fiber loop mirror. IEEE Photonics Technology Letters, 2001, 13, 942-944. | 2.5 | 43 |
| 244 | Fast wavelength tuning of a self-seeded Fabry-Perot laser diode with a Fabry-Perot semiconductor filter. IEEE Photonics Technology Letters, 2001, 13, 1364-1366. | 2.5 | 10 |
| 245 | Propagation characteristics of a segmented cladding fiber. Optics Letters, 2001, 26, 491. | 3.3 | 61 |
| 246 | Design of polarization-insensitive Bragg gratings in zero-birefringence ridge waveguides. IEEE Journal of Quantum Electronics, 2001, 37, 1138-1145. | 1.9 | 22 |
| 247 | <title>Temperature-insensitive fiber-Bragg-grating-based vibration sensor</title> ., 2001, 4317, 585. | | 1 |
| 248 | A push-pull digital optical switch (DOS) in polymer using truncated-structuralX-branches (TSXB). Microwave and Optical Technology Letters, 2001, 30, 208-211. | 1.4 | 0 |
| 249 | The WDM performance of compactX-junction switches in polymer. Microwave and Optical Technology Letters, 2001, 28, 423-426. | 1.4 | 2 |
| 250 | High-sensitivity pressure sensor using a shielded polymer-coated fiber Bragg grating. IEEE Photonics Technology Letters, 2001, 13, 618-619. | 2.5 | 144 |
| 251 | Simultaneous existence of a multiplicity of stable and unstable solitons in dissipative systems. Physics Letters, Section A: General, Atomic and Solid State Physics, 2001, 291, 115-123. | 2.1 | 48 |
| 252 | New design of a detachable bulk-optic Faraday effect current clamp. Optical Engineering, 2001, 40, 914. | 1.0 | 7 |

| # | Article | IF | Citations |
|-----|--|-----|-----------|
| 253 | Temperature-insensitive fiber-Bragg-grating-based vibration sensor. Optical Engineering, 2001, 40, 2582. | 1.0 | 33 |
| 254 | <title>Interrogation of fiber Bragg grating sensors with a fiber grating filter tuned by a cantilever beam <math display="inline"></math> /title>. , 2001, , .</td><td></td><td>0</td></tr><tr><td>255</td><td>Tunable long-period fiber gratings for EDFA gain and ASE equalization. Microwave and Optical Technology Letters, 2000, 25, 181-184.</td><td>1.4</td><td>37</td></tr><tr><td>256</td><td>Calculation of confinement factors for multiple-quantum-well optical amplifiers by the effective-index model. Microwave and Optical Technology Letters, 2000, 25, 275-278.</td><td>1.4</td><td>1</td></tr><tr><td>257</td><td>Tunable fiber attenuators for channel power equalization in WDM systems. Microwave and Optical Technology Letters, 2000, 26, 1-4.</td><td>1.4</td><td>3</td></tr><tr><td>258</td><td>A digital optical switch (DOS) in polymer using truncated-structuralX-branches (TSXB). Microwave and Optical Technology Letters, 2000, 27, 229-233.</td><td>1.4</td><td>3</td></tr><tr><td>259</td><td>A polarization-compensated EDFA gain equalizer. Microwave and Optical Technology Letters, 2000, 27, 419-422.</td><td>1.4</td><td>6</td></tr><tr><td>260</td><td>Experimental demonstration of cross-polarisation mixing of a laser beam and a spectrum of light in a single-mode optical fibre. Optics Communications, 2000, 176, 101-104.</td><td>2.1</td><td>3</td></tr><tr><td>261</td><td>New design of optical electric-current sensor for sensitivity improvement. IEEE Transactions on Instrumentation and Measurement, 2000, 49, 418-423.</td><td>4.7</td><td>13</td></tr><tr><td>262</td><td>Simultaneous pressure and temperature measurement with polymer-coated fibre Bragg grating. Electronics Letters, 2000, 36, 564.</td><td>1.0</td><td>121</td></tr><tr><td>263</td><td>Generation of wavelength-tunable single-mode picosecond pulses from a self-seeded gain-switched Fabry–Perot laser diode with a high-birefringence fiber loop mirror. Applied Physics Letters, 2000, 76, 3676-3678.</td><td>3.3</td><td>24</td></tr><tr><td>264</td><td>Fast accurate wavelength switching of an erbium-doped fiber laser with a Fabry–Perot semiconductor filter and fiber Bragg gratings. Applied Physics Letters, 2000, 77, 4268-4270.</td><td>3.3</td><td>3</td></tr><tr><td>265</td><td>Analysis of etched long-period fibre grating and its response to external refractive index. Electronics Letters, 2000, 36, 966.</td><td>1.0</td><td>167</td></tr><tr><td>266</td><td>Coupling between two parallel long-period fibre gratings. Electronics Letters, 2000, 36, 1408.</td><td>1.0</td><td>54</td></tr><tr><td>267</td><td>Refractive-index profiling of graded-index planar waveguides from effective indexes measured with different external refractive indexes. Journal of Lightwave Technology, 2000, 18, 1412-1417.</td><td>4.6</td><td>22</td></tr><tr><td>268</td><td>Phase drift compensation for electric current sensor employing a twisted fiber or a spun highly birefringent fiber. IEEE Journal of Selected Topics in Quantum Electronics, 2000, 6, 803-809.</td><td>2.9</td><td>9</td></tr><tr><td>269</td><td>Design of waveguide structures for polarization-insensitive optical amplification. IEEE Journal of Quantum Electronics, 2000, 36, 1243-1250.</td><td>1.9</td><td>5</td></tr><tr><td>270</td><td>Multiwavelength erbium-doped fibre laser based on a high-birefringence fibre loop mirror. Electronics Letters, 2000, 36, 1609.</td><td>1.0</td><td>143</td></tr></tbody></table></title> | | |

| # | Article | IF | Citations |
|-----|--|-----|-----------|
| 271 | A novel tunable all-optical incoherent negative-tap fiber-optic transversal filter based on a DFB laser diode and fiber Bragg gratings. IEEE Photonics Technology Letters, 2000, 12, 1207-1209. | 2.5 | 55 |
| 272 | Self-seeding of Fabry-Perot laser diode for generating wavelength-tunable chirp-compensated single-mode pulses with high-sidemode suppression ratio. IEEE Photonics Technology Letters, 2000, 12, 1441-1443. | 2.5 | 26 |
| 273 | The Effect of Radiation on Transmission of Quasi-Periodic Multi-Layer Planar Dielectric Gratings. Journal of Infrared, Millimeter and Terahertz Waves, 1999, 20, 681-698. | 0.6 | 4 |
| 274 | A wide-angle polymeric Y-junction using gradient-index (GRIN) zones. Microwave and Optical Technology Letters, 1999, 22, 126-129. | 1.4 | 5 |
| 275 | A novel wide-angle polymericX-junction using truncated-structural branches (TSB). Microwave and Optical Technology Letters, 1999, 22, 197-200. | 1.4 | 4 |
| 276 | Switching dynamics of short optical pulses in a nonlinear directional coupler. IEEE Journal of Quantum Electronics, 1999, 35, 79-83. | 1.9 | 44 |
| 277 | Theory of zero-birefringence multiple-quantum-well optical waveguides. IEEE Journal of Quantum Electronics, 1999, 35, 1554-1564. | 1.9 | 7 |
| 278 | Effective-index method with built-in perturbation correction for the vector modes of rectangular-core optical waveguides. Journal of Lightwave Technology, 1999, 17, 716-722. | 4.6 | 22 |
| 279 | <title>Novel temperature compensation techniques for fiber Bragg gratings-based magnetostrictive sensors /title>., 1999, 3897, 87.</td><td></td><td>3</td></tr><tr><td>280</td><td>Wavelength tuning in self-seeded gain-switched Fabry-Perot laser diode with Moirelegrating. Electronics Letters, 1999, 35, 2209.</td><td>1.0</td><td>11</td></tr><tr><td>281</td><td>Analysis of phase-shifted long-period fiber gratings. IEEE Photonics Technology Letters, 1998, 10, 1596-1598.</td><td>2.5</td><td>91</td></tr><tr><td>282</td><td>Electrode optimization for high-speed traveling-wave integrated optic modulators. Journal of Lightwave Technology, 1998, 16, 232-238.</td><td>4.6</td><td>34</td></tr><tr><td>283</td><td>Design of optical strip-loaded waveguides with zero modal birefringence. Journal of Lightwave Technology, 1998, 16, 1240-1248.</td><td>4.6</td><td>25</td></tr><tr><td>284</td><td>Design of zero-birefringence semiconductor waveguides., 1998,,.</td><td></td><td>4</td></tr><tr><td>285</td><td>An electric-current sensor employing twisted fibre with compensation for temperature and polarization fluctuations. Measurement Science and Technology, 1997, 8, 606-610.</td><td>2.6</td><td>6</td></tr><tr><td>286</td><td>Temperature sensitivity of coated stress-induced birefringent optical fibers. Optical Engineering, 1997, 36, 999.</td><td>1.0</td><td>10</td></tr><tr><td>287</td><td>Propagation of short optical pulses in directional couplers with Kerr nonlinearity. Journal of the Optical Society of America B: Optical Physics, 1997, 14, 1437.</td><td>2.1</td><td>85</td></tr><tr><td>288</td><td>Coupled-mode equations for pulse switching in parallel waveguides. IEEE Journal of Quantum Electronics, 1997, 33, 950-954.</td><td>1.9</td><td>48</td></tr></tbody></table></title> | | |

| # | Article | IF | Citations |
|-----|--|-----|-----------|
| 289 | Design of modified phase reversal electrode in broad-band electrooptic modulators at 100 GHz. IEEE Transactions on Microwave Theory and Techniques, 1997, 45, 142-145. | 4.6 | 5 |
| 290 | Design and analysis of coplanar waveguide optical modulator using finite element method. Journal of Infrared, Millimeter and Terahertz Waves, 1997, 18, 875-887. | 0.6 | 1 |
| 291 | Experimental separation of different kinds of optical losses in integrated electro-optic modulators. Microwave and Optical Technology Letters, 1997, 14, 305-307. | 1.4 | 0 |
| 292 | Refractive-index profiling of graded-index planar waveguides from effective indexes measured for both mode types and at different wavelengths. Journal of Lightwave Technology, 1996, 14, 827-832. | 4.6 | 17 |
| 293 | Effective-index method with built-in perturbation correction for integrated optical waveguides. Journal of Lightwave Technology, 1996, 14, 223-228. | 4.6 | 17 |
| 294 | Rib waveguides with degenerate polarised modes. Electronics Letters, 1996, 32, 1098. | 1.0 | 14 |
| 295 | Analysis of the effective-index method for the vector modes of rectangular-core dielectric waveguides. IEEE Transactions on Microwave Theory and Techniques, 1996, 44, 692-700. | 4.6 | 44 |
| 296 | <title>Effective-index analysis of optical waveguides</title> ., 1995, , . | | 18 |
| 297 | Simplified universal dispersion curves for graded-index planar waveguides based on the WKB method. Journal of Lightwave Technology, 1995, 13, 158-162. | 4.6 | 6 |
| 298 | Review of numerical and approximate methods for the modal analysis of general optical dielectric waveguides. Optical and Quantum Electronics, 1994, 26, S113-S134. | 3.3 | 153 |
| 299 | Iterative methods and stability of TE modes of nonlinear planar waveguides. Optics Communications, 1994, 109, 59-64. | 2.1 | 7 |
| 300 | Determination of equivalent step-index fibres from Petermann spot sizes. Electronics Letters, 1994, 30, 1881-1882. | 1.0 | 0 |
| 301 | Stimulated Raman scattering in a multimode optical fiber: self-focusing or mode competition?. Optics Communications, 1993, 95, 235-238. | 2.1 | 8 |
| 302 | Ultraviolet photolytic-induced changes in optical fibers: the thermal expansion coefficient. Optics Letters, 1993, 18, 965. | 3.3 | 17 |
| 303 | Effects of elastic inhomogeneity on the intrinsic birefringence in a stress-induced birefringent optical fiber: a simple theory. Journal of Lightwave Technology, 1992, 10, 12-16. | 4.6 | 5 |
| 304 | Coupled-zigzag-wave theory for guided waves in slab waveguide arrays. Journal of Lightwave Technology, 1992, 10, 1380-1387. | 4.6 | 13 |
| 305 | Stimulated Raman scattering in a multimode optical fiber: evolution of modes in Stokes waves. Optics Letters, 1992, 17, 352. | 3.3 | 62 |
| 306 | Effective-index method for the analysis of optical waveguide couplers and arrays: an asymptotic theory. Journal of Lightwave Technology, 1991, 9, 62-72. | 4.6 | 39 |

| # | Article | IF | CITATIONS |
|-----|--|-----|-----------|
| 307 | Comments, with reply, on 'Determination of two-dimensional optical waveguide index distribution function parameters from effective indexes' by T. Shiozawa et al. Journal of Lightwave Technology, 1991, 9, 414-415. | 4.6 | 2 |
| 308 | Design of highly birefringent fibers to optimize or minimize pressure-induced birefringence. IEEE Photonics Technology Letters, 1991, 3, 654-656. | 2.5 | 14 |
| 309 | Dispersion characteristics of strip dielectric waveguides. IEEE Transactions on Microwave Theory and Techniques, 1991, 39, 349-352. | 4.6 | 27 |
| 310 | Perturbation analysis of finitely clad optical waveguides and couplers. Optical and Quantum Electronics, 1990, 22, 239-257. | 3.3 | 2 |
| 311 | Detection of high-frequency ultrasound with a polarization-maintaining fiber. Journal of Lightwave Technology, 1990, 8, 1221-1227. | 4.6 | 32 |
| 312 | The characterization of highâ€frequency ultrasonic fields using a polarimetric optical fiber sensor. Journal of Applied Physics, 1989, 66, 1565-1570. | 2.5 | 25 |
| 313 | Use of a fibre-optic hydrophone in measuring acoustic parameters of high power hyperthermia transducers. Physics in Medicine and Biology, 1989, 34, 1609-1622. | 3.0 | 12 |
| 314 | Acousto-optical modulation method for measuring the beat length of a linearly birefringent optical fiber. Optics Letters, 1989, 14, 1029. | 3.3 | 7 |
| 315 | Stress-induced birefringence fibers designed for single-polarization single-mode operation. Journal of Lightwave Technology, 1989, 7, 436-441. | 4.6 | 44 |
| 316 | Dual-sensor technique for extending the dynamic range of a fiber-optic interferometric sensor. Optics Letters, 1988, 13, 850. | 3.3 | 4 |
| 317 | Geometrical birefringence in a class of step-index fiber. Journal of Lightwave Technology, 1987, 5, 737-744. | 4.6 | 18 |
| 318 | Finite-element analysis of optical fibres with iterative treatment of the infinite 2-D space. Optical and Quantum Electronics, 1985, 17, 381-391. | 3.3 | 39 |
| 319 | Construction of refractive-index profiles of planar dielectric waveguides from the distribution of effective indexes. Journal of Lightwave Technology, 1985, 3, 385-391. | 4.6 | 305 |
| 320 | Finite element method for cutoff frequencies of weakly guiding fibres of arbitrary cross-section. Optical and Quantum Electronics, 1984, 16, 487-493. | 3.3 | 41 |
| 321 | Design of a new thin-film electro-optic switch. Optics and Laser Technology, 1983, 15, 83-90. | 4.6 | 2 |
| 322 | Analysis of a holey optical fiber with circularly distributed holes. , 0, , . | | 0 |