

Zhengtao Zhu

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/6850785/publications.pdf>

Version: 2024-02-01

81
papers

6,049
citations

117625

34
h-index

69250

77
g-index

84
all docs

84
docs citations

84
times ranked

8577
citing authors

| # | ARTICLE | IF | CITATIONS |
|----|---|------|-----------|
| 1 | Biomimetic hydrophilic foam with micro/nano-scale porous hydrophobic surface for highly efficient solar-driven vapor generation. <i>Science China Materials</i> , 2022, 65, 1057-1067. | 6.3 | 16 |
| 2 | Separator with high ionic conductivity and good stability prepared from keratin fibers for supercapacitor applications. <i>Chemical Engineering Journal</i> , 2022, 444, 136537. | 12.7 | 15 |
| 3 | Efficient Triboelectric Nanogenerator (TENG) Output Management for Improving Charge Density and Reducing Charge Loss. <i>ACS Applied Electronic Materials</i> , 2021, 3, 532-549. | 4.3 | 29 |
| 4 | Synergy of Porous Structure and Microstructure in Piezoresistive Material for High-Performance and Flexible Pressure Sensors. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 19211-19220. | 8.0 | 123 |
| 5 | Electrospun nanofibers for tactile sensors. , 2021, , 159-196. | | 2 |
| 6 | Recycled high performance polyester fibers for cement designed from micromechanics theory. <i>Journal of Polymer Research</i> , 2021, 28, 1. | 2.4 | 1 |
| 7 | Preparation and properties of melt-spun poly(fluorinated ethylene-propylene)/graphene composite fibers. <i>Polymer Composites</i> , 2020, 41, 233-243. | 4.6 | 9 |
| 8 | Preparation of keratin/PET nanofiber membrane and its high adsorption performance of Cr(VI). <i>Science of the Total Environment</i> , 2020, 710, 135546. | 8.0 | 42 |
| 9 | Micropatterned Biphasic Nanocomposite Platform for Maintaining Chondrocyte Morphology. <i>ACS Applied Materials & Interfaces</i> , 2020, 12, 14814-14824. | 8.0 | 9 |
| 10 | A porous and air gap elastomeric dielectric layer for wearable capacitive pressure sensor with high sensitivity and a wide detection range. <i>Journal of Materials Chemistry C</i> , 2020, 8, 11468-11476. | 5.5 | 73 |
| 11 | Three-dimensional monolithic porous structures assembled from fragmented electrospun nanofiber mats/membranes: Methods, properties, and applications. <i>Progress in Materials Science</i> , 2020, 112, 100656. | 32.8 | 84 |
| 12 | Nanomaterial Design for Efficient Solar-Driven Steam Generation. <i>ACS Applied Energy Materials</i> , 2019, 2, 6112-6126. | 5.1 | 33 |
| 13 | Preparation of Ag NWs and Ag NWs@PDMS stretchable sensors based on rapid polyol method and semi-dry process. <i>Journal of Alloys and Compounds</i> , 2019, 803, 332-340. | 5.5 | 24 |
| 14 | Recent Advances in Flexible and Wearable Pressure Sensors Based on Piezoresistive 3D Monolithic Conductive Sponges. <i>ACS Applied Materials & Interfaces</i> , 2019, 11, 6685-6704. | 8.0 | 261 |
| 15 | High-strength electrospun carbon nanofibrous mats prepared via rapid stabilization as frameworks for Li-ion battery electrodes. <i>Journal of Materials Science</i> , 2019, 54, 11574-11584. | 3.7 | 14 |
| 16 | Tunable Water Delivery in Carbon-Coated Fabrics for High-Efficiency Solar Vapor Generation. <i>ACS Applied Materials & Interfaces</i> , 2019, 11, 46938-46946. | 8.0 | 36 |
| 17 | A Novel Single-Phase to Three-Phase AC-AC Converter. , 2019, , . | | 0 |
| 18 | Halloysite nanotubes sponges with skeletons made of electrospun nanofibers as innovative dye adsorbent and catalyst support. <i>Chemical Engineering Journal</i> , 2019, 360, 280-288. | 12.7 | 26 |

| # | ARTICLE | IF | CITATIONS |
|----|--|------|-----------|
| 19 | Freestanding electrospun nanofibrous materials embedded in elastomers for stretchable strain sensors. , 2019, , . | | 1 |
| 20 | Flexible, Freestanding, and Functional SiO ₂ Nanofibrous Mat for Dye-Sensitized Solar Cell and Photocatalytic Dye Degradation. ACS Applied Nano Materials, 2018, 1, 1141-1149. | 5.0 | 29 |
| 21 | Flexible and Compressible PEDOT:PSS@Melamine Conductive Sponge Prepared via One-Step Dip Coating as Piezoresistive Pressure Sensor for Human Motion Detection. ACS Applied Materials & Interfaces, 2018, 10, 16077-16086. | 8.0 | 217 |
| 22 | One-Step Preparation of Highly Hydrophobic and Oleophilic Melamine Sponges via Metal-Ion-Induced Wettability Transition. ACS Applied Materials & Interfaces, 2018, 10, 6652-6660. | 8.0 | 87 |
| 23 | One-way water transport fabrics with hydrophobic rough surface formed in one-step electrospray. Materials Letters, 2018, 215, 110-113. | 2.6 | 18 |
| 24 | Preparation of the Au@TiO ₂ nanofibers by one-step electrospinning for the composite photoanode of dye-sensitized solar cells. Materials Chemistry and Physics, 2018, 208, 35-40. | 4.0 | 23 |
| 25 | Ultralight electrospun cellulose sponge with super-high capacity on absorption of organic compounds. Carbohydrate Polymers, 2018, 179, 164-172. | 10.2 | 45 |
| 26 | High-performance polyimide nanofibers reinforced polyimide nanocomposite films fabricated by co-electrospinning followed by hot-pressing. Journal of Applied Polymer Science, 2018, 135, 46849. | 2.6 | 25 |
| 27 | Effects of hydrogen bonding on starch granule dissolution, spinnability of starch solution, and properties of electrospun starch fibers. Polymer, 2018, 153, 643-652. | 3.8 | 33 |
| 28 | One-Way Water Transport Fabrics Based on Roughness Gradient Structure with No Low Surface Energy Substances. ACS Applied Materials & Interfaces, 2018, 10, 32792-32800. | 8.0 | 15 |
| 29 | Electrospinning preparation of a large surface area, hierarchically porous, and interconnected carbon nanofibrous network using polysulfone as a sacrificial polymer for high performance supercapacitors. RSC Advances, 2018, 8, 28480-28486. | 3.6 | 18 |
| 30 | Detection of glutaraldehyde in aqueous environments based on fluorescence quenching of a conjugated polymer with pendant protonated primary amino groups. Journal of Materials Chemistry C, 2017, 5, 5010-5017. | 5.5 | 11 |
| 31 | Fluorescence Quenching of a Conjugated Polymer by Synergistic Amine-Carboxylic Acid and π - π Interactions for Selective Detection of Aromatic Amines in Aqueous Solution. ACS Sensors, 2017, 2, 842-847. | 7.8 | 47 |
| 32 | Three-dimensional and ultralight sponges with tunable conductivity assembled from electrospun nanofibers for a highly sensitive tactile pressure sensor. Journal of Materials Chemistry C, 2017, 5, 10288-10294. | 5.5 | 74 |
| 33 | Scalable and Facile Preparation of Highly Stretchable Electrospun PEDOT:PSS@PU Fibrous Nonwovens toward Wearable Conductive Textile Applications. ACS Applied Materials & Interfaces, 2017, 9, 30014-30023. | 8.0 | 107 |
| 34 | An Innovative Approach for the Preparation of High-Performance Electrospun Poly(<i>p</i> -phenylene)-Based Polymer Nanofiber Belts. Macromolecules, 2017, 50, 9760-9772. | 4.8 | 6 |
| 35 | A highly stretchable strain sensor based on electrospun carbon nanofibers for human motion monitoring. RSC Advances, 2016, 6, 79114-79120. | 3.6 | 79 |
| 36 | Low-temperature seeding and hydrothermal growth of ZnO nanorod on poly(3,4-ethylene) Tj ETQq0 0 0 rgBT /Overlock 10 Tf,50 62 Td (| 2.6 | 20 |

| # | ARTICLE | IF | CITATIONS |
|----|--|------|-----------|
| 37 | Electrospun polyimide nanofibers and their applications. <i>Progress in Polymer Science</i> , 2016, 61, 67-103. | 24.7 | 332 |
| 38 | Flexible composite felt of electrospun TiO ₂ and SiO ₂ nanofibers infused with TiO ₂ nanoparticles for lithium ion battery anode. <i>Electrochimica Acta</i> , 2016, 190, 811-816. | 5.2 | 22 |
| 39 | Reduction of crack formation in TiO ₂ mesoporous films prepared from binder-free nanoparticle pastes via incorporation of electrospun SiO ₂ or TiO ₂ nanofibers for dye-sensitized solar cells. <i>Nano Energy</i> , 2015, 12, 794-800. | 16.0 | 25 |
| 40 | Electrospun ZnO/SiO ₂ hybrid nanofibrous mat for flexible ultraviolet sensor. <i>Applied Physics Letters</i> , 2014, 104, . | 3.3 | 27 |
| 41 | Mechanically flexible hybrid mat consisting of TiO ₂ and SiO ₂ nanofibers electrospun via dual spinnerets for photo-detector. <i>Materials Letters</i> , 2014, 120, 219-223. | 2.6 | 17 |
| 42 | Free-standing and mechanically flexible mats consisting of electrospun carbon nanofibers made from a natural product of alkali lignin as binder-free electrodes for high-performance supercapacitors. <i>Journal of Power Sources</i> , 2014, 247, 134-141. | 7.8 | 289 |
| 43 | Flexible, Transferable, and Thermal-Durable Dye-Sensitized Solar Cell Photoanode Consisting of TiO ₂ Nanoparticles and Electrospun TiO ₂ /SiO ₂ Nanofibers. <i>ACS Applied Materials & Interfaces</i> , 2014, 6, 15925-15932. | 8.0 | 41 |
| 44 | Effects of Surface Modification on Dye-Sensitized Solar Cell Based on an Organic Dye with Naphtho[2,1-b:3,4-b'€²]dithiophene as the Conjugated Linker. <i>ACS Applied Materials & Interfaces</i> , 2014, 6, 1926-1932. | 8.0 | 8 |
| 45 | Fabrication and evaluation of dye-sensitized solar cells with photoanodes based on electrospun TiO ₂ nanotubes. <i>Materials Letters</i> , 2013, 106, 115-118. | 2.6 | 17 |
| 46 | Dye-sensitized solar cells based on organic dyes with naphtho[2,1-b:3,4-b'€²]dithiophene as the conjugated linker. <i>Journal of Materials Chemistry A</i> , 2013, 1, 13328-13336. | 10.3 | 26 |
| 47 | Effects of humidity on the ultraviolet nanosensors of aligned electrospun ZnO nanofibers. <i>RSC Advances</i> , 2013, 3, 6640. | 3.6 | 46 |
| 48 | Electron Transport and Recombination in Photoanode of Electrospun TiO ₂ Nanotubes for Dye-Sensitized Solar Cells. <i>Journal of Physical Chemistry C</i> , 2013, 117, 1641-1646. | 3.1 | 60 |
| 49 | Electrospun anatase-phase TiO ₂ nanofibers with different morphological structures and specific surface areas. <i>Journal of Colloid and Interface Science</i> , 2013, 398, 103-111. | 9.4 | 57 |
| 50 | SERS-active silver nanoparticles on electrospun nanofibers facilitated via oxygen plasma etching. <i>RSC Advances</i> , 2013, 3, 8998. | 3.6 | 51 |
| 51 | Electrospun carbon nanofibrous mats surface-decorated with Pd nanoparticles via the supercritical CO ₂ method for sensing of H ₂ . <i>RSC Advances</i> , 2012, 2, 10195. | 3.6 | 6 |
| 52 | Electrospun carbon nano-felt surface-attached with Pd nanoparticles for hydrogen sensing application. <i>Materials Letters</i> , 2012, 68, 133-136. | 2.6 | 36 |
| 53 | Photoluminescence anisotropy of uni-axially aligned electrospun conjugated polymer nanofibers of MEH-PPV and P3HT. <i>Journal of Materials Chemistry</i> , 2011, 21, 444-448. | 6.7 | 57 |
| 54 | Transient photocurrent and photovoltage studies on charge transport in dye sensitized solar cells made from the composites of TiO ₂ nanofibers and nanoparticles. <i>Applied Physics Letters</i> , 2011, 98, 082114. | 3.3 | 48 |

| # | ARTICLE | IF | CITATIONS |
|----|--|------|-----------|
| 55 | Electrical properties of electrospun carbon nanofibers. <i>Journal of Materials Science</i> , 2011, 46, 6453-6456. | 3.7 | 16 |
| 56 | Effects of surface modification on the fluorescence properties of conjugated polymer/ZnO nanocomposites. <i>Materials Chemistry and Physics</i> , 2010, 124, 417-421. | 4.0 | 36 |
| 57 | One-pot synthesis, characterization, and NH ₃ sensing of Pd/PEDOT:PSS nanocomposite. <i>Synthetic Metals</i> , 2010, 160, 1115-1118. | 3.9 | 21 |
| 58 | Composite of TiO ₂ nanofibers and nanoparticles for dye-sensitized solar cells with significantly improved efficiency. <i>Energy and Environmental Science</i> , 2010, 3, 1507. | 30.8 | 191 |
| 59 | Fluorescence studies of electrospun MEH-PPV/PEO nanofibers. <i>Synthetic Metals</i> , 2009, 159, 1454-1459. | 3.9 | 31 |
| 60 | Aligned electrospun ZnO nanofibers for simple and sensitive ultraviolet nanosensors. <i>Chemical Communications</i> , 2009, , 2568. | 4.1 | 67 |
| 61 | Defect Tolerance and Nanomechanics in Transistors that Use Semiconductor Nanomaterials and Ultrathin Dielectrics. <i>Advanced Functional Materials</i> , 2008, 18, 2535-2540. | 14.9 | 6 |
| 62 | Preparation, characterization, and encapsulation/release studies of a composite nanofiber mat electrospun from an emulsion containing poly(lactic-co-glycolic acid). <i>Polymer</i> , 2008, 49, 5294-5299. | 3.8 | 73 |
| 63 | Bendable integrated circuits on plastic substrates by use of printed ribbons of single-crystalline silicon. <i>Applied Physics Letters</i> , 2007, 90, 213501. | 3.3 | 78 |
| 64 | Transparent flexible organic thin-film transistors that use printed single-walled carbon nanotube electrodes. <i>Applied Physics Letters</i> , 2006, 88, 113511. | 3.3 | 138 |
| 65 | High-speed mechanically flexible single-crystal silicon thin-film transistors on plastic substrates. <i>IEEE Electron Device Letters</i> , 2006, 27, 460-462. | 3.9 | 154 |
| 66 | Transfer printing by kinetic control of adhesion to an elastomeric stamp. <i>Nature Materials</i> , 2006, 5, 33-38. | 27.5 | 1,348 |
| 67 | Highly Bendable, Transparent Thin-Film Transistors That Use Carbon-Nanotube-Based Conductors and Semiconductors with Elastomeric Dielectrics. <i>Advanced Materials</i> , 2006, 18, 304-309. | 21.0 | 338 |
| 68 | Mechanically flexible thin-film transistors that use ultrathin ribbons of silicon derived from bulk wafers. <i>Applied Physics Letters</i> , 2006, 88, 213101. | 3.3 | 157 |
| 69 | Spin on dopants for high-performance single-crystal silicon transistors on flexible plastic substrates. <i>Applied Physics Letters</i> , 2005, 86, 133507. | 3.3 | 145 |
| 70 | Humidity sensors based on pentacene thin-film transistors. <i>Applied Physics Letters</i> , 2002, 81, 4643-4645. | 3.3 | 346 |
| 71 | Dimensionality Effects on the Optical Properties of (PO ₂) ₄ (WO ₃) _{2m} (m = 2, 4, 6, 7). <i>Chemistry of Materials</i> , 2002, 14, 2607-2615. | 6.7 | 8 |
| 72 | Optical studies of the $\text{K}^3\text{-(ET)}_2\text{SF}_5\text{RSO}_3$ (R = CH ₂ CF ₂ , CHF ₂ and CHF) system: chemical tuning of the counterion. <i>Synthetic Metals</i> , 2001, 120, 785-786. | 3.9 | 1 |

| # | ARTICLE | IF | CITATIONS |
|----|---|-----|-----------|
| 73 | Infrared and Optical Properties of $\hat{\Gamma}^2\hat{A}^{\sim}-(\text{ET})_2\text{SF}_5\text{CF}_2\text{SO}_3$: Evidence for a 45 K Spin-Peierls Transition. Chemistry of Materials, 2001, 13, 1326-1333. | 6.7 | 8 |
| 74 | Vibrational Properties of Monophosphate Tungsten Bronzes $(\text{PO}_2)_4(\text{WO}_3)_2m$ ($m = 4, 6$). Chemistry of Materials, 2001, 13, 2940-2944. | 6.7 | 6 |
| 75 | Far-infrared investigations of $\hat{\Gamma}$ - Mo_4O_{11} : Using a magnetic field to open the gap. Ferroelectrics, 2001, 249, 51-56. | 0.6 | 0 |
| 76 | Polarized optical reflectance and electronic structure of the charge-density-wave materials $\hat{\Gamma}$ - and $\hat{\Gamma}^3\hat{A}^{\sim}\text{Mo}_4\text{O}_{11}$. Physical Review B, 2000, 61, 10057-10065. | 3.2 | 11 |
| 77 | Optical Spectra and Electronic Band Structure Calculations of $\hat{\Gamma}^2\hat{A}^{\sim}\hat{A}^{\sim}-(\text{ET})_2\text{SF}_5\text{RSO}_3$ ($R = \text{CH}_2\text{CF}_2, \text{CHFCF}_2$). Chemistry of Materials, 2000, 12, 2490-2495. | 6.7 | 21 |
| 78 | Infrared studies of low-temperature symmetry breaking in the perhenate family of ET-based organic molecular conductors. Physical Review B, 1999, 60, 931-941. | 3.2 | 7 |
| 79 | Infrared Study of the Broken Symmetry Ground States in $\hat{\Gamma}$ - Mo_4O_{11} . Synthetic Metals, 1999, 103, 2238-2241. | 3.9 | 3 |
| 80 | Optical Properties of $\hat{\Gamma}^2\hat{A}^{\sim}\hat{A}^{\sim}-(\text{ET})_2\text{SF}_5\text{RSO}_3$ ($R = \text{CH}_2\text{CF}_2, \text{CHFCF}_2$): Changing Physical Properties by Chemical Tuning of the Counterion. Chemistry of Materials, 1999, 11, 3160-3165. | 6.7 | 15 |
| 81 | Optical Properties of a Supramolecular Assembly Containing Polydiacetylene. Chemistry of Materials, 1999, 11, 3275-3278. | 6.7 | 6 |