

Guo-Ping Bei

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/6852890/publications.pdf>

Version: 2024-02-01

34
papers

854
citations

361045
20
h-index

476904
29
g-index

35
all docs

35
docs citations

35
times ranked

673
citing authors

#	ARTICLE	IF	CITATIONS
1	Point contact abrasive wear behavior of MAX phase materials. <i>Ceramics International</i> , 2020, 46, 1722-1729.	2.3	14
2	Ab initio calculation of the evolution of $[\text{SiN}_4\text{O}_n]$ tetrahedron during $\text{Si}_3\text{N}_4(0001)$ surface oxidation. <i>Journal of the American Ceramic Society</i> , 2020, 103, 2808-2816.	1.9	4
3	Low-temperature oxidation-induced crack healing in $\text{Ti}_2\text{Al}_0.5\text{Sn}_0.5\text{Al}_2\text{O}_3$ composites. <i>International Journal of Applied Ceramic Technology</i> , 2019, 16, 1744-1751.	1.1	2
4	Adsorption and Reaction of Water on the $\text{AlN}(0001)$ Surface from First Principles. <i>Journal of Physical Chemistry C</i> , 2019, 123, 5460-5468.	1.5	17
5	Ultra-high temperature ablation behavior of MoAlB ceramics under an oxyacetylene flame. <i>Journal of the European Ceramic Society</i> , 2019, 39, 2010-2017.	2.8	48
6	Synthesis, crystal structure, microstructure and mechanical properties of $(\text{Ti}_1\text{-Zr})_3\text{SiC}_2$ MAX phase solid solutions. <i>Ceramics International</i> , 2019, 45, 1400-1408.	2.3	21
7	Autonomous high-temperature healing of surface cracks in Al_2O_3 containing Ti_2AlC particles. <i>Journal of the American Ceramic Society</i> , 2018, 101, 5684-5693.	1.9	24
8	Boron doping induced thermal conductivity enhancement of water-based 3C-Si(B)C nanofluids. <i>Nanotechnology</i> , 2018, 29, 355702.	1.3	2
9	Sintering and properties of mechanical alloyed $\text{Ti}_3\text{AlC}_2\text{-Cu}$ composites. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2017, 685, 154-158.	2.6	35
10	Synthesis of Al_4SiC_4 powders via carbothermic reduction: Reaction and grain growth mechanisms. <i>Journal of Advanced Ceramics</i> , 2017, 6, 351-359.	8.9	22
11	Toughening Mechanisms in Nanolayered MAX Phase Ceramics—A Review. <i>Materials</i> , 2017, 10, 366.	1.3	31
12	Preparation and mechanical properties of $\text{Ti}_x\text{Al}_{3-x}\text{CuNi}_2\text{Ti}$ hybrid composites by reactive pressureless sintering pre-alloyed $\text{Cu/Ti}_3\text{AlC}_2$ and Ni as precursor. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2016, 670, 351-356.	2.6	20
13	Crack healing induced electrical and mechanical properties recovery in a Ti_2SnC ceramic. <i>Journal of the European Ceramic Society</i> , 2016, 36, 25-32.	2.8	42
14	Influence of Ti_3SiC_2 Fiber Coating on Interface and Matrix Cracking in an SiC Fiber-Reinforced Polymer-Derived Ceramic. <i>Advanced Engineering Materials</i> , 2015, 17, 1142-1148.	1.6	5
15	Crack Healing in $\text{Ti}_2\text{Al}_0.5\text{Sn}_0.5\text{Al}_2\text{O}_3$ Composites. <i>Journal of the American Ceramic Society</i> , 2015, 98, 1604-1610.	1.9	25
16	A High-Temperature Neutron Diffraction and First-Principles Study of Ti_3AlC_2 and $\text{Ti}_3\text{Al}(\text{Al}_{0.8}\text{Sn}_{0.2})$ Solid Solution. <i>Journal of the American Ceramic Society</i> , 2014, 97, 570-576.	1.9	14
17	Preparation and mechanical properties of in situ TiCx-Ni (Si, Ti) alloy composites. <i>Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing</i> , 2014, 616, 214-218.	2.6	24
18	Oxidation Behavior of MAX Phase $\text{Ti}_2\text{Al}(\text{Al}_{1-x}\text{Sn}_x)$ Solid Solution. <i>Journal of the American Ceramic Society</i> , 2013, 96, 1359-1362.	1.9	58

#	ARTICLE	IF	CITATIONS
19	Formation Mechanisms of Ti ₃ SnC ₂ Nanolaminate Carbide Using Fe as Additive. Journal of the American Ceramic Society, 2013, 96, 3239-3242.	1.9	12
20	Pressure-enforced plasticity in MAX phases: from single grain to polycrystal investigation. Philosophical Magazine, 2013, 93, 1784-1801.	0.7	19
21	Compressive Behavior of Ti ₃ AlC ₂ and Ti ₃ Al _{0.8} Sn _{0.2} Phases at Room Temperature. Journal of the American Ceramic Society, 2013, 96, 567-576.	1.9	27
22	Synthesis, Characterization, and Intrinsic Hardness of Layered Nanolaminate Ti ₃ AlC ₂ and Ti ₃ Al _{0.8} Sn _{0.2} C ₂ Solid Solution. Journal of the American Ceramic Society, 2012, 95, 102-107.	1.9	62
23	Powder metallurgy processing and compressive properties of Ti ₃ AlC ₂ /Al composites. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2011, 530, 168-173.	2.6	68
24	Synthesis, Microstructure, and Mechanical Properties of Ti ₃ Sn(1-x)Al _x C ₂ MAX Phase Solid Solutions. International Journal of Applied Ceramic Technology, 2010, 7, 719-729.	1.1	59
25	Controlling the oriented growth of Ti ₂ SnC grains with carbon fiber as a reactive template in the Ti-Al-C system. Materials Research Bulletin, 2009, 44, 966-969.	2.7	2
26	The origin of driving force for the formation of Sn whiskers at room temperature. Journal of Materials Research, 2007, 22, 3226-3232.	1.2	16
27	Mechanically Activated Low-Temperature Synthesis of Ti ₂ SnC. Key Engineering Materials, 2007, 336-338, 955-957.	0.4	1
28	Synthesis and microstructure of Ti ₃ AlC ₂ by mechanically activated sintering of elemental powders. Ceramics International, 2007, 33, 169-173.	2.3	51
29	Synthesis of Ti ₂ SnC at low-temperature using mechanically activated sintering process. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2007, 457, 282-286.	2.6	23
30	Reaction mechanism for synthesis of Ti ₂ SnC. Materials Research Bulletin, 2007, 42, 1995-1998.	2.7	7
31	Formation of Ti ₃ AlC ₂ by mechanically induced self-propagating reaction in Ti-Al-C system at room temperature. Materials Science and Technology, 2006, 22, 667-672.	0.8	28
32	Bimodal Microstructure and Reaction Mechanism of Ti ₂ SnC Synthesized by a High-Temperature Reaction Using Ti/Sn/C and Ti/Sn/TiC Powder Compacts. Journal of the American Ceramic Society, 2006, 89, 3617-3623.	1.9	28
33	Synthesis and deformation microstructure of Ti ₃ SiAl _{0.2} C _{1.8} solid solution. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2006, 441, 202-205.	2.6	20
34	Synthesis of Ti ₂ SnC from Ti/Sn/TiC powder mixtures by pressureless sintering technique. Materials Letters, 2006, 60, 3530-3532.	1.3	24