

# Pavol Hvizdos

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/6958354/publications.pdf>

Version: 2024-02-01

122  
papers

1,857  
citations

279487

23  
h-index

301761

39  
g-index

128  
all docs

128  
docs citations

128  
times ranked

1655  
citing authors

#	ARTICLE	IF	CITATIONS
1	Effect of ZrC nanopowder addition in WC preforms on microstructure and properties of Wâ€“ZrC composites prepared by the displacive compensation of porosity (DCP) method. Journal of the Australian Ceramic Society, 2021, 57, 515-523.	1.1	3
2	Ceramic Matrix Composites With Carbon Nanophases: Development, Structure, Mechanical and Tribological Properties and Electrical Conductivity. , 2021, , 116-133.		4
3	Influence of the frequency and flow rate of a pulsating water jet on the wear damage of tantalum. Wear, 2021, 477, 203893.	1.5	17
4	Rotary friction welded C45 to 16NiCr6 steel rods: statistical optimization coupled to mechanical and microstructure approaches. International Journal of Advanced Manufacturing Technology, 2021, 116, 2285-2298.	1.5	15
5	Surface Topography Analysis of Mg-Based Composites with Different Nanoparticle Contents Disintegrated Using Abrasive Water Jet. Materials, 2021, 14, 5471.	1.3	5
6	Effect of Post Weld Heat Treatment on Microstructure and Mechanical Behaviors of Weld Overlay Inconel 182 on 4130 Steel Substrate Using SMAW Process. Metallography, Microstructure, and Analysis, 2021, 10, 567-578.	0.5	1
7	Effect of WC-Co cermet positioning and NiCr interlayer on the microstructure and mechanical response of the dissimilar WC-Co / AISI 304ÂŁ rotary friction joint. International Journal of Refractory Metals and Hard Materials, 2021, 101, 105653.	1.7	7
8	Wear and Erosion Resistant Ceramic Materials. , 2021, , 416-424.		2
9	Application of the statistical Taguchi method to optimize the properties of WC preforms to produce W-ZrC composites using reactive infiltration by molten Zr2 Cu. International Journal of Modern Physics B, 2020, 34, 2050233.	1.0	0
10	A Taguchi approach to the influence of infiltration parameters on microstructure and properties of Wâ€“ZrC composites prepared by the displacive compensation of porosity (DCP) method. Composites Communications, 2020, 20, 100356.	3.3	5
11	Effect of pulsating water jet disintegration on hardness and elasticity modulus of austenitic stainless steel AISI 304L. International Journal of Advanced Manufacturing Technology, 2020, 107, 2719-2730.	1.5	6
12	Influence of secondary phases in A356 MMCs on their mechanical properties at macro- and nanoscale. Journal of the Brazilian Society of Mechanical Sciences and Engineering, 2020, 42, 1.	0.8	6
13	Microstructure, fracture behaviour and mechanical properties of conductive alumina based composites manufactured by SPS from graphenated Al2O3 powders. Journal of the European Ceramic Society, 2020, 40, 4818-4824.	2.8	16
14	Preparation, friction, wear, and fracture of the Si3N4-Ag-GNPs composites prepared by SPS. Journal of the European Ceramic Society, 2020, 40, 4853-4859.	2.8	17
15	Mechanical and tribological properties of TiB2-Ti composites prepared by spark plasma sintering. Metallic Materials, 2020, 57, 435-442.	0.2	1
16	Microstructure and tribological behavior of SPS processed Fe/Ti-15wt.%Cu-based metal matrix composites with incorporated waste Ti-chips. Metallic Materials, 2020, 58, 83-91.	0.2	0
17	Microstructure and mechanical behavior of dissimilar AISI 304L/WC-Co cermet rotary friction welds. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2019, 758, 36-46.	2.6	28
18	Small-Scale Mechanical Testing of Cemented Carbides from the Micro- to the Nano-Level: A Review. Metals, 2019, 9, 502.	1.0	18

#	ARTICLE	IF	CITATIONS
19	Mechanical, physical properties and tribological behaviour of silicon carbide composites with addition of carbon nanotubes. International Journal of Refractory Metals and Hard Materials, 2019, 81, 272-280.	1.7	16
20	Study of Ni <sub>63</sub> -Co <sub>37</sub> nanocrystalline electrodeposited alloy as anti-wear coating on mild steel substrate. Materials Research Express, 2019, 6, 126557.	0.8	1
21	Investigation of WC decarburization effect on the microstructure and wear behavior of WC-Ni hardfacing under dry and alkaline wet conditions. Materials Chemistry and Physics, 2018, 208, 237-247.	2.0	26
22	Ultrasonically generated pulsed water jet peening of austenitic stainless-steel surfaces. Journal of Manufacturing Processes, 2018, 32, 455-468.	2.8	66
23	Surface integrity of Mg-based nanocomposite produced by Abrasive Water Jet Machining (AWJM). Materials and Manufacturing Processes, 2017, 32, 1707-1714.	2.7	28
24	Mechanical and tribological properties of electrically conductive SiC based cermets. International Journal of Refractory Metals and Hard Materials, 2017, 65, 76-82.	1.7	8
25	Fractography of Advanced Ceramics V – Fractography from MACRO- to NANO-scale. Journal of the European Ceramic Society, 2017, 37, 4241-4242.	2.8	1
26	Microstructure, fracture, electrical properties and machinability of SiC-TiNbC composites. Journal of the European Ceramic Society, 2017, 37, 4315-4322.	2.8	8
27	Wear damage of TiTaCN-Co cermets at room and elevated temperatures. Procedia Structural Integrity, 2017, 5, 1385-1392.	0.3	2
28	Comparison of the influence of acoustically enhanced pulsating water jet on selected surface integrity characteristics of CW004A copper and CW614N brass. Measurement: Journal of the International Measurement Confederation, 2017, 110, 230-238.	2.5	34
29	Effect of brazing current on microstructure and mechanical behavior of WC-Co/AISI 1020 steel TIG brazed joint. International Journal of Refractory Metals and Hard Materials, 2017, 64, 210-218.	1.7	34
30	The Study of Selected Properties of Ti EB PVD Coating Deposited Onto Inner Tube Surface at Low Temperature. Archives of Metallurgy and Materials, 2016, 61, 67-74.	0.6	3
31	TiTaCN-Co Cermets Prepared by Mechanochemical Technique: Microstructure and Mechanical Properties. Procedia Engineering, 2016, 149, 87-93.	1.2	0
32	Surface Integrity Evaluation of Brass CW614N after Impact of Acoustically Excited Pulsating Water Jet. Procedia Engineering, 2016, 149, 236-244.	1.2	13
33	Effect of Fiber Laser Treating on Magnetic Domains in the Grain-Oriented Silicon Steel: Imaging Domains by Bitter, MFM and Kerr Microscopy. High Temperature Materials and Processes, 2016, 35, 739-744.	0.6	4
34	Tribological behaviour and local mechanical properties of magnesium-alumina composites. Metallic Materials, 2016, 52, 313-319.	0.2	2
35	Structural and nanomechanical properties of sol-gel prepared (K, Na)NbO <sub>3</sub> thin films. Surface and Interface Analysis, 2015, 47, 1063-1071.	0.8	10
36	Sintered composite materials on the basis of Fe/FePO <sub>4</sub> -coated powders. Surface and Interface Analysis, 2015, 47, 350-356.	0.8	4

#	ARTICLE	IF	CITATIONS
37	Tribological behaviour and mechanical properties of copper and magnesium based composites treated by severe plastic deformation. <i>International Journal of Materials and Product Technology</i> , 2015, 50, 80.	0.1	3
38	Experimental in-vitro bone cements disintegration with ultrasonic pulsating water jet for revision arthroplasty. <i>Tehnicki Vjesnik</i> , 2015, 22, .	0.3	5
39	Creep Behaviour and Fracture Analysis of MoSi <sub>2</sub> Based Composites. <i>High Temperature Materials and Processes</i> , 2015, 34, .	0.6	2
40	Nanoindentation of (Ti,Ta)(C,N)-Co cermets prepared by methods of mechanochemistry. <i>International Journal of Refractory Metals and Hard Materials</i> , 2015, 49, 219-224.	1.7	3
41	Structural and mechanical properties of sol-gel prepared pyrochlore lanthanum niobates. <i>Journal of Materials Science</i> , 2015, 50, 7197-7207.	1.7	7
42	Development of Cold-Rolled Dual-Phase Steels with Tensile Strength Above 1000MPa and Good Bendability. <i>Metallurgical and Materials Transactions A: Physical Metallurgy and Materials Science</i> , 2015, 46, 4755-4771.	1.1	9
43	Orientation-dependent hardness and nanoindentation-induced deformation mechanisms of WC crystals. <i>Acta Materialia</i> , 2015, 83, 397-407.	3.8	107
44	Indentation hardness and fatigue of the constituents of WC-Co composites. <i>International Journal of Refractory Metals and Hard Materials</i> , 2015, 49, 178-183.	1.7	19
45	Thermal manifestations and nanoindentation of bone cements for orthopaedic surgery. <i>Thermal Science</i> , 2014, 18, 251-258.	0.5	3
46	Multicomponent Thin Films Deposited by PVD ARC and LARC Technology. <i>Medziagotyra</i> , 2014, 20, .	0.1	2
47	Indentation fatigue of WC grains in WC-Co composite. <i>Journal of the European Ceramic Society</i> , 2014, 34, 3407-3412.	2.8	32
48	Effect of solvent on phase composition and particle morphology of lanthanum niobates prepared by polymeric complex sol-gel method. <i>Journal of Sol-Gel Science and Technology</i> , 2014, 69, 272-280.	1.1	13
49	Effect of tantalum content on the microstructure and mechanical behavior of cermets based on (Ti <sub>x</sub> Ta <sub>1-x</sub> )(Co <sub>0.5</sub> Ni <sub>0.5</sub> ) solid solutions. <i>Materials &amp; Design</i> , 2014, 53, 435-444.	5.1	33
50	Structural properties and phase transformation of sol-gel prepared lanthanum tantalates. <i>Journal of Materials Science</i> , 2014, 49, 8423-8435.	1.7	12
51	Wear damage of Si <sub>3</sub> N <sub>4</sub> -graphene nanocomposites at room and elevated temperatures. <i>Journal of the European Ceramic Society</i> , 2014, 34, 3309-3317.	2.8	42
52	Influence of hBN content on mechanical and tribological properties of Si <sub>3</sub> N <sub>4</sub> /BN ceramic composites. <i>Journal of the European Ceramic Society</i> , 2014, 34, 3319-3328.	2.8	60
53	Coating Surface Roughness Measurement Made On Coining Dies. <i>Manufacturing Technology</i> , 2014, 14, 309-317.	0.2	11
54	Indentation fatigue of WC-Co cemented carbides. <i>International Journal of Refractory Metals and Hard Materials</i> , 2013, 41, 229-235.	1.7	26

#	ARTICLE	IF	CITATIONS
55	Tribological properties of Si <sub>3</sub> N <sub>4</sub> –graphene nanocomposites. <i>Journal of the European Ceramic Society</i> , 2013, 33, 2359-2364.	2.8	125
56	Failure analysis of overhead power line yoke connector. <i>Engineering Failure Analysis</i> , 2013, 33, 66-74.	1.8	8
57	Wear resistance of Al <sub>2</sub> O <sub>3</sub> –CNT ceramic nanocomposites at room and high temperatures. <i>Ceramics International</i> , 2013, 39, 5821-5826.	2.3	80
58	Effect of substrate on microstructure and mechanical properties of sol–gel prepared (K, Na)NbO <sub>3</sub> thin films. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2013, 178, 254-262.	1.7	19
59	Nanoindentation of WC–Co hardmetals. <i>Journal of the European Ceramic Society</i> , 2013, 33, 2227-2232.	2.8	66
60	Tribological Characteristics of Copper Based Composites with Al <sub>2</sub> O <sub>3</sub> Particles at Various Temperatures. <i>High Temperature Materials and Processes</i> , 2013, 32, 437-442.	0.6	0
61	Plasma nitriding and its influence on contact fatigue of sintered steel. <i>Metallic Materials</i> , 2013, 50, 365-371.	0.2	0
62	The effect of surface pre-treatment and coating post-treatment to the properties of TiN coatings. <i>Estonian Journal of Engineering</i> , 2012, 18, 185.	0.3	12
63	Tribological Parameters of Copper-Alumina Composite. <i>Key Engineering Materials</i> , 2012, 527, 191-196.	0.4	1
64	Investigation of thin layers deposited by two PVD techniques on high speed steel produced by powder metallurgy. <i>Applied Surface Science</i> , 2012, 258, 5105-5110.	3.1	17
65	Tribological and electrical properties of ceramic matrix composites with carbon nanotubes. <i>Ceramics International</i> , 2012, 38, 5669-5676.	2.3	52
66	Fracture toughness and toughening mechanisms in graphene platelet reinforced Si <sub>3</sub> N <sub>4</sub> composites. <i>Scripta Materialia</i> , 2012, 66, 793-796.	2.6	191
67	Effect of substrate on phase formation and surface morphology of sol-gel lead-free KNbO <sub>3</sub> , NaNbO <sub>3</sub> , and K <sub>0.5</sub> Na <sub>0.5</sub> NbO <sub>3</sub> thin films. <i>Chemical Papers</i> , 2012, 66, .	1.0	8
68	Effect of sol-gel preparation method on particle morphology in pure and nanocomposite PZT thin films. <i>Chemical Papers</i> , 2011, 65, .	1.0	7
69	Tribological Characteristics of Micro- and Nano-Composites Cu-Al <sub>2</sub> O <sub>3</sub> at Room and Elevated Temperatures. <i>High Temperature Materials and Processes</i> , 2011, 30, .	0.6	1
70	Damage mechanism of AZ61-F Mg alloy with nano-Al <sub>2</sub> O <sub>3</sub> particles. <i>Metallic Materials</i> , 2011, 49, 451-455.	0.2	2
71	Tribological behavior of carbon nanofiber–zirconia composite. <i>Scripta Materialia</i> , 2010, 63, 254-257.	2.6	34
72	Effect of heat treatment on wear damage mechanisms in 3Y-TZP ceramics. <i>Wear</i> , 2010, 269, 26-30.	1.5	14

#	ARTICLE	IF	CITATIONS
73	Wear resistance of hot-pressed Si <sub>3</sub> N <sub>4</sub> /SiC micro/nanocomposites sintered with rare-earth oxide additives. <i>Wear</i> , 2010, 269, 867-874.	1.5	46
74	Study of near surface changes in yttria-doped tetragonal zirconia after low temperature degradation. <i>International Journal of Materials Research</i> , 2009, 100, 92-96.	0.1	18
75	High Temperature Properties of the MoSi <sub>2</sub> and MoSi <sub>2</sub> SiC Nonocomposites. <i>High Temperature Materials and Processes</i> , 2009, 28, 271-276.	0.6	2
76	<i>In situ</i> tensile testing in SEM of Al <sub>4</sub> C <sub>3</sub> nanomaterials. <i>Estonian Journal of Engineering</i> , 2009, 15, 247.	0.3	8
77	Residual Stresses in Laminar Functionally Graded Ceramic Materials. <i>Key Engineering Materials</i> , 2007, 333, 259-262.	0.4	0
78	Mechanical properties and thermal shock behaviour of an alumina/zirconia functionally graded material prepared by electrophoretic deposition. <i>Journal of the European Ceramic Society</i> , 2007, 27, 1365-1371.	2.8	36
79	Processing, microstructure and creep testing of Pt-Y <sub>2</sub> O <sub>3</sub> composites. <i>Materials &amp; Design</i> , 2007, 28, 2540-2543.	5.1	3
80	Creep Testing of MoSi <sub>2</sub> - Bases Composites. <i>High Temperature Materials and Processes</i> , 2006, 25, 139-142.	0.6	2
81	Thermal residual stress gradients in an alumina-zirconia composite obtained by electrophoretic deposition. <i>Journal of the European Ceramic Society</i> , 2006, 26, 553-558.	2.8	7
82	Microstructure and mechanical properties of ZrO <sub>2</sub> reinforced MoSi <sub>2</sub> matrix composites. <i>International Journal of Materials and Product Technology</i> , 2005, 22, 322.	0.1	1
83	Enhanced Creep Resistant Silicon-Nitride-Based Nanocomposite. <i>Journal of the American Ceramic Society</i> , 2005, 88, 1500-1503.	1.9	20
84	Mechanical properties of phases in Al-Al <sub>4</sub> C <sub>3</sub> mechanically alloyed material measured by depth sensing indentation technique. <i>Materials Letters</i> , 2005, 59, 1971-1975.	1.3	22
85	Creep behaviour of MoSi <sub>2</sub> -HfO <sub>2</sub> composites. <i>Journal of Materials Science</i> , 2005, 40, 3869-3871.	1.7	1
86	Residual Stress Profile Determined by Piezo-Spectroscopy in Alumina/Alumina-Zirconia Layers Separated by a Compositionally Graded Intermediate Layer. <i>Key Engineering Materials</i> , 2005, 290, 328-331.	0.4	2
87	Compressive Creep Testing of Pt-Y <sub>2</sub> O <sub>3</sub> Composites. <i>High Temperature Materials and Processes</i> , 2005, 24, 189-192.	0.6	0
88	Mechanical Properties of Alumina/Zirconia Functionally Graded Material Prepared by Electrophoretic Deposition. <i>Key Engineering Materials</i> , 2005, 290, 332-335.	0.4	4
89	Influence of Al <sub>4</sub> C <sub>3</sub> particle volume fraction on fracture mechanism in Al-Al <sub>4</sub> C <sub>3</sub> composite. <i>Journal of Materials Science</i> , 2004, 39, 1071-1074.	1.7	5
90	Creep behavior of MoSi <sub>2</sub> and MoSi <sub>2</sub> + SiC composite. <i>Journal of Materials Science</i> , 2004, 39, 4073-4077.	1.7	3

#	ARTICLE	IF	CITATIONS
91	Mechanical properties of Si <sub>3</sub> N <sub>4</sub> /SiC nanocomposites studied by instrumented indentation with spheres. Journal of the European Ceramic Society, 2004, 24, 3345-3350.	2.8	4
92	Creep behavior of a carbon-derived Si <sub>3</sub> N <sub>4</sub> /SiC nanocomposite. Journal of the European Ceramic Society, 2004, 24, 3307-3315.	2.8	26
93	Damage mechanism of Al <sub>2</sub> O <sub>3</sub> /12Al <sub>4</sub> C <sub>3</sub> . Materials Letters, 2004, 58, 867-870.	1.3	7
94	Indentation moduli and microhardness of RE <sub>2</sub> Si <sub>2</sub> Mg <sub>2</sub> O <sub>7</sub> N glasses (RE=Sc, Y, La, Sm, Yb and Lu) with different nitrogen content. Materials Science & Engineering A: Structural Materials: Properties, Microstructure and Processing, 2003, 357, 181-187.	2.6	30
95	Fracture and Mechanical Properties of MoSi <sub>2</sub> and MoSi <sub>2</sub> + SiC. Key Engineering Materials, 2003, 251-252, 13-18.	0.4	1
96	Indentation Crack Healing in Low Glass-Content Mullite. Key Engineering Materials, 2002, 223, 257-260.	0.4	5
97	Stress-Corrosion Cracking in Alumina Ceramics. Key Engineering Materials, 2002, 223, 187-192.	0.4	1
98	Stress Induced Depolarisation of Ferroelectrics in Thin Film Form. Ferroelectrics, 2002, 267, 367-372.	0.3	0
99	Mechanical and electromechanical properties of PZT sol-gel thin films measured by nanoindentation. Integrated Ferroelectrics, 2001, 41, 53-62.	0.3	12
100	Creep behaviour of MoSi <sub>2</sub> /SiC and MoSi <sub>2</sub> /HfO <sub>2</sub> . Materials Letters, 2001, 51, 485-489.	1.3	11
101	Fatigue behaviour of mullite studied by the indentation flexure method. Journal of the European Ceramic Society, 2001, 21, 53-61.	2.8	2
102	Effect of aqueous solutions on time-dependent failure of a glass-bonded alumina. Journal of Materials Science Letters, 2001, 20, 745-749.	0.5	0
103	Fatigue Crack Growth in Self-Reinforced Silicon Nitride Based Materials. Key Engineering Materials, 2000, 175-176, 253-260.	0.4	0
104	SiC/Si <sub>3</sub> N <sub>4</sub> nano/micro-composite – processing, RT and HT mechanical properties. Journal of the European Ceramic Society, 2000, 20, 453-462.	2.8	82
105	Young's Modulus Measurement of Silicon Nitride Ceramics by Indentation Methods. Key Engineering Materials, 1999, 175-176, 335-0.	0.4	0
106	Bending creep behaviour of pressureless sintered MoSi <sub>2</sub> . Scripta Materialia, 1997, 37, 471-476.	2.6	9
107	Short Term Deformation and Relaxation Behaviour of Silicon Nitride Ceramics. , 1997, , 389-397.		0
108	Indentation Fatigue of Some Si <sub>3</sub> N <sub>4</sub> Based Ceramics. , 1997, , 399-407.		0

#	ARTICLE	IF	CITATIONS
109	Deformation and fracture behaviour of two Si <sub>3</sub> N <sub>4</sub> ceramics with different sintering additives. Scripta Metallurgica Et Materialia, 1995, 32, 1459-1464.	1.0	1
110	Effect of Low Temperature Degradation on Scratch Behaviour of 3Y-TZP. Key Engineering Materials, 0, 409, 322-325.	0.4	1
111	Carbon Nanofibers Reinforced Ceramic Matrix Composites. , 0, , .		9
112	Wear Behavior of ZrO <sub>2</sub> -CNF and Si <sub>3</sub> N <sub>4</sub> -CNT Nanocomposites. Key Engineering Materials, 0, 465, 495-498.	0.4	16
113	Mechanical and Tribological Properties of Al <sub>2</sub> O <sub>3</sub> -ZrO <sub>2</sub> Based Composites Prepared by EPD. Key Engineering Materials, 0, 507, 191-195.	0.4	1
114	Nanohardness of Individual Phases in WC-Co Cemented Carbides. Key Engineering Materials, 0, 586, 23-26.	0.4	6
115	Local Mechanical Properties of Various Bone Cements. Key Engineering Materials, 0, 592-593, 382-385.	0.4	1
116	Local Mechanical Properties of Cast and Sintered High Cr-Alloyed Steel. Key Engineering Materials, 0, 586, 241-244.	0.4	0
117	The Influence of Current Density on Tribological Behavior Ni-Co Electroplated Coatings. Key Engineering Materials, 0, 635, 127-130.	0.4	5
118	Nanoindentation and AFM Studies on Tungsten Carbide Crystals in WC-Co Hardmetal. Key Engineering Materials, 0, 606, 107-110.	0.4	6
119	Instrumented Indentation of Composite Materials Prepared by Methods of Mechanochemistry. Key Engineering Materials, 0, 606, 241-244.	0.4	0
120	Wear and Mechanical Properties of Various Bone Cements Influence of Saline Environment. Key Engineering Materials, 0, 662, 147-150.	0.4	0
121	Local Mechanical Properties of SiC - TiN <sub>2</sub> C Composite and its Constituents. Defect and Diffusion Forum, 0, 368, 158-161.	0.4	2
122	Residual Stress Profile Determined by Piezo-Spectroscopy in Alumina/Alumina-Zirconia Layers Separated by a Compositionally Graded Intermediate Layer. Key Engineering Materials, 0, , 328-331.	0.4	1