

# Jun-Tao Li

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/7013352/publications.pdf>

Version: 2024-02-01

81  
papers

4,879  
citations

94433

37  
h-index

95266

68  
g-index

81  
all docs

81  
docs citations

81  
times ranked

5718  
citing authors

#	ARTICLE	IF	CITATIONS
1	Heteroatom-rich polymers as a protective film to control lithium growth for high-performance lithium-metal batteries. <i>Journal of Power Sources</i> , 2022, 521, 230949.	7.8	9
2	Co/Li-dual-site doping towards $\text{LiCoO}_2$ as a high-voltage, fast-charging, and long-cycling cathode material. <i>Journal of Materials Chemistry A</i> , 2022, 10, 5295-5304.	10.3	21
3	Stabilized and Almost Dendrite-Free Li Metal Anodes by In Situ Construction of a Composite Protective Layer for Li Metal Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2022, 14, 5298-5307.	8.0	22
4	Pushing Lithium Cobalt Oxides to 4.7V by Lattice-Matched Interfacial Engineering. <i>Advanced Energy Materials</i> , 2022, 12, .	19.5	77
5	Electron/ion Conductor Double-coated $\text{LiNi}_{0.8}\text{Co}_{0.1}\text{Mn}_{0.1}\text{O}_2$ Li-ion Battery Cathode Material and Its Electrochemical Performance. <i>Acta Chimica Sinica</i> , 2022, 80, 485.	1.4	0
6	Interfacial Electron Delocalization in Engineering Nanosized Anti-Perovskite Nitride for Efficient $\text{CO}_2$ Electroreduction. <i>Chemistry of Materials</i> , 2022, 34, 5607-5620.	6.7	11
7	A dual force cross-linked $\beta$ -PGA-PAA binder enhancing the cycle stability of silicon-based anodes for lithium-ion batteries. <i>Electrochimica Acta</i> , 2022, 425, 140704.	5.2	15
8	Design Criteria for Silicon-Based Anode Binders in Half and Full Cells. <i>Advanced Energy Materials</i> , 2022, 12, .	19.5	52
9	Engineering the interface between $\text{LiCoO}_2$ and $\text{Li}_{10}\text{GeP}_2\text{S}_{12}$ solid electrolytes with an ultrathin $\text{Li}_2\text{CoTi}_3\text{O}_8$ interlayer to boost the performance of all-solid-state batteries. <i>Energy and Environmental Science</i> , 2021, 14, 437-450.	30.8	82
10	$\text{NiCo}_2\text{O}_4$ /CNF Separator Modifiers for Trapping and Catalyzing Polysulfides for High-Performance Lithium-Sulfur Batteries with High Sulfur Loadings and Lean Electrolytes. <i>ACS Sustainable Chemistry and Engineering</i> , 2021, 9, 1804-1813.	6.7	31
11	Preparation of intergrown P/O-type biphasic layered oxides as high-performance cathodes for sodium ion batteries. <i>Journal of Materials Chemistry A</i> , 2021, 9, 13151-13160.	10.3	26
12	$\text{RuO}_2$ nanoparticles supported on Ni and N co-doped carbon nanotubes as an efficient bifunctional electrocatalyst of lithium-oxygen battery. <i>Science China Materials</i> , 2021, 64, 2397-2408.	6.3	8
13	Multivalent Amide-Hydrogen-Bond Supramolecular Binder Enhances the Cyclic Stability of Silicon-Based Anodes for Lithium-Ion Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 22567-22576.	8.0	26
14	Controlled Synthesis of Porous Hollow $\text{Fe}_3\text{N}/\text{C}$ Nanoshells as High-Performance Oxygen Reduction Reaction Electrocatalysts for Zn-Air Battery. <i>Energy Technology</i> , 2021, 9, 2100142.	3.8	4
15	Customizing Multifunctional Sulfur Host Materials Via a General Anion-Exchange Process with Metal-Organic Solid. <i>Advanced Functional Materials</i> , 2021, 31, 2104513.	14.9	4
16	From bulk to interface: electrochemical phenomena and mechanism studies in batteries via electrochemical quartz crystal microbalance. <i>Chemical Society Reviews</i> , 2021, 50, 10743-10763.	38.1	48
17	Improving the Electrochemical Property of Silicon Anodes through Hydrogen-Bonding Cross-Linked Thiourea-Based Polymeric Binders. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 639-649.	8.0	36
18	Influence of Carbonate Solvents on Solid Electrolyte Interphase Composition over Si Electrodes Monitored by In Situ and Ex Situ Spectroscopies. <i>ACS Omega</i> , 2021, 6, 27335-27350.	3.5	14

#	ARTICLE	IF	CITATIONS
19	Formulating a New Electrolyte: Synergy between Low-Polar and Non-polar Solvents in Tailoring the Solid Electrolyte Interface for the Silicon Anode. <i>ACS Applied Materials &amp; Interfaces</i> , 2021, 13, 55700-55711.	8.0	7
20	Fabrication of multi-shell coated silicon nanoparticles via in-situ electroless deposition as high performance anodes for lithium ion batteries. <i>Journal of Energy Chemistry</i> , 2020, 48, 160-168.	12.9	37
21	Synergetic Effect of Ru and NiO in the Electrocatalytic Decomposition of $\text{Li}_2\text{CO}_3$ to Enhance the Performance of a $\text{Li-CO}_2/\text{O}_2$ Battery. <i>ACS Catalysis</i> , 2020, 10, 1640-1651.	11.2	85
22	The Si@C Network Electrode Prepared by an In-Situ Carbonization Strategy with Enhanced Cycle Performance. <i>ChemElectroChem</i> , 2020, 7, 4999-5004.	3.4	4
23	High Cycling Performance $\text{Li-S}$ Battery via Fenugreek Gum Binder Through Chemical Bonding of the Binder with Polysulfides in Nanosulfur@CNFs Cathode. <i>ChemistrySelect</i> , 2020, 5, 8969-8979.	1.5	11
24	Cubic $\text{MnS-FeS}_2$ Composites Derived from a Prussian Blue Analogue as Anode Materials for Sodium-Ion Batteries with Long-Term Cycle Stability. <i>ACS Applied Materials &amp; Interfaces</i> , 2020, 12, 43624-43633.	8.0	53
25	Germanium Crystalline Nanomaterials for Li-Ion Storage Prepared by Decomposing $\text{LiZnGe}$ in Air. <i>ACS Applied Materials &amp; Interfaces</i> , 2020, 12, 50756-50762.	8.0	7
26	Understanding the role of water-soluble guar gum binder in reducing capacity fading and voltage decay of Li-rich cathode for Li-ion batteries. <i>Electrochimica Acta</i> , 2020, 351, 136401.	5.2	16
27	Controlled synthesis of $\text{Fe}_x\text{-Co}_x$ dual active sites interfaced with metallic Co nanoparticles as bifunctional oxygen electrocatalysts for rechargeable Zn-air batteries. <i>Applied Catalysis B: Environmental</i> , 2020, 278, 119259.	20.2	92
28	High-Voltage $\text{LiCoO}_2$ Material Encapsulated in a $\text{Li}_4\text{Ti}_5\text{O}_{12}$ Ultrathin Layer by High-Speed Solid-Phase Coating Process. <i>ACS Applied Energy Materials</i> , 2020, 3, 2593-2603.	5.1	36
29	Suppressing lithium dendrite growth by a synergetic effect of uniform nucleation and inhibition. <i>Journal of Materials Chemistry A</i> , 2020, 8, 4300-4307.	10.3	29
30	Ion-Doping-Site-Variation-Induced Composite Cathode Adjustment: A Case Study of Layered $\text{Na}_{0.6}\text{MnO}_2$ with $\text{Mg}^{2+}$ Doping at Na/Mn Site. <i>ACS Applied Materials &amp; Interfaces</i> , 2019, 11, 26938-26945.	8.0	28
31	A solid-state dendrite-free lithium-metal battery with improved electrode interphase and ion conductivity enhanced by a bifunctional solid plasticizer. <i>Journal of Materials Chemistry A</i> , 2019, 7, 19565-19572.	10.3	32
32	Si anode for next-generation lithium-ion battery. <i>Current Opinion in Electrochemistry</i> , 2019, 18, 46-54.	4.8	48
33	Ultrahigh sulfur content up to 93 wt% encapsulated in multilayer nanoshell of $\text{V}_2\text{O}_5$ composite to suppress shuttle effect of lithium-sulfur battery with high-performance. <i>Materials Today Energy</i> , 2019, 13, 267-276.	4.7	29
34	High-Energy Density Li metal Dual-Ion Battery with a Lithium Nitrate-Modified Carbonate-Based Electrolyte. <i>ACS Applied Materials &amp; Interfaces</i> , 2019, 11, 18504-18510.	8.0	47
35	Novel $\text{MnO-C}$ Graphite Dual-Ion Battery and New Insights into Its Reaction Mechanism during Initial Cycle by Operando Techniques. <i>ACS Applied Materials &amp; Interfaces</i> , 2019, 11, 12570-12577.	8.0	35
36	Revealing of the Activation Pathway and Cathode Electrolyte Interphase Evolution of Li-Rich $\text{0.5Li}_2\text{MnO}_3\text{-}x\text{LiNi}_{0.3}\text{Co}_{0.3}\text{Mn}_{0.4}\text{O}_2$ Cathode by in Situ Electrochemical Quartz Crystal Microbalance. <i>ACS Applied Materials &amp; Interfaces</i> , 2019, 11, 16214-16222.	8.0	23

#	ARTICLE	IF	CITATIONS
37	Boosting the reactivity of Ni <sup>2+</sup> /Ni <sup>3+</sup> redox couple via fluorine doping of high performance Na <sub>0.6</sub> Mn <sub>0.95</sub> Ni <sub>0.05</sub> O <sub>2</sub> -F cathode. <i>Electrochimica Acta</i> , 2019, 308, 64-73.	5.2	37
38	Aluminum-Based Metal-Organic Frameworks Derived Al <sub>2</sub> O <sub>3</sub> -Loading Mesoporous Carbon as a Host Matrix for Lithium-Metal Anodes. <i>ACS Applied Materials &amp; Interfaces</i> , 2019, 11, 47939-47947.	8.0	26
39	Core-Shell Structured S@Co(OH) <sub>2</sub> with a Carbon-Nanofiber Interlayer: A Conductive Cathode with Suppressed Shuttling Effect for High-Performance Lithium-Sulfur Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2019, 11, 4065-4073.	8.0	35
40	Suppressing Li dendrite by a protective biopolymeric film from tamarind seed polysaccharide for high-performance Li metal anode. <i>Electrochimica Acta</i> , 2019, 299, 636-644.	5.2	34
41	High-performance rechargeable Li-CO <sub>2</sub> /O <sub>2</sub> battery with Ru/N-doped CNT catalyst. <i>Chemical Engineering Journal</i> , 2019, 363, 224-233.	12.7	58
42	Aluminum-sulfur composites for Li S batteries with a high-rate performance. <i>Composites Part B: Engineering</i> , 2019, 164, 740-746.	12.0	7
43	Cu <sup>2+</sup> Dual-Doped Layer-Tunnel Hybrid Na <sub>0.6</sub> Mn <sub>1-x</sub> Cu <sub>x</sub> O <sub>2</sub> as a Cathode of Sodium-Ion Battery with Enhanced Structure Stability, Electrochemical Property, and Air Stability. <i>ACS Applied Materials &amp; Interfaces</i> , 2018, 10, 10147-10156.	8.0	98
44	Sodium-Alginate-Based Binders for Lithium-Rich Cathode Materials in Lithium-Ion Batteries to Suppress Voltage and Capacity Fading. <i>ChemElectroChem</i> , 2018, 5, 1321-1329.	3.4	29
45	Sulfur Microspheres Encapsulated in Porous Silver-Based Shell with Superior Performance for Lithium-Sulfur Batteries. <i>ChemElectroChem</i> , 2018, 5, 1683-1690.	3.4	9
46	Novel Sulfur Host Composed of Cobalt and Porous Graphitic Carbon Derived from MOFs for the High-Performance Li-S Battery. <i>ACS Applied Materials &amp; Interfaces</i> , 2018, 10, 13499-13508.	8.0	54
47	Tuning the component ratio and corresponding sodium storage properties of layer-tunnel hybrid Na <sub>0.6</sub> Mn <sub>1-x</sub> Ni <sub>x</sub> O <sub>2</sub> cathode by a simple cationic Ni <sup>2+</sup> doping strategy. <i>Electrochimica Acta</i> , 2018, 273, 63-70.	5.2	23
48	Three-Dimensional Networks of S-Doped Fe/N/C with Hierarchical Porosity for Efficient Oxygen Reduction in Polymer Electrolyte Membrane Fuel Cells. <i>ACS Applied Materials &amp; Interfaces</i> , 2018, 10, 14602-14613.	8.0	50
49	Tuning Electrochemical Properties of Li-Rich Layered Oxide Cathodes by Adjusting Co/Ni Ratios and Mechanism Investigation Using in situ X-ray Diffraction and Online Continuous Flow Differential Electrochemical Mass Spectrometry. <i>ACS Applied Materials &amp; Interfaces</i> , 2018, 10, 12666-12677.	8.0	72
50	High-performance Si Mn/C composite anodes with integrating inactive Mn <sub>4</sub> Si <sub>7</sub> alloy for lithium-ion batteries. <i>Electrochimica Acta</i> , 2018, 260, 830-837.	5.2	26
51	Enabling Lithium-Metal Anode Encapsulated in a 3D Carbon Skeleton with a Superior Rate Performance and Capacity Retention in Full Cells. <i>ACS Applied Materials &amp; Interfaces</i> , 2018, 10, 35296-35305.	8.0	19
52	Interfacial Interaction between FeOOH and Ni-Fe LDH to Modulate the Local Electronic Structure for Enhanced OER Electrocatalysis. <i>ACS Catalysis</i> , 2018, 8, 11342-11351.	11.2	414
53	A Natural Biopolymer Film as a Robust Protective Layer to Effectively Stabilize Lithium-Metal Anodes. <i>Small</i> , 2018, 14, e1801054.	10.0	61
54	Unexpected effects of zirconium-doping in the high performance sodium manganese-based layer-tunnel cathode. <i>Journal of Materials Chemistry A</i> , 2018, 6, 13934-13942.	10.3	32

#	ARTICLE	IF	CITATIONS
55	Fabrication of Si Nanoparticles@Conductive Carbon Framework@Polymer Composite as High-Areal-Capacity Anode of Lithium-Ion Batteries. <i>ChemElectroChem</i> , 2018, 5, 3258-3265.	3.4	20
56	Mn-Based Cathode with Synergetic Layered-Tunnel Hybrid Structures and Their Enhanced Electrochemical Performance in Sodium Ion Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 21267-21275.	8.0	60
57	Layered/Spinel Heterostructured and Hierarchical Micro/Nanostructured Li-Rich Cathode Materials with Enhanced Electrochemical Properties for Li-Ion Batteries. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 21065-21070.	8.0	79
58	Multiple hydrogel alginate binders for Si anodes of lithium-ion battery. <i>Electrochimica Acta</i> , 2017, 245, 371-378.	5.2	106
59	Graphitized porous carbon materials with high sulfur loading for lithium-sulfur batteries. <i>Nano Energy</i> , 2017, 32, 503-510.	16.0	118
60	Synthesis-cum-assembly toward hierarchical nanoarchitectures. <i>Coordination Chemistry Reviews</i> , 2017, 352, 291-305.	18.8	6
61	Co <sub>3</sub> O <sub>4</sub> @(Fe-Doped)Co(OH) <sub>2</sub> Microfibers: Facile Synthesis, Oriented-Assembly, Formation Mechanism, and High Electrocatalytic Activity. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 30880-30890.	8.0	20
62	Water Soluble Binder, an Electrochemical Performance Booster for Electrode Materials with High Energy Density. <i>Advanced Energy Materials</i> , 2017, 7, 1701185.	19.5	248
63	Origin of Structural Evolution in Capacity Degradation for Overcharged NMC622 via Operando Coupled Investigation. <i>ACS Applied Materials &amp; Interfaces</i> , 2017, 9, 24731-24742.	8.0	78
64	<i>In Situ</i> Multitechnical Investigation into Capacity Fading of High-Voltage Li <sub>0.5</sub> Co <sub>0.2</sub> Mn <sub>0.3</sub> O <sub>2</sub> . <i>ACS Applied Materials &amp; Interfaces</i> , 2016, 8, 35323-35335.	8.0	63
65	Improving the Electrochemical Performance of Li <sub>1.14</sub> Ni <sub>0.18</sub> Mn <sub>0.62</sub> O <sub>2</sub> by Modulating Structure Defects via a Molten Salt Method. <i>ChemElectroChem</i> , 2016, 3, 98-104.	3.4	13
66	Suppressing the voltage-fading of layered lithium-rich cathode materials via an aqueous binder for Li-ion batteries. <i>Chemical Communications</i> , 2016, 52, 4683-4686.	4.1	85
67	Achieving high capacity retention in lithium-sulfur batteries with an aqueous binder. <i>Electrochemistry Communications</i> , 2016, 72, 79-82.	4.7	43
68	P2-type Na <sub>0.67</sub> Mn <sub>0.72</sub> Ni <sub>0.14</sub> Co <sub>0.14</sub> O <sub>2</sub> with K <sup>+</sup> doping as new high rate performance cathode material for sodium-ion batteries. <i>Electrochimica Acta</i> , 2016, 216, 51-57.	5.2	59
69	A Synergistic Effect in a Composite Cathode Consisting of Spinel and Layered Structures To Increase the Electrochemical Performance for Li-Ion Batteries. <i>Journal of Physical Chemistry C</i> , 2016, 120, 25647-25656.	3.1	13
70	Layered/spinel heterostructured Li-rich materials synthesized by a one-step solvothermal strategy with enhanced electrochemical performance for Li-ion batteries. <i>Journal of Materials Chemistry A</i> , 2016, 4, 257-263.	10.3	111
71	A Robust Ion-Conductive Biopolymer as a Binder for Si Anodes of Lithium-Ion Batteries. <i>Advanced Functional Materials</i> , 2015, 25, 3599-3605.	14.9	329
72	New insight into structural transformation in Li-rich layered oxide during the initial charging. <i>Journal of Materials Chemistry A</i> , 2015, 3, 12220-12229.	10.3	57

#	ARTICLE	IF	CITATIONS
73	Facile Synthesis of The Li-rich Layered Oxide $\text{Li}_{1.23}\text{Ni}_{0.09}\text{Co}_{0.12}\text{Mn}_{0.56}\text{O}_2$ with Superior Lithium Storage Performance and New Insights into Structural Transformation of the Layered Oxide Material during Charge/Discharge Cycle: In Situ XRD Characterization. <i>ACS Applied Materials &amp; Interfaces</i> , 2014, 6, 5516-5524.	8.0	96
74	A high-performance alginate hydrogel binder for the Si/C anode of a Li-ion battery. <i>Chemical Communications</i> , 2014, 50, 6386.	4.1	181
75	Synthesis of single crystalline hexagonal nanobricks of $\text{LiNi}_{1/3}\text{Co}_{1/3}\text{Mn}_{1/3}\text{O}_2$ with high percentage of exposed {010} active facets as high rate performance cathode material for lithium-ion battery. <i>Journal of Materials Chemistry A</i> , 2013, 1, 3860.	10.3	195
76	XPS and ToF-SIMS Study of Electrode Processes on $\text{Sn}^{\delta+}\text{Ni}$ Alloy Anodes for Li-Ion Batteries. <i>Journal of Physical Chemistry C</i> , 2011, 115, 7012-7018.	3.1	89
77	Ordered mesoporous carbon/sulfur nanocomposite of high performances as cathode for lithium-sulfur battery. <i>Electrochimica Acta</i> , 2011, 56, 9549-9555.	5.2	329
78	XPS and ToF-SIMS study of $\text{Sn}^{\delta+}\text{Co}$ alloy thin films as anode for lithium ion battery. <i>Journal of Power Sources</i> , 2010, 195, 8251-8257.	7.8	111
79	XPS, time-of-flight-SIMS and polarization modulation IRRAS study of $\text{Cr}_2\text{O}_3$ thin film materials as anode for lithium ion battery. <i>Electrochimica Acta</i> , 2009, 54, 3700-3707.	5.2	81
80	Studies of the Interfacial Properties of an Electroplated Sn Thin Film Electrode/Electrolyte Using in Situ MFTIRS and EQCM. <i>Langmuir</i> , 2007, 23, 13174-13180.	3.5	79
81	Surface combinatorial studies of IR properties of nanostructured Ru film electrodes using CO as probe molecule. <i>Electrochimica Acta</i> , 2003, 48, 2933-2942.	5.2	21